
Volatility 3 Documentation

Release 2.7.0

Volatility Foundation

May 09, 2024

DOCUMENTATION

1	Volatility 3 Basics	3
1.1	Memory layers	3
1.2	Templates and Objects	4
1.3	Symbol Tables	5
1.4	Plugins	5
1.5	Output Renderers	5
1.6	Configuration Tree	6
1.7	Automagic	6
2	Writing Plugins	7
2.1	How to Write a Simple Plugin	7
2.2	Writing more advanced Plugins	12
2.3	Using Volatility 3 as a Library	17
3	Creating New Symbol Tables	23
3.1	How Volatility finds symbol tables	23
3.2	Windows symbol tables	23
3.3	Mac or Linux symbol tables	24
4	Changes between Volatility 2 and Volatility 3	25
4.1	Library and Context	25
4.2	Symbols and Types	25
4.3	Object Model changes	25
4.4	Layer and Layer dependencies	26
4.5	Automagic	26
4.6	Searching and Scanning	26
4.7	Output Rendering	26
5	Volshell - A CLI tool for working with memory	27
5.1	Starting volshell	27
5.2	Accessing objects	28
5.3	Running plugins	29
5.4	Running scripts	30
5.5	Loading files	30
6	Glossary	31
6.1	A	31
6.2	D	31
6.3	M	32
6.4	O	32
6.5	P	32

6.6	R	33
6.7	S	33
6.8	T	33
6.9	U	34
7	Linux Tutorial	35
7.1	Acquiring memory	35
7.2	Procedure to create symbol tables for linux	35
7.3	Listing plugins	35
7.4	Using plugins	36
7.5	Example	36
8	macOS Tutorial	39
8.1	Acquiring memory	39
8.2	Procedure to create symbol tables for macOS	39
8.3	Listing plugins	39
8.4	Using plugins	40
8.5	Example	40
9	Windows Tutorial	43
9.1	Acquiring memory	43
9.2	Listing Plugins	43
9.3	Using plugins	44
9.4	Example	44
10	volatility3 package	47
10.1	Subpackages	48
11	Indices and tables	791
	Python Module Index	793
	Index	797

This is the documentation for Volatility 3, the most advanced memory forensics framework in the world. Like previous versions of the Volatility framework, Volatility 3 is Open Source.

List of plugins

Below is the main documentation regarding volatility 3:

VOLATILITY 3 BASICS

Volatility splits memory analysis down to several components. The main ones are:

- Memory layers
- Templates and Objects
- Symbol Tables

Volatility 3 stores all of these within a *Context*, which acts as a container for all the various layers and tables necessary to conduct memory analysis.

1.1 Memory layers

A memory layer is a body of data that can be accessed by requesting data at a specific address. At its lowest level this data is stored on a physical medium (RAM) and very early computers addresses locations in memory directly. However, as the size of memory increased and it became more difficult to manage memory most architectures moved to a “paged” model of memory, where the available memory is cut into specific fixed-sized pages. To help further, programs can ask for any address and the processor will look up their (virtual) address in a map, to find out where the (physical) address that it lives at is, in the actual memory of the system.

Volatility can work with these layers as long as it knows the map (so, for example that virtual address 1 looks up at physical address 9). The automagic that runs at the start of every volatility session often locates the kernel’s memory map, and creates a kernel virtual layer, which allows for kernel addresses to be looked up and the correct data returned. There can, however, be several maps, and in general there is a different map for each process (although a portion of the operating system’s memory is usually mapped to the same location across all processes). The maps may take the same address but point to a different part of physical memory. It also means that two processes could theoretically share memory, but having an virtual address mapped to the same physical address as another process. See the worked example below for more information.

To translate an address on a layer, call *layer.mapping(offset, length, ignore_errors)* and it will return a list of chunks without overlap, in order, for the requested range. If a portion cannot be mapped, an exception will be thrown unless *ignore_errors* is true. Each chunk will contain the original offset of the chunk, the translated offset, the original size and the translated size of the chunk, as well as the lower layer the chunk lives within.

1.1.1 Worked example

The operating system and two programs may all appear to have access to all of physical memory, but actually the maps they each have mean they each see something different:

Listing 1: Memory mapping example

Operating system map	Physical Memory
1 -> 9	1 - Free
2 -> 3	2 - OS.4, Process 1.4, Process 2.4
3 -> 7	3 - OS.2
4 -> 2	4 - Free
	5 - Free
Process 1 map	6 - Process 1.2, Process 2.3
1 -> 12	7 - OS.3
2 -> 6	8 - Process1.3
3 -> 8	9 - OS.1
4 -> 2	10 - Process2.1
	11 - Free
Process 2 map	12 - Process1.1
1 -> 10	13 - Free
2 -> 15	14 - Free
3 -> 6	15 - Process2.2
4 -> 2	16 - Free

In this example, part of the operating system is visible across all processes (although not all processes can write to the memory, there is a permissions model for intel addressing which is not discussed further here).)

In Volatility 3 mappings are represented by a directed graph of layers, whose end nodes are *DataLayers* and whose internal nodes are *TranslationLayers*. In this way, a raw memory image in the LiME file format and a page file can be combined to form a single Intel virtual memory layer. When requesting addresses from the Intel layer, it will use the Intel memory mapping algorithm, along with the address of the directory table base or page table map, to translate that address into a physical address, which will then either be directed towards the swap layer or the LiME layer. Should it be directed towards the LiME layer, the LiME file format algorithm will be translate the new address to determine where within the file the data is stored. When the *layer.read()* method is called, the translation is done automatically and the correct data gathered and combined.

Note: Volatility 2 had a similar concept, called address spaces, but these could only stack linearly one on top of another.

The list of layers supported by volatility can be determined by running the *frameworkinfo* plugin.

1.2 Templates and Objects

Once we can address contiguous chunks of memory with a means to translate a virtual address (as seen by the programs) into the actual data used by the processor, we can start pulling out *Objects* by taking a *Template* and constructing it on the memory layer at a specific offset. A *Template* contains all the information you can know about the structure of the object without actually being populated by any data. As such a *Template* can tell you the size of a structure and its members, how far into the structure a particular member lives and potentially what various values in that field would mean, but not what resides in a particular member.

Using a *Template* on a memory layer at a particular offset, an *Object* can be constructed. In Volatility 3, once an *Object* has been created, the data has been read from the layer and is not read again. An object allows its members

to be interrogated and in particular allows pointers to be followed, providing easy access to the data contained in the object.

Note: Volatility 2 would re-read the data which was useful for live memory forensics but quite inefficient for the more common static memory analysis typically conducted. Volatility 3 requires that objects be manually reconstructed if the data may have changed. Volatility 3 also constructs actual Python integers and floats whereas Volatility 2 created proxy objects which would sometimes cause problems with type checking.

1.3 Symbol Tables

Most compiled programs know of their own templates, and define the structure (and location within the program) of these templates as a *Symbol*. A *Symbol* is often an address and a template and can be used to refer to either independently. Lookup tables of these symbols are often produced as debugging information alongside the compilation of the program. Volatility 3 provides access to these through a *SymbolTable*, many of which can be collected within a *Context* as a *SymbolSpace*. A *Context* can store only one *SymbolSpace* at a time, although a *SymbolSpace* can store as many *SymbolTable* items as necessary.

Volatility 3 uses the de facto naming convention for symbols of *module!symbol* to refer to them. It reads them from its own JSON formatted file, which acts as a common intermediary between Windows PDB files, Linux DWARF files, other symbol formats and the internal Python format that Volatility 3 uses to represent a *Template* or a *Symbol*.

Note: Volatility 2's name for a *SymbolSpace* was a profile, but it could not differentiate between symbols from different modules and required special handling for 32-bit programs that used Wow64 on Windows. This meant that all symbols lived in a single namespace with the possibility of symbol name collisions. It read the symbols using a format called *vtypes*, written in Python code directly. This made it less transferable or able to be used by other software.

1.4 Plugins

A plugin acts as a means of requesting data from the user interface (and so the user) and then using it to carry out a specific form of analysis on the *Context* (containing whatever symbol tables and memory layers it may). The means of communication between the user interface and the library is the configuration tree, which is used by components within the *Context* to store configurable data. After the plugin has been run, it then returns the results in a specific format known as a *TreeGrid*. This ensures that the data can be handled by consumers of the library, without knowing exactly what the data is or how it's formatted.

1.5 Output Renderers

User interfaces can choose how best to present the output of the results to their users. The library always responds from every plugin with a *TreeGrid*, and the user interface can then determine how best to display it. For the Command Line Interface, that might be via text output as a table, or it might output to an SQLite database or a CSV file. For a web interface, the best output is probably as JSON where it could be displayed as a table, or inserted into a database like Elastic Search and trawled using an existing frontend such as Kibana.

The renderers only need to know how to process very basic types (booleans, strings, integers, bytes) and a few additional specific ones (disassembly and various absent values).

1.6 Configuration Tree

The configuration tree acts as the interface between the calling program and Volatility 3 library. Elements of the library (such as a *Plugin*, a *TranslationLayer*, an *Automagic*, etc.) can use the configuration tree to inform the calling program of the options they require and/or optionally support, and allows the calling program to provide that information when the library is then called.

1.7 Automagic

There are certain setup tasks that establish the context in a way favorable to a plugin before it runs, removing several tasks that are repetitive and also easy to get wrong. These are called *Automagic*, since they do things like magically taking a raw memory image and automatically providing the plugin with an appropriate Intel translation layer and an accurate symbol table without either the plugin or the calling program having to specify all the necessary details.

Note: Volatility 2 used to do this as well, but it wasn't a particularly modular mechanism, and was used only for stacking address spaces (rather than identifying profiles), and it couldn't really be disabled/configured easily. Automagics in Volatility 3 are a core component which consumers of the library can call or not at their discretion.

WRITING PLUGINS

2.1 How to Write a Simple Plugin

This guide will step through how to construct a simple plugin using Volatility 3.

The example plugin we'll use is *DllList*, which features the main traits of a normal plugin, and reuses other plugins appropriately.

Note: This document will not include the complete code necessary for a working plugin (such as imports, etc) since it's designed to focus on the necessary components for writing a plugin. For complete and functioning plugins, the `framework/plugins` directory should be consulted.

2.1.1 Inherit from PluginInterface

The first step is to define a class that inherits from *PluginInterface*. Volatility automatically finds all plugins defined under the various plugin directories by importing them and then making use of any classes that inherit from *PluginInterface*.

```
from volatility3.framework import interfaces

class DllList(interfaces.plugins.PluginInterface):
```

The next step is to define the requirements of the plugin, these will be converted into options the user can provide based on the User Interface.

2.1.2 Define the plugin requirements

These requirements are the names of variables that will need to be populated in the configuration tree for the plugin to be able to run properly. Any that are defined as optional need not necessarily be provided.

```
_version = (1, 0, 0)
_required_framework_version = (2, 0, 0)

@classmethod
def get_requirements(cls):
    return [requirements.ModuleRequirement(name = 'kernel', description = 'Windows kernel
↪',
                                           architectures = ["Intel32", "Intel64"])]
```

(continues on next page)

(continued from previous page)

```
requirements.ListRequirement(name = 'pid',
                             element_type = int,
                             description = "Process IDs to include (all
↳ other processes are excluded)",
                             optional = True),
requirements.PluginRequirement(name = 'pslist',
                               plugin = pslist.PsList,
                               version = (2, 0, 0))]
```

This is a classmethod, because it is called before the specific plugin object has been instantiated (in order to know how to instantiate the plugin). At the moment these requirements are fairly straightforward:

```
requirements.ModuleRequirement(name = 'kernel', description = 'Windows kernel',
                              architectures = ["Intel32", "Intel64"]),
```

This requirement specifies the need for a particular submodule. Each module requires a *TranslationLayer* and a *SymbolTable*, which are fulfilled by two subrequirements: a *TranslationLayerRequirement* and a *SymbolTableRequirement*. At the moment, the automagic only fills *ModuleRequirements* with kernels, and so has relatively few parameters. It requires the architecture for the underlying *TranslationLayer*, and the offset of the module within that layer.

The name of the module will be stored in the `kernel` configuration option, and the module object itself can be accessed from the `context.modules` collection. This requirement is a Complex Requirement and therefore will not be requested directly from the user.

Note: In previous versions of volatility 3, there was no *ModuleRequirement*, and instead two requirements were defined a *TranslationLayer* and a *SymbolTableRequirement*. These still exist, and can be used, most plugins just define a single *ModuleRequirement* for the kernel, which the automagic will populate. The *ModuleRequirement* has two automatic sub-requirements, a *TranslationLayerRequirement* and a *SymbolTableRequirement*, but the module also includes the offset of the module, and will allow future expansion to specify specific modules when application level plugins become more common. Below are how the requirements would be specified:

```
requirements.TranslationLayerRequirement(name = 'primary',
                                         description = 'Memory layer for the kernel',
                                         architectures = ["Intel32", "Intel64"]),
```

This requirement indicates that the plugin will operate on a single *TranslationLayer*. The name of the loaded layer will appear in the plugin's configuration under the name `primary`. Requirement values can be accessed within the plugin through the plugin's *config* attribute (for example `self.config['pid']`).

Note: The name itself is dynamic depending on the other layers already present in the Context. Always use the value from the configuration rather than attempting to guess what the layer will be called.

Finally, this defines that the translation layer must be on the Intel Architecture. At the moment, this acts as a filter, failing to be satisfied by memory images that do not match the architecture required.

Most plugins will only operate on a single layer, but it is entirely possible for a plugin to request two different layers, for example a plugin that carries out some form of difference or statistics against multiple memory images.

This requirement (and the next two) are known as Complex Requirements, and user interfaces will likely not directly request a value for this from a user. The value stored in the configuration tree for a *TranslationLayerRequirement* is the string name of a layer present in the context's memory that satisfies the requirement.

```
requirements.SymbolTableRequirement(name = "nt_symbols",
                                   description = "Windows kernel symbols"),
```

This requirement specifies the need for a particular *SymbolTable* to be loaded. This gets populated by various Automagic as the nearest sibling to a particular *TranslationLayerRequirement*. This means that if the *TranslationLayerRequirement* is satisfied and the Automagic can determine the appropriate *SymbolTable*, the name of the *SymbolTable* will be stored in the configuration.

This requirement is also a Complex Requirement and therefore will not be requested directly from the user.

```
requirements.ListRequirement(name = 'pid',
                             description = 'Filter on specific process IDs',
                             element_type = int,
                             optional = True),
```

The next requirement is a List Requirement, populated by integers. The description will be presented to the user to describe what the value represents. The optional flag indicates that the plugin can function without the pid value being defined within the configuration tree at all.

```
requirements.PluginRequirement(name = 'pslist',
                              plugin = pslist.PsList,
                              version = (2, 0, 0))]
```

This requirement indicates that the plugin will make use of another plugin's code, and specifies the version requirements on that plugin. The version is specified in terms of Semantic Versioning meaning that, to be compatible, the major versions must be identical and the minor version must be equal to or higher than the one provided. This requirement does not make use of any data from the configuration, even if it were provided, it is merely a functional check before running the plugin. To define the version of a plugin, populate the *_version* class variable as a tuple of version numbers (*major, minor, patch*). So for example:

```
_version = (1, 0, 0)
```

The plugin may also require a specific version of the framework, and this also uses Semantic Versioning, and can be set by defining the *_required_framework_version*. The major version should match the version of volatility the plugin is to be used with, which at the time of writing would be 2.2.0, and so would be specified as below. If only features, for example, from 2.0.0 are used, then the lowest applicable version number should be used to support the greatest number of installations:

```
_required_framework_version = (2, 0, 0)
```

2.1.3 Define the *run* method

The run method is the primary method called on a plugin. It takes no parameters (these have been passed through the context's configuration tree, and the context is provided at plugin initialization time) and returns an unpopulated *TreeGrid* object. These are typically constructed based on a generator that carries out the bulk of the plugin's processing. The *TreeGrid* also specifies the column names and types that will be output as part of the *TreeGrid*.

```
def run(self):

    filter_func = pslist.PsList.create_pid_filter(self.config.get('pid', None))
    kernel = self.context.modules[self.config['kernel']]
```

(continues on next page)

(continued from previous page)

```

return renderers.TreeGrid([("PID", int),
                           ("Process", str),
                           ("Base", format_hints.Hex),
                           ("Size", format_hints.Hex),
                           ("Name", str),
                           ("Path", str)],
                           self._generator(pslist.PsList.list_processes(self.context,
                                                                           kernel.layer_
↳name,
                                                                           kernel.symbol_
↳table_name,
                                                                           filter_func =
↳filter_func)))

```

In this instance, the plugin constructs a filter (using the PsList plugin's *classmethod* for creating filters). It checks the plugin's configuration for the pid value, and passes it in as a list if it finds it, or None if it does not. The *create_pid_filter()* method accepts a list of process identifiers that are included in the list. If the list is empty, all processes are returned.

The next line specifies the columns by their name and type. The types are simple types (int, str, bytes, float, and bool) but can also provide hints as to how the output should be displayed (such as a hexadecimal number, using *volatility3.framework.renderers.format_hints.Hex*). This indicates to user interfaces that the value should be displayed in a particular way, but does not guarantee that the value will be displayed that way (for example, if it doesn't make sense to do so in a particular interface).

Finally, the generator is provided. The generator accepts a list of processes, which is gathered using a different plugin, the *PsList* plugin. That plugin features a *classmethod*, so that other plugins can call it. As such, it takes all the necessary parameters rather than accessing them from a configuration. Since it must be portable code, it takes a context, as well as the layer name, symbol table and optionally a filter. In this instance we unconditionally pass it the values from the configuration for the layer and symbol table from the kernel module object, constructed from the kernel configuration requirement. This will generate a list of *EPROCESS* objects, as provided by the PsList plugin, and is not covered here but is used as an example for how to share code across plugins (both as the provider and the consumer of the shared code).

2.1.4 Define the generator

The *TreeGrid* can be populated without a generator, but it is quite a common model to use. This is where the main processing for this plugin lives.

```

def _generator(self, procs):

    for proc in procs:

        for entry in proc.load_order_modules():

            BaseDllName = FullDllName = renderers.UnreadableValue()
            try:
                BaseDllName = entry.BaseDllName.get_string()
                # We assume that if the BaseDllName points to an invalid buffer, so will
↳FullDllName
                FullDllName = entry.FullDllName.get_string()
            except exceptions.InvalidAddressException:

```

(continues on next page)

(continued from previous page)

```

        pass

        yield (0, (proc.UniqueProcessId,
                    proc.ImageFileName.cast("string", max_length = proc.ImageFileName.
↪ vol.count,
                                errors = 'replace'),
                    format_hints.Hex(entry.DllBase), format_hints.Hex(entry.
↪ SizeOfImage),
                    BaseDllName, FullDllName))

```

This iterates through the list of processes and for each one calls the `load_order_modules()` method on it. This provides a list of the loaded modules within the process.

The plugin then defaults the `BaseDllName` and `FullDllName` variables to an `UnreadableValue`, which is a way of indicating to the user interface that the value couldn't be read for some reason (but that it isn't fatal). There are currently four different reasons a value may be unreadable:

- **Unreadable**: values which are empty because the data cannot be read
- **Unparsable**: values which are empty because the data cannot be interpreted correctly
- **NotApplicable**: values which are empty because they don't make sense for this particular entry
- **NotAvailable**: values which cannot be provided now (but might in a future run, via new symbols or an updated plugin)

This is a safety provision to ensure that the data returned by the Volatility library is accurate and describes why information may not be provided.

The plugin then takes the process's `BaseDllName` value, and calls `get_string()` on it. All structure attributes, as defined by the symbols, are directly accessible and use the case-style of the symbol library it came from (in Windows, attributes are CamelCase), such as `entry.BaseDllName` in this instance. Any attributes not defined by the symbol but added by Volatility extensions cannot be properties (in case they overlap with the attributes defined in the symbol libraries) and are therefore always methods and prepended with `get_`, in this example `BaseDllName.get_string()`.

Finally, `FullDllName` is populated. These operations read from memory, and as such, the memory image may be unable to read the data at a particular offset. This will cause an exception to be thrown. In Volatility 3, exceptions are thrown as a means of communicating when something exceptional happens. It is the responsibility of the plugin developer to appropriately catch and handle any non-fatal exceptions and otherwise allow the exception to be thrown by the user interface.

In this instance, the `InvalidAddressException` class is caught, which is thrown by any layer which cannot access an offset requested of it. Since we have already populated both values with `UnreadableValue` we do not need to write code for the exception handler.

Finally, we yield the record in the format required by the `TreeGrid`, a tuple, listing the indentation level (for trees) and then the list of values for each column. This plugin demonstrates casting a value `ImageFileName` to ensure it's returned as a string with a specific maximum length, rather than its original type (potentially an array of characters, etc). This is carried out using the `cast()` method which takes a type (either a native type, such as string or pointer, or a structure type defined in a `SymbolTable` such as `<table>!_UNICODE`) and the parameters to that type.

Since the cast value must populate a string typed column, it had to be a Python string (such as being cast to the native type string) and could not have been a special Structure such as `_UNICODE`. For the format hint columns, the format hint type must be used to ensure the error checking does not fail.

2.2 Writing more advanced Plugins

There are several common tasks you might wish to accomplish, there is a recommended means of achieving most of these which are discussed below.

2.2.1 Writing Reusable Methods

Classes which inherit from *PluginInterface* all have a `run()` method which takes no parameters and will return a *TreeGrid*. Since most useful functions are parameterized, to provide parameters to a plugin the *configuration* for the context must be appropriately manipulated. There is scope for this, in order to run multiple plugins (see *Writing plugins that run other plugins*) but a much simpler method is to provide a parameterized *classmethod* within the plugin, which will allow the method to yield whatever kind of output it will generate and take whatever parameters it might need.

This is how processes are listed, which is an often used function. The code lives within the *PsList* plugin but can be used by other plugins by providing the appropriate parameters (see *list_processes()*). It is up to the author of a plugin to validate that any required plugins are present and are the appropriate version.

2.2.2 Writing plugins that run other plugins

Occasionally plugins will want to process the output from other plugins (for example, the *timeliner* plugin which runs all other available plugins that feature a *Timeliner* interface). This can be achieved with the following example code:

```
automagics = automagic.choose_automagic(automagic.available(self._context), plugin_class)
plugin = plugins.construct_plugin(self.context, automagics, plugin_class, self.config_
↳ path,
                                self._progress_callback, self.open)
```

This code will first generate suitable automagics for running against the context. Unfortunately this must be re-run for each plugin in order to populate the context's configuration correctly based on the plugin's requirements (which may vary between plugins). Once the automagics have been constructed, the plugin can be instantiated using the helper function *construct_plugin()* providing:

- the base context (containing the configuration and any already loaded layers or symbol tables),
- the plugin class to run,
- the configuration path within the context for the plugin
- any callback to determine progress in lengthy operations
- an open method for the plugin to create files during the run

With the constructed plugin, it can either be run by calling its *run()* method, or any other known method can be invoked on it.

2.2.3 Writing plugins that output files

Every plugin can create files, but since the user interface must decide how to actually provide these files to the user, an abstraction layer is used.

The user interface specifies an `open_method` (which is actually a class constructor that can double as a python `ContextManager`, so it can be used by the python `with` keyword). This is set on the plugin using `plugin.set_open_method` and can then be called or accessed using `plugin.open(preferred_filename)`. There are no additional options that can be set on the filename, and a `FileHandlerInterface` is the result. This mimics an `IO[bytes]` object, which closely mimics a standard python file-like object.

As such code for outputting to a file would be expected to look something like:

```
with self.open(preferred_filename) as file_handle:
    file_handle.write(data)
```

Since `self.open` returns a `ContextManager` the file is closed automatically and thus committed for the UI to process as necessary. If the file is not closed, the UI may not be able to properly process it and unexpected results may arise. In certain instances you may receive a `file_handle` from another plugin's method, in which case the file is unlikely to be closed to allow the preferred filename to be changed (or data to be added/modified, if necessary).

2.2.4 Writing Scanners

Scanners are objects that adhere to the `ScannerInterface`. They are passed to the `scan()` method on layers which will divide the provided range of sections (or the entire layer if none are provided) and call the `ScannerInterface()`'s `call_method` method with each chunk as a parameter, ensuring a suitable amount of overlap (as defined by the scanner). The offset of the chunk, within the layer, is also provided as a parameter.

Scanners can technically maintain state, but it is not recommended since the ordering that the chunks are scanned is not guaranteed. Scanners may be executed in parallel if they mark themselves as `thread_safe` although the threading technique may be either standard threading or multiprocessing. Note, the only component of the scans which is parallelized are those that go on within the scan method. As such, any processing carried out on the results yielded by the scanner will be processed in serial. It should also be noted that generating the addresses to be scanned are not iterated in parallel (in full, before the scanning occurs), meaning the smaller the sections to scan the quicker the scan will run.

Empirically it was found that scanners are typically not the most time intensive part of plugins (even those that do extensive scanning) and so parallelism does not offer significant gains. As such, parallelism is not enabled by default but interfaces can easily enable parallelism when desired.

2.2.5 Writing/Using Intermediate Symbol Format Files

It can occasionally be useful to create a data file containing the static structures that can create a `Template` to be instantiated on a layer. Volatility has all the machinery necessary to construct these for you from properly formatted JSON data.

The JSON format is documented by the JSON schema files located in schemas. These are versioned using standard .so library versioning, so they may not increment as expected. Each schema lists an available version that can be used, which specifies five different sections:

- `Base_types` - These are the basic type names that will make up the native/primitive types
- `User_types` - These are the standard definitions of type structures, most will go here
- `Symbols` - These list offsets that are associated with specific names (and can be associated with specific type names)
- `Enums` - Enumerations that offer a number of choices

- Metadata - This is information about the generator, when the file was generated and similar

Constructing an appropriate file, the file can be loaded into a symbol table as follows:

```
table_name = intermed.IntermediateSymbolTable.create(context, config_path, 'sub_path',
↪ 'filename')
```

This code will load a JSON file from one of the standard symbol paths (volatility3/symbols and volatility3/framework/symbols) under the additional directory `sub_path`, with a name matching `filename.json` (the extension should not be included in the filename).

The `sub_path` parameter acts as a filter, so that similarly named symbol tables for each operating system can be addressed separately. The top level directories which `sub_path` filters are also checked as zipfiles to determine any symbols within them. As such, group of symbol tables can be included in a single zip file. The filename for the symbol tables should not contain an extension, as extensions for JSON (and compressed JSON files) will be tested to find a match.

Additional parameters exist, such as `native_types` which can be used to provide pre-populated native types.

Another useful parameter is `table_mapping` which allows for type referenced inside the JSON (such as `one_table!type_name`) would allow remapping of `one_table` to `another_table` by providing a dictionary as follows:

```
table_name = intermed.IntermediateSymbolTable.create(context, config_path, 'sub_path',
↪ 'filename',
    table_mapping = {'one_table': 'another_table'})
```

The last parameter that can be used is called `class_types` which allows a particular structure to be instantiated on a class other than `StructType`, allowing for additional methods to be defined and associated with the type.

The table name can then be used to access the constructed table from the context, such as:

```
context.symbol_space[table_name]
```

2.2.6 Writing new Translation Layers

Translation layers offer a way for data to be translated from a higher (domain) layer to a lower (range) layer. The main method that must be overloaded for a translation layer is the `mapping` method. Usually this is a linear mapping whereby a value at an offset in the domain maps directly to an offset in the range.

Most new layers should inherit from `LinearlyMappedLayer` where they can define a mapping method as follows:

```
def mapping(self,
            offset: int,
            length: int,
            ignore_errors: bool = False) -> Iterable[Tuple[int, int, int, int, str]]:
```

This takes a (domain) offset and a length of block, and returns a sorted list of chunks that cover the requested amount of data. Each chunk contains the following information, in order:

offset (domain offset)

requested offset in the domain

chunk length

the length of the data in the domain

mapped offset (range offset)

where the data lives in the lower layer

mapped length

the length of the data in the range

layer_name

the layer that this data comes from

An example (and the most common layer encountered in memory forensics) would be an Intel layer, which models the intel page mapping system. Based on a series of tables stored within the layer itself, an intel layer can convert a virtual address to a physical address. It should be noted that intel layers allow multiple virtual addresses to map to the same physical address (but a single virtual address cannot ever map to more than one physical address).

As a simple example, in a virtual layer which looks like *abracadabra* but maps to a physical layer that looks like *abcd*, requesting *mapping(5, 4)* would return:

```
[(5,1,0,1, 'physical_layer'),
 (6,1,3,1, 'physical_layer'),
 (7,2,0,2, 'physical_layer')
]
```

This mapping mechanism allows for great flexibility in that chunks making up a virtual layer can come from multiple different range layers, allowing for swap space to be used to construct the virtual layer, for example. Also, by defining the mapping method, the read and write methods (which read and write into the domain layer) are defined for you to write to the lower layers (which in turn can write to layers even lower than that) until eventually they arrive at a *DataLayer*, such as a file or a buffer.

This mechanism also allowed for some minor optimization in scanning such a layer, but should further control over the scanning of layers be needed, please refer to the Layer Scanning page.

Whilst it may seem as though some of the data seems redundant (the length values are always the same) this is not the case for *NonLinearlySegmentedLayer*. These layers do not guarantee that each domain address maps directly to a range address, and in fact can carry out processing on the data. These layers are most commonly encountered as compression or encryption layers (whereby a domain address may map into a chunk of the range, but not directly). In this instance, the mapping will likely define additional methods that can take a chunk and process it from its original value into its final value (such as decompressing for read and compressing for write).

These methods are private to the class, and are used within the standard *read* and *write* methods of a layer. A non-linear layer's mapping method should return the data required to be able to return the original data. As an example, a run length encoded layer, whose domain data looks like *aaabbbbbcdddd* could be stored as *3a5b1c4d*. The mapping method call for *mapping(5,4)* should return all the regions that encompass the data required. The layer would return the following data:

```
[(5, 4, 2, 4, 'rle layer')]
```

It would then define *_decode* and *_encode* methods that could convert from one to the other. In the case of *read(5, 4)*, the *_decode* method would be provided with the following parameters:

```
data = "5b1c"
mapped_offset = 2
offset = 5
output_length = 4
```

This requires that the *_decode* method can unpack the encoding back to *bbbbc* and also know that the decoded block starts at 3, so that it can return just *bbbc*, as required. Such layers therefore typically need to keep much more internal state, to keep track of which offset of encoded data relates to which decoded offset for both the mapping and *_encode* and *_decode* methods.

If the data processing produces known fixed length values, then it is possible to write an *_encode* method in much the same way as the decode method. *_encode* is provided with the data to encode, the mapped_offset to write it to the lower (range) layer, the original offset of the data in the higher (domain) layer and the value of the not yet encoded data to write. The encoded result, regardless of length will be written over the current image at the mapped_offset. No other changes or updates to tables, etc are carried out.

`_encode` is much more difficult if the encoded data can be variable length, as it may involve rewriting most, if not all of the data in the image. Such a situation is not currently supported with this API and it is strongly recommended to raise `NotImplementedError` in this method.

Communicating between layers

Layers can ask for information from lower layers using the `layer.metadata` lookup. In the following example, a `LayerStacker` automagic that generates the intel `TranslationLayer` requests whether the base layer knows what the `page_map_offset` value should be, a `CrashDumpLayer` would have that information. As such the `TranslationLayer` would just lookup the `page_map_offset` value in the `base_layer.metadata` dictionary:

```
if base_layer.metadata.get('page_layer_offset', None) is not None:
```

Most layers will return `None`, since this is the default, but the `CrashDumpLayer` may know what the value should be, so it therefore populates the `metadata` property. This is defined as a read-only mapping to ensure that every layer includes data from every underlying layer. As such, `CrashDumpLayer` would actually specify this value by setting it in the protected dictionary by `self._direct_metadata['page_map_offset']`.

There is, unfortunately, no easy way to form consensus between a particular layer may want and what a particular layer may be able to provide. At the moment, the main information that layers may populate are:

- `os` with values of *Windows*, *Linux*, *Mac* or *unknown*
- `architecture` with values of *Intel32*, *Intel64* or *unknown*
- `pae` a boolean specifying whether the PAE mode is enabled for windows
- `page_map_offset` the value pointing to the intel `page_map_offset`

Any value can be specified and used by layers but consideration towards ambiguity should be used to ensure that overly generic names aren't used for something and then best describe something else that may be needed later on.

Note: The data stored in metadata is *not* restored when constructed from a configuration, so metadata should only be used as a temporary means of storing information to be used in constructing later objects and all information required to recreate an object must be written through the requirements mechanism.

2.2.7 Writing new Templates and Objects

In most cases, a whole new type of object is unnecessary. It will usually be derived from an `StructType` (which is itself just another name for a `AggregateType`, but it's better to use `StructType` for readability).

This can be used as a class override for a particular symbol table, so that an existing structure can be augmented with additional methods. An example of this would be:

```
symbol_table = contexts.symbol_space[symbol_table_name]
symbol_table.set_type_class('<structure_name>', NewStructureClass)
```

This will mean that when a specific structure is loaded from the `symbol_space`, it is not constructed as a standard `StructType`, but instead is instantiated using the `NewStructureClass`, meaning new methods can be called directly on it.

If the situation really calls for an entirely new object, that isn't covered by one of the existing `PrimitiveObject` objects (such as `Integer`, `Boolean`, `Float`, `Char`, `Bytes`) or the other builtins (such as `Array`, `Bitfield`, `Enumeration`, `Pointer`, `String`, `Void`) then you can review the following information about defining an entirely new object.

All objects must inherit from *ObjectInterface* which defines a constructor that takes a context, a *type_name*, an *ObjectInformation* object and then can accept additional keywords (which will not necessarily be provided if the object is constructed from a JSON reference).

The *ObjectInformation* class contains all the basic elements that define an object, which include:

- *layer_name*
- *offset*
- *member_name*
- *parent*
- *native_layer_name*
- *size*

The *layer_name* and *offset* are how volatility reads the data of the object. Since objects can reference other objects (specifically pointers), and contain values that are used as offsets in a particular layer, there is also the concept of a *native_layer_name*. The *native_layer_name* allows an object to be constructed based on physical data (for instance) but to reference virtual addresses, or for an object in the kernel virtual layer to reference offsets in a process virtual layer.

The *member_name* and *parent* are optional and are used for when an object is constructed as a member of a structure. The *parent* points back to the object that created this one, and *member_name* is the name of the attribute of the parent used to get to this object.

Finally, some objects are dynamically sized, and this *size* parameter allows a constructor to specify how big the object should be. Note, the *size* can change throughout the lifespan of the object, and the object will need to ensure that it compensates for such a change.

Objects must also contain a specific class called *VolTemplateProxy* which must inherit from *ObjectInterface*. This is used to access information about a structure before it has been associated with data and becomes an Object. The *VolTemplateProxy* class contains a number of abstract classmethods, which take a *Template*. The main method that is likely to need overwriting is the *size* method, which should return the size of the object (for the template of a dynamically-sized object, this should be a suitable value, and calculated based on the best available information). For most objects, this can be determined from the JSON data used to construct a normal *Struct* and therefore only needs to be defined for very specific objects.

2.3 Using Volatility 3 as a Library

This portion of the documentation discusses how to access the Volatility 3 framework from an external application.

The general process of using volatility as a library is to as follows:

1. *Creating a context*
2. (Optional) *Determine what plugins are available*
3. (Optional) *Determine what configuration options a plugin requires*
4. *Set the configuration in the context*
5. (Optional) *Using automagic to complete the configuration*
6. *Run the plugin*
7. *Render the TreeGrid*

2.3.1 Creating a context

First we make sure the volatility framework works the way we expect it (and is the version we expect). The versioning used is semantic versioning, meaning any version with the same major number and a higher or equal minor number will satisfy the requirement. An example is below since the CLI doesn't need any of the features from versions 1.1 or 1.2:

```
volatility3.framework.require_interface_version(1, 0, 0)
```

Contexts can be spun up quite easily, just construct one. It's not a singleton, so multiple contexts can be constructed and operate independently, but be aware of which context you're handing where and make sure to use the correct one. Typically once a context has been handed to a plugin, all objects will be created with a reference to that context.

```
ctx = contexts.Context() # Construct a blank context
```

2.3.2 Determine what plugins are available

You can also interrogate the framework to see which plugins are available. First we have to try to load all available plugins. The `import_files()` method will automatically use the module paths for the provided module (in this case, `volatility3.plugins`) and walk the directory (or directories) loading up all python files. Any import failures will be provided in the failures return value, unless the second parameter is `False` in which case the call will raise any exceptions encountered. Any additional directories containing plugins should be added to the `__path__` attribute for the `volatility3.plugins` module. The standard paths should generally also be included, which can be found in `volatility3.constants.PLUGINS_PATH`.

```
volatility3.plugins.__path__ = <new_plugin_path> + constants.PLUGINS_PATH
failures = framework.import_files(volatility3.plugins, True)
```

Note: Volatility uses the `volatility3.plugins` namespace for all plugins (including those in `volatility3.framework.plugins`). Please ensure you only use `volatility3.plugins` and only ever import plugins from this namespace. This ensures the ability of users to override core plugins without needing write access to the framework directory.

Once the plugins have been imported, we can interrogate which plugins are available. The `list_plugins()` call will return a dictionary of plugin names and the plugin classes.

```
plugin_list = framework.list_plugins()
```

2.3.3 Determine what configuration options a plugin requires

For each plugin class, we can call the classmethod `get_requirements()` on it, which will return a list of objects that adhere to the `RequirementInterface` method. The various types of Requirement are split roughly in two, `SimpleTypeRequirement` (such as integers, booleans, floats and strings) and more complex requirements (such as lists, choices, multiple requirements, translation layer requirements or symbol table requirements). A requirement just specifies a type of data and a name, and must be combined with a configuration hierarchy to have meaning.

List requirements are a list of simple types (integers, booleans, floats and strings), choices must match the available options, multiple requirements needs all their subrequirements fulfilled and the other types require the names of valid translation layers or symbol tables within the context, respectively. Luckily, each of these requirements can tell you whether they've been fulfilled or not later in the process. For now, they can be used to ask the user to fill in any parameters they made need to. Some requirements are optional, others are not.

The plugin is essentially a multiple requirement. It should also be noted that automagic classes can have requirements (as can translation layers).

2.3.4 Set the configuration in the context

Once you know what requirements the plugin will need, you can populate them within the *context.config*. The configuration is essentially a hierarchical tree of values, much like the windows registry. Each plugin is instantiated at a particular branch within the hierarchy and will look for its configuration options under that hierarchy (if it holds any configurable items, it will likely instantiate those at a point underneath its own branch). To set the hierarchy, you'll need to know where the configurables will be constructed.

For this example, we'll assume plugins' *base_config_path* is set as *plugins*, and that automagics are configured under the *automagic* tree. We'll see later how to ensure this matches up with the plugins and automagic when they're constructed. Joining configuration options should always be carried out using *path_join()* in case the separator value gets changed in the future. Configuration items can then be set as follows:

```
config_path = path_join(base_config_path, plugin.__class__.__name__, <plugin_parameter>)
context.config['plugins.<plugin_class_name>.<plugin_parameter>'] = value
```

2.3.5 Using automagic to complete the configuration

Many of the options will require a lot of construction (layers on layers on layers). The automagic functionality is there to help take some of that burden away. There are automagics designed to stack layers (such as compression and file formats, as well as architectures) and automagics for determining critical information from windows, linux and mac layers about the operating system. The list of available automagics can be found using:

```
available_automagics = automagic.available(ctx)
```

This again, will require that all automagic modules have been loaded but this should happen simply as part of importing the *automagic* module. The available list will be pre-instantiated copies of the automagic with their configuration path and context provided (based on *constants.AUTOMAGIC_CONFIG_PATH* and the automagic class name).

A suitable list of automagics for a particular plugin (based on operating system) can be found using:

```
automagics = automagic.choose_automagic(available_automagics, plugin)
```

This will take the plugin module, extract the operating system (first level of the hierarchy) and then return just the automagics which apply to the operating system. Each automagic can exclude itself from being used for specific operating systems, so that an automagic designed for linux is not used for windows or mac plugins.

These automagics can then be run by providing the list, the context, the plugin to be run, the hierarchy name that the plugin will be constructed on ('plugins' by default) and a *progress_callback*. This is a callable which takes a percentage of completion and a description string and will be called throughout the process to indicate to the user how much progress has been made.

```
errors = automagic.run(automagics, context, plugin, base_config_path, progress_callback,
↳ progress_callback)
```

Any exceptions that occur during the execution of the automagic will be returned as a list of exceptions.

2.3.6 Run the plugin

Firstly, we should check whether the plugin will be able to run (ie, whether the configuration options it needs have been successfully set). We do this as follow (where `plugin_config_path` is the `base_config_path` (which defaults to *plugins* and then the name of the class itself):

```
unsatisfied = plugin.unsatisfied(context, plugin_config_path)
```

If `unsatisfied` is an empty list, then the plugin has been given everything it requires. If not, it will be a Dictionary of the hierarchy paths and their associated requirements that weren't satisfied.

The plugin can then be instantiated with the context (containing the plugin's configuration) and the path that the plugin can find its configuration at. This configuration path only needs to be a unique value to identify where the configuration details can be found, similar to a registry key in Windows.

A `progress_callback` can also be provided to give users feedback whilst the plugin is running. A progress callback is a function (callable) that takes a percentage and a descriptive string. User interfaces implementing these can therefore provide progress feedback to a user, as the framework will call these every so often during intensive actions, to update the user as to how much has been completed so far.

Also, should the plugin produce files, an `open_method` can be set on the plugin, which will be called whenever a plugin produces an auxiliary file.

```
constructed = plugin(context, plugin_config_path, progress_callback = progress_callback)
constructed.set_open_method(file_handler)
```

The `file_handler` must adhere to the [FileHandlerInterface](#), which represents an `IO[bytes]` object but also contains a `preferred_filename` attribute as a hint indicating what the file being produced should be called. When a plugin produces a new file, rather than opening it with the python `open` method, it will use the `FileHandlerInterface` and construct it with a descriptive filename, and then write bytes to it using the `write` method, just like other python file-like objects. This allows web user interfaces to offer the files for download, whilst CLIs to write them to disk and other UIs to handle files however they need.

All of this functionality has been condensed into a framework method called `construct_plugin` which will take and run the automagics, and instantiate the plugin on the provided `base_config_path`. It also accepts an optional `progress_callback` and an optional `file_consumer`.

```
constructed = plugins.construct_plugin(ctx, automagics, plugin, base_config_path,
↪progress_callback, file_consumer)
```

Finally the plugin can be run, and will return a [TreeGrid](#).

```
treegrid = constructed.run()
```

2.3.7 Render the TreeGrid

The results are now in a structure of rows, with a hierarchy (allowing a row to be a child of another row).

The `TreeGrid` can tell you what columns it contains, and the types of each column, but does not contain any data yet. It must first be populated. This actually iterates through the results of the plugin, which may have been provided as a generator, meaning this step may take the actual processing time, whilst the plugin does the actual work. This can return an exception if one occurs during the running of the plugin.

The results can be accessed either as the results are being processed, or by visiting the nodes in the tree once it is fully populated. In either case, a visitor method will be required. The visitor method should accept a [TreeNode](#) and an *accumulator*. It will return an updated accumulator.

When provided a [TreeNode](#), it can be accessed as a dictionary based on the column names that the treegrid contains. It should be noted that each column can contain only the type specified in the *column.type* field (which can be a simple type like string, integer, float, bytes or a more complex type, like a `DateTime`, a `Disassembly` or a descendant of [BaseAbsentValue](#)). The various fields may also be wrapped in *format_hints* designed to tell the user interface how to render the data. These hints can be things like `Bin`, `Hex` or `HexBytes`, so that fields like offsets are displayed in hex form or so that bytes are displayed in their hex form rather than their raw form. Descendants of [BaseAbsentValue](#) can currently be one of [UnreadableValue](#), [UnparsableValue](#), [NotApplicableValue](#) or [NotAvailableValue](#). These indicate that data could not be read from the memory for some reason, could not be parsed properly, was not applicable or was not available.

A simple text renderer (that returns output immediately) would appear as follows. This doesn't use the accumulator, but instead uses `print` to directly produce the output. This is not recommended:

```
for column in grid.columns:
    print(column.name)

def visitor(node, _accumulator):
    # Nodes always have a path value, giving them a path_depth of at least 1, we use max_
    ↪ just in case
    print(" " * max(0, node.path_depth - 1), end = " ")
    for column_index in range(len(grid.columns)):
        column = grid.columns[column_index]
        print(repr(node.values[column_index]), end = '\t')

    print('')
    return None

grid.populate(visitor, None)
```

More complex examples of renderers can be found in the default CLI implementation, such as the [QuickTextRenderer](#) or the [PrettyTextRenderer](#).

CREATING NEW SYMBOL TABLES

This page details how symbol tables are located and used by Volatility, and documents the tools and methods that can be used to make new symbol tables.

3.1 How Volatility finds symbol tables

All files are stored as JSON data, they can be in pure JSON files as `.json`, or compressed as `.json.gz` or `.json.xz`. Volatility will automatically decompress them on use. It will also cache their contents (compressed) when used, located under the user's home directory, in `.cache/volatility3`, along with other useful data. The cache directory currently cannot be altered.

Symbol table JSON files live, by default, under the `volatility3/symbols` directory. The symbols directory is configurable within the framework and can usually be set within the user interface.

These files can also be compressed into ZIP files, which Volatility will process in order to locate symbol files.

Volatility maintains a cache mapping the appropriate identifier for each symbol file against its filename. This cache is updated by automagic called as part of the standard automagic that's run each time a plugin is run. If a large number of new symbols file are detected, this may take some time, but can be safely interrupted and restarted and will not need to run again as long as the symbol files stay in the same location.

3.2 Windows symbol tables

For Windows systems, Volatility accepts a string made up of the GUID and Age of the required PDB file. It then searches all files under the configured symbol directories under the windows subdirectory. Any that contain metadata which matches the pdb name and GUID/age (or any compressed variant) will be used. If such a symbol table cannot be found, then the associated PDB file will be downloaded from Microsoft's Symbol Server and converted into the appropriate JSON format, and will be saved in the correct location.

Windows symbol tables can be manually constructed from an appropriate PDB file. The primary tool for doing this is built into Volatility 3, called `pdbconv.py`. It can be run from the top-level Volatility path, using the following command:

```
PYTHONPATH="." python volatility3/framework/symbols/windows/pdbconv.py
```

The `PYTHONPATH` environment variable is not required if the Volatility library is installed in the system's library path or a virtual environment.

3.3 Mac or Linux symbol tables

For Mac/Linux systems, both use the same mechanism for identification. The generated files contain an identifying string (the operating system banner), which Volatility's automagic can detect. Volatility caches the mapping between the strings and the symbol tables they come from, meaning the precise file names don't matter and can be organized under any necessary hierarchy under the symbols directory.

Linux and Mac symbol tables can be generated from a DWARF file using a tool called [dwarf2json](#). Currently a kernel with debugging symbols is the only suitable means for recovering all the information required by most Volatility plugins. Note that in most linux distributions, the standard kernel is stripped of debugging information and the kernel with debugging information is stored in a package that must be acquired separately.

A generic table isn't guaranteed to produce accurate results, and would reduce the number of structures that all plugins could rely on. As such, and because linux kernels with different configurations can produce different structures, volatility 3 requires that the banners in the JSON file match the banners found in the image *exactly*, not just the version number. This can include elements such as the compilation time and even the version of gcc used for the compilation. The exact match is required to ensure that the results volatility returns are accurate, therefore there is no simple means provided to get the wrong JSON ISF file to easily match.

To determine the string for a particular memory image, use the *banners* plugin. Once the specific banner is known, try to locate that exact kernel debugging package for the operating system. Unfortunately each distribution provides its debugging packages under different package names and there are so many that the distribution may not keep all old versions of the debugging symbols, and therefore **it may not be possible to find the right symbols to analyze a linux memory image with volatility**. With Macs there are far fewer kernels and only one distribution, making it easier to ensure that the right symbols can be found.

Once a kernel with debugging symbols/appropriate DWARF file has been located, [dwarf2json](#) will convert it into an appropriate JSON file. Example code for automatically creating a JSON from URLs for the kernel debugging package and the package containing the System.map, can be found in [stock-linux-json.py](#). The System.map file is recommended for completeness, but a kernel with debugging information often contains the same symbol offsets within the DWARF data, which dwarf2json can extract into the JSON ISF file.

The banners available for volatility to use can be found using the *isinfo* plugin, but this will potentially take a long time to run depending on the number of JSON files available. This will list all the JSON (ISF) files that volatility3 is aware of, and for linux/mac systems what banner string they search for. For volatility to use the JSON file, the banners must match exactly (down to the compilation date).

Note: Steps for constructing a new kernel ISF JSON file:

- Run the *banners* plugin on the image to determine the necessary kernel
 - Locate a copy of the debug kernel that matches the identified banner
 - Clone or update the dwarf2json repo: `git clone https://github.com/volatilityfoundation/dwarf2json`
 - Run `go build` in the directory if the source has changed
 - Run `dwarf2json linux --elf [path to debug kernel] > [kernel name].json`
 - For Mac change *linux* to *mac*
 - Copy the *.json* file to the symbols directory into *[symbols directory]/linux*
 - For Mac change *linux* to *mac*
-

CHANGES BETWEEN VOLATILITY 2 AND VOLATILITY 3

4.1 Library and Context

Volatility 3 has been designed from the ground up to be a library, this means the components are independent and all state required to run a particular plugin at a particular time is self-contained in an object derived from a *ContextInterface*.

The context contains the two core components that make up Volatility, layers of data and the available symbols.

4.2 Symbols and Types

Volatility 3 no longer uses profiles, it comes with an extensive library of *symbol tables*, and can generate new symbol tables for most windows memory images, based on the memory image itself. This allows symbol tables to include specific offsets for locations (symbol locations) based on that operating system in particular. This means it is easier and quicker to identify structures within an operating system, by having known offsets for those structures provided by the official debugging information.

4.3 Object Model changes

The object model has changed as well, objects now inherit directly from their Python counterparts, meaning an integer object is actually a Python integer (and has all the associated methods, and can be used wherever a normal int could). In Volatility 2, a complex proxy object was constructed which tried to emulate all the methods of the host object, but ultimately it was a different type and could not be used in the same places (critically, it could make the ordering of operations important, since $a + b$ might not work, but $b + a$ might work fine).

Volatility 3 has also had significant speed improvements, where Volatility 2 was designed to allow access to live memory images and situations in which the underlying data could change during the run of the plugin, in Volatility 3 the data is now read once at the time of object construction, and will remain static, even if the underlying layer changes. This was because live memory analysis was barely ever used, and this feature could cause a particular value to be re-read many times over for no benefit (particularly since each re-read could result in many additional image reads from following page table translations).

Finally, in order to provide Volatility specific information without impact on the ability for structures to have members with arbitrary names, all the metadata about the object (such as its layer or offset) have been moved to a read-only *vol()* dictionary.

Further the distinction between a *Template* (the thing that constructs an object) and the *Object* itself has been made more explicit. In Volatility 2, some information (such as size) could only be determined from a constructed object, leading to instantiating a template on an empty buffer, just to determine the size. In Volatility 3, templates contain information such as their size, which can be queried directly without constructing the object.

4.4 Layer and Layer dependencies

Address spaces in Volatility 2, are now more accurately referred to as *Translation Layers*, since each one typically sits atop another and can translate addresses between the higher logical layer and the lower physical layer. Address spaces in Volatility 2 were strictly limited to a stack, one on top of one other. In Volatility 3, layers can have multiple “dependencies” (lower layers), which allows for the integration of features such as swap space.

4.5 Automagic

In Volatility 2, we often tried to make this simpler for both users and developers. This resulted in something was referred to as automagic, in that it was magic that happened automatically. We’ve now codified that more, so that the automagic processes are clearly defined and can be enabled or disabled as necessary for any particular run. We also included a stacker automagic to emulate the most common feature of Volatility 2, automatically stacking address spaces (now translation layers) on top of each other.

By default the automagic chosen to be run are determined based on the plugin requested, so that linux plugins get linux specific automagic and windows plugins get windows specific automagic. This should reduce unnecessarily searching for linux kernels in a windows image, for example. At the moment this is not user configurable.

4.6 Searching and Scanning

Scanning is very similar to scanning in Volatility 2, a scanner object (such as a *BytesScanner* or *RegexScanner*) is primed with the data to be searched for, and the *scan()* method is called on the layer to be searched.

4.7 Output Rendering

This is extremely similar to Volatility 2, because we were developing it for Volatility 3 when we added it to Volatility 2. We now require that all plugins produce output in a *TreeGrid* object, which ensure that the library can be used regardless of which interface is driving it. An example web GUI is also available called Volumetric which allows all the plugins that can be run from the command line to be run from a webpage, and offers features such as automatic formatting and sorting of the data, which previously couldn’t be provided easily from the CLI.

There is also the ability to provide file output such that the user interface can provide a means to render or save those files.

VOLSHELL - A CLI TOOL FOR WORKING WITH MEMORY

Volshell is a utility to access the volatility framework interactively with a specific memory image. It allows for direct introspection and access to all features of the volatility library from within a command line environment.

5.1 Starting volshell

Volshell is started in much the same way as volatility. Rather than providing a plugin, you just specify the file. If the operating system of the memory image is known, a flag can be provided allowing additional methods for the specific operating system.

```
$ volshell.py -f <path-to-memory-image> [-w|-m|-l]
```

The flags to specify a known operating system are -w for windows, -m for mac and -l for linux. Volshell will run through the usual automagic, trying to load the memory image. If no operating system is specified, all automagic will be run.

When volshell starts, it will show the version of volshell, a brief message indicating how to get more help, the current operating system mode for volshell, and the current layer available for use.

```
Volshell (Volatility 3 Framework) 2.0.2
Readline imported successfully      PDB scanning finished

    Call help() to see available functions

Volshell mode      : Generic
Current Layer      : primary
Current Symbol Table : None
Current Kernel Name : None

(primary) >>>
```

Volshell itself is essentially a plugin, but an interactive one. As such, most values are accessed through *self* although there is also a *context* object whenever a context must be provided.

The prompt for the tool will indicate the name of the current layer (which can be accessed as *self.current_layer* from within the tool).

The generic mode is quite limited, won't have any symbols loaded and therefore won't be able to display much information. When an operating system is chosen, the appropriate symbols should be loaded and additional functions become available. The mode cannot easily be changed once the tool has started.

5.2 Accessing objects

All operating systems come with their equivalent of a process list, aliased to the function `ps()`. Running this will provide a list of volatility objects, based on the operating system in question. We will use these objects to run our examples against.

We'll start by creating a process variable, and putting the first result from `ps()` in it. Since the shell is a python environment, we can do the following:

```
(layer_name) >>> proc = ps()[0]
(layer_name) >>> proc
<EPROCESS symbol_table_name1!_EPROCESS: layer_name @ 0xe08ff2459040 #1968>
```

When printing a volatility structure, various information is output, in this case the *type_name*, the *layer* and *offset* that it's been constructed on, and the size of the structure.

We can directly access the volatility information about a structure, using the *.vol* attribute, which contains basic information such as structure size, *type_name*, and the list of members amongst others. However, volshell has a built-in mechanism for providing more information about a structure, called *display_type* or *dt*. This can be given either a type name (which if not prefixed with symbol table name, will use the kernel symbol table identified by the automagic).

```
(layer_name) >>> dt('_EPROCESS')
symbol_table_name1!_EPROCESS (1968 bytes)
    0x0 : Pcb                                symbol_table_name1!_KPROCESS
    0x2d8 : ProcessLock                      symbol_table_name1!_EX_PUSH_LOCK
    0x2e0 : RundownProtect                  symbol_table_name1!_EX_RUNDOWN_REF
    0x2e8 : UniqueProcessId                symbol_table_name1!pointer
...
```

It can also be provided with an object and will interpret the data for each in the process:

```
(layer_name) >>> dt(proc)
symbol_table_name1!_EPROCESS (1968 bytes)
    0x0 : Pcb                                symbol_table_name1!_KPROCESS
    → 0xe08ff2459040
    0x2d8 : ProcessLock                      symbol_table_name1!_EX_PUSH_LOCK
    → 0xe08ff2459318
    0x2e0 : RundownProtect                  symbol_table_name1!_EX_RUNDOWN_
    → REF                                0xe08ff2459320
    0x2e8 : UniqueProcessId                symbol_table_name1!pointer
    → 4
...
```

These values can be accessed directly as attributes

```
(layer_name) >>> proc.UniqueProcessId
356
```

Pointer structures contain the value they point to, but attributes accessed are forwarded to the object they point to. This means that pointers do not need to be explicitly dereferenced to access underlying objects.

```
(layer_name) >>> proc.Pcb.DirectoryTableBase
4355817472
```


5.3 Running plugins

It's possible to run any plugin by importing it appropriately and passing it to the `display_plugin_output` or `dpo` method. In the following example we'll provide no additional parameters. Volatility will show us which parameters were required:

```
(layer_name) >>> from volatility3.plugins.windows import pslist
(layer_name) >>> display_plugin_output(pslist.PsList)
Unable to validate the plugin requirements: ['plugins.Volshell.
↳ VH3FSA1JBG0QP9E62Z80T5UCIMLNK4.PsList.kernel']
```

We can see that it's made a temporary configuration path for the plugin, and that the `kernel` requirement was not fulfilled.

We can see all the options that the plugin can accept by access the `get_requirements()` method of the plugin. This is a classmethod, so can be called on an uninstantiated copy of the plugin.

```
(layer_name) >>> pslist.PsList.get_requirements()
[<ModuleRequirement: kernel>, <BooleanRequirement: physical>, <ListRequirement: pid>,
↳ <BooleanRequirement: dump>]
```

We can provide arguments via the `dpo` method call:

```
(layer_name) >>> display_plugin_output(pslist.PsList, kernel = self.config['kernel'])
```

PID	PPID	ImageFileName	Offset(V)	Threads	Handles	SessionId	Wow64
↳ CreateTime		ExitTime	File output				
4	0	System	0x8c0bcac87040	143	-	N/A	False
↳ 0000000		N/A	Disabled				
92	4	Registry	0x8c0bcac5d080	4	-	N/A	False
↳ 17:25:28.000000		N/A	Disabled				
356	4	smss.exe	0x8c0bccf8d040	3	-	N/A	False
↳ 17:25:33.000000		N/A	Disabled				
...							

Here's we've provided the kernel name that was requested by the volshell plugin itself (the generic volshell does not load a kernel module, and instead only has a TranslationLayerRequirement). A different module could be created and provided instead. The context used by the `dpo` method is always `context`.

Instead of print the results directly to screen, they can be gathered into a TreeGrid objects for direct access by using the `generate_treegrid` or `gt` command.

```
(layer_name) >>> treegrid = gt(pslist.PsList, kernel = self.config['kernel'])
(layer_name) >>> treegrid.populate()
```

Treegrids must be populated before the data in them can be accessed. This is where the plugin actually runs and produces data.

5.4 Running scripts

It might be beneficial to code up a small snippet of code, and execute that on a memory image, rather than writing a full plugin.

The snippet should be lines that will be executed within the volshell context (as such they can immediately access *self* and *context*, for example). These can be executed using the *run_script* or *rs* command, or by providing the file on the command line with *-script*.

For example, to load a layer and extract bytes from a particular offset into a new file, the following snippet could be used:

```
import volatility3.framework.layers.mynewlayer as mynewlayer

layer = cc(mynewlayer.MyNewLayer, on_top_of = 'primary', other_parameter = 'important')
with open('output.dmp', 'wb') as fp:
    for i in range(0, 1073741824, 0x1000):
        data = layer.read(i, 0x1000, pad = True)
        fp.write(data)
```

As this demonstrates, all of the python is accessible, as are the volshell built in functions (such as *cc* which creates a constructable, like a layer or a symbol table).

5.5 Loading files

Files can be loaded as physical layers using the *load_file* or *lf* command, which takes a filename or a URI. This will be added to *context.layers* and can be accessed by the name returned by *lf*.

GLOSSARY

There are many terms when talking about memory forensics, this list hopes to define the common ones and provide some commonality on how to refer to particular ideas within the field.

6.1 A

Address Space

This is the name in volatility 2 for what's referred to as a *Translation Layer*. It encompasses all values that can be addresses, usually in reference to addresses in memory.

Alignment

This value is what all data *offsets* will typically be a multiple of within a *type*.

Array

This represents a list of items, which can be access by an index, which is zero-based (meaning the first element has index 0). Items in arrays are almost always the same size (it is not a generic list, as in python) even if they are *pointers* to different sized objects.

6.2 D

Data Layer

A group of bytes, where each byte can be addressed by a specific offset. Data layers are usually contiguous chunks of data.

Dereference

The act of taking the value of a pointer, and using it as an offset to another object, as a reference.

Domain

This the grouping for input values for a mapping or mathematical function.

6.3 M

Map, mapping

A mapping is a relationship between two sets (where elements of the *Domain* map to elements of the *Range*). Mappings can be seen as a mathematical function, and therefore volatility 3 attempts to use mathematical functional notation where possible. Within volatility a mapping is most often used to refer to the function for translating addresses from a higher layer (domain) to a lower layer (range). For further information, please see *Function (mathematics)* in wikipedia [https://en.wikipedia.org/wiki/Function_\(mathematics\)](https://en.wikipedia.org/wiki/Function_(mathematics))

Member

The name of subcomponents of a type, similar to attributes of objects in common programming parlance. These are usually recorded as *offset* and *type* pairs within a *structure*.

6.4 O

Object

This has a specific meaning within computer programming (as in Object Oriented Programming), but within the world of Volatility it is used to refer to a type that has been associated with a chunk of data, or a specific instance of a type. See also *Type*.

Offset

A numeric value that identifies a distance within a group of bytes, to uniquely identify a single byte, or the start of a run of bytes. An offset is often relative (offset from another object/item) but can be absolute (offset from the start of a region of data).

6.5 P

Packed

Structures are often *aligned* meaning that the various members (subtypes) are always aligned at particular values (usually multiples of 2, 4 or 8). Thus if the data used to represent a particular value has an odd number of bytes, not a multiple of the chosen number, there will be *padding* between it and the next member. In packed structs, no padding is used and the offset of the next member depends on the length of the previous one.

Padding

Data that (usually) contains no useful information. The typical value used for padding is 0 (sometimes called a null byte). As an example, if a string *object* that has been allocated a particular number of bytes, actually contains fewer bytes, the rest of the data (to make up the original length) will be padded with null (0) bytes.

Page

A specific chunk of contiguous data. It is an organizational quantity of memory (usually 0x1000, or 4096 bytes). Pages, like pages in a book, make up the whole, but allow for specific chunks to be allocated and used as necessary. Operating systems uses pages as a means to have granular control over chunks of memory. This allows them to be reordered and reused as necessary (without having to move large chunks of data around), and allows them to have access controls placed upon them, limiting actions such as reading and writing.

Page Table

A table that points to a series of *pages*. Each page table is typically the size of a single page, and page tables can point to pages that are in fact other page tables. Using tables that point to tables, it's possible to use them as a way to map a particular address within a (potentially larger, but sparsely populated) virtual space to a concrete (and usually contiguous) physical space, through the process of *mapping*.

Pointer

A value within memory that points to a different area of memory. This allows objects to contain references to

other objects without containing all the data of the other object. Following a pointer is known as *dereferencing* a pointer. Pointers are usually the same length as the maximum address of the address space, since they should be able to point to any address within the space.

6.6 R

Range

This is the set of the possible output values for a mapping or mathematical function.

6.7 S

Struct, Structure

A means of containing multiple different *type* associated together. A struct typically contains other *type*, usually *aligned* (unless *packing* is involved). In this way the *members* of a type can be accessed by finding the data at the relative *offset* to the start of the structure.

Symbol

This is used in many different contexts, as a short term for many things. Within Volatility, a symbol is a construct that usually encompasses a specific *type* at a specific *offset*, representing a particular instance of that type within the memory of a compiled and running program. An example would be the location in memory of a list of active tcp endpoints maintained by the networking stack within an operating system.

6.8 T

Template

Within volatility 3, the term template applies to a *type* that has not yet been instantiated or linked to any data or a specific location within memory. Once a type has been tied to a particular chunk of data, it is called an *object*.

Translation Layer

This is a type of data layer which allows accessing data from lower layers using addresses different to those used by the lower layers themselves. When accessing data in a translation layer, it translates (or *maps*) addresses from its own *address space* to the address space of the lower layer and returns the corresponding data from the lower layer. Note that multiple addresses in the higher layer might refer to the same address in the lower layer. Conversely, some addresses in the higher layer might have no corresponding address in the lower layer at all. Translation layers most commonly handle the translation from virtual to physical addresses, but can be used to translate data to and from a compressed form or translate data from a particular file format into another format.

Type

This is a structure definition of multiple elements that expresses how data is laid out. Basic types define how the data should be interpreted in terms of a run of bits (or more commonly a collection of 8 bits at a time, called bytes). New types can be constructed by combining other types at specific relative offsets, forming something called a *struct*, or by repeating the same type, known as an *array*. They can even contain other types at the same offset depending on the data itself, known as *Unions*. Once a type has been linked to a specific chunk of data, the result is referred to as an *object*.

6.9 U

Union

A union is a type that can hold multiple different subtypes, whose relative offsets specifically overlap. A union is a means for holding multiple different types within the same size of data, the relative offsets of the types within the union specifically overlap. This means that the data in a union object is interpreted differently based on the types of the union used to access it.

There is also some information to get you started quickly:

LINUX TUTORIAL

This guide will give you a brief overview of how volatility3 works as well as a demonstration of several of the plugins available in the suite.

7.1 Acquiring memory

Volatility3 does not provide the ability to acquire memory. Below are some examples of tools that can be used to acquire memory, but more are available:

- [AVML](#) - Acquire Volatile Memory for Linux
- [LiME](#) - Linux Memory Extract

7.2 Procedure to create symbol tables for linux

To create a symbol table please refer to *Mac or Linux symbol tables*.

Tip: It may be possible to locate pre-made ISF files from the [Linux ISF Server](#), which is built and maintained by [kevthehermit](#). After creating the file or downloading it from the ISF server, place the file under the directory `volatility3/symbols/linux`. If necessary create a linux directory under the symbols directory (this will become unnecessary in future versions).

7.3 Listing plugins

The following is a sample of the linux plugins available for volatility3, it is not complete and more more plugins may be added. For a complete reference, please see the volatility 3 *list of plugins*. For plugin requests, please create an issue with a description of the requested plugin.

```
$ python3 vol.py --help | grep -i linux. | head -n 5
banners.Banners      Attempts to identify potential linux banners in an
linux.bash.Bash       Recovers bash command history from memory.
linux.check_afinfo.Check_afinfo
linux.check_creds.Check_creds
linux.check_idt.Check_idt
```

Note: Here the the command is piped to grep and head in-order to provide the start of the list of linux plugins.

7.4 Using plugins

The following is the syntax to run the volatility CLI.

```
$ python3 vol.py -f <path to memory image> <plugin_name> <plugin_option>
```

7.5 Example

7.5.1 banners

In this example we will be using a memory dump from the Insomni'hack teaser 2020 CTF Challenge called Getdents. We will limit the discussion to memory forensics with volatility 3 and not extend it to other parts of the challenge. Thanks go to [stuxnet](#) for providing this memory dump and [writeup](#).

```
$ python3 vol.py -f memory.vmem banners

Volatility 3 Framework 2.0.1

Progress: 100.00          PDB scanning finished
Offset  Banner

0x141c1390      Linux version 4.15.0-42-generic (buldd@lgw01-amd64-023) (gcc_
↪version 7.3.0 (Ubuntu 7.3.0-16ubuntu3)) #45-Ubuntu SMP Thu Nov 15 19:32:57 UTC 2018_
↪(Ubuntu 4.15.0-42.45-generic 4.15.18)
0x63a00160      Linux version 4.15.0-72-generic (buldd@lcy01-amd64-026) (gcc_
↪version 7.4.0 (Ubuntu 7.4.0-1ubuntu1~18.04.1)) #81-Ubuntu SMP Tue Nov 26 12:20:02 UTC_
↪2019 (Ubuntu 4.15.0-72.81-generic 4.15.18)
0x6455c4d4      Linux version 4.15.0-72-generic (buldd@lcy01-amd64-026) (gcc_
↪version 7.4.0 (Ubuntu 7.4.0-1ubuntu1~18.04.1)) #81-Ubuntu SMP Tue Nov 26 12:20:02 UTC_
↪2019 (Ubuntu 4.15.0-72.81-generic 4.15.18)
0x6e1e055f      Linux version 4.15.0-72-generic (buldd@lcy01-amd64-026) (gcc_
↪version 7.4.0 (Ubuntu 7.4.0-1ubuntu1~18.04.1)) #81-Ubuntu SMP Tue Nov 26 12:20:02 UTC_
↪2019 (Ubuntu 4.15.0-72.81-generic 4.15.18)
0x7fde0010      Linux version 4.15.0-72-generic (buldd@lcy01-amd64-026) (gcc_
↪version 7.4.0 (Ubuntu 7.4.0-1ubuntu1~18.04.1)) #81-Ubuntu SMP Tue Nov 26 12:20:02 UTC_
↪2019 (Ubuntu 4.15.0-72.81-generic 4.15.18)
```

The above command helps us to find the memory dump's kernel version and the distribution version. Now using the above banner we can search for the needed ISF file from the ISF server. If ISF file cannot be found then, follow the instructions on [Procedure to create symbol tables for linux](#). After that, place the ISF file under the volatility3/symbols/linux directory.

Tip: Use the banner text which is most repeated to search from ISF Server.

7.5.2 linux.pslist

```
$ python3 vol.py -f memory.vmem linux.pslist

Volatility 3 Framework 2.0.1    Stacking attempts finished

PID      PPID     COMM
1         0        systemd
2         0        kthreadd
3         2        kworker/0:0
4         2        kworker/0:0H
5         2        kworker/u256:0
6         2        mm_percpu_wq
7         2        ksoftirqd/0
8         2        rcu_sched
9         2        rcu_bh
10        2        migration/0
11        2        watchdog/0
12        2        cpuhp/0
13        2        kdevtmpfs
14        2        netns
15        2        rcu_tasks_kthre
16        2        kauditd
.....
```

linux.pslist helps us to list the processes which are running, their PIDs and PPIDs.

7.5.3 linux.pstree

```
$ python3 vol.py -f memory.vmem linux.pstree

Volatility 3 Framework 2.0.1
Progress: 100.00    Stacking attempts finished

PID      PPID     COMM
1         0        systemd
* 636    1        polkitd
* 514    1        acpid
* 1411   1        pulseaudio
* 517    1        rsyslogd
* 637    1        cups-browsed
* 903    1        whoopsie
* 522    1        ModemManager
* 525    1        cron
* 526    1        avahi-daemon
** 542   526     avahi-daemon
* 657    1        unattended-upgr
* 914    1        kerneloops
* 532    1        dbus-daemon
* 1429   1        ibus-x11
* 929    1        kerneloops
* 1572   1        gsd-printer
```

(continues on next page)

(continued from previous page)

```

* 933 1 upowerd
* 1071 1 rtkit-daemon
* 692 1 gdm3
** 1234 692 gdm-session-wor
*** 1255 1234 gdm-x-session
**** 1257 1255 Xorg
**** 1266 1255 gnome-session-b
***** 1537 1266 gsd-clipboard
***** 1539 1266 gsd-color
***** 1542 1266 gsd-datetime
***** 2950 1266 deja-dup-monito
***** 1546 1266 gsd-housekeepin
***** 1548 1266 gsd-keyboard
***** 1550 1266 gsd-media-keys

```

`linux.pstree` helps us to display the parent child relationships between processes.

7.5.4 linux.bash

Now to find the commands that were run in the bash shell by using `linux.bash`.

```
$ python3 vol.py -f memory.vmem linux.bash
```

```

Volatility 3 Framework 2.0.1
Progress: 100.00 Stacking attempts finished
PID Process CommandTime Command

1733 bash 2020-01-16 14:00:36.000000 sudo reboot
1733 bash 2020-01-16 14:00:36.000000 AWAVH
1733 bash 2020-01-16 14:00:36.000000 sudo apt upgrade
1733 bash 2020-01-16 14:00:36.000000 sudo apt upgrade
1733 bash 2020-01-16 14:00:36.000000 sudo reboot
1733 bash 2020-01-16 14:00:36.000000 sudo apt update
1733 bash 2020-01-16 14:00:36.000000 sudo apt update
1733 bash 2020-01-16 14:00:36.000000 sudo reboot
1733 bash 2020-01-16 14:00:36.000000 sudo apt upgrade
1733 bash 2020-01-16 14:00:36.000000 sudo apt update
1733 bash 2020-01-16 14:00:36.000000 rub
1733 bash 2020-01-16 14:00:36.000000 sudo apt upgrade
1733 bash 2020-01-16 14:00:36.000000 uname -a
1733 bash 2020-01-16 14:00:36.000000 uname -a
1733 bash 2020-01-16 14:00:36.000000 sudo apt autoclean
1733 bash 2020-01-16 14:00:36.000000 sudo reboot
1733 bash 2020-01-16 14:00:36.000000 sudo apt upgrade
1733 bash 2020-01-16 14:00:41.000000 chmod +x meterpreter
1733 bash 2020-01-16 14:00:42.000000 sudo ./meterpreter

```

MACOS TUTORIAL

This guide will give you a brief overview of how volatility3 works as well as a demonstration of several of the plugins available in the suite.

8.1 Acquiring memory

Volatility3 does not provide the ability to acquire memory. The example below is an open source tool. Other commercial tools are also available.

- `osxpmem`

8.2 Procedure to create symbol tables for macOS

To create a symbol table please refer to *Mac or Linux symbol tables*.

Tip: It may be possible to locate pre-made ISF files from the [download link](#), which is built and maintained by [volatilityfoundation](#). After creating the file or downloading it from the link, place the file under the directory `volatility3/symbols/`.

8.3 Listing plugins

The following is a sample of the macOS plugins available for volatility3, it is not complete and more plugins may be added. For a complete reference, please see the volatility 3 *list of plugins*. For plugin requests, please create an issue with a description of the requested plugin.

```
$ python3 vol.py --help | grep -i mac. | head -n 4
mac.bash.Bash          Recovers bash command history from memory.
mac.check_syscall.Check_syscall
mac.check_sysctl.Check_sysctl
mac.check_trap_table.Check_trap_table
```

Note: Here the the command is piped to `grep` and `head` in-order to provide the start of the list of macOS plugins.

8.4 Using plugins

The following is the syntax to run the volatility CLI.

```
$ python3 vol.py -f <path to memory image> <plugin_name> <plugin_option>
```

8.5 Example

8.5.1 banners

In this example we will be using a memory dump from the Securinets CTF Quals 2019 Challenge called `Contact_me`. We will limit the discussion to memory forensics with volatility 3 and not extend it to other parts of the challenge. Thanks go to [stuxnet](#) for providing this memory dump and [writeup](#).

```
$ python3 vol.py -f contact_me banners.Banners

Volatility 3 Framework 2.4.2

Progress: 100.00          PDB scanning finished
Offset  Banner

0x4d2c7d0      Darwin Kernel Version 16.7.0: Thu Jun 15 17:36:27 PDT 2017; root:xnu-
↪3789.70.16~2/RELEASE_ARM64_T8020
0xb42b180      Darwin Kernel Version 16.7.0: Thu Jun 15 17:36:27 PDT 2017; root:xnu-
↪3789.70.16~2/RELEASE_ARM64_T8020
0xcda9100      Darwin Kernel Version 16.7.0: Thu Jun 15 17:36:27 PDT 2017; root:xnu-
↪3789.70.16~2/RELEASE_ARM64_T8020
0x1275e7d0     Darwin Kernel Version 16.7.0: Thu Jun 15 17:36:27 PDT 2017; root:xnu-
↪3789.70.16~2/RELEASE_ARM64_T8020
0x1284fba4     Darwin Kernel Version 16.7.0: Thu Jun 15 17:36:27 PDT 2017; root:xnu-
↪3789.70.16~2/RELEASE_ARM64_T8020
0x34ad0180     Darwin Kernel Version 16.7.0: Thu Jun 15 17:36:27 PDT 2017; root:xnu-
↪3789.70.16~2/RELEASE_ARM64_T8020
```

The above command helps us to find the memory dump's Darwin kernel version. Now using the above banner we can search for the needed ISF file. If ISF file cannot be found then, follow the instructions on [Procedure to create symbol tables for macOS](#). After that, place the ISF file under the `volatility3/symbols` directory.

8.5.2 mac.pslist

```
$ python3 vol.py -f contact_me mac.pslist.PsList

Volatility 3 Framework 2.4.2
Progress: 100.00          Stacking attempts finished

PID      PPID      COMM
0         0         kernel_task
1         0         launchd
```

(continues on next page)

(continued from previous page)

```

35      1      UserEventAgent
38      1      kextd
39      1      fsevents
37      1      uninstalld
45      1      configd
46      1      powerd
52      1      logd
58      1      warmd
.....

```

mac.pslist helps us to list the processes which are running, their PIDs and PPIDs.

8.5.3 mac.pstree

```

$ python3 vol.py -f contact_me mac.pstree.PsTree
Volatility 3 Framework 2.4.2
Progress: 100.00          Stacking attempts finished
PID      PPID      COMM
35      1      UserEventAgent
38      1      kextd
39      1      fsevents
37      1      uninstalld
204     1      softwareupdated
* 449    204     SoftwareUpdateCo
337     1      system_installd
* 455    337     update_dyld_shar

```

mac.pstree helps us to display the parent child relationships between processes.

8.5.4 mac.ifconfig

```

$ python3 vol.py -f contact_me mac.ifconfig.Ifconfig

Volatility 3 Framework 2.4.2
Progress: 100.00          Stacking attempts finished
Interface      IP Address      Mac Address      Promiscuous
lo0
lo0      127.0.0.1      False
lo0      ::1            False
lo0      fe80:1::1      False
gif0
stf0
en0      00:0C:29:89:8B:F0      00:0C:29:89:8B:F0      False
en0      fe80:4::10fb:c89d:217f:52ae      00:0C:29:89:8B:F0      False
en0      192.168.140.128      00:0C:29:89:8B:F0      False
utun0
utun0      fe80:5::2a95:bb15:87e3:977c      False

```

we can use the `mac.ifconfig` plugin to get information about the configuration of the network interfaces of the host under investigation.

WINDOWS TUTORIAL

This guide provides a brief introduction to how volatility3 works as a demonstration of several of the plugins available in the suite.

9.1 Acquiring memory

Volatility does not provide the ability to acquire memory. Memory can be acquired using a number of tools, below are some examples but others exist:

- WinPmem
- FTK Imager

9.2 Listing Plugins

The following is a sample of the windows plugins available for volatility3, it is not complete and more more plugins may be added. For a complete reference, please see the volatility 3 *list of plugins*. For plugin requests, please create an issue with a description of the requested plugin.

```
$ python3 vol.py --help | grep windows | head -n 5
windows.bigpools.BigPools
windows.cmdline.CmdLine
windows.crashinfo.Crashinfo
windows.dlllist.DllList
```

Note: Here the the command is piped to grep and head in-order to provide the start of a list of the available windows plugins.

9.3 Using plugins

The following is the syntax to run the volatility CLI.

```
$ python3 vol.py -f <path to memory image> plugin_name plugin_option
```

9.4 Example

9.4.1 windows.pslist

In this example we will be using a memory dump from the PragyanCTF'22. We will limit the discussion to memory forensics with volatility 3 and not extend it to other parts of the challenges.

When using windows plugins in volatility 3, the required ISF file can often be generated from PDB files automatically downloaded from Microsoft servers, and therefore does not require locating or adding specific ISF files to the volatility 3 symbols directory.

```
$ python3 vol.py -f MemDump.DMP windows.pslist | head -n 10
```

Volatility 3 Framework 2.0.1 PDB scanning finished									
PID	PPID	ImageFileName	Offset(V)	Threads	Handles	SessionId			
↳ Wow64	CreateTime	ExitTime		File output					
4	0	System	0xfa8000cbc040	85		492	N/A		
↳ False	2022-02-07	16:30:12.000000		N/A	Disabled				
276	4	smss.exe	0xfa8001e04040	2		29	N/A		
↳ False	2022-02-07	16:30:12.000000		N/A	Disabled				
352	336	csrss.exe	0xfa8002110b30	9		375	0		
↳ False	2022-02-07	16:30:13.000000		N/A	Disabled				
404	336	wininit.exe	0xfa800219f060	3		74	0		
↳ False	2022-02-07	16:30:13.000000		N/A	Disabled				
412	396	csrss.exe	0xfa80021c5b30	9		224	1		
↳ False	2022-02-07	16:30:13.000000		N/A	Disabled				
468	396	winlogon.exe	0xfa8002284060	5		113	1		
↳ False	2022-02-07	16:30:14.000000		N/A	Disabled				

windows.pslist helps list the processes running while the memory dump was taken.

9.4.2 windows.pstree

```
$ python3 vol.py -f MemDump.DMP windows.pstree | head -n 20
```

Volatility 3 Framework 2.0.1 PDB scanning finished									
PID	PPID	ImageFileName	Offset(V)	Threads	Handles	SessionId			
↳ Wow64	CreateTime	ExitTime							
4	0	System	0xfa8000cbc040	85	492	N/A	False	2022-02-07	↳
↳ 16:30:12.000000		N/A							
* 276	4	smss.exe	0xfa8001e04040	2	29	N/A	False	2022-	

(continues on next page)

(continued from previous page)

↪02-07 16:30:12.000000	N/A								
352	336	csrss.exe	0xfa8002110b30	9	375	0	False	2022-	
↪02-07 16:30:13.000000	N/A								
404	336	wininit.exe	0xfa800219f060	3	74	0	False	2022-	
↪02-07 16:30:13.000000	N/A								
* 504	404	services.exe	0xfa80022ccb30	7	190	0	False	2022-	
↪02-07 16:30:14.000000	N/A								
** 960	504	svchost.exe	0xfa8001c17b30	39	1003	0	False	2022-	
↪02-07 16:30:14.000000	N/A								
** 1216	504	svchost.exe	0xfa80026e0b30	18	311	0	False	2022-	
↪02-07 16:30:15.000000	N/A								
** 1312	504	svchost.exe	0xfa8002740380	19	287	0	False	2022-	
↪02-07 16:30:15.000000	N/A								
** 1984	504	taskhost.exe	0xfa8002eb1b30	8	129	1	False	2022-	
↪02-07 16:30:27.000000	N/A								
** 804	504	svchost.exe	0xfa80024ca5f0	20	450	0	False	2022-	
↪02-07 16:30:14.000000	N/A								
*** 100	804	audiodg.exe	0xfa80025b4b30	6	131	0	False	2022-	
↪02-07 16:30:14.000000	N/A								
** 1568	504	SearchIndexer.	0xfa800254b480	12	616	0	False	2022-	
↪02-07 16:30:32.000000	N/A								
** 744	504	svchost.exe	0xfa8002477b30	8	265	0	False	2022-	
↪02-07 16:30:14.000000	N/A								
** 1096	504	svchost.exe	0xfa800260db30	14	357	0	False	2022-	
↪02-07 16:30:14.000000	N/A								
** 616	504	svchost.exe	0xfa8002b86ab0	13	314	0	False	2022-	
↪02-07 16:32:16.000000	N/A								
** 624	504	svchost.exe	0xfa8002410630	10	350	0	False	2022-	
↪02-07 16:30:14.000000	N/A								

windows.pstree helps to display the parent child relationships between processes.

Note: Here the the command is piped to head in-order to provide smaller output, here listing only the first 20.

9.4.3 windows.hashdump

```
$ python3 vol.py -f MemDump.DMP windows.hashdump
Volatility 3 Framework 2.0.3
Progress: 100.00          PDB scanning finished
User      rid      lmhash  nthash

Administrator      500      aad3b435b51404eeaad3b435b51404ee  ↪
↪31d6cfe0d16ae931b73c59d7e0c089c0
Guest                501      aad3b435b51404eeaad3b435b51404ee  ↪
↪31d6cfe0d16ae931b73c59d7e0c089c0
Frank Reynolds      1000     aad3b435b51404eeaad3b435b51404ee  ↪
↪a88d1e18706d3aa676e01e5943d15911
HomeGroupUser$      1002     aad3b435b51404eeaad3b435b51404ee  ↪
↪af10ecac6ea817d2bb56e3e5c33ce1cd
```

(continues on next page)

(continued from previous page)

Dennis	1003	aad3b435b51404eeaad3b435b51404ee	↪ cf96684bbc7877920adaa9663698bf54
--------	------	----------------------------------	------------------------------------

`windows.hashdump` helps to list the hashes of the users in the system.

VOLATILITY3 PACKAGE

Volatility 3 - An open-source memory forensics framework

class `WarningFindSpec`

Bases: `MetaPathFinder`

Checks import attempts and throws a warning if the name shouldn't be used.

find_module(*fullname*, *path*)

Return a loader for the module.

If no module is found, return None. The fullname is a str and the path is a list of strings or None.

This method is deprecated since Python 3.4 in favor of `finder.find_spec()`. If `find_spec()` exists then backwards-compatible functionality is provided for this method.

static find_spec(*fullname*, *path*, *target=None*, ***kwargs*)

Mock `find_spec` method that just checks the name, this must go first.

Return type

`None`

invalidate_caches()

An optional method for clearing the finder's cache, if any. This method is used by `importlib.invalidate_caches()`.

class `classproperty`(*func*)

Bases: `property`

Class property decorator.

Note this will change the return type

deleter()

Descriptor to obtain a copy of the property with a different deleter.

fdel

fget

fset

getter()

Descriptor to obtain a copy of the property with a different getter.

setter()

Descriptor to obtain a copy of the property with a different setter.

10.1 Subpackages

10.1.1 volatility3.cli package

A CommandLine User Interface for the volatility framework.

User interfaces make use of the framework to:

- determine available plugins
- request necessary information for those plugins from the user
- determine what “automagic” modules will be used to populate information the user does not provide
- run the plugin
- display the results

class `CommandLine`

Bases: `object`

Constructs a command-line interface object for users to run plugins.

CLI_NAME = 'volatility'

file_handler_class_factory(*direct=True*)

load_system_defaults(*filename*)

Modify the main configuration based on the default configuration override

Return type

`Tuple[List[Tuple[int, str]], Dict[str, Any]]`

classmethod `location_from_file`(*filename*)

Returns the URL location from a file parameter (which may be a URL)

Parameters

filename (`str`) – The path to the file (either an absolute, relative, or URL path)

Return type

`str`

Returns

The URL for the location of the file

order_extra_verbose_levels()

populate_config(*context, configurables_list, args, plugin_config_path*)

Populate the context config based on the returned args.

We have already determined these elements must be descended from ConfigurableInterface

Parameters

- **context** (`ContextInterface`) – The volatility3 context to operate on
- **configurables_list** (`Dict[str, Type[ConfigurableInterface]]`) – A dictionary of configurable items that can be configured on the plugin
- **args** (`Namespace`) – An object containing the arguments necessary
- **plugin_config_path** (`str`) – The path within the context’s config containing the plugin’s configuration

Return type`None`**populate_requirements_argparse**(*parser, configurable*)

Adds the plugin's simple requirements to the provided parser.

Parameters

- **parser** (`Union[ArgumentParser, _ArgumentGroup]`) – The parser to add the plugin's (simple) requirements to
- **configurable** (`Type[ConfigurableInterface]`) – The plugin object to pull the requirements from

process_exceptions(*excp*)

Provide useful feedback if an exception occurs during a run of a plugin.

process_unsatisfied_exceptions(*excp*)

Provide useful feedback if an exception occurs during requirement fulfillment.

run()

Executes the command line module, taking the system arguments, determining the plugin to run and then running it.

classmethod setup_logging()**class MuteProgress**Bases: `PrintedProgress`

A dummy progress handler that produces no output when called.

class PrintedProgressBases: `object`

A progress handler that prints the progress value and the description onto the command line.

main()A convenience function for constructing and running the `CommandLine`'s run method.**Subpackages****volatility3.cli.volshell package****class VolShell**Bases: `CommandLine`

Program to allow interactive interaction with a memory image.

This allows a memory image to be examined through an interactive python terminal with all the volatility support calls available.

CLI_NAME = 'volshell'**file_handler_class_factory**(*direct=True*)**load_system_defaults**(*filename*)

Modify the main configuration based on the default configuration override

Return type`Tuple[List[Tuple[int, str]], Dict[str, Any]]`

classmethod `location_from_file(filename)`

Returns the URL location from a file parameter (which may be a URL)

Parameters

filename (`str`) – The path to the file (either an absolute, relative, or URL path)

Return type

`str`

Returns

The URL for the location of the file

order_extra_verbose_levels()

populate_config(*context, configurables_list, args, plugin_config_path*)

Populate the context config based on the returned args.

We have already determined these elements must be descended from ConfigurableInterface

Parameters

- **context** (`ContextInterface`) – The volatility3 context to operate on
- **configurables_list** (`Dict[str, Type[ConfigurableInterface]]`) – A dictionary of configurable items that can be configured on the plugin
- **args** (`Namespace`) – An object containing the arguments necessary
- **plugin_config_path** (`str`) – The path within the context’s config containing the plugin’s configuration

Return type

`None`

populate_requirements_argparse(*parser, configurable*)

Adds the plugin’s simple requirements to the provided parser.

Parameters

- **parser** (`Union[ArgumentParser, _ArgumentGroup]`) – The parser to add the plugin’s (simple) requirements to
- **configurable** (`Type[ConfigurableInterface]`) – The plugin object to pull the requirements from

process_exceptions(*excp*)

Provide useful feedback if an exception occurs during a run of a plugin.

process_unsatisfied_exceptions(*excp*)

Provide useful feedback if an exception occurs during requirement fulfillment.

run()

Executes the command line module, taking the system arguments, determining the plugin to run and then running it.

classmethod `setup_logging()`

main()

A convenience function for constructing and running the CommandLine’s run method.

Submodules

volatility3.cli.volshell.generic module

class NullFileHandler(*preferred_name*)

Bases: BytesIO, *FileHandlerInterface*

Null FileHandler that swallows files whole without consuming memory

close()

Disable all I/O operations.

closed

True if the file is closed.

detach()

Disconnect this buffer from its underlying raw stream and return it.

After the raw stream has been detached, the buffer is in an unusable state.

fileno()

Returns underlying file descriptor if one exists.

OSError is raised if the IO object does not use a file descriptor.

flush()

Does nothing.

getbuffer()

Get a read-write view over the contents of the BytesIO object.

getvalue()

Retrieve the entire contents of the BytesIO object.

isatty()

Always returns False.

BytesIO objects are not connected to a TTY-like device.

property preferred_filename

The preferred filename to save the data to. Until this file has been written, this value may not be the final filename the data is written to.

read(*size=-1, /*)

Read at most size bytes, returned as a bytes object.

If the size argument is negative, read until EOF is reached. Return an empty bytes object at EOF.

read1(*size=-1, /*)

Read at most size bytes, returned as a bytes object.

If the size argument is negative or omitted, read until EOF is reached. Return an empty bytes object at EOF.

readable()

Returns True if the IO object can be read.

readall()

Read until EOF, using multiple read() call.

readinto(*buffer*, /)

Read bytes into buffer.

Returns number of bytes read (0 for EOF), or None if the object is set not to block and has no data to read.

readinto1(*buffer*, /)

readline(*size=-1*, /)

Next line from the file, as a bytes object.

Retain newline. A non-negative size argument limits the maximum number of bytes to return (an incomplete line may be returned then). Return an empty bytes object at EOF.

readlines(*size=None*, /)

List of bytes objects, each a line from the file.

Call readline() repeatedly and return a list of the lines so read. The optional size argument, if given, is an approximate bound on the total number of bytes in the lines returned.

static sanitize_filename(*filename*)

Sanitizes the filename to ensure only a specific whitelist of characters is allowed through

Return type

`str`

seek(*pos*, *whence=0*, /)

Change stream position.

Seek to byte offset pos relative to position indicated by whence:

0 Start of stream (the default). pos should be ≥ 0 ; 1 Current position - pos may be negative; 2 End of stream - pos usually negative.

Returns the new absolute position.

seekable()

Returns True if the IO object can be seeked.

tell()

Current file position, an integer.

truncate(*size=None*, /)

Truncate the file to at most size bytes.

Size defaults to the current file position, as returned by tell(). The current file position is unchanged. Returns the new size.

writable()

Returns True if the IO object can be written.

write(*b*)

Dummy method

writelines(*lines*)

Dummy method

class Volshell(*args, **kwargs)

Bases: [`PluginInterface`](#)

Shell environment to directly interact with a memory image.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

change_kernel(*kernel_name=None*)**change_layer**(*layer_name=None*)

Changes the current default layer

change_symbol_table(*symbol_table_name=None*)

Changes the current_symbol_table

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

construct_locals()

Returns a dictionary listing the functions to be added to the environment.

Return type

List[Tuple[List[str], Any]]

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

create_configurable(*clazz, **kwargs*)

Creates a configurable object, converting arguments to configuration

property current_kernel_name**property current_layer****property current_symbol_table****disassemble**(*offset, count=128, layer_name=None, architecture=None*)

Disassembles a number of instructions from the code at offset

display_bytes(*offset, count=128, layer_name=None*)

Displays byte values and ASCII characters

display_doublewords(*offset, count=128, layer_name=None*)

Displays double-word values (4 bytes) and corresponding ASCII characters

display_plugin_output(*plugin, **kwargs*)

Displays the output for a particular plugin (with keyword arguments)

Return type`None`**display_quadwords**(*offset*, *count*=128, *layer_name*=None)

Displays quad-word values (8 bytes) and corresponding ASCII characters

display_symbols(*symbol_table*=None)

Prints an alphabetical list of symbols for a symbol table

display_type(*object*, *offset*=None)

Display Type describes the members of a particular object in alphabetical order

display_words(*offset*, *count*=128, *layer_name*=None)

Displays word values (2 bytes) and corresponding ASCII characters

generate_treegrid(*plugin*, ***kwargs*)

Generates a TreeGrid based on a specific plugin passing in kwarg configuration values

Return type`Optional[TreeGrid]`**classmethod get_requirements**()

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`**help**(**args*)

Describes the available commands

property kernel

Returns the current kernel object

load_file(*location*)

Loads a file into a Filelayer and returns the name of the layer

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

random_string(*length*=32)**Return type**`str`

render_treegrid(*treegrid*, *renderer=None*)

Renders a treegrid as produced by generate_treegrid

Return type

`None`

run(*additional_locals=None*)

Runs the interactive volshell plugin.

Return type

`TreeGrid`

Returns

Return a TreeGrid but this is always empty since the point of this plugin is to run interactively

run_script(*location*)

Runs a python script within the context of volshell

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.cli.volshell.linux module

class Volshell(**args*, ***kwargs*)

Bases: `Volshell`

Shell environment to directly interact with a linux memory image.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***change_kernel**(*kernel_name=None*)**change_layer**(*layer_name=None*)

Changes the current default layer

change_symbol_table(*symbol_table_name=None*)

Changes the current_symbol_table

change_task(*pid=None*)

Change the current process and layer, based on a process ID

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

construct_locals()

Returns a dictionary listing the functions to be added to the environment.

Return type*List[Tuple[List[str], Any]]***property context:** *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

create_configurable(*clazz, **kwargs*)

Creates a configurable object, converting arguments to configuration

property current_kernel_name**property current_layer****property current_symbol_table****disassemble**(*offset, count=128, layer_name=None, architecture=None*)

Disassembles a number of instructions from the code at offset

display_bytes(*offset, count=128, layer_name=None*)

Displays byte values and ASCII characters

display_doublewords(*offset, count=128, layer_name=None*)

Displays double-word values (4 bytes) and corresponding ASCII characters

display_plugin_output(*plugin, **kwargs*)

Displays the output for a particular plugin (with keyword arguments)

Return type*None***display_quadwords**(*offset, count=128, layer_name=None*)

Displays quad-word values (8 bytes) and corresponding ASCII characters

display_symbols(*symbol_table=None*)

Prints an alphabetical list of symbols for a symbol table

display_type(*object*, *offset=None*)

Display Type describes the members of a particular object in alphabetical order

display_words(*offset*, *count=128*, *layer_name=None*)

Displays word values (2 bytes) and corresponding ASCII characters

generate_treegrid(*plugin*, ***kwargs*)

Generates a TreeGrid based on a specific plugin passing in kwarg configuration values

Return type

`Optional[TreeGrid]`

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

help(**args*)

Describes the available commands

property kernel

Returns the current kernel object

list_tasks()

Returns a list of task objects from the primary layer

load_file(*location*)

Loads a file into a Filelayer and returns the name of the layer

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

random_string(*length=32*)

Return type

`str`

render_treegrid(*treegrid*, *renderer=None*)

Renders a treegrid as produced by generate_treegrid

Return type

`None`

run(*additional_locals=None*)

Runs the interactive volshell plugin.

Return type

TreeGrid

Returns

Return a TreeGrid but this is always empty since the point of this plugin is to run interactively

run_script(*location*)

Runs a python script within the context of volshell

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.cli.volshell.mac module

class Volshell(**args, **kwargs*)

Bases: *Volshell*

Shell environment to directly interact with a mac memory image.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

change_kernel(*kernel_name=None*)

change_layer(*layer_name=None*)

Changes the current default layer

change_symbol_table(*symbol_table_name=None*)

Changes the current_symbol_table

change_task(*pid=None*)

Change the current process and layer, based on a process ID

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

construct_locals()

Returns a dictionary listing the functions to be added to the environment.

Return type

List[Tuple[List[str], Any]]

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

create_configurable(*clazz, **kwargs*)

Creates a configurable object, converting arguments to configuration

property current_kernel_name

property current_layer

property current_symbol_table

disassemble(*offset, count=128, layer_name=None, architecture=None*)

Disassembles a number of instructions from the code at offset

display_bytes(*offset, count=128, layer_name=None*)

Displays byte values and ASCII characters

display_doublewords(*offset, count=128, layer_name=None*)

Displays double-word values (4 bytes) and corresponding ASCII characters

display_plugin_output(*plugin, **kwargs*)

Displays the output for a particular plugin (with keyword arguments)

Return type

None

display_quadwords(*offset, count=128, layer_name=None*)

Displays quad-word values (8 bytes) and corresponding ASCII characters

display_symbols(*symbol_table=None*)

Prints an alphabetical list of symbols for a symbol table

display_type(*object, offset=None*)

Display Type describes the members of a particular object in alphabetical order

display_words(*offset, count=128, layer_name=None*)

Displays word values (2 bytes) and corresponding ASCII characters

generate_treegrid(*plugin*, ***kwargs*)

Generates a TreeGrid based on a specific plugin passing in kwarg configuration values

Return type

`Optional[TreeGrid]`

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

help(**args*)

Describes the available commands

property kernel

Returns the current kernel object

list_tasks(*method=None*)

Returns a list of task objects from the primary layer

load_file(*location*)

Loads a file into a Filelayer and returns the name of the layer

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

random_string(*length=32*)

Return type

`str`

render_treegrid(*treegrid*, *renderer=None*)

Renders a treegrid as produced by generate_treegrid

Return type

`None`

run(*additional_locals=None*)

Runs the interactive volshell plugin.

Return type

`TreeGrid`

Returns

Return a TreeGrid but this is always empty since the point of this plugin is to run interactively

run_script(*location*)

Runs a python script within the context of volshell

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.cli.volshell.windows module

class Volshell(**args, **kwargs*)

Bases: `Volshell`

Shell environment to directly interact with a windows memory image.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

change_kernel(*kernel_name=None*)

change_layer(*layer_name=None*)

Changes the current default layer

change_process(*pid=None*)

Change the current process and layer, based on a process ID

change_symbol_table(*symbol_table_name=None*)

Changes the current_symbol_table

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

construct_locals()

Returns a dictionary listing the functions to be added to the environment.

Return type

List[Tuple[List[str], Any]]

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

create_configurable(*clazz*, ***kwargs*)

Creates a configurable object, converting arguments to configuration

property current_kernel_name

property current_layer

property current_symbol_table

disassemble(*offset*, *count=128*, *layer_name=None*, *architecture=None*)

Disassembles a number of instructions from the code at offset

display_bytes(*offset*, *count=128*, *layer_name=None*)

Displays byte values and ASCII characters

display_doublewords(*offset*, *count=128*, *layer_name=None*)

Displays double-word values (4 bytes) and corresponding ASCII characters

display_plugin_output(*plugin*, ***kwargs*)

Displays the output for a particular plugin (with keyword arguments)

Return type

None

display_quadwords(*offset*, *count=128*, *layer_name=None*)

Displays quad-word values (8 bytes) and corresponding ASCII characters

display_symbols(*symbol_table=None*)

Prints an alphabetical list of symbols for a symbol table

display_type(*object*, *offset=None*)

Display Type describes the members of a particular object in alphabetical order

display_words(*offset*, *count=128*, *layer_name=None*)

Displays word values (2 bytes) and corresponding ASCII characters

generate_treegrid(*plugin*, ***kwargs*)

Generates a TreeGrid based on a specific plugin passing in kwarg configuration values

Return type

Optional[TreeGrid]

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

help(*args)

Describes the available commands

property kernel

Returns the current kernel object

list_processes()

Returns a list of EPROCESS objects from the primary layer

load_file(location)

Loads a file into a Filelayer and returns the name of the layer

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

random_string(length=32)

Return type

str

render_treegrid(treegrid, renderer=None)

Renders a treegrid as produced by generate_treegrid

Return type

None

run(additional_locals=None)

Runs the interactive volshell plugin.

Return type

TreeGrid

Returns

Return a TreeGrid but this is always empty since the point of this plugin is to run interactively

run_script(location)

Runs a python script within the context of volshell

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

Submodules

volatility3.cli.text_filter module

class `CLIFilter(treegrid, filters)`

Bases: `object`

filter(row)

Filters the row based on each of the column_filters

Return type

`bool`

class `ColumnFilter(column_num, pattern, regex=False, exclude=False)`

Bases: `object`

find(item)

Identifies whether an item is found in the appropriate column

Return type

`bool`

found(row)

Determines whether a row should be filtered

If the classes exclude value is false, and the necessary pattern is found, the row is not filtered, otherwise it is filtered.

Return type

`bool`

volatility3.cli.text_renderer module

class `CLIRenderer(options=None)`

Bases: `Renderer`

Class to add specific requirements for CLI renderers.

Accepts an options object to configure the renderers.

filter: `CLIFilter` = None

abstract get_render_options()

Returns a list of rendering options.

Return type

`List[Any]`

name = 'unnamed'

abstract render(*grid*)

Takes a grid object and renders it based on the object's preferences.

Return type

`None`

structured_output = False

class CSVRenderer(*options=None*)

Bases: `CLIRenderer`

Accepts an options object to configure the renderers.

filter: `CLIFilter` = `None`

get_render_options()

Returns a list of rendering options.

name = 'csv'

render(*grid*)

Renders each row immediately to stdout.

Parameters

grid (`TreeGrid`) – The TreeGrid object to render

Return type

`None`

structured_output = True

class JsonLinesRenderer(*options=None*)

Bases: `JsonRenderer`

Accepts an options object to configure the renderers.

filter: `CLIFilter` = `None`

get_render_options()

Returns a list of rendering options.

Return type

`List[Any]`

name = 'JSONL'

output_result(*outfd, result*)

Outputs the JSON results as JSON lines

render(*grid*)

Takes a grid object and renders it based on the object's preferences.

structured_output = True

class `JsonRenderer`(*options=None*)

Bases: `CLIRenderer`

Accepts an options object to configure the renderers.

filter: `CLIFilter` = `None`

get_render_options()

Returns a list of rendering options.

Return type

`List[Any]`

name = `'JSON'`

output_result(*outfd, result*)

Outputs the JSON data to a file in a particular format

render(*grid*)

Takes a grid object and renders it based on the object's preferences.

structured_output = `True`

class `NoneRenderer`(*options=None*)

Bases: `CLIRenderer`

Outputs no results

Accepts an options object to configure the renderers.

filter: `CLIFilter` = `None`

get_render_options()

Returns a list of rendering options.

name = `'none'`

render(*grid*)

Takes a grid object and renders it based on the object's preferences.

Return type

`None`

structured_output = `False`

class `PrettyTextRenderer`(*options=None*)

Bases: `CLIRenderer`

Accepts an options object to configure the renderers.

filter: `CLIFilter` = `None`

get_render_options()

Returns a list of rendering options.

name = `'pretty'`

render(*grid*)

Renders each column immediately to stdout.

This does not format each line's width appropriately, it merely tab separates each field

Parameters**grid** (*TreeGrid*) – The TreeGrid object to render**Return type***None***structured_output** = **False****tab_stop**(*line*)**Return type***str***class QuickTextRenderer**(*options=None*)Bases: *CLIRenderer*

Accepts an options object to configure the renderers.

filter: *CLIFilter* = **None****get_render_options**()

Returns a list of rendering options.

name = **'quick'****render**(*grid*)

Renders each column immediately to stdout.

This does not format each line's width appropriately, it merely tab separates each field

Parameters**grid** (*TreeGrid*) – The TreeGrid object to render**Return type***None***structured_output** = **False****display_disassembly**(*disasm*)

Renders a disassembly renderer type into string format.

Parameters**disasm** (*Disassembly*) – Input disassembly objects**Return type***str***Returns**

A string as rendered by capstone where available, otherwise output as if it were just bytes

hex_bytes_as_text(*value*)

Renders HexBytes as text.

Parameters**value** (*bytes*) – A series of bytes to convert to text**Return type***str***Returns**

A text representation of the hexadecimal bytes plus their ascii equivalents, separated by newline characters

multitypedata_as_text(*value*)

Renders the bytes as a string where possible, otherwise it displays hex data

This attempts to convert the string based on its encoding and if no data's been lost due to the split on the null character, then it displays it as is

Return type

`str`

optional(*func*)

Return type

`Callable`

quoted_optional(*func*)

Return type

`Callable`

volatility3.cli.volargparse module

```
class HelpfulArgParser(prog=None, usage=None, description=None, epilog=None, parents=[],
                        formatter_class=<class 'argparse.HelpFormatter'>, prefix_chars='-',
                        fromfile_prefix_chars=None, argument_default=None, conflict_handler='error',
                        add_help=True, allow_abbrev=True, exit_on_error=True)
```

Bases: `ArgumentParser`

add_argument(*dest*, ..., *name=value*, ...)

add_argument(*option_string*, *option_string*, ..., *name=value*, ...) → `None`

add_argument_group(**args*, ***kwargs*)

add_mutually_exclusive_group(***kwargs*)

add_subparsers(***kwargs*)

convert_arg_line_to_args(*arg_line*)

error(*message: string*)

Prints a usage message incorporating the message to stderr and exits.

If you override this in a subclass, it should not return – it should either exit or raise an exception.

exit(*status=0*, *message=None*)

format_help()

format_usage()

get_default(*dest*)

parse_args(*args=None*, *namespace=None*)

parse_intermixed_args(*args=None*, *namespace=None*)

parse_known_args(*args=None*, *namespace=None*)

parse_known_intermixed_args(*args=None*, *namespace=None*)


```

print_help(file=None)
print_usage(file=None)
register(registry_name, value, object)
set_defaults(**kwargs)
class HelpfulSubparserAction(*args, **kwargs)
    Bases: _SubParsersAction
    Class to either select a unique plugin based on a substring, or identify the alternatives.
add_parser(name, **kwargs)
format_usage()

```

10.1.2 volatility3.framework package

Volatility 3 framework.

```

class NonInheritable(value, cls)
    Bases: object
class_subclasses(cls)
    Returns all the (recursive) subclasses of a given class.
    Return type
        Generator[Type[TypeVar(T)], None, None]
clear_cache(complete=True)
hide_from_subclasses(cls)
    Return type
        Type
import_file(module, path, ignore_errors=False)
    Imports a python file based on an existing module, a submodule and a filepath for error messages
    Return type
        List[str]
    Args
        module: Module name to be imported path: File to be imported from (used for error messages)
    Returns
        List of modules that may have failed to import
import_files(base_module, ignore_errors=False)
    Imports all plugins present under plugins module namespace.
    Return type
        List[str]

```

interface_version()

Provides the so version number of the library.

Return type

`Tuple[int, int, int]`

list_plugins()**Return type**

`Dict[str, Type[PluginInterface]]`

require_interface_version(*args)

Checks the required version of a plugin.

Return type

`None`

Subpackages

volatility3.framework.automagic package

Automagic modules allow the framework to populate configuration elements that a user has not provided.

Automagic objects accept a *context* and a *configurable*, and will make appropriate changes to the *context* in an attempt to fulfill the requirements of the *configurable* object (or objects upon which that configurable may rely).

Several pre-existing modules include one to stack layers on top of each other (allowing automatic detection and loading of file format types) as well as a module to reconstruct layers based on their provided requirements.

available(context)

Returns an ordered list of all subclasses of *AutomagicInterface*.

The order is based on the priority attributes of the subclasses, in order to ensure the automagics are listed in an appropriate order.

Parameters

context (*ContextInterface*) – The context that will contain any automagic configuration values.

Return type

`List[AutomagicInterface]`

choose_automagic(automagics, plugin)

Chooses which automagics to run, maintaining the order they were handed in.

Return type

`List[Type[AutomagicInterface]]`

run(automagics, context, configurable, config_path, progress_callback=None)

Runs through the list of *automagics* in order, allowing them to make changes to the context.

Parameters

- **automagics** (`List[AutomagicInterface]`) – A list of *AutomagicInterface* objects
- **context** (*ContextInterface*) – The context (that inherits from *ContextInterface*) for modification
- **configurable** (`Union[ConfigurableInterface, Type[ConfigurableInterface]]`) – An object that inherits from *ConfigurableInterface*

- **config_path** (`str`) – The path within the *context.config* for options required by the *configurable*
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A function that takes a percentage (and an optional description) that will be called periodically

Return type`List[TracebackException]`

This is where any automagic is allowed to run, and alter the context in order to satisfy/improve all requirements

Returns a list of traceback objects that occurred during the autorun procedure

Note: The order of the *automagics* list is important. An *automagic* that populates configurations may be necessary for an *automagic* that populates the context based on the configuration information.

Submodules**volatility3.framework.automagic.construct_layers module**

An automagic module to use configuration data to configure and then construct classes that fulfill the descendants of a *ConfigurableInterface*.

class ConstructionMagic(*context, config_path, *args, **kwargs*)

Bases: *AutomagicInterface*

Constructs underlying layers.

Class to run through the requirement tree of the *ConfigurableInterface* and from the bottom of the tree upwards, attempt to construct all *ConstructableRequirementInterface* based classes.

Warning

This *automagic* should run first to allow existing configurations to have been constructed for use by later automagic

Basic initializer that allows configurables to access their own config settings.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict*

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

exclusion_list = []

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_requirements(*context*, *config_path*, *requirement_root*, *requirement_type*, *shortcut=True*)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **config_path** (*str*) – Configuration path of the top-level requirement
- **requirement_root** (*RequirementInterface*) – Top-level requirement whose subrequirements will all be searched
- **requirement_type** (*Union[Tuple[Type[RequirementInterface], ...], Type[RequirementInterface]*]) – Type of requirement to find
- **shortcut** (*bool*) – Only returns requirements that live under unsatisfied requirements

Return type

List[Tuple[str, RequirementInterface]

Returns

A list of tuples containing the *config_path*, *sub_config_path* and requirement identifying the unsatisfied *Requirements*

classmethod **get_requirements**()

Returns a list of *RequirementInterface* objects required by this object.

Return type

List[RequirementInterface]

classmethod **make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

priority = 0

An ordering to indicate how soon this automagic should be run

classmethod **unsatisfied**(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type

`Dict[str, RequirementInterface]`

volatility3.framework.automagic.linux module

class LinuxIntelStacker

Bases: `StackerLayerInterface`

exclusion_list: `List[str] = ['mac', 'windows']`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod find_aslr(*context, symbol_table, layer_name, progress_callback=None*)

Determines the offset of the actual DTB in physical space and its symbol offset.

Return type

`Tuple[int, int]`

classmethod stack(*context, layer_name, progress_callback=None*)

Attempts to identify linux within this layer.

Return type

`Optional[DataLayerInterface]`

stack_order = 35

The order in which to attempt stacking, the lower the earlier

classmethod stacker_slow_warning()

classmethod virtual_to_physical_address(*addr*)

Converts a virtual linux address to a physical one (does not account of ASLR)

Return type

`int`

class LinuxSymbolFinder(*context, config_path*)

Bases: `SymbolFinder`

Linux symbol loader based on uname signature strings.

Basic initializer that allows configurables to access their own config settings.

banner_config_key: `str = 'kernel_banner'`

property banners: `Dict[bytes, List[str]]`

Creates a cached copy of the results, but only it's been requested.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

exclusion_list = ['mac', 'windows']

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_aslr(*args)**find_requirements**(context, config_path, requirement_root, requirement_type, shortcut=True)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **config_path** (*str*) – Configuration path of the top-level requirement
- **requirement_root** (*RequirementInterface*) – Top-level requirement whose subrequirements will all be searched
- **requirement_type** (Union[Tuple[Type[*RequirementInterface*], ...], Type[*RequirementInterface*]]) – Type of requirement to find
- **shortcut** (*bool*) – Only returns requirements that live under unsatisfied requirements

Return type*List[Tuple[str, RequirementInterface]]***Returns**

A list of tuples containing the config_path, sub_config_path and requirement identifying the unsatisfied *Requirements*

classmethod get_requirements()

Returns a list of *RequirementInterface* objects required by this object.

Return type*List[RequirementInterface]***classmethod make_subconfig**(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**operating_system:** `Optional[str] = 'linux'`**priority** = 40

An ordering to indicate how soon this automagic should be run

symbol_class: `Optional[str] = 'volatility3.framework.symbols.linux.LinuxKernelIntermedSymbols'`**classmethod** `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]`**volatility3.framework.automagic.mac module****class** `MacIntelStacker`

Bases: `StackerLayerInterface`

exclusion_list: `List[str] = ['windows', 'linux']`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod `find_aslr(context, symbol_table, layer_name, compare_banner="", compare_banner_offset=0, progress_callback=None)`

Determines the offset of the actual DTB in physical space and its symbol offset.

Return type`int`**classmethod** `stack(context, layer_name, progress_callback=None)`

Attempts to identify mac within this layer.

Return type`Optional[DataLayerInterface]`**stack_order** = 35

The order in which to attempt stacking, the lower the earlier

classmethod `stacker_slow_warning()`**classmethod** `virtual_to_physical_address(addr)`

Converts a virtual mac address to a physical one (does not account of ASLR)

Return type`int`

class `MacSymbolFinder`(*context*, *config_path*)

Bases: `SymbolFinder`

Mac symbol loader based on uname signature strings.

Basic initializer that allows configurables to access their own config settings.

banner_config_key: `str = 'kernel_banner'`

property `banners:` `Dict[bytes, List[str]]`

Creates a cached copy of the results, but only if it's been requested.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type

`HierarchicalDict`

property `config:` `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path:` `str`

The configuration path on which this configurable lives.

property `context:` `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

exclusion_list = `['windows', 'linux']`

A list of plugin categories (typically operating systems) which the plugin will not operate on.

classmethod `find_aslr`(*context*, *symbol_table*, *layer_name*, *compare_banner=""*,
compare_banner_offset=0, *progress_callback=None*)

Determines the offset of the actual DTB in physical space and its symbol offset.

Return type

`int`

find_requirements(*context*, *config_path*, *requirement_root*, *requirement_type*, *shortcut=True*)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*.

Parameters

- **context** (`ContextInterface`) – Context on which to operate
- **config_path** (`str`) – Configuration path of the top-level requirement
- **requirement_root** (`RequirementInterface`) – Top-level requirement whose sub-requirements will all be searched
- **requirement_type** (`Union[Tuple[Type[RequirementInterface], ...], Type[RequirementInterface]]`) – Type of requirement to find
- **shortcut** (`bool`) – Only returns requirements that live under unsatisfied requirements

Return type

`List[Tuple[str, RequirementInterface]]`

Returns

A list of tuples containing the `config_path`, `sub_config_path` and requirement identifying the unsatisfied *Requirements*

classmethod `get_requirements()`

Returns a list of RequirementInterface objects required by this object.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

operating_system: `Optional[str] = 'mac'`

priority = 40

An ordering to indicate how soon this automagic should be run

symbol_class: `Optional[str] =`

`'volatility3.framework.symbols.mac.MacKernelIntermedSymbols'`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

volatility3.framework.automagic.module module**class** `KernelModule(context, config_path, *args, **kwargs)`Bases: `AutomagicInterface`

Finds ModuleRequirements and ensures their layer, symbols and offsets

Basic initializer that allows configurables to access their own config settings.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

exclusion_list = []

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_requirements(context, config_path, requirement_root, requirement_type, shortcut=True)Determines if there is actually an unfulfilled *Requirement* waiting.This ensures we do not carry out an expensive search when there is no need for a particular *Requirement***Parameters**

- **context** (`ContextInterface`) – Context on which to operate
- **config_path** (`str`) – Configuration path of the top-level requirement
- **requirement_root** (`RequirementInterface`) – Top-level requirement whose subrequirements will all be searched
- **requirement_type** (`Union[Tuple[Type[RequirementInterface], ...], Type[RequirementInterface]]`) – Type of requirement to find
- **shortcut** (`bool`) – Only returns requirements that live under unsatisfied requirements

Return type`List[Tuple[str, RequirementInterface]]`**Returns**A list of tuples containing the config_path, sub_config_path and requirement identifying the unsatisfied *Requirements***classmethod get_requirements()**

Returns a list of RequirementInterface objects required by this object.

Return type`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

priority = 100

An ordering to indicate how soon this automagic should be run

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

volatility3.framework.automagic.pdbscan module

A module for scanning translation layers looking for Windows PDB records from loaded PE files.

This module contains a standalone scanner, and also a *ScannerInterface* based scanner for use within the framework by calling `scan()`.

class `KernelPDBScanner(context, config_path, *args, **kwargs)`

Bases: *AutomagicInterface*

Windows symbol loader based on PDB signatures.

An Automagic object that looks for all Intel translation layers and scans each of them for a pdb signature. When found, a search for a corresponding Intermediate Format data file is carried out and if found an appropriate symbol space is automatically loaded.

Once a specific kernel PDB signature has been found, a virtual address for the loaded kernel is determined by one of two methods. The first method assumes a specific mapping from the kernel's physical address to its virtual address (typically the kernel is loaded at its physical location plus a specific offset). The second method searches for a particular structure that lists the kernel module's virtual address, its size (not checked) and the module's name. This value is then used if one was not found using the previous method.

Basic initializer that allows configurables to access their own config settings.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

check_kernel_offset(context, vlayer, address, progress_callback=None)

Scans a virtual address.

Return type

Optional[Tuple[str, int, Dict[str, Union[bytes, str, int, None]]]]

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

determine_valid_kernel(context, potential_layers, progress_callback=None)

Runs through the identified potential kernels and verifies their suitability.

This carries out a scan using the pdb_signature scanner on a physical layer. It uses the results of the scan to determine the virtual offset of the kernel. On early windows implementations there is a fixed mapping between the physical and virtual addresses of the kernel. On more recent versions a search is conducted for a structure that will identify the kernel's virtual offset.

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **potential_layers** (*List[str]*) – List of layer names that the kernel might live at
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Function taking a percentage and optional description to be called during expensive computations to indicate progress

Return type

Optional[Tuple[str, int, Dict[str, Union[bytes, str, int, None]]]]

Returns

A dictionary of valid kernels

exclusion_list = ['linux', 'mac']

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_requirements(context, config_path, requirement_root, requirement_type, shortcut=True)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **config_path** (*str*) – Configuration path of the top-level requirement

- **requirement_root** (*RequirementInterface*) – Top-level requirement whose sub-requirements will all be searched
- **requirement_type** (*Union[Tuple[Type[RequirementInterface], ...], Type[RequirementInterface]*) – Type of requirement to find
- **shortcut** (*bool*) – Only returns requirements that live under unsatisfied requirements

Return type

List[Tuple[str, RequirementInterface]

Returns

A list of tuples containing the *config_path*, *sub_config_path* and requirement identifying the unsatisfied *Requirements*

find_virtual_layers_from_req(*context, config_path, requirement*)

Traverses the requirement tree, rooted at *requirement* looking for virtual layers that might contain a windows PDB.

Returns a list of possible layers

Parameters

- **context** (*ContextInterface*) – The context in which the *requirement* lives
- **config_path** (*str*) – The path within the *context* for the *requirement*'s configuration variables
- **requirement** (*RequirementInterface*) – The root of the requirement tree to search for `:class:`~volatility3.framework.interfaces.layers.TranslationLayerRequirement`` objects to scan

Return type

List[str]

Returns

A list of (layer_name, scan_results)

get_physical_layer_name(*context, vlayer*)

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

max_pdb_size = 4194304

method_fixed_mapping(*context, vlayer, progress_callback=None*)

Return type

`Optional[Tuple[str, int, Dict[str, Union[bytes, str, int, None]]]]`

method_kdbg_offset(*context, vlayer, progress_callback=None*)

Return type

`Optional[Tuple[str, int, Dict[str, Union[bytes, str, int, None]]]]`

method_module_offset(*context, vlayer, progress_callback=None*)

Return type

`Optional[Tuple[str, int, Dict[str, Union[bytes, str, int, None]]]]`

method_slow_scan(*context, vlayer, progress_callback=None*)

Return type

`Optional[Tuple[str, int, Dict[str, Union[bytes, str, int, None]]]]`

methods = [<function KernelPDBScanner.method_kdbg_offset>, <function KernelPDBScanner.method_module_offset>, <function KernelPDBScanner.method_fixed_mapping>, <function KernelPDBScanner.method_slow_scan>]

priority = 30

An ordering to indicate how soon this automagic should be run

recurse_symbol_fulfiller(*context, valid_kernel, progress_callback=None*)

Fulfills the `SymbolTableRequirements` in `self._symbol_requirements` found by the `recurse_symbol_requirements`.

This pass will construct any requirements that may need it in the context it was passed

Parameters

- **context** (`ContextInterface`) – Context on which to operate
- **valid_kernel** (`Tuple[str, int, Dict[str, Union[bytes, str, int, None]]]`) – A list of offsets where valid kernels have been found
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – Means of providing the user with feedback during long processes

Return type

`None`

set_kernel_virtual_offset(*context, valid_kernel*)

Traverses the requirement tree, looking for `kernel_virtual_offset` values that may need setting and sets it based on the previously identified `valid_kernel`.

Parameters

- **context** (`ContextInterface`) – Context on which to operate and provide the kernel virtual offset
- **valid_kernel** (`Tuple[str, int, Dict[str, Union[bytes, str, int, None]]]`) – List of valid kernels and offsets

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

volatility3.framework.automagic.stacker module

This module attempts to automatically stack layers.

This automagic module fulfills `TranslationLayerRequirement` that are not already fulfilled, by attempting to stack as many layers on top of each other as possible. The base/lowest layer is derived from the “automagic.general.single_location” configuration path. Layers are then attempting in likely height order, and once a layer successfully stacks on top of the existing layers, it is removed from the possible choices list (so no layer type can exist twice in the layer stack).

class `LayerStacker(*args, **kwargs)`

Bases: `AutomagicInterface`

Builds up layers in a single stack.

This class mimics the volatility 2 style of stacking address spaces. It builds up various layers based on separate `StackerLayerInterface` classes. These classes are built up based on a `stack_order` class variable each has.

This has a high priority to provide other automagic modules as complete a context/configuration tree as possible. Upon completion it will re-call the `ConstructionMagic`, so that any stacked layers are actually constructed and added to the context.

Basic initializer that allows configurables to access their own config settings.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

create_stackers_list()

Creates the list of stackers to use based on the config option

Return type`List[Type[StackerLayerInterface]]`**exclusion_list** = []

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_requirements(*context*, *config_path*, *requirement_root*, *requirement_type*, *shortcut=True*)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **config_path** (*str*) – Configuration path of the top-level requirement
- **requirement_root** (*RequirementInterface*) – Top-level requirement whose sub-requirements will all be searched
- **requirement_type** (`Union[Tuple[Type[RequirementInterface], ...], Type[RequirementInterface]]`) – Type of requirement to find
- **shortcut** (*bool*) – Only returns requirements that live under unsatisfied requirements

Return type`List[Tuple[str, RequirementInterface]]`**Returns**

A list of tuples containing the *config_path*, *sub_config_path* and requirement identifying the unsatisfied *Requirements*

classmethod find_suitable_requirements(*context*, *config_path*, *requirement*, *stacked_layers*)

Looks for translation layer requirements and attempts to apply the stacked layers to it. If it succeeds it returns the configuration path and layer name where the stacked nodes were spliced into the tree.

Return type`Optional[Tuple[str, str]]`**Returns**

A tuple of a configuration path and layer name for the top of the stacked layers
or None if suitable requirements are not found

classmethod get_requirements()

Returns a list of *RequirementInterface* objects required by this object.

Return type`List[RequirementInterface]`**classmethod make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

priority = 10

An ordering to indicate how soon this automagic should be run

stack(context, config_path, requirement, progress_callback)

Stacks the various layers and attaches these to a specific requirement.

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **config_path** (*str*) – Configuration path under which to store stacking data
- **requirement** (*RequirementInterface*) – Requirement that should have layers stacked on it
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Function to provide callback progress

Return type

`None`

classmethod stack_layer(context, initial_layer, stack_set=None, progress_callback=None)

Stacks as many possible layers on top of the initial layer as can be done.

WARNING: This modifies the context provided and may pollute it with unnecessary layers Recommended use is to: 1. Pass in context.clone() instead of context 2. When provided the layer list, choose the desired layer 3. Build the configuration using layer.build_configuration() 4. Merge the configuration into the original context with context.config.merge() 5. Call Construction magic to reconstruct the layers from just the configuration

Parameters

- **context** (*ContextInterface*) – The context on which to operate
- **initial_layer** (*str*) – The name of the initial layer within the context
- **stack_set** (*List[Type[StackerLayerInterface]]*) – A list of StackerLayerInterface objects in the order they should be stacked
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A function to report progress during the process

Returns

A list of layer names that exist in the provided context, stacked in order (highest to lowest)

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

choose_os_stackers(*plugin*)

Identifies the stackers that should be run, based on the plugin (and thus os) provided

Return type

`List[str]`

volatility3.framework.automagic.symbol_cache module

class **CacheManagerInterface**(*filename*)

Bases: `VersionableInterface`

add_identifier(*location, operating_system, identifier*)

Adds an identifier to the store

find_location(*identifier, operating_system*)

Returns the location of the symbol file given the identifier

Parameters

- **identifier** (`bytes`) – string that uniquely identifies a particular symbol table
- **operating_system** (`Optional[str]`) – optional string to restrict identifiers to just those for a particular operating system

Return type

`Optional[str]`

Returns

The location of the symbols file that matches the identifier

get_hash(*location*)

Returns the hash of the JSON from within a location ISF

Return type

`Optional[str]`

get_identifier(*location*)

Returns an identifier based on a specific location or None

Return type

`Optional[bytes]`

get_identifier_dictionary(*operating_system=None, local_only=False*)

Returns a dictionary of identifiers and locations

Parameters

- **operating_system** (`Optional[str]`) – If set, limits responses to a specific operating system
- **local_only** (`bool`) – Returns only local locations

Return type

`Dict[bytes, str]`

Returns

A dictionary of identifiers mapped to a location

get_identifiers(*operating_system*)

Returns all identifiers for a particular operating system

Return type

`List[bytes]`

get_local_locations()

Returns a list of all the local locations

Return type

`Iterable[str]`

get_location_statistics(*location*)

Returns ISF statistics based on the location

Return type

`Optional[Tuple[int, int, int, int]]`

Returns

A tuple of base_types, types, enums, symbols, or None is location not found

update()

Locates all files under the symbol directories. Updates the cache with additions, modifications and removals. This also updates remote locations based on a cache timeout.

version = (0, 0, 0)

class IdentifierProcessor

Bases: `object`

abstract classmethod get_identifier(*json*)

Method to extract the identifier from a particular operating system's JSON

Return type

`Optional[bytes]`

Returns

identifier is valid or None if not found

operating_system = None

class LinuxIdentifier

Bases: `IdentifierProcessor`

classmethod get_identifier(*json*)

Method to extract the identifier from a particular operating system's JSON

Return type

`Optional[bytes]`

Returns

identifier is valid or None if not found

operating_system = 'linux'

class MacIdentifier

Bases: `IdentifierProcessor`

classmethod `get_identifier(json)`

Method to extract the identifier from a particular operating system's JSON

Return type

`Optional[bytes]`

Returns

identifier is valid or None if not found

`operating_system = 'mac'`

class `RemoteIdentifierFormat(location)`

Bases: `object`

process(*identifiers, operating_system*)

Return type

`Generator[Tuple[bytes, str], None, None]`

process_v1(*identifiers, operating_system*)

Return type

`Generator[Tuple[bytes, str], None, None]`

class `SqliteCache(filename)`

Bases: `CacheManagerInterface`

add_identifier(*location, operating_system, identifier*)

Adds an identifier to the store

find_location(*identifier, operating_system*)

Returns the location of the symbol file given the identifier. If multiple locations exist for an identifier, the last found is returned

Parameters

- **identifier** (`bytes`) – string that uniquely identifies a particular symbol table
- **operating_system** (`Optional[str]`) – optional string to restrict identifiers to just those for a particular operating system

Return type

`Optional[str]`

Returns

The location of the symbols file that matches the identifier or None

get_hash(*location*)

Returns the hash of the JSON from within a location ISF

Return type

`Optional[str]`

get_identifier(*location*)

Returns an identifier based on a specific location or None

Return type

`Optional[bytes]`

get_identifier_dictionary(*operating_system=None, local_only=False*)

Returns a dictionary of identifiers and locations

Parameters

- **operating_system** (*Optional[str]*) – If set, limits responses to a specific operating system
- **local_only** (*bool*) – Returns only local locations

Return type

Dict[bytes, str]

Returns

A dictionary of identifiers mapped to a location

get_identifiers(*operating_system*)

Returns all identifiers for a particular operating system

Return type

List[bytes]

get_local_locations()

Returns a list of all the local locations

Return type

Generator[str, None, None]

get_location_statistics(*location*)

Returns ISF statistics based on the location

Return type

Optional[Tuple[int, int, int, int]]

Returns

A tuple of base_types, types, enums, symbols, or None is location not found

is_url_local(*url*)

Determines whether an url is local or not

Return type

bool

update(*progress_callback=None*)

Locates all files under the symbol directories. Updates the cache with additions, modifications and removals. This also updates remote locations based on a cache timeout.

version = (1, 0, 0)

class SymbolCacheMagic(*args, **kwargs)

Bases: *AutomagicInterface*

Runs through all symbol tables and caches their identifiers

Basic initializer that allows configurables to access their own config settings.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

exclusion_list = []

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_requirements(*context, config_path, requirement_root, requirement_type, shortcut=True*)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **config_path** (*str*) – Configuration path of the top-level requirement
- **requirement_root** (*RequirementInterface*) – Top-level requirement whose sub-requirements will all be searched
- **requirement_type** (*Union[Tuple[Type[RequirementInterface], ...], Type[RequirementInterface]*]) – Type of requirement to find
- **shortcut** (*bool*) – Only returns requirements that live under unsatisfied requirements

Return type*List[Tuple[str, RequirementInterface]]***Returns**

A list of tuples containing the config_path, sub_config_path and requirement identifying the unsatisfied *Requirements*

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type*List[RequirementInterface]***classmethod make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**priority = 0**

An ordering to indicate how soon this automagic should be run

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]`**class** `WindowsIdentifier`

Bases: `IdentifierProcessor`

classmethod `generate(pdb_name, guid, age)`**Return type**`bytes`**classmethod** `get_identifier(json)`

Returns the identifier for the file if one can be found

Return type`Optional[bytes]`**operating_system** = 'windows'**separator** = '|'**volatility3.framework.automagic.symbol_finder module****class** `SymbolFinder(context, config_path)`

Bases: `AutomagicInterface`

Symbol loader based on signature strings.

Basic initializer that allows configurables to access their own config settings.

banner_config_key: `str` = 'banner'**property** **banners:** `Dict[bytes, List[str]]`

Creates a cached copy of the results, but only it's been requested.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

exclusion_list = []

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_aslr: *Optional[Callable]* = None**find_requirements**(*context, config_path, requirement_root, requirement_type, shortcut=True*)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **config_path** (*str*) – Configuration path of the top-level requirement
- **requirement_root** (*RequirementInterface*) – Top-level requirement whose subrequirements will all be searched
- **requirement_type** (*Union[Tuple[Type[RequirementInterface], ...], Type[RequirementInterface]*]) – Type of requirement to find
- **shortcut** (*bool*) – Only returns requirements that live under unsatisfied requirements

Return type*List[Tuple[str, RequirementInterface]]***Returns**

A list of tuples containing the *config_path*, *sub_config_path* and requirement identifying the unsatisfied *Requirements*

classmethod get_requirements()

Returns a list of *RequirementInterface* objects required by this object.

Return type*List[RequirementInterface]***classmethod make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**operating_system:** `Optional[str] = None`**priority** = 40

An ordering to indicate how soon this automagic should be run

symbol_class: `Optional[str] = None`**classmethod** `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]`**volatility3.framework.automagic.windows module**

Module to identify the Directory Table Base and architecture of windows memory images.

This module contains a PageMapScanner that scans a physical layer to identify self-referential pointers. All windows versions include a self-referential pointer in their Directory Table Base's top table, in order to have a single offset that will allow manipulation of the page tables themselves.

In older windows version the self-referential pointer was at a specific fixed index within the table, which was different for each architecture. In very recent Windows versions, the self-referential pointer index has been randomized, so a different heuristic must be used. In these versions of windows it was found that the physical offset for the DTB was always within the range of 0x1a0000 to 0x1b0000. As such, a search for any self-referential pointer within these pages gives a high probability of being an accurate DTB.

The self-referential indices for older versions of windows are listed below:

Architecture	Index
x86	0x300
PAE	0x3
x64	0x1ED

class `DtbSelfRef32bit`Bases: `DtbSelfReferential`**class** `DtbSelfRef64bit`Bases: `DtbSelfReferential`**class** `DtbSelfRef64bitOldWindows`Bases: `DtbSelfReferential`**class** `DtbSelfRefPae`Bases: `DtbSelfReferential`

class DtbSelfReferential(*layer_type, ptr_struct, mask, valid_range, reserved_bits*)

Bases: [object](#)

A generic DTB test which looks for a self-referential pointer at *any* index within the page.

class PageMapScanner(*tests*)

Bases: [ScannerInterface](#)

Scans through all pages using DTB tests to determine a dtb offset and architecture.

property context: [ContextInterface](#) | **None**

property layer_name: **str** | **None**

overlap = 16384

tests = [<volatility3.framework.automagic.windows.DtbSelfRef64bit object>,
<volatility3.framework.automagic.windows.DtbSelfRefPae object>,
<volatility3.framework.automagic.windows.DtbSelfRef32bit object>]

The default tests to run when searching for DTBs

thread_safe = **True**

version = (0, 0, 0)

class WinSwapLayers(*context, config_path, *args, **kwargs*)

Bases: [AutomagicInterface](#)

Class to read swap_layers filenames from single-swap-layers, create the layers and populate the single-layers swap_layers.

Basic initializer that allows configurables to access their own config settings.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

[HierarchicalDict](#)

property config: [HierarchicalDict](#)

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: **str**

The configuration path on which this configurable lives.

property context: [ContextInterface](#)

The context object that this configurable belongs to/configuration is stored in.

exclusion_list = ['linux', 'mac']

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_requirements(*context, config_path, requirement_root, requirement_type, shortcut=True*)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*

Parameters

- **context** (*ContextInterface*) – Context on which to operate
- **config_path** (*str*) – Configuration path of the top-level requirement
- **requirement_root** (*RequirementInterface*) – Top-level requirement whose sub-requirements will all be searched
- **requirement_type** (*Union[Tuple[Type[RequirementInterface], ...], Type[RequirementInterface]*) – Type of requirement to find
- **shortcut** (*bool*) – Only returns requirements that live under unsatisfied requirements

Return type

List[Tuple[str, RequirementInterface]

Returns

A list of tuples containing the config_path, sub_config_path and requirement identifying the unsatisfied *Requirements*

static find_swap_requirement(*config, requirement*)

Takes a Translation layer and returns its swap_layer requirement.

Return type

Tuple[str, Optional[LayerListRequirement]]

classmethod get_requirements()

Returns the requirements of this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

priority = 10

An ordering to indicate how soon this automagic should be run

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`**class WindowsIntelStacker**Bases: `StackerLayerInterface`**exclusion_list:** `List[str] = ['mac', 'linux']`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod stack(*context, layer_name, progress_callback=None*)

Attempts to determine and stack an intel layer on a physical layer where possible.

Where the DTB scan fails, it attempts a heuristic of checking for the DTB within a specific range. New versions of windows, with randomized self-referential pointers, appear to always load their dtb within a small specific range (`0x1a0000` and `0x1b0000`), so instead we scan for all self-referential pointers in that range, and ignore any that contain multiple self-references (since the DTB is very unlikely to point to itself more than once).

Return type`Optional[DataLayerInterface]`**stack_order** = 40

The order in which to attempt stacking, the lower the earlier

classmethod stacker_slow_warning()

```
test_sets = [('Detecting Self-referential pointer for recent windows',
[<volatility3.framework.automagic.windows.DtbSelfRef64bit object>], [(1376256,
1376256), (6619136, 655360)]), ('Older windows fixed location self-referential
pointers', [<volatility3.framework.automagic.windows.DtbSelfRefPae object>,
<volatility3.framework.automagic.windows.DtbSelfRef32bit object>,
<volatility3.framework.automagic.windows.DtbSelfRef64bitOldWindows object>],
[(196608, 16777216)])]
```

volatility3.framework.configuration package**Submodules****volatility3.framework.configuration.requirements module**

Contains standard Requirement types that all adhere to the RequirementInterface.

These requirement types allow plugins to request simple information types (such as strings, integers, etc) as well as indicating what they expect to be in the context (such as particular layers or symboltables).

class BooleanRequirement(*name, description=None, default=None, optional=False*)Bases: `SimpleTypeRequirement`

A requirement type that contains a boolean value.

Parameters

- **name** (`str`) – The name of the requirement
- **description** (`str`) – A short textual description of the requirement
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – The default value for the requirement if no value is provided

- **optional** (`bool`) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Always raises a `TypeError` as instance requirements cannot have children.

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (`ContextInterface`) – the configuration store to find the value for this requirement
- **config_path** (`str`) – the configuration path of the instance of the requirement to be recovered
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – a default value to provide if the requirement's configuration value is not found

Return type

`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`

property default: `int | bool | bytes | str | List[int | bool | bytes | str] | None`

Returns the default value if one is set.

property description: `str`

A short description of what the Requirement is designed to affect or achieve.

instance_type

alias of `bool`

property name: `str`

The name of the Requirement.

Names cannot contain `CONFIG_SEPARATOR` ('.' by default) since this is used within the configuration hierarchy.

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Always raises a `TypeError` as instance requirements cannot have children.

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Validates the instance requirement based upon its *instance_type*.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (`ContextInterface`) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type`Dict[str, RequirementInterface]`**Returns**

A dictionary of full configuration paths for each unsatisfied child-requirement

class BytesRequirement(*name*, *description=None*, *default=None*, *optional=False*)

Bases: `SimpleTypeRequirement`

A requirement type that contains a byte string.

Parameters

- **name** (`str`) – The name of the requirement
- **description** (`str`) – A short textual description of the requirement
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – The default value for the requirement if no value is provided
- **optional** (`bool`) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Always raises a `TypeError` as instance requirements cannot have children.

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (`ContextInterface`) – the configuration store to find the value for this requirement
- **config_path** (`str`) – the configuration path of the instance of the requirement to be recovered
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – a default value to provide if the requirement's configuration value is not found

Return type`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`

property default: `int | bool | bytes | str | List[int | bool | bytes | str] | None`

Returns the default value if one is set.

property description: `str`

A short description of what the Requirement is designed to affect or achieve.

instance_type

alias of `bytes`

property name: `str`

The name of the Requirement.

Names cannot contain `CONFIG_SEPARATOR` ('.' by default) since this is used within the configuration hierarchy.

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Always raises a `TypeError` as instance requirements cannot have children.

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Validates the instance requirement based upon its *instance_type*.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class ChoiceRequirement(*choices*, **args*, ***kwargs*)

Bases: *RequirementInterface*

Allows one from a choice of strings.

Constructs the object.

Parameters

choices (*List[str]*) – A list of possible string options that can be chosen from

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

None

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: `str`

A short description of what the Requirement is designed to affect or achieve.

property name: `str`

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

`None`

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context, config_path*)

Validates the provided value to ensure it is one of the available choices.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context, config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class ComplexListRequirement(*name, description=None, default=None, optional=False*)

Bases: *MultiRequirement, ConfigurableRequirementInterface*

Allows a variable length list of requirements.

Parameters

- **name** (`str`) – The name of the requirement
- **description** (`str`) – A short textual description of the requirement
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – The default value for the requirement if no value is provided
- **optional** (`bool`) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

None

build_configuration(*context*, *config_path*, *_*)

Proxies to a ConfigurableInterface if necessary.

Return type

HierarchicalDict

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

abstract construct(*context*, *config_path*)

Method for constructing within the context any required elements from subrequirements.

Return type

None

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

classmethod get_requirements()

Return type

List[RequirementInterface]

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

abstract new_requirement(*index*)

Builds a new requirement based on the specified index.

Return type

RequirementInterface

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

`None`

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context, config_path*)

Validates the provided value to ensure it is one of the available choices.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context, config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class IntRequirement(*name, description=None, default=None, optional=False*)

Bases: *SimpleTypeRequirement*

A requirement type that contains a single integer.

Parameters

- **name** (`str`) – The name of the requirement
- **description** (`str`) – A short textual description of the requirement
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – The default value for the requirement if no value is provided
- **optional** (`bool`) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Always raises a `TypeError` as instance requirements cannot have children.

config_value(*context, config_path, default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement

- **config_path** (*str*) – the configuration path of the instance of the requirement to be re-covered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement’s configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

instance_type

alias of *int*

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: *bool*

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Always raises a *TypeError* as instance requirements cannot have children.

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context, config_path*)

Validates the instance requirement based upon its *instance_type*.

Return type

Dict[str, RequirementInterface]

unsatisfied_children(*context, config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class LayerListRequirement(*name, description=None, default=None, optional=False*)

Bases: *ComplexListRequirement*

Allows a variable length list of layers that must exist.

Parameters

- **name** (*str*) – The name of the requirement

- **description** (*str*) – A short textual description of the requirement
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]*) – The default value for the requirement if no value is provided
- **optional** (*bool*) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

None

build_configuration(*context, config_path, _*)

Proxies to a ConfigurableInterface if necessary.

Return type

HierarchicalDict

config_value(*context, config_path, default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

construct(*context, config_path*)

Method for constructing within the context any required elements from subrequirements.

Return type

None

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

classmethod get_requirements()

Return type

List[RequirementInterface]

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR ('.' by default) since this is used within the configuration hierarchy.

new_requirement(*index*)

Constructs a new requirement based on the specified index.

Return type

RequirementInterface

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

`None`

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context, config_path*)

Validates the provided value to ensure it is one of the available choices.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context, config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class ListRequirement(*element_type=<class 'str'>, max_elements=0, min_elements=None, *args, **kwargs*)

Bases: *RequirementInterface*

Allows for a list of a specific type of requirement (all of which must be met for this requirement to be met) to be specified.

This roughly correlates to allowing a number of arguments to follow a command line parameter, such as a list of integers or a list of strings.

It is distinct from a multi-requirement which stores the subrequirements in a dictionary, not a list, and does not allow for a dynamic number of values.

Constructs the object.

Parameters

- **element_type** (`Type[Union[int, bool, bytes, str]]`) – The (requirement) type of each element within the list

- **contain** (*max_elements*; *The maximum number of acceptable elements this list can*) –
- **min_elements** (*Optional[int]*) – The minimum number of acceptable elements this list can contain

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

None

config_value(*context, config_path, default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: *bool*

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

None

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Check the types on each of the returned values and their number and then call the element type's check for each one.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class ModuleRequirement(*name*, *description=None*, *default=False*, *architectures=None*, *optional=False*)

Bases: *ConstructableRequirementInterface*, *ConfigurableRequirementInterface*

Parameters

- **name** (*str*) – The name of the requirement
- **description** (*str*) – A short textual description of the requirement
- **default** (*bool*) – The default value for the requirement if no value is provided
- **optional** (*bool*) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

`None`

build_configuration(*context*, *_*, *value*)

Builds the appropriate configuration for the specified requirement.

Return type

HierarchicalDict

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]*) – a default value to provide if the requirement's configuration value is not found

Return type`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`**construct**(*context*, *config_path*)

Constructs the appropriate layer and adds it based on the class parameter.

Return type`None`**property default:** `int | bool | bytes | str | List[int | bool | bytes | str] | None`

Returns the default value if one is set.

property description: `str`

A short description of what the Requirement is designed to affect or achieve.

classmethod `get_requirements()`**Return type**`List[RequirementInterface]`**property name:** `str`

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type`None`**property requirements:** `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Validate that the value is a valid module

Return type`Dict[str, RequirementInterface]`**unsatisfied_children**(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class MultiRequirement(*name, description=None, default=None, optional=False*)

Bases: [RequirementInterface](#)

Class to hold multiple requirements.

Technically the Interface could handle this, but it's an interface, so this is a concrete implementation.

Parameters

- **name** ([str](#)) – The name of the requirement
- **description** ([str](#)) – A short textual description of the requirement
- **default** ([Union\[int, bool, bytes, str, List\[Union\[int, bool, bytes, str\]\], None\]](#)) – The default value for the requirement if no value is provided
- **optional** ([bool](#)) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement ([RequirementInterface](#)) – The requirement to add as a child-requirement

Return type

[None](#)

config_value(*context, config_path, default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** ([ContextInterface](#)) – the configuration store to find the value for this requirement
- **config_path** ([str](#)) – the configuration path of the instance of the requirement to be recovered
- **default** ([Union\[int, bool, bytes, str, List\[Union\[int, bool, bytes, str\]\], None\]](#)) – a default value to provide if the requirement's configuration value is not found

Return type

[Union\[int, bool, bytes, str, List\[Union\[int, bool, bytes, str\]\], None\]](#)

property default: [int](#) | [bool](#) | [bytes](#) | [str](#) | [List\[int | bool | bytes | str\]](#) | [None](#)

Returns the default value if one is set.

property description: [str](#)

A short description of what the Requirement is designed to affect or achieve.

property name: [str](#)

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: [bool](#)

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

None

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context, config_path*)

Method to validate the value stored at *config_path* for the configuration object against a context.

Returns a list containing its own name (or multiple unsatisfied requirement names) when invalid

Parameters

- **context** (*ContextInterface*) – The context object containing the configuration for this requirement
- **config_path** (*str*) – The configuration path for this requirement to test satisfaction

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of configuration-paths to requirements that could not be satisfied

unsatisfied_children(*context, config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class PluginRequirement(*name, description=None, default=False, optional=False, plugin=None, version=None*)

Bases: *VersionRequirement*

Parameters

- **name** (*str*) – The name of the requirement
- **description** (*str*) – A short textual description of the requirement
- **default** (*bool*) – The default value for the requirement if no value is provided
- **optional** (*bool*) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

None

config_value(*context, config_path, default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

classmethod matches_required(*required, version*)

Return type

bool

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: *bool*

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

None

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Method to validate the value stored at *config_path* for the configuration object against a context.

Returns a list containing its own name (or multiple unsatisfied requirement names) when invalid

Parameters

- **context** (*ContextInterface*) – The context object containing the configuration for this requirement
- **config_path** (*str*) – The configuration path for this requirement to test satisfaction

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of configuration-paths to requirements that could not be satisfied

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class StringRequirement(*name*, *description=None*, *default=None*, *optional=False*)

Bases: *SimpleTypeRequirement*

A requirement type that contains a single unicode string.

Parameters

- **name** (*str*) – The name of the requirement
- **description** (*str*) – A short textual description of the requirement
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]*) – The default value for the requirement if no value is provided
- **optional** (*bool*) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Always raises a *TypeError* as instance requirements cannot have children.

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered

- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None`)
– a default value to provide if the requirement’s configuration value is not found

Return type

`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`

property default: `int | bool | bytes | str | List[int | bool | bytes | str] | None`

Returns the default value if one is set.

property description: `str`

A short description of what the Requirement is designed to affect or achieve.

instance_type

alias of `str`

property name: `str`

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Always raises a `TypeError` as instance requirements cannot have children.

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context, config_path*)

Validates the instance requirement based upon its *instance_type*.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context, config_path*)

Method that will validate all child requirements.

Parameters

- **context** (`ContextInterface`) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class SymbolTableRequirement(*args, **kwargs)

Bases: `ConstructableRequirementInterface, ConfigurableRequirementInterface`

Class maintaining the limitations on what sort of symbol spaces are acceptable.

Parameters

- **name** – The name of the requirement
- **description** – A short textual description of the requirement

- **default** – The default value for the requirement if no value is provided
- **optional** – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

None

build_configuration(*context*, *_*, *value*)

Builds the appropriate configuration for the specified requirement.

Return type

HierarchicalDict

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

construct(*context*, *config_path*)

Constructs the symbol space within the context based on the subrequirements.

Return type

None

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: *bool*

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type`None`**property requirements:** `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Validate that the value is a valid within the symbol space of the provided context.

Return type`Dict[str, RequirementInterface]`**unsatisfied_children**(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (`ContextInterface`) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type`Dict[str, RequirementInterface]`**Returns**

A dictionary of full configuration paths for each unsatisfied child-requirement

class TranslationLayerRequirement(*name*, *description=None*, *default=None*, *optional=False*, *oses=None*, *architectures=None*)

Bases: `ConstructableRequirementInterface`, `ConfigurableRequirementInterface`

Class maintaining the limitations on what sort of translation layers are acceptable.

Constructs a Translation Layer Requirement.

The configuration option's value will be the name of the layer once it exists in the store

Parameters

- **name** (`str`) – Name of the configuration requirement
- **description** (`str`) – Description of the configuration requirement
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – A default value (should not be used for TranslationLayers)
- **optional** (`bool`) – Whether the translation layer is required or not
- **oses** (`List`) – A list of valid operating systems which can satisfy this requirement
- **architectures** (`List`) – A list of valid architectures which can satisfy this requirement

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters**requirement** (`RequirementInterface`) – The requirement to add as a child-requirement**Return type**`None`

build_configuration(*context*, *_*, *value*)

Builds the appropriate configuration for the specified requirement.

Return type

HierarchicalDict

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement’s configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

construct(*context*, *config_path*)

Constructs the appropriate layer and adds it based on the class parameter.

Return type

None

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: *bool*

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

None

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Validate that the value is a valid layer name and that the layer adheres to the requirements.

Return type

Dict[str, RequirementInterface]

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class URIRequirement(*name*, *description=None*, *default=None*, *optional=False*)

Bases: *StringRequirement*

A requirement type that contains a single unicode string that is a valid URI.

Parameters

- **name** (*str*) – The name of the requirement
- **description** (*str*) – A short textual description of the requirement
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]*) – The default value for the requirement if no value is provided
- **optional** (*bool*) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Always raises a *TypeError* as instance requirements cannot have children.

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

instance_type

alias of *str*

classmethod `location_from_file(filename)`

Returns the URL location from a file parameter (which may be a URL)

Parameters

filename (`str`) – The path to the file (either an absolute, relative, or URL path)

Return type

`str`

Returns

The URL for the location of the file

property name: `str`

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Always raises a `TypeError` as instance requirements cannot have children.

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Validates the instance requirement based upon its *instance_type*.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (`ContextInterface`) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class `VersionRequirement(name, description=None, default=False, optional=False, component=None, version=None)`

Bases: `RequirementInterface`

Parameters

- **name** (`str`) – The name of the requirement
- **description** (`str`) – A short textual description of the requirement
- **default** (`bool`) – The default value for the requirement if no value is provided
- **optional** (`bool`) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

None

config_value(*context, config_path, default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

classmethod matches_required(*required, version*)

Return type

bool

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: *bool*

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

None

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Method to validate the value stored at *config_path* for the configuration object against a context.

Returns a list containing its own name (or multiple unsatisfied requirement names) when invalid

Parameters

- **context** (*ContextInterface*) – The context object containing the configuration for this requirement
- **config_path** (*str*) – The configuration path for this requirement to test satisfaction

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of configuration-paths to requirements that could not be satisfied

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

volatility3.framework.constants package

Volatility 3 Constants.

Stores all the constant values that are generally fixed throughout volatility This includes default scanning block sizes, etc.

AUTOMAGIC_CONFIG_PATH = 'automagic'

The root section within the context configuration for automagic values

BANG = '!'

Constant used to delimit table names from type names when referring to a symbol

CACHE_PATH = '/home/docs/.cache/volatility3'

Default path to store cached data

CACHE_SQLITE_SCHEMA_VERSION = 1

Version for the sqlite3 cache schema

IDENTIFIERS_FILENAME = 'identifier.cache'

Default location to record information about available identifiers

ISF_EXTENSIONS = ['.json', '.json.xz', '.json.gz', '.json.bz2']

List of accepted extensions for ISF files

ISF_MINIMUM_DEPRECATED = (3, 9, 9)

The highest version of the ISF that's deprecated (usually higher than supported)

ISF_MINIMUM_SUPPORTED = (2, 0, 0)

The minimum supported version of the Intermediate Symbol Format

LOGLEVEL_DEBUG = 10

-vv

Type

Logging level for debugging data, showed when the user requests more logging detail

LOGLEVEL_INFO = 20

-v

Type

Logging level for information data, showed when use the requests any logging

LOGLEVEL_V = 9

-vvv

Type

Logging level for the lowest "extra" level of logging

LOGLEVEL_VV = 8

-vvvv

Type

Logging level for two levels of detail

LOGLEVEL_VVV = 7

-vvvvv

Type

Logging level for three levels of detail

LOGLEVEL_VVVV = 6

-vvvvvv

Type

Logging level for four levels of detail

OFFLINE = False

Whether to go online to retrieve missing/necessary JSON files

PACKAGE_VERSION = '2.7.0'

The canonical version of the volatility3 package

PARALLELISM = Parallelism.Off

Default value to the parallelism setting used throughout volatility

**PLUGINS_PATH = ['/home/docs/checkouts/readthedocs.org/user_builds/volatility3/checkouts/latest/volatility3/plugins',
'/home/docs/checkouts/readthedocs.org/user_builds/volatility3/checkouts/latest/volatility3/framework/plugins']**

Default list of paths to load plugins from (volatility3/plugins and volatility3/framework/plugins)

```
class Parallelism(value, names=None, *, module=None, qualname=None, type=None, start=1,
                  boundary=None)
```

Bases: `IntEnum`

An enumeration listing the different types of parallelism applied to volatility.

Multiprocessing = 2

Off = 0

Threading = 1

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(byteorder='big', *, signed=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(length=1, byteorder='big', *, signed=False)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an `OverflowError` is raised.

ProgressCallback

Type information for ProgressCallback objects

alias of `Optional[Callable[[float, str], None]]`

REMOTE_ISF_URL = None

Remote URL to query for a list of ISF addresses

SQLITE_CACHE_PERIOD = '-3 days'

SQLite time modifier for how long each item is valid in the cache for

```
SYMBOL_BASEPATHS = ['/home/docs/checkouts/readthedocs.org/user_builds/volatility3/
checkouts/latest/volatility3/symbols',
'/home/docs/checkouts/readthedocs.org/user_builds/volatility3/checkouts/latest/
volatility3/framework/symbols']
```

Default list of paths to load symbols from (volatility3/symbols and volatility3/framework/symbols)

Subpackages

volatility3.framework.constants.linux package

Volatility 3 Linux Constants.

Linux-specific values that aren't found in debug symbols

class **ELF_CLASS**(*value*, *names=None*, *, *module=None*, *qualname=None*, *type=None*, *start=1*, *boundary=None*)

Bases: `IntEnum`

ELF header class types

ELFCLASS32 = 1

ELFCLASS64 = 2

ELFCLASSNONE = 0

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(*byteorder='big', *, signed=False*)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use 'sys.byteorder' as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An OverflowError is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use 'sys.byteorder' as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an OverflowError is raised.

class ELF_IDENT(*value, names=None, *, module=None, qualname=None, type=None, start=1, boundary=None*)

Bases: `IntEnum`

ELF header e_ident indexes

EI_CLASS = 4

EI_DATA = 5

EI_MAG0 = 0

EI_MAG1 = 1

EI_MAG2 = 2

EI_MAG3 = 3

EI_OSABI = 7

EI_PAD = 8

EI_VERSION = 6

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(*byteorder*='big', *, *signed*=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(length=1, byteorder='big', *, signed=False)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `'sys.byteorder'` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an `OverflowError` is raised.

KERNEL_NAME = '__kernel__'

The value hard coded from the Linux Kernel (hence not extracted from the layer itself)

volatility3.framework.constants.windows package

Volatility 3 Windows Constants.

Windows-specific values that aren't found in debug symbols

KERNEL_MODULE_NAMES = ['ntkrnlmp', 'ntkrnlpa', 'ntkrpamp', 'ntoskrnl']

The list of names that kernel modules can have within the windows OS

volatility3.framework.contexts package

A *Context* maintains the accumulated state required for various plugins and framework functions.

This has been made an object to allow quick swapping and changing of contexts, to allow a plugin to act on multiple different contexts without them interfering with each other.

class ConfigurableModule(context, config_path, name)

Bases: [Module](#), [ConfigurableInterface](#)

Constructs a new os-independent module.

Parameters

- **context** ([ContextInterface](#)) – The context within which this module will exist
- **config_path** ([str](#)) – The path within the context's configuration tree
- **name** ([str](#)) – The name of the module

build_configuration()

Builds the configuration dictionary for this specific Module

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

Context that the module uses.

classmethod create(*context, module_name, layer_name, offset, **kwargs*)**Return type**

Module

get_absolute_symbol_address(*name*)

Returns the absolute address of the symbol within this module

Return type

int

get_enumeration(*name*)

Returns an enumeration from the module's symbol table.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(*name*)

Returns a symbol object from the module's symbol table.

Return type

SymbolInterface

get_symbols_by_absolute_location(*offset, size=0*)

Returns the symbols within this module that live at the specified absolute offset provided.

Return type

List[str]

get_type(*name*)

Returns a type from the module's symbol table.

Return type

Template

has_enumeration(*name*)

Determines whether an enumeration is present in the module's symbol table.

Return type

bool

has_symbol(*name*)

Determines whether a symbol is present in the module's symbol table.

Return type

`bool`

has_type(*name*)

Determines whether a type is present in the module's symbol table.

Return type

`bool`

property layer_name: `str`

Layer name in which the Module resides.

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property name: `str`

The name of the constructed module.

object(*object_type*, *offset=None*, *native_layer_name=None*, *absolute=False*, ***kwargs*)

Returns an object created using the `symbol_table_name` and `layer_name` of the Module.

Parameters

- **object_type** (`str`) – Name of the type/enumeration (within the module) to construct
- **offset** (`int`) – The location of the object, ignored when `symbol_type` is `SYMBOL`
- **native_layer_name** (*Optional*[`str`]) – Name of the layer in which constructed objects are made (for pointers)
- **absolute** (`bool`) – whether the type's offset is absolute within memory or relative to the module

Return type

ObjectInterface

object_from_symbol(*symbol_name*, *native_layer_name=None*, *absolute=False*, *object_type=None*, ***kwargs*)

Returns an object based on a specific symbol (containing type and offset information) and the `layer_name` of the Module. This will throw a `ValueError` if the symbol does not contain an associated type, or if the symbol name is invalid. It will throw a `SymbolError` if the symbol cannot be found.

Parameters

- **symbol_name** (*str*) – Name of the symbol (within the module) to construct
- **native_layer_name** (*Optional[str]*) – Name of the layer in which constructed objects are made (for pointers)
- **absolute** (*bool*) – whether the symbol’s address is absolute or relative to the module
- **object_type** (*Union[str, ObjectInterface, None]*) – Override for the type from the symbol to use (or if the symbol type is missing)

Return type*ObjectInterface***property offset:** *int*

Returns the offset that the module resides within the layer of layer_name.

property symbol_table_name: *str*

The name of the symbol table associated with this module

property symbols

Lists the symbols contained in the symbol table for this module

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type*Dict[str, RequirementInterface]***class Context**

Bases: *ContextInterface*

Maintains the context within which to construct objects.

The context object is the main method of carrying around state that’s been constructed for the purposes of investigating memory. It contains a `symbol_space` of all the symbols that can be accessed by plugins using the context. It also contains the memory made up of data and translation layers, and it contains a factory method for creating new objects.

Other context objects can be constructed as long as they support the *ContextInterface*. This is the primary context object to be used in the volatility framework. It maintains the

Initializes the context.

add_layer(*layer*)

Adds a named translation layer to the context.

Parameters

layer (*DataLayerInterface*) – The layer to be added to the memory

Raises

volatility3.framework.exceptions.LayerException – if the layer is already present, or has unmet dependencies

Return type*None*

add_module(*module*)

Adds a named module to the context.

Parameters

module (*ModuleInterface*) – The module to be added to the module object collection

Raises

volatility3.framework.exceptions.VolatilityException – if the module is already present, or has unmet dependencies

clone()

Produce a clone of the context (and configuration), allowing modifications to be made without affecting any mutable objects in the original.

Memory constraints may become an issue for this function depending on how much is actually stored in the context

Return type

ContextInterface

property config: *HierarchicalDict*

Returns a mutable copy of the configuration, but does not allow the whole configuration to be altered.

property layers: *LayerContainer*

A LayerContainer object, allowing access to all data and translation layers currently available within the context.

module(*module_name*, *layer_name*, *offset*, *native_layer_name*=None, *size*=None)

Constructs a new os-independent module.

Parameters

- **module_name** (*str*) – The name of the module
- **layer_name** (*str*) – The layer within the context in which the module exists
- **offset** (*int*) – The offset at which the module exists in the layer
- **native_layer_name** (*Optional[str]*) – The default native layer for objects constructed by the module
- **size** (*Optional[int]*) – The size, in bytes, that the module occupies from offset location within the layer named *layer_name*

Return type

ModuleInterface

property modules: *ModuleContainer*

A container for modules loaded in this context

object(*object_type*, *layer_name*, *offset*, *native_layer_name*=None, *arguments*)**

Object factory, takes a context, symbol, offset and optional layername.

Looks up the layername in the context, finds the object template based on the symbol, and constructs an object using the object template on the layer at the offset.

Parameters

- **object_type** (*Union[str, Template]*) – The name (or template) of the symbol type on which to construct the object. If this is a name, it should contain an explicit table name.
- **layer_name** (*str*) – The name of the layer on which to construct the object

- **offset** (`int`) – The offset within the layer at which the data used to create the object lives
- **native_layer_name** (`Optional[str]`) – The name of the layer the object references (for pointers) if different to `layer_name`

Return type*ObjectInterface***Returns**

A fully constructed object

property symbol_space: *SymbolSpaceInterface*

The space of all symbols that can be accessed within this context.

class Module(*context, config_path, name*)Bases: *ModuleInterface*

Constructs a new os-independent module.

Parameters

- **context** (*ContextInterface*) – The context within which this module will exist
- **config_path** (`str`) – The path within the context's configuration tree
- **name** (`str`) – The name of the module

build_configuration()

Builds the configuration dictionary for this specific Module

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: *ContextInterface*

Context that the module uses.

classmethod create(*context, module_name, layer_name, offset, **kwargs*)**Return type***Module***get_absolute_symbol_address**(*name*)

Returns the absolute address of the symbol within this module

Return type`int`**get_enumeration**(*name*)

Returns an enumeration from the module's symbol table.

Return type*Template***classmethod get_requirements()**

Returns a list of RequirementInterface objects required by this object.

Return type`List[RequirementInterface]`**get_symbol(name)**

Returns a symbol object from the module's symbol table.

Return type`SymbolInterface`**get_symbols_by_absolute_location(offset, size=0)**

Returns the symbols within this module that live at the specified absolute offset provided.

Return type`List[str]`**get_type(name)**

Returns a type from the module's symbol table.

Return type`Template`**has_enumeration(name)**

Determines whether an enumeration is present in the module's symbol table.

Return type`bool`**has_symbol(name)**

Determines whether a symbol is present in the module's symbol table.

Return type`bool`**has_type(name)**

Determines whether a type is present in the module's symbol table.

Return type`bool`**property layer_name: str**

Layer name in which the Module resides.

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`

property name: `str`

The name of the constructed module.

object(*object_type*, *offset=None*, *native_layer_name=None*, *absolute=False*, ***kwargs*)

Returns an object created using the `symbol_table_name` and `layer_name` of the Module.

Parameters

- **object_type** (`str`) – Name of the type/enumeration (within the module) to construct
- **offset** (`int`) – The location of the object, ignored when `symbol_type` is `SYMBOL`
- **native_layer_name** (`Optional[str]`) – Name of the layer in which constructed objects are made (for pointers)
- **absolute** (`bool`) – whether the type's offset is absolute within memory or relative to the module

Return type

`ObjectInterface`

object_from_symbol(*symbol_name*, *native_layer_name=None*, *absolute=False*, *object_type=None*, ***kwargs*)

Returns an object based on a specific symbol (containing type and offset information) and the `layer_name` of the Module. This will throw a `ValueError` if the symbol does not contain an associated type, or if the symbol name is invalid. It will throw a `SymbolError` if the symbol cannot be found.

Parameters

- **symbol_name** (`str`) – Name of the symbol (within the module) to construct
- **native_layer_name** (`Optional[str]`) – Name of the layer in which constructed objects are made (for pointers)
- **absolute** (`bool`) – whether the symbol's address is absolute or relative to the module
- **object_type** (`Union[str, ObjectInterface, None]`) – Override for the type from the symbol to use (or if the symbol type is missing)

Return type

`ObjectInterface`

property offset: `int`

Returns the offset that the module resides within the layer of `layer_name`.

property symbol_table_name: `str`

The name of the symbol table associated with this module

property symbols

Lists the symbols contained in the symbol table for this module

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return `[]`, it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

class ModuleCollection(*modules=None*)

Bases: *ModuleContainer*

Class to contain a collection of SizedModules and reason about their contents.

add_module(*module*)

Adds a module to the module collection

This will throw an exception if the required dependencies are not met

Parameters

module (*ModuleInterface*) – the module to add to the list of modules (based on module.name)

Return type

None

deduplicate()

Returns a new deduplicated ModuleCollection featuring no repeated modules (based on data hash)

All 0 sized modules will have identical hashes and are therefore included in the deduplicated version

Return type

ModuleCollection

free_module_name(*prefix='module'*)

Returns an unused module name

Return type

str

get(*k*, *d*) → D[k] if k in D, else d. d defaults to None.

get_module_symbols_by_absolute_location(*offset*, *size=0*)

Returns a tuple of (module_name, list_of_symbol_names) for each module, where symbols live at the absolute offset in memory provided.

Return type

Iterable[Tuple[str, List[str]]]

get_modules_by_symbol_tables(*symbol_table*)

Returns the modules which use the specified symbol table name

Return type

Iterable[str]

items() → a set-like object providing a view on D's items

keys() → a set-like object providing a view on D's keys

property modules: *ModuleCollection*

A name indexed dictionary of modules using that name in this collection.

values() → an object providing a view on D's values

class SizedModule(*context*, *config_path*, *name*)

Bases: *Module*

Constructs a new os-independent module.

Parameters

- **context** (*ContextInterface*) – The context within which this module will exist

- **config_path** (*str*) – The path within the context’s configuration tree
- **name** (*str*) – The name of the module

build_configuration()

Builds the configuration dictionary for this specific Module

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

Context that the module uses.

classmethod create(*context, module_name, layer_name, offset, **kwargs*)

Return type

Module

get_absolute_symbol_address(*name*)

Returns the absolute address of the symbol within this module

Return type

int

get_enumeration(*name*)

Returns an enumeration from the module’s symbol table.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(*name*)

Returns a symbol object from the module’s symbol table.

Return type

SymbolInterface

get_symbols_by_absolute_location(*offset, size=0*)

Returns the symbols within this module that live at the specified absolute offset provided.

Return type

List[str]

get_type(*name*)

Returns a type from the module’s symbol table.

Return type

Template

has_enumeration(*name*)

Determines whether an enumeration is present in the module's symbol table.

Return type

`bool`

has_symbol(*name*)

Determines whether a symbol is present in the module's symbol table.

Return type

`bool`

has_type(*name*)

Determines whether a type is present in the module's symbol table.

Return type

`bool`

property hash: `str`

Hashes the module for equality checks.

The mapping should be sorted and should be quicker than reading the data We turn it into JSON to make a common string and use a quick hash, because collisions are unlikely

property layer_name: `str`

Layer name in which the Module resides.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property name: `str`

The name of the constructed module.

object(*object_type, offset=None, native_layer_name=None, absolute=False, **kwargs*)

Returns an object created using the symbol_table_name and layer_name of the Module.

Parameters

- **object_type** (`str`) – Name of the type/enumeration (within the module) to construct
- **offset** (`int`) – The location of the object, ignored when symbol_type is SYMBOL
- **native_layer_name** (*Optional*[`str`]) – Name of the layer in which constructed objects are made (for pointers)
- **absolute** (`bool`) – whether the type's offset is absolute within memory or relative to the module

Return type*ObjectInterface*

object_from_symbol(*symbol_name*, *native_layer_name*=None, *absolute*=False, *object_type*=None, ***kwargs*)

Returns an object based on a specific symbol (containing type and offset information) and the *layer_name* of the Module. This will throw a `ValueError` if the symbol does not contain an associated type, or if the symbol name is invalid. It will throw a `SymbolError` if the symbol cannot be found.

Parameters

- **symbol_name** (*str*) – Name of the symbol (within the module) to construct
- **native_layer_name** (*Optional[str]*) – Name of the layer in which constructed objects are made (for pointers)
- **absolute** (*bool*) – whether the symbol's address is absolute or relative to the module
- **object_type** (*Union[str, ObjectInterface, None]*) – Override for the type from the symbol to use (or if the symbol type is missing)

Return type*ObjectInterface*

property offset: *int*

Returns the offset that the module resides within the layer of *layer_name*.

property size: *int*

Returns the size of the module (0 for unknown size)

property symbol_table_name: *str*

The name of the symbol table associated with this module

property symbols

Lists the symbols contained in the symbol table for this module

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type*Dict[str, RequirementInterface]*

get_module_wrapper(*method*)

Returns a symbol using the *symbol_table_name* of the Module.

Return type*Callable*

volatility3.framework.interfaces package

The interfaces module contains the API interface for the core volatility framework.

These interfaces should help developers attempting to write components for the main framework and help them understand how to use the internal components of volatility to write plugins.

Submodules

volatility3.framework.interfaces.automagic module

Defines the automagic interfaces for populating the context before a plugin runs.

Automagic objects attempt to automatically fill configuration values that a user has not filled.

class AutomagicInterface(*context*, *config_path*, *args, **kwargs)

Bases: [ConfigurableInterface](#)

Class that defines an automagic component that can help fulfill *Requirements*

These classes are callable with the following parameters:

Parameters

- **context** ([ContextInterface](#)) – The context in which to store configuration data that the automagic might populate
- **config_path** ([str](#)) – Configuration path where the configurable's data under the context's config lives
- **configurable** – The top level configurable whose requirements may need satisfying
- **progress_callback** – An optional function accepting a percentage and optional description to indicate progress during long calculations

Note: The *context* provided here may be different to that provided during initialization. The *context* provided at initialization should be used for local configuration of the automagic itself, the *context* provided during the call is to be populated by the automagic.

Basic initializer that allows configurables to access their own config settings.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

[HierarchicalDict](#)

property config: [HierarchicalDict](#)

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: [str](#)

The configuration path on which this configurable lives.

property context: [*ContextInterface*](#)

The context object that this configurable belongs to/configuration is stored in.

exclusion_list = []

A list of plugin categories (typically operating systems) which the plugin will not operate on

find_requirements(*context, config_path, requirement_root, requirement_type, shortcut=True*)

Determines if there is actually an unfulfilled *Requirement* waiting.

This ensures we do not carry out an expensive search when there is no need for a particular *Requirement*

Parameters

- **context** ([*ContextInterface*](#)) – Context on which to operate
- **config_path** (*str*) – Configuration path of the top-level requirement
- **requirement_root** ([*RequirementInterface*](#)) – Top-level requirement whose subrequirements will all be searched
- **requirement_type** ([*Union\[Tuple\[Type\[RequirementInterface\], ...\], Type\[RequirementInterface\]\]*](#)) – Type of requirement to find
- **shortcut** (*bool*) – Only returns requirements that live under unsatisfied requirements

Return type

[*List\[Tuple\[str, RequirementInterface\]\]*](#)

Returns

A list of tuples containing the *config_path*, *sub_config_path* and requirement identifying the unsatisfied *Requirements*

classmethod get_requirements()

Returns a list of *RequirementInterface* objects required by this object.

Return type

[*List\[RequirementInterface\]*](#)

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** ([*ContextInterface*](#)) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

priority = 10

An ordering to indicate how soon this automagic should be run

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:


```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type

`Dict[str, RequirementInterface]`

class StackerLayerInterface

Bases: `object`

Class that takes a lower layer and attempts to build on it.

`stack_order` determines the order (from low to high) that stacking layers should be attempted lower levels should have lower *stack_orders*

exclusion_list: `List[str] = []`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod stack(*context, layer_name, progress_callback=None*)

Method to determine whether this builder can operate on the named layer. If so, modify the context appropriately.

Returns the name of any new layer stacked on top of this layer or None. The stacking is therefore strictly linear rather than tree driven.

Configuration options provided by the context are ignored, and defaults are to be used by this method to build a space where possible.

Parameters

- **context** (`ContextInterface`) – Context in which to construct the higher layer
- **layer_name** (`str`) – Name of the layer to stack on top of
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callback function to indicate progress through a scan (if one is necessary)

Return type

`Optional[DataLayerInterface]`

stack_order = 0

The order in which to attempt stacking, the lower the earlier

classmethod stacker_slow_warning()

volatility3.framework.interfaces.configuration module

The configuration module contains classes and functions for interacting with the configuration and requirement trees.

Volatility plugins can specify a list of requirements (which may have subrequirements, thus forming a requirement tree). These requirement trees can contain values, which are contained in a complementary configuration tree. These two trees act as a protocol between the plugins and users. The plugins provide requirements that must be fulfilled, and the users provide configurations values that fulfill those requirements. Where the user does not provide sufficient configuration values, automatic modules may extend the configuration tree themselves.

CONFIG_SEPARATOR = '.'

Use to specify the separator between configuration hierarchies

class `ClassRequirement(*args, **kwargs)`

Bases: `RequirementInterface`

Requires a specific class.

This is used as means to serialize specific classes for `TranslationLayerRequirement` and `SymbolTableRequirement` classes.

Parameters

- **name** – The name of the requirement
- **description** – A short textual description of the requirement
- **default** – The default value for the requirement if no value is provided
- **optional** – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (`RequirementInterface`) – The requirement to add as a child-requirement

Return type

`None`

property `cls`: `Type` | `None`

Contains the actual chosen class based on the configuration value's class name.

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (`ContextInterface`) – the configuration store to find the value for this requirement
- **config_path** (`str`) – the configuration path of the instance of the requirement to be recovered
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – a default value to provide if the requirement's configuration value is not found

Return type

`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`

property `default`: `int` | `bool` | `bytes` | `str` | `List[int | bool | bytes | str]` | `None`

Returns the default value if one is set.

property `description`: `str`

A short description of what the Requirement is designed to affect or achieve.

property `name`: `str`

The name of the Requirement.

Names cannot contain `CONFIG_SEPARATOR` (‘.’ by default) since this is used within the configuration hierarchy.

property `optional`: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

None

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context, config_path*)

Checks to see if a class can be recovered.

Return type

Dict[str, RequirementInterface]

unsatisfied_children(*context, config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class ConfigurableInterface(*context, config_path*)

Bases: *object*

Class to allow objects to have requirements and read configuration data from the context config tree.

Basic initializer that allows configurables to access their own config settings.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of RequirementInterface objects required by this object.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

class `ConfigurableRequirementInterface(name, description=None, default=None, optional=False)`

Bases: `RequirementInterface`

Simple Abstract class to provide build_required_config.

Parameters

- **name** (`str`) – The name of the requirement
- **description** (`str`) – A short textual description of the requirement
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – The default value for the requirement if no value is provided
- **optional** (`bool`) – Whether the requirement must be satisfied or not

add_requirement(requirement)

Adds a child to the list of requirements.

Parameters

requirement (`RequirementInterface`) – The requirement to add as a child-requirement

Return type

`None`

build_configuration(*context*, *config_path*, *value*)

Proxies to a ConfigurableInterface if necessary.

Return type

HierarchicalDict

config_value(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: *bool*

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

- **requirement** (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

None

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

abstract unsatisfied(*context*, *config_path*)

Method to validate the value stored at config_path for the configuration object against a context.

Returns a list containing its own name (or multiple unsatisfied requirement names) when invalid

Parameters

- **context** (*ContextInterface*) – The context object containing the configuration for this requirement
- **config_path** (*str*) – The configuration path for this requirement to test satisfaction

Return type`Dict[str, RequirementInterface]`**Returns**

A dictionary of configuration-paths to requirements that could not be satisfied

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type`Dict[str, RequirementInterface]`**Returns**

A dictionary of full configuration paths for each unsatisfied child-requirement

class ConstructableRequirementInterface(*args, **kwargs)

Bases: *RequirementInterface*

Defines a Requirement that can be constructed based on their own requirements.

This effectively offers a means for serializing specific python types, to be reconstructed based on simple configuration data. Each constructable records a *class* requirement, which indicates the object that will be constructed. That class may have its own requirements (which is why validation of a ConstructableRequirement must happen after the class configuration value has been provided). These values are then provided to the object's constructor by name as arguments (as well as the standard *context* and *config_path* arguments).

Parameters

- **name** – The name of the requirement
- **description** – A short textual description of the requirement
- **default** – The default value for the requirement if no value is provided
- **optional** – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type`None`**config_value**(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`) – a default value to provide if the requirement's configuration value is not found

Return type

`Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]`

abstract construct(*context*, *config_path*)

Method for constructing within the context any required elements from subrequirements.

Parameters

- **context** (*ContextInterface*) – The context object containing the configuration data for the constructable
- **config_path** (*str*) – The configuration path for the specific instance of this constructable

Return type

`None`

property default: `int | bool | bytes | str | List[int | bool | bytes | str] | None`

Returns the default value if one is set.

property description: `str`

A short description of what the Requirement is designed to affect or achieve.

property name: `str`

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

- **requirement** (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

`None`

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

abstract unsatisfied(*context*, *config_path*)

Method to validate the value stored at config_path for the configuration object against a context.

Returns a list containing its own name (or multiple unsatisfied requirement names) when invalid

Parameters

- **context** (*ContextInterface*) – The context object containing the configuration for this requirement
- **config_path** (*str*) – The configuration path for this requirement to test satisfaction

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of configuration-paths to requirements that could not be satisfied

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type

Dict[str, RequirementInterface]

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class HierarchicalDict(*initial_dict=None*, *separator='.'*)

Bases: *Mapping*

The core of configuration data, it is a mapping class that stores keys within itself, and also stores lower hierarchies.

Parameters

- **initial_dict** (*Dict[str, SimpleTypeRequirement]*) – A dictionary to populate the HierarchicalDict with initially
- **separator** (*str*) – A custom hierarchy separator (defaults to CONFIG_SEPARATOR)

branch(*key*)

Returns the HierarchicalDict housed under the key.

This differs from the data property, in that it is directed by the *key*, and all layers under that key are returned, not just those in that level.

Higher layers are not prefixed with the location of earlier layers, so branching a hierarchy containing *a.b.c.d* on *a.b* would return a hierarchy containing *c.d*, not *a.b.c.d*.

Parameters

key (*str*) – The location within the hierarchy to return higher layers.

Return type

HierarchicalDict

Returns

The HierarchicalDict underneath the specified key (not just the data at that key location in the tree)

clone()

Duplicates the configuration, allowing changes without affecting the original.

Return type

HierarchicalDict

Returns

A duplicate HierarchicalDict of this object

property data: *Dict*

Returns just the data-containing mappings on this level of the Hierarchy.

generator()

A generator for the data in this level and lower levels of this mapping.

Return type

Generator[str, None, None]

Returns

Returns each item in the top level data, and then all subkeys in a depth first order

get(*k*[, *d*]) → *D*[*k*] if *k* in *D*, else *d*. *d* defaults to *None*.

items() → a set-like object providing a view on *D*'s items

keys() → a set-like object providing a view on *D*'s keys

merge(*key*, *value*, *overwrite=False*)

Acts similarly to *splice*, but maintains previous values.

If *overwrite* is true, then entries in the new value are used over those that exist within key already

Parameters

- **key** (*str*) – The location within the hierarchy at which to merge the *value*
- **value** (*HierarchicalDict*) – *HierarchicalDict* to be merged under the key node
- **overwrite** (*bool*) – A boolean defining whether the value will be overwritten if it already exists

Return type

None

property separator: *str*

Specifies the hierarchy separator in use in this *HierarchyDict*.

splice(*key*, *value*)

Splices an existing *HierarchicalDictionary* under a specific key.

This can be thought of as an inverse of *branch*(), although *branch* does not remove the requested hierarchy, it simply returns it.

Return type

None

values() → an object providing a view on *D*'s values

class RequirementInterface(*name*, *description=None*, *default=None*, *optional=False*)

Bases: *object*

Class that defines a requirement.

A requirement is a means for plugins and other framework components to request specific configuration data. Requirements can either be simple types (such as *SimpleTypeRequirement*, *IntRequirement*, *BytesRequirement* and *StringRequirement*) or complex types (such as *TranslationLayerRequirement*, *SymbolTableRequirement* and *ClassRequirement*)

Parameters

- **name** (*str*) – The name of the requirement
- **description** (*str*) – A short textual description of the requirement
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]*) – The default value for the requirement if no value is provided
- **optional** (*bool*) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)

Adds a child to the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to add as a child-requirement

Return type

None

config_value(*context, config_path, default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None*) – a default value to provide if the requirement's configuration value is not found

Return type

Union[int, bool, bytes, str, List[Union[int, bool, bytes, str]], None]

property default: *int | bool | bytes | str | List[int | bool | bytes | str] | None*

Returns the default value if one is set.

property description: *str*

A short description of what the Requirement is designed to affect or achieve.

property name: *str*

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: *bool*

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Removes a child from the list of requirements.

Parameters

requirement (*RequirementInterface*) – The requirement to remove as a child-requirement

Return type

None

property requirements: *Dict[str, RequirementInterface]*

Returns a dictionary of all the child requirements, indexed by name.

abstract unsatisfied(*context, config_path*)

Method to validate the value stored at config_path for the configuration object against a context.

Returns a list containing its own name (or multiple unsatisfied requirement names) when invalid

Parameters

- **context** (*ContextInterface*) – The context object containing the configuration for this requirement

- **config_path** (*str*) – The configuration path for this requirement to test satisfaction

Return type*Dict*[*str*, *RequirementInterface*]**Returns**

A dictionary of configuration-paths to requirements that could not be satisfied

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (*ContextInterface*) – the context containing the configuration data for this requirement
- **config_path** (*str*) – the configuration path of this instance of the requirement

Return type*Dict*[*str*, *RequirementInterface*]**Returns**

A dictionary of full configuration paths for each unsatisfied child-requirement

class SimpleTypeRequirement(*name*, *description=None*, *default=None*, *optional=False*)Bases: *RequirementInterface*

Class to represent a single simple type (such as a boolean, a string, an integer or a series of bytes)

Parameters

- **name** (*str*) – The name of the requirement
- **description** (*str*) – A short textual description of the requirement
- **default** (*Union*[*int*, *bool*, *bytes*, *str*, *List*[*Union*[*int*, *bool*, *bytes*, *str*]], *None*) – The default value for the requirement if no value is provided
- **optional** (*bool*) – Whether the requirement must be satisfied or not

add_requirement(*requirement*)Always raises a *TypeError* as instance requirements cannot have children.**config_value**(*context*, *config_path*, *default=None*)

Returns the value for this Requirement from its config path.

Parameters

- **context** (*ContextInterface*) – the configuration store to find the value for this requirement
- **config_path** (*str*) – the configuration path of the instance of the requirement to be recovered
- **default** (*Union*[*int*, *bool*, *bytes*, *str*, *List*[*Union*[*int*, *bool*, *bytes*, *str*]], *None*) – a default value to provide if the requirement's configuration value is not found

Return type*Union*[*int*, *bool*, *bytes*, *str*, *List*[*Union*[*int*, *bool*, *bytes*, *str*]], *None*]**property default:** *int* | *bool* | *bytes* | *str* | *List*[*int* | *bool* | *bytes* | *str*] | *None*

Returns the default value if one is set.

property description: `str`

A short description of what the Requirement is designed to affect or achieve.

instance_type

alias of `bool`

property name: `str`

The name of the Requirement.

Names cannot contain CONFIG_SEPARATOR (‘.’ by default) since this is used within the configuration hierarchy.

property optional: `bool`

Whether the Requirement is optional or not.

remove_requirement(*requirement*)

Always raises a `TypeError` as instance requirements cannot have children.

property requirements: `Dict[str, RequirementInterface]`

Returns a dictionary of all the child requirements, indexed by name.

unsatisfied(*context*, *config_path*)

Validates the instance requirement based upon its *instance_type*.

Return type

`Dict[str, RequirementInterface]`

unsatisfied_children(*context*, *config_path*)

Method that will validate all child requirements.

Parameters

- **context** (`ContextInterface`) – the context containing the configuration data for this requirement
- **config_path** (`str`) – the configuration path of this instance of the requirement

Return type

`Dict[str, RequirementInterface]`

Returns

A dictionary of full configuration paths for each unsatisfied child-requirement

class VersionableInterface(*args, **kwargs)

Bases: `object`

A class that allows version checking so that plugins can request specific versions of components they made need

This currently includes other Plugins and scanners, but may be extended in the future

All version number should use semantic versioning

version = (0, 0, 0)

parent_path(*value*)

Returns the parent configuration path from a configuration path.

Return type

`str`

path_depth(*path*, *depth=1*)

Returns the *path* up to a certain depth.

Note that *depth* can be negative (such as *-x*) and will return all elements except for the last *x* components

Return type

str

path_head(*value*)

Return the top of the configuration path

Return type

str

path_join(**args*)

Joins configuration paths together.

Return type

str

volatility3.framework.interfaces.context module

Defines an interface for contexts, which hold the core components that a plugin will operate upon when running.

These include a *memory* container which holds a series of forest of layers, and a *symbol_space* which contains tables of symbols that can be used to interpret data in a layer. The context also provides some convenience functions, most notably the object constructor function, *object*, which will construct a symbol on a layer at a particular offset.

class ContextInterface

Bases: *object*

All context-like objects must adhere to the following interface.

This interface is present to avoid import dependency cycles.

Initializes the context with a *symbol_space*.

add_layer(*layer*)

Adds a named translation layer to the context memory.

Parameters

layer (*DataLayerInterface*) – Layer object to be added to the context memory

add_module(*module*)

Adds a named module to the context.

Parameters

module (*ModuleInterface*) – The module to be added to the module object collection

Raises

volatility3.framework.exceptions.VolatilityException – if the module is already present, or has unmet dependencies

clone()

Produce a clone of the context (and configuration), allowing modifications to be made without affecting any mutable objects in the original.

Memory constraints may become an issue for this function depending on how much is actually stored in the context

Return type*ContextInterface***abstract property config:** *HierarchicalDict*

Returns the configuration object for this context.

abstract property layers: *LayerContainer*

Returns the memory object for the context.

module(*module_name*, *layer_name*, *offset*, *native_layer_name=None*, *size=None*)

Create a module object.

A module object is associated with a symbol table, and acts like a context, but offsets locations by a known value and looks up symbols, by default within the associated symbol table. It can also be sized should that information be available.

Parameters

- **module_name** (*str*) – The name of the module
- **layer_name** (*str*) – The layer the module is associated with (which layer the module lives within)
- **offset** (*int*) – The initial/base offset of the module (used as the offset for relative symbols)
- **native_layer_name** (*Optional[str]*) – The default *native_layer_name* to use when the module constructs objects
- **size** (*Optional[int]*) – The size, in bytes, that the module occupies from offset location within the layer named *layer_name*

Return type*ModuleInterface***Returns**

A module object

abstract property modules: *ModuleContainer*

Returns the memory object for the context.

abstract object(*object_type*, *layer_name*, *offset*, *native_layer_name=None*, ***arguments*)

Object factory, takes a context, symbol, offset and optional *layer_name*.

Looks up the *layer_name* in the context, finds the object template based on the symbol, and constructs an object using the object template on the layer at the offset.

Parameters

- **object_type** (*Union[str, Template]*) – Either a string name of the type, or a *Template* of the type to be constructed
- **layer_name** (*str*) – The name of the layer on which to construct the object
- **offset** (*int*) – The address within the layer at which to construct the object
- **native_layer_name** (*str*) – The layer this object references (should it be a pointer or similar)

Return type*ObjectInterface***Returns**

A fully constructed object

abstract property symbol_space: [*SymbolSpaceInterface*](#)

Returns the symbol_space for the context.

This object must support the [*SymbolSpaceInterface*](#)

class ModuleContainer(*modules=None*)

Bases: [*Mapping*](#)

Container for multiple layers of data.

add_module(*module*)

Adds a module to the module collection

This will throw an exception if the required dependencies are not met

Parameters

module ([*ModuleInterface*](#)) – the module to add to the list of modules (based on module.name)

Return type

[*None*](#)

free_module_name(*prefix='module'*)

Returns an unused table name to ensure no collision occurs when inserting a symbol table.

Return type

[*str*](#)

get(*k[, d]*) → D[k] if k in D, else d. d defaults to None.

get_modules_by_symbol_tables(*symbol_table*)

Returns the modules which use the specified symbol table name

Return type

[*Iterable\[str\]*](#)

items() → a set-like object providing a view on D's items

keys() → a set-like object providing a view on D's keys

values() → an object providing a view on D's values

class ModuleInterface(*context, config_path, name*)

Bases: [*ConfigurableInterface*](#)

Maintains state concerning a particular loaded module in memory.

This object is OS-independent.

Constructs a new os-independent module.

Parameters

- **context** ([*ContextInterface*](#)) – The context within which this module will exist
- **config_path** ([*str*](#)) – The path within the context's configuration tree
- **name** ([*str*](#)) – The name of the module

build_configuration()

Builds the configuration dictionary for this specific Module

Return type

[*HierarchicalDict*](#)

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

Context that the module uses.

get_absolute_symbol_address(*name*)

Returns the absolute address of the symbol within this module

Return type

int

get_enumeration(*name*)

Returns an enumeration from the module's symbol table.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(*name*)

Returns a symbol object from the module's symbol table.

Return type

SymbolInterface

get_symbols_by_absolute_location(*offset*, *size=0*)

Returns the symbols within table_name (or this module if not specified) that live at the specified absolute offset provided.

Return type

List[str]

get_type(*name*)

Returns a type from the module's symbol table.

Return type

Template

has_enumeration(*name*)

Determines whether an enumeration is present in the module's symbol table.

Return type

bool

has_symbol(*name*)

Determines whether a symbol is present in the module's symbol table.

Return type

bool

has_type(*name*)

Determines whether a type is present in the module's symbol table.

Return type

`bool`

property layer_name: `str`

Layer name in which the Module resides.

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property name: `str`

The name of the constructed module.

abstract object(*object_type*, *offset=None*, *native_layer_name=None*, *absolute=False*, ***kwargs*)

Returns an object created using the `symbol_table_name` and `layer_name` of the Module.

Parameters

- **object_type** (`str`) – The name of object type to construct (using the module's `symbol_table`)
- **offset** (`int`) – the offset (unless `absolute` is set) from the start of the module
- **native_layer_name** (*Optional*[`str`]) – The native layer for objects that reference a different layer (if not the default provided during module construction)
- **absolute** (`bool`) – A boolean specifying whether the offset is absolute within the layer, or relative to the start of the module

Return type

ObjectInterface

Returns

The constructed object

abstract object_from_symbol(*symbol_name*, *native_layer_name=None*, *absolute=False*, *object_type=None*, ***kwargs*)

Returns an object created using the `symbol_table_name` and `layer_name` of the Module.

Parameters

- **symbol_name** (`str`) – The name of a symbol (that must be present in the module's `symbol_table`). The symbol's associated type will be used to construct an object at the symbol's offset.

- **native_layer_name** (`Optional[str]`) – The native layer for objects that reference a different layer (if not the default provided during module construction)
- **absolute** (`bool`) – A boolean specifying whether the offset is absolute within the layer, or relative to the start of the module
- **object_type** (`Union[str, ObjectInterface, None]`) – Override for the type from the symbol to use (or if the symbol type is missing)

Return type`ObjectInterface`**Returns**

The constructed object

property offset: `int`

Returns the offset that the module resides within the layer of layer_name.

property symbol_table_name: `str`

The name of the symbol table associated with this module

symbols()

Lists the symbols contained in the symbol table for this module

Return type`List`**classmethod unsatisfied**(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`

volatility3.framework.interfaces.layers module

Defines layers for containing data.

One layer may combine other layers, map data based on the data itself, or map a procedure (such as decryption) across another layer of data.

class DataLayerInterface(*context, config_path, name, metadata=None*)Bases: `ConfigurableInterface`

A Layer that directly holds data (and does not translate it).

This is effectively a leaf node in a layer tree. It directly accesses a data source and exposes it within volatility.

Basic initializer that allows configurables to access their own config settings.

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

property dependencies: *List[str]*

A list of other layer names required by this layer.

Note: DataLayers must never define other layers

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

None

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

List[RequirementInterface]

abstract is_valid(offset, length=1)

Returns a boolean based on whether the entire chunk of data (from offset to length) is valid or not.

Parameters

- **offset** (*int*) – The address to start determining whether bytes are readable/valid
- **length** (*int*) – The number of bytes from offset of which to test the validity

Return type

bool

Returns

Whether the bytes are valid and accessible

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

abstract property maximum_address: *int*

Returns the maximum valid address of the space.

property metadata: *Mapping*

Returns a ReadOnly copy of the metadata published by this layer.

abstract property minimum_address: *int*

Returns the minimum valid address of the space.

property name: *str*

Returns the layer name.

abstract read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

If there is a fault of any kind (such as a page fault), an exception will be thrown unless pad is set, in which case the read errors will be replaced by null characters.

Parameters

- **offset** (*int*) – The offset at which to begin reading within the layer
- **length** (*int*) – The number of bytes to read within the layer
- **pad** (*bool*) – A boolean indicating whether exceptions should be raised or bad bytes replaced with null characters

Return type

bytes

Returns

The bytes read from the layer, starting at offset for length bytes

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[Any]

Returns

The output iterable from the scanner object having been run against the layer

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

abstract `write(offset, data)`

Writes a chunk of data at offset.

Any unavailable sections in the underlying bases will cause an exception to be thrown. Note: Writes are not guaranteed atomic, therefore some data may have been written, even if an exception is thrown.

Return type

`None`

class `DummyProgress`

Bases: `object`

A class to emulate Multiprocessing/threading Value objects.

class `LayerContainer`

Bases: `Mapping`

Container for multiple layers of data.

add_layer(layer)

Adds a layer to memory model.

This will throw an exception if the required dependencies are not met

Parameters

layer (`DataLayerInterface`) – the layer to add to the list of layers (based on layer.name)

Return type

`None`

check_cycles()

Runs through the available layers and identifies if there are cycles in the DAG.

Return type

`None`

del_layer(name)

Removes the layer called name.

This will throw an exception if other layers depend upon this layer

Parameters

name (`str`) – The name of the layer to delete

Return type

`None`

free_layer_name(*prefix*='layer')

Returns an unused layer name to ensure no collision occurs when inserting a layer.

Parameters

prefix (*str*) – A descriptive string with which to prefix the layer name

Return type

str

Returns

A string containing a name, prefixed with prefix, not currently in use within the LayerContainer

get(*k*[, *d*]) → *D*[*k*] if *k* in *D*, else *d*. *d* defaults to None.

items() → a set-like object providing a view on *D*'s items

keys() → a set-like object providing a view on *D*'s keys

read(*layer*, *offset*, *length*, *pad*=False)

Reads from a particular layer at offset for length bytes.

Returns 'bytes' not 'str'

Parameters

- **layer** (*str*) – The name of the layer to read from
- **offset** (*int*) – Where to begin reading within the layer
- **length** (*int*) – How many bytes to read from the layer
- **pad** (*bool*) – Whether to raise exceptions or return null bytes when errors occur

Return type

bytes

Returns

The result of reading from the requested layer

values() → an object providing a view on *D*'s values

write(*layer*, *offset*, *data*)

Writes to a particular layer at offset for length bytes.

Return type

None

class ScannerInterface

Bases: *VersionableInterface*

Class for layer scanners that return locations of particular values from within the data.

These are designed to be given a chunk of data and return a generator which yields any found items. They should NOT perform complex/time-consuming tasks, these should be carried out by the consumer of the generator on the items returned.

They will be provided all *available* data (therefore not necessarily contiguous) in ascending offset order, in chunks no larger than *chunk_size* + *overlap* where *overlap* is the amount of data read twice once at the end of an earlier chunk and once at the start of the next chunk.

It should be noted that the scanner can maintain state if necessary. Scanners should balance the size of chunk based on the amount of time scanning the chunk will take (ie, do not set an excessively large chunksize and try not to take a significant amount of time in the `__call__` method).

Scanners must NOT return results found *after* self.chunk_size (ie, entirely contained within the overlap). It is the responsibility of the scanner not to return such duplicate results.

Scanners can mark themselves as thread_safe, if they do not require state in either their own class or the context. This will allow the scanner to be run in parallel against multiple blocks.

property context: `ContextInterface` | `None`

property layer_name: `str` | `None`

thread_safe = `False`

version = `(0, 0, 0)`

class TranslationLayerInterface(*context, config_path, name, metadata=None*)

Bases: `DataLayerInterface`

Provides a layer that translates or transforms another layer or layers.

Translation layers always depend on another layer (typically translating offsets in a virtual offset space into a smaller physical offset space).

Basic initializer that allows configurables to access their own config settings.

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

abstract property dependencies: `List[str]`

Returns a list of layer names that this layer translates onto.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type`List[RequirementInterface]`**abstract** `is_valid(offset, length=1)`

Returns a boolean based on whether the entire chunk of data (from offset to length) is valid or not.

Parameters

- **offset** (`int`) – The address to start determining whether bytes are readable/valid
- **length** (`int`) – The number of bytes from offset of which to test the validity

Return type`bool`**Returns**

Whether the bytes are valid and accessible

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**abstract** `mapping(offset, length, ignore_errors=False)`

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

`ignore_errors` will provide all available maps with gaps, but their total length may not add up to the requested length This allows translation layers to provide maps of contiguous regions in one layer

Return type`Iterable[Tuple[int, int, int, int, str]]`**abstract** `property maximum_address: int`

Returns the maximum valid address of the space.

property `metadata: Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

abstract `property minimum_address: int`

Returns the minimum valid address of the space.

property `name: str`

Returns the layer name.

read(`offset, length, pad=False`)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type`bytes`

scan(*context*, *scanner*, *progress_callback=None*, *sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable*[*Tuple*[*int*, *int*]]) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[*Any*]

Returns

The output iterable from the scanner object having been run against the layer

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[*str*, *RequirementInterface*]

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

None

volatility3.framework.interfaces.objects module

Objects are the core of volatility, and provide pythonic access to interpreted values of data from a layer.

class ObjectInformation(*layer_name*, *offset*, *member_name=None*, *parent=None*, *native_layer_name=None*, *size=None*)

Bases: *ReadOnlyMapping*

Contains common information useful/pertinent only to an individual object (like an instance)

This typically contains information such as the layer the object belongs to, the offset where it was constructed, and if it is a subordinate object, its parent.

This is primarily used to reduce the number of parameters passed to object constructors and keep them all together in a single place. These values are based on the *ReadOnlyMapping* class, to prevent their modification.

Constructs a container for basic information about an object.

Parameters

- **layer_name** (*str*) – Layer from which the data for the object will be read
- **offset** (*int*) – Offset within the layer at which the data for the object will be read
- **member_name** (*Optional[str]*) – If the object was accessed as a member of a parent object, this was the name used to access it
- **parent** (*Optional[ObjectInterface]*) – If the object was accessed as a member of a parent object, this is the parent object
- **native_layer_name** (*Optional[str]*) – If this object references other objects (such as a pointer), what layer those objects live in
- **size** (*Optional[int]*) – The size that the whole structure consumes in bytes

get(*k*, *d*) → *D*[*k*] if *k* in *D*, else *d*. *d* defaults to *None*.

items() → a set-like object providing a view on *D*'s items

keys() → a set-like object providing a view on *D*'s keys

values() → an object providing a view on *D*'s values

class ObjectInterface(*context*, *type_name*, *object_info*, ***kwargs*)

Bases: *object*

A base object required to be the ancestor of every object used in volatility.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *object*

A container for proxied methods that the ObjectTemplate of this object will call. This is primarily to keep methods together for easy organization/management, there is no significant need for it to be a separate class.

The methods of this class *must* be class methods rather than standard methods, to allow for code reuse. Each method also takes a template since the templates may contain the necessary data about the yet-to-be-constructed object. It allows objects to control how their templates respond without needing to write new templates for each and every potential object type.

abstract classmethod child_template(*template*, *child*)

Returns the template of the child member from the parent.

Return type

Template

abstract classmethod children(*template*)

Returns the children of the template.

Return type

List[Template]

abstract classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

abstract classmethod relative_child_offset(*template*, *child*)

Returns the relative offset from the head of the parent data to the child member.

Return type

`int`

abstract classmethod replace_child(*template*, *old_child*, *new_child*)

Substitutes the *old_child* for the *new_child*.

Return type

`None`

abstract classmethod size(*template*)

Returns the size of the template object.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. `:rtype:`
`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the *table_name* is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

abstract write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class ReadOnlyMapping(*dictionary*)

Bases: *Mapping*

A read-only mapping of various values that offer attribute access as well.

This ensures that the data stored in the mapping should not be modified, making an immutable mapping.

get(*k*, *d*) → *D[k]* if *k* in *D*, else *d*. *d* defaults to *None*.

items() → a set-like object providing a view on *D*'s items

keys() → a set-like object providing a view on *D*'s keys

values() → an object providing a view on *D*'s values

class Template(*type_name*, ***arguments*)

Bases: *object*

Class for all Factories that take offsets, and data layers and produce objects.

This is effectively a class for currying object calls. It creates a callable that can be called with the following parameters:

Parameters

- **context** – The context containing the memory layers and symbols required to construct the object
- **object_info** – Basic information about the object, see the *ObjectInformation* class for more information

Returns

The constructed object

The keyword arguments handed to the constructor, along with the *type_name* are stored for later retrieval. These will be access as *object.vol.<keyword>* or *template.vol.<keyword>* for each object and should contain as least the basic information that each object will require before it is instantiated (so *offset* and *parent* are explicitly not recorded here). This dictionary can be updated after construction, but any changes made after that point will *not* be cloned. This is so that templates such as those for string objects may contain different length limits, without affecting all other strings using the same template from a *SymbolTable*, constructed at resolution time and then cached.

Stores the keyword arguments for later object creation.

abstract child_template(*child*)

Returns the *child* member template from its parent.

Return type*Template***property children:** *List[Template]*

The children of this template (such as member types, sub-types and base-types where they are relevant).

Used to traverse the template tree.

clone()

Returns a copy of the original Template as constructed (without *update_vol* additions having been made)

Return type*Template***abstract has_member**(*member_name*)

Returns whether the object would contain a member called *member_name*

Return type*bool***abstract relative_child_offset**(*child*)

Returns the relative offset of the *child* member from its parent offset.

Return type*int***abstract replace_child**(*old_child*, *new_child*)

Replaces *old_child* with *new_child* in the list of children.

Return type*None***abstract property size:** *int*

Returns the size of the template.

update_vol(***new_arguments*)

Updates the keyword arguments with values that will **not** be carried across to clones.

Return type*None***property vol:** *ReadOnlyMapping*

Returns a volatility information object, much like the *ObjectInformation* provides.

volatility3.framework.interfaces.plugins module

Plugins are the *functions* of the volatility framework.

They are called and carry out some algorithms on data stored in layers using objects constructed from symbols.

class FileHandlerInterface(*filename*)

Bases: *RawIOBase*

Class for storing Files in the plugin as a means to output a file when necessary.

This can be used as ContextManager that will close/produce the file automatically when exiting the context block

Creates a FileHandler

Parameters

filename (*str*) – The requested name of the filename for the data

abstract close()

Method that commits the file and fixes the final filename for use

closed**fileno()**

Returns underlying file descriptor if one exists.

OSError is raised if the IO object does not use a file descriptor.

flush()

Flush write buffers, if applicable.

This is not implemented for read-only and non-blocking streams.

isatty()

Return whether this is an ‘interactive’ stream.

Return False if it can’t be determined.

property preferred_filename

The preferred filename to save the data to. Until this file has been written, this value may not be the final filename the data is written to.

read(*size=-1, /*)**readable()**

Return whether object was opened for reading.

If False, read() will raise OSError.

readall()

Read until EOF, using multiple read() call.

readinto()**readline(*size=-1, /*)**

Read and return a line from the stream.

If size is specified, at most size bytes will be read.

The line terminator is always b’n’ for binary files; for text files, the newlines argument to open can be used to select the line terminator(s) recognized.

readlines(*hint=-1, /*)

Return a list of lines from the stream.

hint can be specified to control the number of lines read: no more lines will be read if the total size (in bytes/characters) of all lines so far exceeds hint.

static sanitize_filename(*filename*)

Sanitizes the filename to ensure only a specific whitelist of characters is allowed through

Return type

str

seek(*offset, whence=0, /*)

Change the stream position to the given byte offset.

offset

The stream position, relative to ‘whence’.

whence

The relative position to seek from.

The offset is interpreted relative to the position indicated by whence. Values for whence are:

- `os.SEEK_SET` or 0 – start of stream (the default); offset should be zero or positive
- `os.SEEK_CUR` or 1 – current stream position; offset may be negative
- `os.SEEK_END` or 2 – end of stream; offset is usually negative

Return the new absolute position.

seekable()

Return whether object supports random access.

If False, `seek()`, `tell()` and `truncate()` will raise `OSError`. This method may need to do a test `seek()`.

tell()

Return current stream position.

truncate()

Truncate file to size bytes.

File pointer is left unchanged. Size defaults to the current IO position as reported by `tell()`. Returns the new size.

writable()

Return whether object was opened for writing.

If False, `write()` will raise `OSError`.

write()**writelines(*lines*, /)**

Write a list of lines to stream.

Line separators are not added, so it is usual for each of the lines provided to have a line separator at the end.

class PluginInterface(*context*, *config_path*, *progress_callback=None*)

Bases: [ConfigurableInterface](#), [VersionableInterface](#)

Class that defines the basic interface that all Plugins must maintain.

The constructor must only take a *context* and *config_path*, so that plugins can be launched automatically. As such all configuration information must be provided through the requirements and configuration information in the context it is passed.

Parameters

- **context** ([ContextInterface](#)) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a `HierarchicalDictionary` of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type*List[RequirementInterface]***classmethod make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

abstract run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Return type*TreeGrid***Returns**

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type*None*

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.framework.interfaces.renderers module

All plugins output a `TreeGrid` object which must then be rendered (either by a GUI, or as text output, html output or in some other form).

This module defines both the output format (*TreeGrid*) and the renderer interface which can interact with a `TreeGrid` to produce suitable output.

class `BaseAbsentValue`

Bases: `object`

Class that represents values which are not present for some reason.

class `Column(name, type)`

Bases: `tuple`

Create new instance of `Column(name, type)`

count(value, /)

Return number of occurrences of value.

index(value, start=0, stop=9223372036854775807, /)

Return first index of value.

Raises `ValueError` if the value is not present.

name: `str`

Alias for field number 0

type: `Any`

Alias for field number 1

class `ColumnSortKey`

Bases: `object`

ascending: `bool = True`

class `Disassembly(data, offset=0, architecture='intel64')`

Bases: `object`

A class to indicate that the bytes provided should be disassembled (based on the architecture)

possible_architectures = ['intel', 'intel64', 'arm', 'arm64']

class `Renderer`(*options=None*)

Bases: `object`

Class that defines the interface that all output renderers must support.

Accepts an options object to configure the renderers.

abstract `get_render_options()`

Returns a list of rendering options.

Return type

`List[Any]`

abstract `render(grid)`

Takes a grid object and renders it based on the object's preferences.

Return type

`None`

class `TreeGrid`(*columns, generator*)

Bases: `object`

Class providing the interface for a TreeGrid (which contains TreeNodes)

The structure of a TreeGrid is designed to maintain the structure of the tree in a single object. For this reason each TreeNode does not hold its children, they are managed by the top level object. This leaves the Nodes as simple data carries and prevents them being used to manipulate the tree as a whole. This is a data structure, and is not expected to be modified much once created.

Carrying the children under the parent makes recursion easier, but then every node is its own little tree and must have all the supporting tree functions. It also allows for a node to be present in several different trees, and to create cycles.

Constructs a TreeGrid object using a specific set of columns.

The TreeGrid itself is a root element, that can have children but no values. The TreeGrid does *not* contain any information about formatting, these are up to the renderers and plugins.

Parameters

- **columns** (`List[Tuple[str, Union[Type[int], Type[str], Type[float], Type[bytes], Type[datetime], Type[BaseAbsentValue], Type[Disassembly]]]]`) – A list of column tuples made up of (name, type).
- **generator** (`Generator`) – An iterable containing row for a tree grid, each row contains a indent level followed by the values for each column in order.

base_types: `ClassVar[Tuple] = (<class 'int'>, <class 'str'>, <class 'float'>, <class 'bytes'>, <class 'datetime.datetime'>, <class 'volatility3.framework.interfaces.renderers.Disassembly'>)`

abstract `children(node)`

Returns the subnodes of a particular node in order.

Return type

`List[TreeNode]`

abstract `property columns:` `List[Column]`

Returns the available columns and their ordering and types.

abstract `is_ancestor(node, descendant)`

Returns true if descendant is a child, grandchild, etc of node.

Return type

`bool`

abstract `max_depth()`

Returns the maximum depth of the tree.

Return type

`int`

static `path_depth(node)`

Returns the path depth of a particular node.

Return type

`int`

abstract `populate(function=None, initial_accumulator=None, fail_on_errors=True)`

Populates the tree by consuming the TreeGrid's construction generator Func is called on every node, so can be used to create output on demand.

This is equivalent to a one-time visit.

Return type

`Optional[Exception]`

abstract `property populated: bool`

Indicates that population has completed and the tree may now be manipulated separately.

abstract `static sanitize_name(text)`

Method used to sanitize column names for TreeNodes.

Return type

`str`

abstract `values(node)`

Returns the values for a particular node.

The values returned are mutable,

Return type

`Tuple[Union[Type[int], Type[str], Type[float], Type[bytes], Type[datetime], Type[BaseAbsentValue], Type[Disassembly]], ...]`

abstract `visit(node, function, initial_accumulator, sort_key=None)`

Visits all the nodes in a tree, calling function on each one.

function should have the signature function(node, accumulator) and return new_accumulator If accumulators are not needed, the function must still accept a second parameter.

The order of that the nodes are visited is always depth first, however, the order children are traversed can be set based on a sort_key function which should accept a node's values and return something that can be sorted to receive the desired order (similar to the sort/sorted key).

If node is None, then the root node is used.

Parameters

- **node** (`Optional[TreeNode]`) – The initial node to be visited
- **function** (`Callable[[TreeNode, TypeVar(_Type)], TypeVar(_Type)]`) – The visitor to apply to the nodes under the initial node

- **initial_accumulator** (`TypeVar(_Type)`) – An accumulator that allows data to be transferred between one visitor call to the next
- **sort_key** (`ColumnSortKey`) – Information about the sort order of columns in order to determine the ordering of results

Return type`None`**class** `TreeNode`(*path, treegrid, parent, values*)Bases: `Sequence`Initializes the `TreeNode`.**count**(*value*) → integer -- return number of occurrences of value**index**(*value*[, *start*[, *stop*]]) → integer -- return first index of value.Raises `ValueError` if the value is not present.

Supporting start and stop arguments is optional, but recommended.

abstract property parent: `TreeNode` | `None`Returns the parent node of this node or `None`.**abstract property path:** `str`

Returns a path identifying string.

This should be seen as opaque by external classes, Parsing of path locations based on this string are not guaranteed to remain stable.

abstract path_changed(*path, added=False*)

Updates the path based on the addition or removal of a node higher up in the tree.

This should only be called by the containing `TreeGrid` and expects to only be called for affected nodes.**Return type**`None`**abstract property path_depth:** `int`

Return the path depth of the current node.

abstract property values: `List[Type[int] | Type[str] | Type[float] | Type[bytes] | Type[datetime] | Type[BaseAbsentValue] | Type[Disassembly]]`

Returns the list of values from the particular node, based on column index.

volatility3.framework.interfaces.symbols module

Symbols provide structural information about a set of bytes.

class `BaseSymbolTableInterface`(*name, native_types, table_mapping=None, class_types=None*)Bases: `object`The base interface, inherited by both `NativeTables` and `SymbolTables`.`native_types` is a `NativeTableInterface` used for native types for the particular loaded symbol table `table_mapping` allows tables referenced by symbols to be remapped to a different table name if necessaryNote: `table_mapping` is a rarely used feature (since symbol tables are typically self-contained)**Parameters**

- **name** (*str*) – Name of the symbol table
- **native_types** (*NativeTableInterface*) – The native symbol table used to resolve any base/native types
- **table_mapping** (*Optional[Dict[str, str]]*) – A dictionary mapping names of tables (which when present within the table will be changed to the mapped table)
- **class_types** (*Optional[Mapping[str, Type[ObjectInterface]]]*) – A dictionary of types and classes that should be instantiated instead of Struct to construct them

clear_symbol_cache()

Clears the symbol cache of this symbol table.

Return type

None

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[Any]*

Returns an iterator of the Enumeration names.

get_symbol(name)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

Return type

SymbolInterface

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

Optional[Template]

get_symbols_by_location(offset, size=0)

Returns the name of all symbols in this table that live at a particular offset.

Return type

Iterable[str]

get_symbols_by_type(type_name)

Returns the name of all symbols in this table that have type matching type_name.

Return type

Iterable[str]

get_type(name)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a SymbolError exception

Return type

Template

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the set_type_class function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type

`None`

property symbols: `Iterable[str]`

Returns an iterator of the Symbol names.

property types: `Iterable[str]`

Returns an iterator of the Symbol type names.

class MetadataInterface(*json_data*)

Bases: `object`

Interface for accessing metadata stored within a symbol table.

Constructor that accepts json_data.

class NativeTableInterface(*name*, *native_types*, *table_mapping=None*, *class_types=None*)

Bases: `BaseSymbolTableInterface`

Class to distinguish NativeSymbolLists from other symbol lists.

Parameters

- **name** (`str`) – Name of the symbol table
- **native_types** (`NativeTableInterface`) – The native symbol table used to resolve any base/native types
- **table_mapping** (`Optional[Dict[str, str]]`) – A dictionary mapping names of tables (which when present within the table will be changed to the mapped table)
- **class_types** (`Optional[Mapping[str, Type[ObjectInterface]]]`) – A dictionary of types and classes that should be instantiated instead of Struct to construct them

clear_symbol_cache()

Clears the symbol cache of this symbol table.

Return type

None

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the Enumeration names.

get_enumeration(name)**Return type**

Template

get_symbol(name)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

Return type

SymbolInterface

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

Optional[Template]

get_symbols_by_location(offset, size=0)

Returns the name of all symbols in this table that live at a particular offset.

Return type

Iterable[str]

get_symbols_by_type(type_name)

Returns the name of all symbols in this table that have type matching type_name.

Return type

Iterable[str]

get_type(name)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a SymbolError exception

Return type

Template

get_type_class(name)

Returns the class associated with a Symbol type.

Return type

Type[ObjectInterface]

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type

`None`

property symbols: `Iterable[str]`

Returns an iterator of the Symbol names.

property types: `Iterable[str]`

Returns an iterator of the Symbol type names.

class SymbolInterface(*name*, *address*, *type=None*, *constant_data=None*)

Bases: `object`

Contains information about a named location in a program's memory.

Parameters

- **name** (`str`) – Name of the symbol
- **address** (`int`) – Numeric address value of the symbol
- **type** (`Optional[Template]`) – Optional type structure information associated with the symbol
- **constant_data** (`Optional[bytes]`) – Potential constant data the symbol points at

property address: `int`

Returns the relative address of the symbol within the compilation unit.

property constant_data: `bytes | None`

Returns any constant data associated with the symbol.

property name: `str`

Returns the name of the symbol.

property type: `Template | None`

Returns the type that the symbol represents.

property type_name: `str | None`

Returns the name of the type that the symbol represents.

class SymbolSpaceInterfaceBases: `Mapping`

An interface for the container that holds all the symbol-containing tables for use within a context.

abstract append(*value*)Adds a `symbol_list` to the end of the space.**Return type**`None`**abstract clear_symbol_cache**(*table_name*)

Clears the symbol cache for the specified table name. If no table name is specified, the caches of all symbol tables are cleared.

Return type`None`**free_table_name**(*prefix='layer'*)

Returns an unused table name to ensure no collision occurs when inserting a symbol table.

Return type`str`**get**(*k*[, *d*]) → *D*[*k*] if *k* in *D*, else *d*. *d* defaults to `None`.**abstract get_enumeration**(*enum_name*)

Look-up an enumeration across all the contained symbol tables.

Return type`Template`**abstract get_symbol**(*symbol_name*)

Look-up a symbol name across all the contained symbol tables.

Return type`SymbolInterface`**abstract get_symbols_by_location**(*offset*, *size=0*, *table_name=None*)

Returns all symbols that exist at a specific relative address.

Return type`Iterable[str]`**abstract get_symbols_by_type**(*type_name*)

Returns all symbols based on the type of the symbol.

Return type`Iterable[str]`**abstract get_type**(*type_name*)

Look-up a type name across all the contained symbol tables.

Return type`Template`**abstract has_enumeration**(*name*)

Determines whether an enumeration choice exists in the contained symbol tables.

Return type`bool`

abstract has_symbol(*name*)

Determines whether a symbol exists in the contained symbol tables.

Return type

`bool`

abstract has_type(*name*)

Determines whether a type exists in the contained symbol tables.

Return type

`bool`

items() → a set-like object providing a view on D's items

keys() → a set-like object providing a view on D's keys

values() → an object providing a view on D's values

class SymbolTableInterface(*context, config_path, name, native_types, table_mapping=None, class_types=None*)

Bases: `BaseSymbolTableInterface`, `ConfigurableInterface`, `ABC`

Handles a table of symbols.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (`ContextInterface`) – The volatility context for the symbol table
- **config_path** (`str`) – The configuration path for the symbol table
- **name** (`str`) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (`NativeTableInterface`) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (`Optional[Dict[str, str]]`) – A dictionary linking names referenced in the file with symbol tables in the context
- **class_types** (`Optional[Mapping[str, Type[ObjectInterface]]]`) – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

clear_symbol_cache()

Clears the symbol cache of this symbol table.

Return type

`None`

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(*name*)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[Any]*

Returns an iterator of the Enumeration names.

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(*name*)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

Return type

SymbolInterface

get_symbol_type(*name*)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

Optional[Template]

get_symbols_by_location(*offset, size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

Iterable[str]

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching type_name.

Return type

Iterable[str]

get_type(*name*)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a SymbolError exception

Return type

Template

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type`Type[ObjectInterface]`**classmethod** `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property natives:** `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(`name, clazz`)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type`bool`**set_type_class**(`name, clazz`)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type`None`**property symbols:** `Iterable[str]`

Returns an iterator of the Symbol names.

property types: `Iterable[str]`

Returns an iterator of the Symbol type names.

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`**volatility3.framework.layers package****Subpackages****volatility3.framework.layers.codecs package**

Codecs used for encoding or decoding data should live here

volatility3.framework.layers.scanners package

```
class BytesScanner(needle)
```

Bases: `ScannerInterface`

property context: `ContextInterface` | `None`

property layer_name: `str` | `None`

thread_safe = `True`

version = (`0`, `0`, `0`)

```
class MultiStringScanner(patterns)
```

Bases: `ScannerInterface`

property context: `ContextInterface` | `None`

property layer_name: `str` | `None`

search(*haystack*)

Return type`Generator[Tuple[int, bytes], None, None]`

thread_safe = `True`

version = (`0`, `0`, `0`)

```
class RegExScanner(pattern, flags=RegexFlag.DOTALL)
```

Bases: `ScannerInterface`

A scanner that can be provided with a bytes-object regular expression pattern The scanner will scan all blocks for the regular expression and report the absolute offset of any finds

The default flags include DOTALL, since the searches are through binary data and the newline character should have no specific significance in such searches

property context: `ContextInterface` | `None`

property layer_name: `str` | `None`

thread_safe = `True`

version = (`0`, `0`, `0`)

Submodules

volatility3.framework.layers.scanners.multiregexp module

class MultiRegexp

Bases: `object`

Algorithm for multi-string matching.

add_pattern(*pattern*)

Return type

`None`

preprocess()

Return type

`None`

search(*haystack*)

Return type

`Generator[Tuple[int, bytes], None, None]`

Submodules

volatility3.framework.layers.avml module

Functions that read AVML files.

The user of the file doesn't have to worry about the compression, but random access is not allowed.

class AVMLLayer(*args, **kwargs)

Bases: `NonLinearlySegmentedLayer`

A Lime format TranslationLayer.

Lime is generally used to store physical memory images where there are large holes in the physical layer

Basic initializer that allows configurables to access their own config settings.

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

property dependencies: `List[str]`

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_valid(offset, length=1)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(offset, length, ignore_errors=False)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

`Iterable[Tuple[int, int, int, int, str]]`

property maximum_address: `int`

Returns the maximum valid address of the space.

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property minimum_address: `int`

Returns the minimum valid address of the space.

property name: `str`

Returns the layer name.

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset, value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

class AVMLStacker

Bases: *StackerLayerInterface*

exclusion_list: `List[str] = []`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod `stack(context, layer_name, progress_callback=None)`

Method to determine whether this builder can operate on the named layer. If so, modify the context appropriately.

Returns the name of any new layer stacked on top of this layer or None. The stacking is therefore strictly linear rather than tree driven.

Configuration options provided by the context are ignored, and defaults are to be used by this method to build a space where possible.

Parameters

- **context** (*ContextInterface*) – Context in which to construct the higher layer
- **layer_name** (*str*) – Name of the layer to stack on top of
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callback function to indicate progress through a scan (if one is necessary)

Return type

Optional[DataLayerInterface]

stack_order = 10

The order in which to attempt stacking, the lower the earlier

classmethod `stacker_slow_warning()`

exception `SnappyException`

Bases: *VolatilityException*

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

uncompress(s)

Uncompress a snappy compressed string.

volatility3.framework.layers.cloudstorage module

volatility3.framework.layers.crash module

class `WindowsCrashDump32Layer(context, config_path, name)`

Bases: *SegmentedLayer*

A Windows crash format TranslationLayer. This TranslationLayer supports Microsoft complete memory dump files. It currently does not support kernel or small memory dump files.

Basic initializer that allows configurables to access their own config settings.

SIGNATURE = 1162297680

VALIDDUMP = 1347245380

property `address_mask: int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

classmethod check_header(*base_layer, offset=0*)**Return type**

Tuple[int, int]

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

crashdump_json = 'crash'**property dependencies:** *List[str]*

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

None

dump_header_name = '_DUMP_HEADER'**get_header()****Return type**

ObjectInterface

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

List[RequirementInterface]

get_summary_header()**Return type**

ObjectInterface

headerpages = 1

is_valid(*offset*, *length=1*)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod **make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(*offset*, *length*, *ignore_errors=False*)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

`Iterable[Tuple[int, int, int, int, str]]`

property **maximum_address**: `int`

Returns the maximum valid address of the space.

property **metadata**: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property **minimum_address**: `int`

Returns the minimum valid address of the space.

property **name**: `str`

Returns the layer name.

provides = {'type': 'physical'}

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context*, *scanner*, *progress_callback=None*, *sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied

- **progress_callback** (`Optional[Callable[[float, str], None]]`) – Method that is called periodically during scanning to update progress
- **sections** (`Iterable[Tuple[int, int]]`) – A list of (start, size) tuples defining the portions of the layer to scan

Return type`Iterable[Any]`**Returns**

The output iterable from the scanner object having been run against the layer

supported_dumptypes = [1, 5]

translate(*offset*, *ignore_errors=False*)

Return type`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type`None`

class WindowsCrashDump64Layer(*context*, *config_path*, *name*)

Bases: `WindowsCrashDump32Layer`

A Windows crash format TranslationLayer. This TranslationLayer supports Microsoft complete memory dump files. It currently does not support kernel or small memory dump files.

Basic initializer that allows configurables to access their own config settings.

SIGNATURE = 1162297680

VALIDDUMP = 875976004

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`

classmethod `check_header`(*base_layer*, *offset=0*)

Return type

`Tuple[int, int]`

property `config`: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path`: `str`

The configuration path on which this configurable lives.

property `context`: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

`crashdump_json = 'crash64'`

property `dependencies`: `List[str]`

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

`dump_header_name = '_DUMP_HEADER64'`

get_header()

Return type

ObjectInterface

classmethod `get_requirements`()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

get_summary_header()

Return type

ObjectInterface

`headerpages = 2`

is_valid(*offset*, *length=1*)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod `make_subconfig`(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration

- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

mapping(*offset, length, ignore_errors=False*)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

Iterable[Tuple[int, int, int, int, str]]

property maximum_address: *int*

Returns the maximum valid address of the space.

property metadata: *Mapping*

Returns a ReadOnly copy of the metadata published by this layer.

property minimum_address: *int*

Returns the minimum valid address of the space.

property name: *str*

Returns the layer name.

provides = {'type': 'physical'}

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

bytes

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[Any]

Returns

The output iterable from the scanner object having been run against the layer

supported_dumptypes = [1, 5]

translate(*offset*, *ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod **unsatisfied**(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

exception **WindowsCrashDumpFormatException**(*layer_name*, **args*)

Bases: `LayerException`

Thrown when an error occurs with the underlying Crash file format.

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

class **WindowsCrashDumpStacker**

Bases: `StackerLayerInterface`

exclusion_list: `List[str] = []`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod **stack**(*context*, *layer_name*, *progress_callback=None*)

Method to determine whether this builder can operate on the named layer. If so, modify the context appropriately.

Returns the name of any new layer stacked on top of this layer or None. The stacking is therefore strictly linear rather than tree driven.

Configuration options provided by the context are ignored, and defaults are to be used by this method to build a space where possible.

Parameters

- **context** (`ContextInterface`) – Context in which to construct the higher layer
- **layer_name** (`str`) – Name of the layer to stack on top of
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callback function to indicate progress through a scan (if one is necessary)

Return type*Optional*[*DataLayerInterface*]**stack_order** = 11

The order in which to attempt stacking, the lower the earlier

classmethod **stacker_slow_warning**()**volatility3.framework.layers.elf module****class** **Elf64Layer**(*context, config_path, name*)Bases: *SegmentedLayer*A layer that supports the Elf64 format as documented at: <http://ftp.openwatcom.org/devel/docs/elf-64-gen.pdf>

Basic initializer that allows configurables to access their own config settings.

ELF_CLASS = 2**MAGIC** = 1179403647**property** **address_mask**: *int*

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property** **config**: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property **config_path**: *str*

The configuration path on which this configurable lives.

property **context**: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

property **dependencies**: *List*[*str*]

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type*None***classmethod** **get_requirements**()

Returns a list of Requirement objects for this type of layer.

Return type*List*[*RequirementInterface*]

is_valid(*offset*, *length=1*)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod **make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(*offset*, *length*, *ignore_errors=False*)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

`Iterable[Tuple[int, int, int, int, str]]`

property **maximum_address**: `int`

Returns the maximum valid address of the space.

property **metadata**: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property **minimum_address**: `int`

Returns the minimum valid address of the space.

property **name**: `str`

Returns the layer name.

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns ‘bytes’ (not ‘str’) of length size.

Return type

`bytes`

scan(*context*, *scanner*, *progress_callback=None*, *sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress

- **sections** (`Iterable[Tuple[int, int]]`) – A list of (start, size) tuples defining the portions of the layer to scan

Return type`Iterable[Any]`**Returns**

The output iterable from the scanner object having been run against the layer

translate(*offset*, *ignore_errors=False*)

Return type`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type`None`

class Elf64Stacker

Bases: `StackerLayerInterface`

exclusion_list: `List[str] = []`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod stack(*context*, *layer_name*, *progress_callback=None*)

Method to determine whether this builder can operate on the named layer. If so, modify the context appropriately.

Returns the name of any new layer stacked on top of this layer or None. The stacking is therefore strictly linear rather than tree driven.

Configuration options provided by the context are ignored, and defaults are to be used by this method to build a space where possible.

Parameters

- **context** (`ContextInterface`) – Context in which to construct the higher layer
- **layer_name** (`str`) – Name of the layer to stack on top of
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callback function to indicate progress through a scan (if one is necessary)

Return type`Optional[DataLayerInterface]`

stack_order = 10

The order in which to attempt stacking, the lower the earlier

classmethod stacker_slow_warning()

exception ElfFormatException(layer_name, *args)

Bases: *LayerException*

Thrown when an error occurs with the underlying ELF file format.

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

volatility3.framework.layers.intel module

class Intel(context, config_path, name, metadata=None)

Bases: *LinearlyMappedLayer*

Translation Layer for the Intel IA32 memory mapping.

Basic initializer that allows configurables to access their own config settings.

property address_mask: int

Returns a mask which encapsulates all the active bits of an address for this layer.

bits_per_register = 32

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

canonicalize(addr)

Canonicalizes an address by performing an appropriate sign extension on the higher addresses

Return type

int

property config: HierarchicalDict

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: str

The configuration path on which this configurable lives.

property context: ContextInterface

The context object that this configurable belongs to/configuration is stored in.

decanonicalize(addr)

Removes canonicalization to ensure an address fits within the correct range if it has been canonicalized

This will produce an address outside the range if the canonicalization is incorrect

Return type

`int`

property dependencies: `List[str]`

Returns a list of the lower layer names that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_dirty(offset)

Returns whether the page at offset is marked dirty

Return type

`bool`

is_valid(offset, length=1)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(offset, length, ignore_errors=False)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

This allows translation layers to provide maps of contiguous regions in one layer

Return type`Iterable[Tuple[int, int, int, int, str]]``maximum_address = 4294967295``property metadata: Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

`minimum_address = 0``property name: str`

Returns the layer name.

`page_mask = -4096``page_shift = 12``page_size = 4096``read(offset, length, pad=False)`

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type`bytes``scan(context, scanner, progress_callback=None, sections=None)`

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (`ContextInterface`) – The context containing the data layer
- **scanner** (`ScannerInterface`) – The constructed Scanner object to be applied
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – Method that is called periodically during scanning to update progress
- **sections** (`Iterable[Tuple[int, int]]`) – A list of (start, size) tuples defining the portions of the layer to scan

Return type`Iterable[Any]`**Returns**

The output iterable from the scanner object having been run against the layer

`structure = [('page directory', 10, False), ('page table', 10, True)]``translate(offset, ignore_errors=False)`**Return type**`Tuple[Optional[int], Optional[str]]``classmethod unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]`**write**(*offset, value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type`None`**class Intel32e**(*context, config_path, name, metadata=None*)

Bases: `Intel`

Class for handling 64-bit (32-bit extensions) for Intel architectures.

Basic initializer that allows configurables to access their own config settings.

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

bits_per_register = 64**build_configuration**()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type`HierarchicalDict`**canonicalize**(*addr*)

Canonicalizes an address by performing an appropriate sign extension on the higher addresses.

Return type`int`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

decanonicalize(*addr*)

Removes canonicalization to ensure an address fits within the correct range if it has been canonicalized.

This will produce an address outside the range if the canonicalization is incorrect.

Return type`int`**property dependencies:** `List[str]`

Returns a list of the lower layer names that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_dirty(offset)

Returns whether the page at offset is marked dirty

Return type

`bool`

is_valid(offset, length=1)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(offset, length, ignore_errors=False)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

This allows translation layers to provide maps of contiguous regions in one layer

Return type

`Iterable[Tuple[int, int, int, int, str]]`

maximum_address = 281474976710655

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

minimum_address = 0

property name: `str`

Returns the layer name.

page_mask = `-4096`

page_shift = `12`

page_size = `4096`

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

```
structure = [('page map layer 4', 9, False), ('page directory pointer', 9, True),
('page directory', 9, True), ('page table', 9, True)]
```

translate(*offset, ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset, value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

None

class IntelPAE(*context, config_path, name, metadata=None*)

Bases: *Intel*

Class for handling Physical Address Extensions for Intel architectures.

Basic initializer that allows configurables to access their own config settings.

property address_mask: *int*

Returns a mask which encapsulates all the active bits of an address for this layer.

bits_per_register = 32

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

canonicalize(*addr*)

Canonicalizes an address by performing an appropriate sign extension on the higher addresses

Return type

int

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

decanonicalize(*addr*)

Removes canonicalization to ensure an adress fits within the correct range if it has been canonicalized

This will produce an address outside the range if the canonicalization is incorrect

Return type

int

property dependencies: *List[str]*

Returns a list of the lower layer names that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

None

classmethod `get_requirements()`

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_dirty(*offset*)

Returns whether the page at offset is marked dirty

Return type

`bool`

is_valid(*offset*, *length=1*)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(*offset*, *length*, *ignore_errors=False*)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

This allows translation layers to provide maps of contiguous regions in one layer

Return type

`Iterable[Tuple[int, int, int, int, str]]`

maximum_address = 4294967295

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

minimum_address = 0

property name: `str`

Returns the layer name.

page_mask = -4096

page_shift = 12

page_size = 4096

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context*, *scanner*, *progress_callback=None*, *sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable*[*Tuple*[*int*, *int*]]) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

```
structure = [('page directory pointer', 2, False), ('page directory', 9, True),
('page table', 9, True)]
```

translate(*offset*, *ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

class WindowsIntel(*context*, *config_path*, *name*, *metadata=None*)

Bases: *WindowsMixin*, *Intel*

Basic initializer that allows configurables to access their own config settings.

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

bits_per_register = 32

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

canonicalize(addr)

Canonicalizes an address by performing an appropriate sign extension on the higher addresses

Return type

`int`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

decanonicalize(addr)

Removes canonicalization to ensure an address fits within the correct range if it has been canonicalized

This will produce an address outside the range if the canonicalization is incorrect

Return type

`int`

property dependencies: `List[str]`

Returns a list of the lower layer names that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_dirty(offset)

Returns whether the page at offset is marked dirty

Return type

`bool`

is_valid(*offset*, *length=1*)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod **make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(*offset*, *length*, *ignore_errors=False*)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

This allows translation layers to provide maps of contiguous regions in one layer

Return type

`Iterable[Tuple[int, int, int, int, str]]`

maximum_address = 4294967295

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

minimum_address = 0

property name: `str`

Returns the layer name.

page_mask = -4096

page_shift = 12

page_size = 4096

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns ‘bytes’ (not ‘str’) of length size.

Return type

`bytes`

scan(*context*, *scanner*, *progress_callback=None*, *sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer

- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable*[*Tuple*[*int*, *int*]]) – A list of (start, size) tuples defining the portions of the layer to scan

Return type*Iterable*[*Any*]**Returns**

The output iterable from the scanner object having been run against the layer

```
structure = [('page directory', 10, False), ('page table', 10, True)]
```

```
translate(offset, ignore_errors=False)
```

Return type*Tuple*[*Optional*[*int*], *Optional*[*str*]]

```
classmethod unsatisfied(context, config_path)
```

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type*Dict*[*str*, *RequirementInterface*]

```
write(offset, value)
```

Writes a value at offset, distributing the writing across any underlying mapping.

Return type*None*

```
class WindowsIntel32e(context, config_path, name, metadata=None)
```

Bases: *WindowsMixin*, *Intel32e*

Basic initializer that allows configurables to access their own config settings.

```
property address_mask: int
```

Returns a mask which encapsulates all the active bits of an address for this layer.

```
bits_per_register = 64
```

```
build_configuration()
```

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict*

canonicalize(addr)

Canonicalizes an address by performing an appropriate sign extension on the higher addresses

Return type

`int`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

decanonicalize(addr)

Removes canonicalization to ensure an address fits within the correct range if it has been canonicalized

This will produce an address outside the range if the canonicalization is incorrect

Return type

`int`

property dependencies: `List[str]`

Returns a list of the lower layer names that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_dirty(offset)

Returns whether the page at offset is marked dirty

Return type

`bool`

is_valid(offset, length=1)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration

- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

mapping(*offset, length, ignore_errors=False*)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

This allows translation layers to provide maps of contiguous regions in one layer

Return type

Iterable[Tuple[int, int, int, int, str]]

maximum_address = 281474976710655

property metadata: *Mapping*

Returns a ReadOnly copy of the metadata published by this layer.

minimum_address = 0

property name: *str*

Returns the layer name.

page_mask = -4096

page_shift = 12

page_size = 4096

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

bytes

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[Any]

Returns

The output iterable from the scanner object having been run against the layer


```
structure = [('page map layer 4', 9, False), ('page directory pointer', 9, True),
('page directory', 9, True), ('page table', 9, True)]
```

```
translate(offset, ignore_errors=False)
```

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(offset, value)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

class `WindowsIntelPAE(context, config_path, name, metadata=None)`

Bases: `WindowsMixin`, `IntelPAE`

Basic initializer that allows configurables to access their own config settings.

property `address_mask: int`

Returns a mask which encapsulates all the active bits of an address for this layer.

`bits_per_register = 32`

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type

`HierarchicalDict`

canonicalize(addr)

Canonicalizes an address by performing an appropriate sign extension on the higher addresses.

Return type

`int`

property `config: HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path: str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

decanonicalize(*addr*)

Removes canonicalization to ensure an address fits within the correct range if it has been canonicalized

This will produce an address outside the range if the canonicalization is incorrect

Return type

`int`

property dependencies: `List[str]`

Returns a list of the lower layer names that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_dirty(*offset*)

Returns whether the page at offset is marked dirty

Return type

`bool`

is_valid(*offset*, *length=1*)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(*offset, length, ignore_errors=False*)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

This allows translation layers to provide maps of contiguous regions in one layer

Return type

`Iterable[Tuple[int, int, int, int, str]]`

maximum_address = 4294967295

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

minimum_address = 0

property name: `str`

Returns the layer name.

page_mask = -4096

page_shift = 12

page_size = 4096

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (`ContextInterface`) – The context containing the data layer
- **scanner** (`ScannerInterface`) – The constructed Scanner object to be applied
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – Method that is called periodically during scanning to update progress
- **sections** (`Iterable[Tuple[int, int]]`) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

structure = [('page directory pointer', 2, False), ('page directory', 9, True), ('page table', 9, True)]

translate(*offset, ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

class `WindowsMixin(context, config_path, name, metadata=None)`

Bases: `Intel`

Basic initializer that allows configurables to access their own config settings.

property `address_mask: int`

Returns a mask which encapsulates all the active bits of an address for this layer.

bits_per_register = 32

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

canonicalize(*addr*)

Canonicalizes an address by performing an appropriate sign extension on the higher addresses

Return type

`int`

property `config: HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path: str`

The configuration path on which this configurable lives.

property `context: ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

decanonicalize(*addr*)

Removes canonicalization to ensure an address fits within the correct range if it has been canonicalized

This will produce an address outside the range if the canonicalization is incorrect

Return type

`int`

property dependencies: `List[str]`

Returns a list of the lower layer names that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_dirty(offset)

Returns whether the page at offset is marked dirty

Return type

`bool`

is_valid(offset, length=1)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(offset, length, ignore_errors=False)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

This allows translation layers to provide maps of contiguous regions in one layer

Return type

`Iterable[Tuple[int, int, int, int, str]]`

maximum_address = 4294967295

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

minimum_address = 0

property name: `str`

Returns the layer name.

page_mask = -4096

page_shift = 12

page_size = 4096

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

structure = [('page directory', 10, False), ('page table', 10, True)]

translate(*offset, ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

volatility3.framework.layers.leechcore module

volatility3.framework.layers.lime module

exception `LineFormatException`(*layer_name*, **args*)

Bases: `LayerException`

Thrown when an error occurs with the underlying Lime file format.

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

class `LimeLayer`(*context*, *config_path*, *name*)

Bases: `SegmentedLayer`

A Lime format TranslationLayer.

Lime is generally used to store physical memory images where there are large holes in the physical layer

Basic initializer that allows configurables to access their own config settings.

MAGIC = 1281969477

VERSION = 1

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

property dependencies: `List[str]`

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_valid(offset, length=1)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(offset, length, ignore_errors=False)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

`Iterable[Tuple[int, int, int, int, str]]`

property maximum_address: `int`

Returns the maximum valid address of the space.

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property minimum_address: `int`

Returns the minimum valid address of the space.

property name: `str`

Returns the layer name.

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

bytes

scan(*context*, *scanner*, *progress_callback=None*, *sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional*[*Callable*[[float, str], None]]) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable*[*Tuple*[int, int]]) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[Any]

Returns

The output iterable from the scanner object having been run against the layer

translate(*offset*, *ignore_errors=False*)

Return type

Tuple[Optional[int], Optional[str]]

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

None

class LimeStacker

Bases: *StackerLayerInterface*

exclusion_list: List[str] = []

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod `stack(context, layer_name, progress_callback=None)`

Method to determine whether this builder can operate on the named layer. If so, modify the context appropriately.

Returns the name of any new layer stacked on top of this layer or None. The stacking is therefore strictly linear rather than tree driven.

Configuration options provided by the context are ignored, and defaults are to be used by this method to build a space where possible.

Parameters

- **context** (*ContextInterface*) – Context in which to construct the higher layer
- **layer_name** (*str*) – Name of the layer to stack on top of
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callback function to indicate progress through a scan (if one is necessary)

Return type

Optional[DataLayerInterface]

stack_order = 10

The order in which to attempt stacking, the lower the earlier

classmethod `stacker_slow_warning()`

volatility3.framework.layers.linear module

class `LinearlyMappedLayer(context, config_path, name, metadata=None)`

Bases: *TranslationLayerInterface*

Class to differentiate Linearly Mapped layers (where $a \Rightarrow b$ implies that $a + c \Rightarrow b + c$)

Basic initializer that allows configurables to access their own config settings.

property `address_mask`: *int*

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property `config`: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path`: *str*

The configuration path on which this configurable lives.

property `context`: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

abstract property `dependencies`: *List[str]*

Returns a list of layer names that this layer translates onto.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

abstract is_valid(offset, length=1)

Returns a boolean based on whether the entire chunk of data (from offset to length) is valid or not.

Parameters

- **offset** (`int`) – The address to start determining whether bytes are readable/valid
- **length** (`int`) – The number of bytes from offset of which to test the validity

Return type

`bool`

Returns

Whether the bytes are valid and accessible

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

abstract mapping(offset, length, ignore_errors=False)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

`ignore_errors` will provide all available maps with gaps, but their total length may not add up to the requested length. This allows translation layers to provide maps of contiguous regions in one layer

Return type

`Iterable[Tuple[int, int, int, int, str]]`

abstract property maximum_address: int

Returns the maximum valid address of the space.

property metadata: Mapping

Returns a ReadOnly copy of the metadata published by this layer.

abstract property minimum_address: `int`

Returns the minimum valid address of the space.

property name: `str`

Returns the layer name.

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

translate(*offset, ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset, value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

volatility3.framework.layers.msf module**exception PDBFormatException**(*layer_name*, *args)Bases: *LayerException*

Thrown when an error occurs with the underlying MSF file format.

add_note()

Exception.add_note(note) – add a note to the exception

args**with_traceback()**

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

class PdbMSFStream(*context*, *config_path*, *name*, *metadata=None*)Bases: *LinearlyMappedLayer*

Basic initializer that allows configurables to access their own config settings.

property address_mask: **int**

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: **str**

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

property dependencies: **List[str]**

Returns a list of layer names that this layer translates onto.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type*None***classmethod get_requirements()**

Returns a list of Requirement objects for this type of layer.

Return type*List[RequirementInterface]*

is_valid(*offset*, *length=1*)

Returns a boolean based on whether the entire chunk of data (from offset to length) is valid or not.

Parameters

- **offset** (*int*) – The address to start determining whether bytes are readable/valid
- **length** (*int*) – The number of bytes from offset of which to test the validity

Return type

bool

Returns

Whether the bytes are valid and accessible

classmethod **make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

mapping(*offset*, *length*, *ignore_errors=False*)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

ignore_errors will provide all available maps with gaps, but their total length may not add up to the requested length This allows translation layers to provide maps of contiguous regions in one layer

Return type

Iterable[Tuple[int, int, int, int, str]]

property **maximum_address**: *int*

Returns the maximum valid address of the space.

property **metadata**: *Mapping*

Returns a ReadOnly copy of the metadata published by this layer.

property **minimum_address**: *int*

Returns the minimum valid address of the space.

property **name**: *str*

Returns the layer name.

property **pdb_symbol_table**: *str* | *None*

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns ‘bytes’ (not ‘str’) of length size.

Return type

bytes

scan(*context*, *scanner*, *progress_callback*=None, *sections*=None)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable*[*Tuple*[*int*, *int*]]) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[*Any*]

Returns

The output iterable from the scanner object having been run against the layer

translate(*offset*, *ignore_errors*=False)

Return type

Tuple[*Optional*[*int*], *Optional*[*str*]]

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[*str*, *RequirementInterface*]

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

None

class PdbMultiStreamFormat(*context*, *config_path*, *name*, *metadata*=None)

Bases: *LinearlyMappedLayer*

Basic initializer that allows configurables to access their own config settings.

property address_mask: *int*

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

create_stream_from_pages(*stream_name, maximum_size, pages*)**Return type**`str`**property dependencies:** `List[str]`

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type`None`**classmethod get_requirements()**

Returns a list of Requirement objects for this type of layer.

Return type`List[RequirementInterface]`**get_stream**(*index*)**Return type**`Optional[PdbMSFStream]`**is_valid**(*offset, length=1*)

Returns a boolean based on whether the entire chunk of data (from offset to length) is valid or not.

Parameters

- **offset** (`int`) – The address to start determining whether bytes are readable/valid
- **length** (`int`) – The number of bytes from offset of which to test the validity

Return type`bool`**Returns**

Whether the bytes are valid and accessible

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration

- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

mapping(*offset, length, ignore_errors=False*)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

ignore_errors will provide all available maps with gaps, but their total length may not add up to the requested length This allows translation layers to provide maps of contiguous regions in one layer

Return type

Iterable[Tuple[int, int, int, int, str]]

property maximum_address: *int*

Returns the maximum valid address of the space.

property metadata: *Mapping*

Returns a ReadOnly copy of the metadata published by this layer.

property minimum_address: *int*

Returns the minimum valid address of the space.

property name: *str*

Returns the layer name.

property page_size

property pdb_symbol_table: *str*

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

bytes

read_streams()

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[Any]

Returns

The output iterable from the scanner object having been run against the layer

translate(*offset*, *ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

volatility3.framework.layers.physical module

class BufferDataLayer(*context*, *config_path*, *name*, *buffer*, *metadata=None*)

Bases: `DataLayerInterface`

A DataLayer class backed by a buffer in memory, designed for testing and swift data access.

Basic initializer that allows configurables to access their own config settings.

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

property dependencies: `List[str]`

A list of other layer names required by this layer.

Note: DataLayers must never define other layers

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_valid(offset, length=1)

Returns whether the offset is valid or not.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property maximum_address: `int`

Returns the largest available address in the space.

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property minimum_address: `int`

Returns the smallest available address in the space.

property name: `str`

Returns the layer name.

read(*address, length, pad=False*)

Reads the data from the buffer.

Return type

`bytes`

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

classmethod **unsatisfied**(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*address, data*)

Writes the data from to the buffer.

class **DummyLock**

Bases: *object*

class **FileLayer**(*context, config_path, name, metadata=None*)

Bases: *DataLayerInterface*

a DataLayer backed by a file on the filesystem.

Basic initializer that allows configurables to access their own config settings.

property **address_mask**: *int*

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

property dependencies: *List[str]*

A list of other layer names required by this layer.

Note: DataLayers must never define other layers

destroy()

Closes the file handle.

Return type

None

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

List[RequirementInterface]

is_valid(offset, length=1)

Returns whether the offset is valid or not.

Return type

bool

property location: *str*

Returns the location on which this Layer abstracts.

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property maximum_address:** `int`

Returns the largest available address in the space.

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property minimum_address: `int`

Returns the smallest available address in the space.

property name: `str`

Returns the layer name.

read(*offset, length, pad=False*)

Reads from the file at offset for length.

Return type`bytes`**scan**(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (`ContextInterface`) – The context containing the data layer
- **scanner** (`ScannerInterface`) – The constructed Scanner object to be applied
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – Method that is called periodically during scanning to update progress
- **sections** (`Iterable[Tuple[int, int]]`) – A list of (start, size) tuples defining the portions of the layer to scan

Return type`Iterable[Any]`**Returns**

The output iterable from the scanner object having been run against the layer

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`**write**(*offset, data*)

Writes to the file.

This will technically allow writes beyond the extent of the file

Return type`None`**volatility3.framework.layers.qemu module****class QemuStacker**Bases: *StackerLayerInterface***exclusion_list:** `List[str] = []`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod stack(*context, layer_name, progress_callback=None*)

Method to determine whether this builder can operate on the named layer. If so, modify the context appropriately.

Returns the name of any new layer stacked on top of this layer or None. The stacking is therefore strictly linear rather than tree driven.

Configuration options provided by the context are ignored, and defaults are to be used by this method to build a space where possible.

Parameters

- **context** (*ContextInterface*) – Context in which to construct the higher layer
- **layer_name** (*str*) – Name of the layer to stack on top of
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callback function to indicate progress through a scan (if one is necessary)

Return type*Optional[DataLayerInterface]***stack_order** = 10

The order in which to attempt stacking, the lower the earlier

classmethod stacker_slow_warning()**class QemuSuspendLayer**(*context, config_path, name, metadata=None*)Bases: *NonLinearlySegmentedLayer*

A Qemu suspend-to-disk translation layer.

Basic initializer that allows configurables to access their own config settings.

HASH_PTE_SIZE_64 = 16**QEVm_CONFIGURATION** = 7**QEVm_EOF** = 0**QEVm_SECTION_END** = 3**QEVm_SECTION_FOOTER** = 126**QEVm_SECTION_FULL** = 4**QEVm_SECTION_PART** = 2**QEVm_SECTION_START** = 1

QEVMSUBSECTION = 5

QEVMSDESCRIPTION = 6

SEGMENTFLAGCOMPRESS = 2

SEGMENTFLAGCONTINUE = 32

SEGMENTFLAGEOS = 16

SEGMENTFLAGHOOK = 128

SEGMENTFLAGMEMSIZE = 4

SEGMENTFLAGPAGE = 8

SEGMENTFLAGXBZRLE = 64

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

property dependencies: `List[str]`

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

distro_re = `'(\\w+[\\d{1,2}\\.]*)'`

extract_data(*index, name, version_id*)

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

List[RequirementInterface]

is_valid(*offset*, *length=1*)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod **make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(*offset*, *length*, *ignore_errors=False*)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

`Iterable[Tuple[int, int, int, int, str]]`

property **maximum_address**: `int`

Returns the maximum valid address of the space.

property **metadata**: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property **minimum_address**: `int`

Returns the minimum valid address of the space.

property **name**: `str`

Returns the layer name.

```
pci_hole_table = {re.compile('^pc-i440fx-([23456789]|\\d\\d+)\\.\\.\\.\\d$'):
(3758096384, 3221225472, 4294967296), re.compile('^pc-i440fx-[01]\\.\\.\\.\\d$'):
(3758096384, 3758096384, 4294967296), re.compile('^pc-q35-\\d\\.\\.\\.\\d$'):
(2952790016, 2147483648, 4294967296), re.compile('^microvm$'): (3221225472,
3221225472, 4294967296), re.compile('^xen$'): (4026531840, 4026531840, 4294967296),
re.compile('^pc-i440fx-(\\w+[\\d{1,2}\\.]*)$'): (3758096384, 3221225472,
4294967296), re.compile('^pc-q35-(\\w+[\\d{1,2}\\.]*)$'): (2952790016, 2147483648,
4294967296)}
```

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context*, *scanner*, *progress_callback*=None, *sections*=None)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable*[*Tuple*[*int*, *int*]]) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[*Any*]

Returns

The output iterable from the scanner object having been run against the layer

classmethod **unsatisfied**(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[*str*, *RequirementInterface*]

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

None

volatility3.framework.layers.registry module

exception **RegistryFormatException**(*layer_name*, **args*)

Bases: *LayerException*

Thrown when an error occurs with the underlying Registry file format.

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

class RegistryHive(*context, config_path, name, metadata=None*)

Bases: *LinearlyMappedLayer*

Basic initializer that allows configurables to access their own config settings.

property address_mask: *int*

Return a mask that allows for the volatile bit to be set.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

property dependencies: *List[str]*

Returns a list of layer names that this layer translates onto.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

None

get_cell(*cell_offset*)

Returns the appropriate Cell value for a cell offset.

Return type

StructType

get_key(*key, return_list=False*)

Gets a specific registry key by key path.

return_list specifies whether the return result will be a single node (default) or a list of nodes from root to the current node (if return_list is true).

Return type

Union[List[StructType], StructType]

get_name()

Return type

str

get_node(*cell_offset*)

Returns the appropriate Node, interpreted from the Cell based on its Signature.

Return type

StructType

classmethod **get_requirements**()

Returns a list of Requirement objects for this type of layer.

Return type

List[RequirementInterface]

property **hive_offset**: **int**

is_valid(*offset*, *length=1*)

Returns a boolean based on whether the offset is valid or not.

Return type

bool

classmethod **make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

mapping(*offset*, *length*, *ignore_errors=False*)

Returns a sorted iterable of (offset, sublength, mapped_offset, mapped_length, layer) mappings.

ignore_errors will provide all available maps with gaps, but their total length may not add up to the requested length This allows translation layers to provide maps of contiguous regions in one layer

Return type

Iterable[Tuple[int, int, int, int, str]]

property **maximum_address**: **int**

Returns the maximum valid address of the space.

property **metadata**: **Mapping**

Returns a ReadOnly copy of the metadata published by this layer.

property **minimum_address**: **int**

Returns the minimum valid address of the space.

property **name**: **str**

Returns the layer name.

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

bytes

property root_cell_offset: int

Returns the offset for the root cell in this hive.

scan(*context*, *scanner*, *progress_callback=None*, *sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable*[*Tuple*[*int*, *int*]]) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[Any]

Returns

The output iterable from the scanner object having been run against the layer

translate(*offset*, *ignore_errors=False*)

Return type

Tuple[Optional[int], Optional[str]]

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

visit_nodes(*visitor*, *node=None*)

Applies a callable (visitor) to all nodes within the registry tree from a given node.

Return type

None

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

None

exception RegistryInvalidIndex(*layer_name*, **args*)

Bases: *LayerException*

Thrown when an index that doesn't exist or can't be found occurs.

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

volatility3.framework.layers.resources module

class JarHandler

Bases: *VolatilityHandler*

Handles the jar scheme for URIs.

Reference used for the schema syntax: <http://docs.netkernel.org/book/view/book:mod:reference/doc:layer1:schemes:jar>

Actual reference (found from <https://www.w3.org/wiki/UriSchemes/jar>) seemed not to return: <http://developer.java.sun.com/developer/onlineTraining/protocolhandlers/>

add_parent(*parent*)

close()

static default_open(*req*)

Handles the request if it's the jar scheme.

Return type

Optional[*Any*]

handler_order = 500

classmethod non_cached_schemes()

Return type

List[*str*]

class OfflineHandler

Bases: *VolatilityHandler*

add_parent(*parent*)

close()

static default_open(*req*)

Return type

Optional[*Any*]

handler_order = 500

classmethod `non_cached_schemes()`

Return type

`List[str]`

class `ResourceAccessor`(*progress_callback=None, context=None, enable_cache=True*)

Bases: `object`

Object for opening URLs as files (downloading locally first if necessary)

Creates a resource accessor.

Note: context is an SSL context, not a volatility context

list_handlers = `True`

open(*url, mode='rb'*)

Returns a file-like object for a particular URL opened in mode.

If the file is remote, it will be downloaded and locally cached

Return type

`Any`

uses_cache(*url*)

Determines whether a URLs contents should be cached

Return type

`bool`

class `VolatilityHandler`

Bases: `BaseHandler`

add_parent(*parent*)

close()

handler_order = `500`

classmethod `non_cached_schemes()`

Return type

`List[str]`

cascadeCloseFile(*new_fp, original_fp*)

Really horrible solution for ensuring files aren't left open

Parameters

- **new_fp** (`IO[bytes]`) – The file pointer constructed based on the original file pointer
- **original_fp** (`IO[bytes]`) – The original file pointer that should be closed when the new file pointer is closed, but isn't

Return type

`IO[bytes]`

volatility3.framework.layers.segmented module**class NonLinearlySegmentedLayer**(*context, config_path, name, metadata=None*)Bases: *TranslationLayerInterface*

A class to handle a single run-based layer-to-layer mapping.

In the documentation “mapped address” or “mapped offset” refers to an offset once it has been mapped to the underlying layer

Basic initializer that allows configurables to access their own config settings.

property address_mask: *int*

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

property dependencies: *List[str]*

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type*None***classmethod get_requirements()**

Returns a list of Requirement objects for this type of layer.

Return type*List[RequirementInterface]***is_valid**(*offset, length=1*)

Returns whether the address offset can be translated to a valid address.

Return type*bool*

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

mapping(*offset, length, ignore_errors=False*)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

Iterable[Tuple[int, int, int, int, str]]

property `maximum_address: int`

Returns the maximum valid address of the space.

property `metadata: Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property `minimum_address: int`

Returns the minimum valid address of the space.

property `name: str`

Returns the layer name.

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns ‘bytes’ (not ‘str’) of length size.

Return type

bytes

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (*ContextInterface*) – The context containing the data layer
- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable[Tuple[int, int]]*) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

Iterable[Any]

Returns

The output iterable from the scanner object having been run against the layer

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(offset, value)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

class `SegmentedLayer(context, config_path, name, metadata=None)`

Bases: `NonLinearlySegmentedLayer`, `LinearlyMappedLayer`

Basic initializer that allows configurables to access their own config settings.

property `address_mask: int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property `config: HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path: str`

The configuration path on which this configurable lives.

property `context: ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

property `dependencies: List[str]`

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod `get_requirements()`

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_valid(*offset*, *length=1*)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(*offset*, *length*, *ignore_errors=False*)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

`Iterable[Tuple[int, int, int, int, str]]`

property `maximum_address: int`

Returns the maximum valid address of the space.

property `metadata: Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property `minimum_address: int`

Returns the minimum valid address of the space.

property `name: str`

Returns the layer name.

read(*offset*, *length*, *pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context*, *scanner*, *progress_callback=None*, *sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (`ContextInterface`) – The context containing the data layer

- **scanner** (*ScannerInterface*) – The constructed Scanner object to be applied
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – Method that is called periodically during scanning to update progress
- **sections** (*Iterable*[*Tuple*[*int*, *int*]]) – A list of (start, size) tuples defining the portions of the layer to scan

Return type*Iterable*[*Any*]**Returns**

The output iterable from the scanner object having been run against the layer

translate(*offset*, *ignore_errors=False*)

Return type*Tuple*[*Optional*[*int*], *Optional*[*str*]]

classmethod **unsatisfied**(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type*Dict*[*str*, *RequirementInterface*]

write(*offset*, *value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type*None*

volatility3.framework.layers.vmware module

exception **VmwareFormatException**(*layer_name*, **args*)

Bases: *LayerException*

Thrown when an error occurs with the underlying VMware vmem file format.

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

class **VmwareLayer**(*context*, *config_path*, *name*, *metadata=None*)

Bases: *SegmentedLayer*

Basic initializer that allows configurables to access their own config settings.

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

property dependencies: `List[str]`

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

This vmware translation layer always requires a separate metadata layer.

Return type

`List[RequirementInterface]`

group_structure = `'64sQQ'`

header_structure = `'<4sII'`

is_valid(offset, length=1)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(*offset, length, ignore_errors=False*)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

`Iterable[Tuple[int, int, int, int, str]]`

property maximum_address: `int`

Returns the maximum valid address of the space.

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property minimum_address: `int`

Returns the minimum valid address of the space.

property name: `str`

Returns the layer name.

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (`ContextInterface`) – The context containing the data layer
- **scanner** (`ScannerInterface`) – The constructed Scanner object to be applied
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – Method that is called periodically during scanning to update progress
- **sections** (`Iterable[Tuple[int, int]]`) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

translate(*offset, ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type

`Dict[str, RequirementInterface]`

write(*offset, value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

class VmwareStacker

Bases: `StackerLayerInterface`

exclusion_list: `List[str] = []`

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod stack(*context, layer_name, progress_callback=None*)

Attempt to stack this based on the starting information.

Return type

`Optional[DataLayerInterface]`

stack_order = 20

The order in which to attempt stacking, the lower the earlier

classmethod stacker_slow_warning()

volatility3.framework.layers.xen module

class XenCoreDumpLayer(*context, config_path, name*)

Bases: `Elf64Layer`

A layer that supports the Xen Dump-Core format as documented at: <https://xenbits.xen.org/docs/4.6-testing/misc/dump-core-format.txt>

Basic initializer that allows configurables to access their own config settings.

ELF_CLASS = 2

MAGIC = 1179403647

property address_mask: `int`

Returns a mask which encapsulates all the active bits of an address for this layer.

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

property dependencies: `List[str]`

Returns a list of the lower layers that this layer is dependent upon.

destroy()

Causes a DataLayer to close any open handles, etc.

Systems that make use of Data Layers should call destroy when they are done with them. This will close all handles, and make the object unreadable (exceptions will be thrown using a DataLayer after destruction)

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this type of layer.

Return type

`List[RequirementInterface]`

is_valid(offset, length=1)

Returns whether the address offset can be translated to a valid address.

Return type

`bool`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

mapping(offset, length, ignore_errors=False)

Returns a sorted iterable of (offset, length, mapped_offset, mapped_length, layer) mappings.

Return type

`Iterable[Tuple[int, int, int, int, str]]`

property maximum_address: `int`

Returns the maximum valid address of the space.

property metadata: `Mapping`

Returns a ReadOnly copy of the metadata published by this layer.

property minimum_address: `int`

Returns the minimum valid address of the space.

property name: `str`

Returns the layer name.

read(*offset, length, pad=False*)

Reads an offset for length bytes and returns 'bytes' (not 'str') of length size.

Return type

`bytes`

scan(*context, scanner, progress_callback=None, sections=None*)

Scans a Translation layer by chunk.

Note: this will skip missing/unmappable chunks of memory

Parameters

- **context** (`ContextInterface`) – The context containing the data layer
- **scanner** (`ScannerInterface`) – The constructed Scanner object to be applied
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – Method that is called periodically during scanning to update progress
- **sections** (`Iterable[Tuple[int, int]]`) – A list of (start, size) tuples defining the portions of the layer to scan

Return type

`Iterable[Any]`

Returns

The output iterable from the scanner object having been run against the layer

translate(*offset, ignore_errors=False*)

Return type

`Tuple[Optional[int], Optional[str]]`

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

write(*offset, value*)

Writes a value at offset, distributing the writing across any underlying mapping.

Return type

`None`

class XenCoreDumpStackerBases: *Elf64Stacker***exclusion_list:** List[str] = []

The list operating systems/first-level plugin hierarchy that should exclude this stacker

classmethod stack(context, layer_name, progress_callback=None)

Method to determine whether this builder can operate on the named layer. If so, modify the context appropriately.

Returns the name of any new layer stacked on top of this layer or None. The stacking is therefore strictly linear rather than tree driven.

Configuration options provided by the context are ignored, and defaults are to be used by this method to build a space where possible.

Parameters

- **context** (*ContextInterface*) – Context in which to construct the higher layer
- **layer_name** (str) – Name of the layer to stack on top of
- **progress_callback** (Optional[Callable[[float, str], None]]) – A callback function to indicate progress through a scan (if one is necessary)

Return type*Optional[DataLayerInterface]***stack_order** = 10

The order in which to attempt stacking, the lower the earlier

classmethod stacker_slow_warning()**volatility3.framework.objects package****class AggregateType**(context, type_name, object_info, size, members)Bases: *ObjectInterface*

Object which can contain members that are other objects.

Keep the number of methods in this class low or very specific, since each one could overload a valid member.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (str) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: *VolTemplateProxy***classmethod child_template**(template, child)

Returns the template of a child to its parent.

Return type*Template*

classmethod children(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

classmethod relative_child_offset(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod replace_child(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod size(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the *table_name* is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class Array(*context, type_name, object_info, count=0, subtype=None*)

Bases: *ObjectInterface, Sequence*

Object which can contain a fixed number of an object type.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of the child member.

Return type

Template

classmethod children(*template*)

Returns the children of the template.

Return type

List[Template]

abstract classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset from the head of the parent data to the child member.

Return type

int

classmethod `replace_child(template, old_child, new_child)`

Substitutes the old_child for the new_child.

Return type

`None`

classmethod `size(template)`

Returns the size of the array, based on the count and the subtype.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

property count: `int`

Returns the count dynamically.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

index(*value*[, *start*[, *stop*]]) → integer -- return first index of value.

Raises ValueError if the value is not present.

Supporting start and stop arguments is optional, but recommended.

property *vol*: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

Return type

[*None*](#)

class [*BitField*](#)(*context*, *type_name*, *object_info*, *base_type*, *start_bit*=0, *end_bit*=0)

Bases: [*ObjectInterface*](#), [*int*](#)

Object containing a field which is made up of bits rather than whole bytes.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** ([*str*](#)) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class [*VolTemplateProxy*](#)

Bases: [*VolTemplateProxy*](#)

abstract classmethod [*child_template*](#)(*template*, *child*)

Returns the template of the child member from the parent.

Return type

[*Template*](#)

classmethod [*children*](#)(*template*)

Returns the children of the template.

Return type

[*List\[Template\]*](#)

abstract classmethod [*has_member*](#)(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

[*bool*](#)

abstract classmethod [*relative_child_offset*](#)(*template*, *child*)

Returns the relative offset from the head of the parent data to the child member.

Return type

[*int*](#)

classmethod [*replace_child*](#)(*template*, *old_child*, *new_child*)

Substitutes the old_child for the new_child.

Return type

[*None*](#)

classmethod `size(template)`

Returns the size of the template object.

Return type

`int`

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(byteorder='big', *, signed=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(length=1, byteorder='big', *, signed=False)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an `OverflowError` is raised.

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class Boolean(context, type_name, object_info, data_format)

Bases: [*PrimitiveObject*](#), `int`

Primitive Object that handles boolean types.

Constructs an Object adhering to the `ObjectInterface`.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [*VolTemplateProxy*](#)

abstract classmethod child_template(template, child)

Returns the template of the child member from the parent.

Return type

[*Template*](#)

abstract classmethod children(template)

Returns the children of the template.

Return type

[*List\[Template\]*](#)

abstract classmethod has_member(template, member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

abstract classmethod relative_child_offset(template, child)

Returns the relative offset from the head of the parent data to the child member.

Return type

`int`

abstract classmethod `replace_child(template, old_child, new_child)`

Substitutes the `old_child` for the `new_child`.

Return type

`None`

classmethod `size(template)`

Returns the size of the templated object.

Return type

`int`

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: [*ObjectInterface*](#)

Note: If new type name does not include a symbol table, the symbol table for the current object is used

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(byteorder='big', *, signed=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use 'sys.byteorder' as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If `byteorder` is 'big', the most significant byte is at the beginning of the byte array. If `byteorder` is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `'sys.byteorder'` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If `signed` is `False` and a negative integer is given, an `OverflowError` is raised.

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the object into the layer of the context at the current offset.

Return type

ObjectInterface

class Bytes(*context, type_name, object_info, length=1*)

Bases: *PrimitiveObject, bytes*

Primitive Object that handles specific series of bytes.

Constructs an Object adhering to the `ObjectInterface`.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

abstract classmethod child_template(*template, child*)

Returns the template of the child member from the parent.

Return type

Template

abstract classmethod children(*template*)

Returns the children of the template.

Return type

List[Template]

abstract classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called `member_name`.

Return type`bool`**abstract classmethod** `relative_child_offset(template, child)`

Returns the relative offset from the head of the parent data to the child member.

Return type`int`**abstract classmethod** `replace_child(template, old_child, new_child)`

Substitutes the old_child for the new_child.

Return type`None`**classmethod** `size(template)`

Returns the size of the template object.

Return type`int`**capitalize()** → copy of B

Return a copy of B with only its first character capitalized (ASCII) and the rest lower-cased.

cast(*new_type_name*, ***additional*)Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

center(*width*, *fillchar=b' ', /*)

Return a centered string of length width.

Padding is done using the specified fill character.

count(*sub*[, *start*[, *end*]]) → `int`

Return the number of non-overlapping occurrences of subsection sub in bytes B[start:end]. Optional arguments start and end are interpreted as in slice notation.

decode(*encoding='utf-8'*, *errors='strict'*)

Decode the bytes using the codec registered for encoding.

encoding

The encoding with which to decode the bytes.

errors

The error handling scheme to use for the handling of decoding errors. The default is 'strict' meaning that decoding errors raise a UnicodeDecodeError. Other possible values are 'ignore' and 'replace' as well as any other name registered with codecs.register_error that can handle UnicodeDecodeErrors.

endswith(*suffix*[, *start*[, *end*]]) → `bool`

Return True if B ends with the specified suffix, False otherwise. With optional start, test B beginning at that position. With optional end, stop comparing B at that position. suffix can also be a tuple of bytes to try.

expandtabs(*tabsize=8*)

Return a copy where all tab characters are expanded using spaces.

If tabsize is not given, a tab size of 8 characters is assumed.

find(*sub*[, *start*[, *end*]]) → int

Return the lowest index in B where subsection sub is found, such that sub is contained within B[start,end]. Optional arguments start and end are interpreted as in slice notation.

Return -1 on failure.

fromhex()

Create a bytes object from a string of hexadecimal numbers.

Spaces between two numbers are accepted. Example: bytes.fromhex('B9 01EF') -> b'\xb9\x01\xef'.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Parameters

member_name (str) – Name to test whether a member exists within the type structure

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (str) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (List[str]) – List of names to test as to members with those names validity

Return type

bool

hex()

Create a string of hexadecimal numbers from a bytes object.

sep

An optional single character or byte to separate hex bytes.

bytes_per_sep

How many bytes between separators. Positive values count from the right, negative values count from the left.

Example: >>> value = b'\xb9\x01\xef' >>> value.hex() 'b901ef' >>> value.hex(':') 'b9:01:ef' >>> value.hex(':', 2) 'b9:01ef' >>> value.hex(':', -2) 'b901:ef'

index(*sub*[, *start*[, *end*]]) → int

Return the lowest index in B where subsection sub is found, such that sub is contained within B[start,end]. Optional arguments start and end are interpreted as in slice notation.

Raises ValueError when the subsection is not found.

isalnum() → bool

Return True if all characters in B are alphanumeric and there is at least one character in B, False otherwise.

isalpha() → bool

Return True if all characters in B are alphabetic and there is at least one character in B, False otherwise.

isascii() → bool

Return True if B is empty or all characters in B are ASCII, False otherwise.

isdigit() → bool

Return True if all characters in B are digits and there is at least one character in B, False otherwise.

islower() → bool

Return True if all cased characters in B are lowercase and there is at least one cased character in B, False otherwise.

isspace() → bool

Return True if all characters in B are whitespace and there is at least one character in B, False otherwise.

istitle() → bool

Return True if B is a titlecased string and there is at least one character in B, i.e. uppercase characters may only follow uncased characters and lowercase characters only cased ones. Return False otherwise.

isupper() → bool

Return True if all cased characters in B are uppercase and there is at least one cased character in B, False otherwise.

join(*iterable_of_bytes*, /)

Concatenate any number of bytes objects.

The bytes whose method is called is inserted in between each pair.

The result is returned as a new bytes object.

Example: b'.'.join([b'ab', b'pq', b'rs']) -> b'ab.pq.rs'.

ljust(*width*, *fillchar*=b' ', /)

Return a left-justified string of length width.

Padding is done using the specified fill character.

lower() → copy of B

Return a copy of B with all ASCII characters converted to lowercase.

lstrip(*bytes*=None, /)

Strip leading bytes contained in the argument.

If the argument is omitted or None, strip leading ASCII whitespace.

static maketrans(*frm*, *to*, /)

Return a translation table useable for the bytes or bytearray translate method.

The returned table will be one where each byte in frm is mapped to the byte at the same position in to.

The bytes objects frm and to must be of the same length.

partition(*sep*, /)

Partition the bytes into three parts using the given separator.

This will search for the separator *sep* in the bytes. If the separator is found, returns a 3-tuple containing the part before the separator, the separator itself, and the part after it.

If the separator is not found, returns a 3-tuple containing the original bytes object and two empty bytes objects.

removeprefix(*prefix*, /)

Return a bytes object with the given prefix string removed if present.

If the bytes starts with the prefix string, return bytes[len(prefix):]. Otherwise, return a copy of the original bytes.

removesuffix(*suffix*, /)

Return a bytes object with the given suffix string removed if present.

If the bytes ends with the suffix string and that suffix is not empty, return bytes[:-len(suffix)]. Otherwise, return a copy of the original bytes.

replace(*old*, *new*, *count=-1*, /)

Return a copy with all occurrences of substring *old* replaced by *new*.

count

Maximum number of occurrences to replace. -1 (the default value) means replace all occurrences.

If the optional argument *count* is given, only the first *count* occurrences are replaced.

rfind(*sub*[, *start*[, *end*]]) → int

Return the highest index in *B* where subsection *sub* is found, such that *sub* is contained within *B*[*start*,*end*]. Optional arguments *start* and *end* are interpreted as in slice notation.

Return -1 on failure.

rindex(*sub*[, *start*[, *end*]]) → int

Return the highest index in *B* where subsection *sub* is found, such that *sub* is contained within *B*[*start*,*end*]. Optional arguments *start* and *end* are interpreted as in slice notation.

Raise *ValueError* when the subsection is not found.

rjust(*width*, *fillchar=b' '*, /)

Return a right-justified string of length *width*.

Padding is done using the specified fill character.

rpartition(*sep*, /)

Partition the bytes into three parts using the given separator.

This will search for the separator *sep* in the bytes, starting at the end. If the separator is found, returns a 3-tuple containing the part before the separator, the separator itself, and the part after it.

If the separator is not found, returns a 3-tuple containing two empty bytes objects and the original bytes object.

rsplit(*sep=None*, *maxsplit=-1*)

Return a list of the sections in the bytes, using *sep* as the delimiter.

sep

The delimiter according which to split the bytes. *None* (the default value) means split on ASCII whitespace characters (space, tab, return, newline, formfeed, vertical tab).

maxsplit

Maximum number of splits to do. -1 (the default value) means no limit.

Splitting is done starting at the end of the bytes and working to the front.

rstrip(*bytes=None, /*)

Strip trailing bytes contained in the argument.

If the argument is omitted or None, strip trailing ASCII whitespace.

split(*sep=None, maxsplit=-1*)

Return a list of the sections in the bytes, using sep as the delimiter.

sep

The delimiter according which to split the bytes. None (the default value) means split on ASCII whitespace characters (space, tab, return, newline, formfeed, vertical tab).

maxsplit

Maximum number of splits to do. -1 (the default value) means no limit.

splitlines(*keepends=False*)

Return a list of the lines in the bytes, breaking at line boundaries.

Line breaks are not included in the resulting list unless keepends is given and true.

startswith(*prefix[, start[, end]]*) → bool

Return True if B starts with the specified prefix, False otherwise. With optional start, test B beginning at that position. With optional end, stop comparing B at that position. prefix can also be a tuple of bytes to try.

strip(*bytes=None, /*)

Strip leading and trailing bytes contained in the argument.

If the argument is omitted or None, strip leading and trailing ASCII whitespace.

swapcase() → copy of B

Return a copy of B with uppercase ASCII characters converted to lowercase ASCII and vice versa.

title() → copy of B

Return a titlecased version of B, i.e. ASCII words start with uppercase characters, all remaining cased characters have lowercase.

translate(*table, /, delete=b''*)

Return a copy with each character mapped by the given translation table.

table

Translation table, which must be a bytes object of length 256.

All characters occurring in the optional argument delete are removed. The remaining characters are mapped through the given translation table.

upper() → copy of B

Return a copy of B with all ASCII characters converted to uppercase.

property vol: [ReadOnlyMapping](#)

Returns the volatility specific object information.

write(*value*)

Writes the object into the layer of the context at the current offset.

Return type

[ObjectInterface](#)

zfill(*width*, /)

Pad a numeric string with zeros on the left, to fill a field of the given width.

The original string is never truncated.

class Char(*context*, *type_name*, *object_info*, *data_format*)

Bases: [PrimitiveObject](#), [int](#)

Primitive Object that handles characters.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([ContextInterface](#)) – The context associated with the object
- **type_name** ([str](#)) – The name of the type structure for the object
- **object_info** ([ObjectInformation](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [VolTemplateProxy](#)

abstract classmethod child_template(*template*, *child*)

Returns the template of the child member from the parent.

Return type

[Template](#)

abstract classmethod children(*template*)

Returns the children of the template.

Return type

[List\[Template\]](#)

abstract classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

[bool](#)

abstract classmethod relative_child_offset(*template*, *child*)

Returns the relative offset from the head of the parent data to the child member.

Return type

[int](#)

abstract classmethod replace_child(*template*, *old_child*, *new_child*)

Substitutes the old_child for the new_child.

Return type

[None](#)

classmethod size(*template*)

Returns the size of the templated object.

Return type

[int](#)

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(byteorder='big', *, signed=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use 'sys.byteorder' as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is ‘big’, the most significant byte is at the beginning of the byte array. If byteorder is ‘little’, the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use ‘big’.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an OverflowError is raised.

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the object into the layer of the context at the current offset.

Return type

ObjectInterface

class ClassType(context, type_name, object_info, size, members)

Bases: *AggregateType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(template, child)

Returns the template of a child to its parent.

Return type

Template

classmethod children(template)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(template, member_name)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(template, child)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(template, old_child, new_child)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(template)

Method to return the size of this type.

Return type

int

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class DataFormatInfo(*length, byteorder, signed*)

Bases: *tuple*

Create new instance of DataFormatInfo(length, byteorder, signed)

byteorder

Alias for field number 1

count(*value*, /)

Return number of occurrences of value.

index(*value*, *start*=0, *stop*=9223372036854775807, /)

Return first index of value.

Raises ValueError if the value is not present.

length

Alias for field number 0

signed

Alias for field number 2

class Enumeration(*context*, *type_name*, *object_info*, *base_type*, *choices*)

Bases: [ObjectInterface](#), [int](#)

Returns an object made up of choices.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([ContextInterface](#)) – The context associated with the object
- **type_name** ([str](#)) – The name of the type structure for the object
- **object_info** ([ObjectInformation](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [VolTemplateProxy](#)

abstract classmethod child_template(*template*, *child*)

Returns the template of the child member from the parent.

Return type

[Template](#)

classmethod children(*template*)

Returns the children of the template.

Return type

[List](#)[[Template](#)]

abstract classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

[bool](#)

classmethod lookup(*template*, *value*)

Looks up an individual value and returns the associated name.

If multiple identifiers map to the same value, the first matching identifier will be returned

Return type

[str](#)

abstract classmethod `relative_child_offset(template, child)`

Returns the relative offset from the head of the parent data to the child member.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Substitutes the `old_child` for the `new_child`.

Return type

`None`

classmethod `size(template)`

Returns the size of the template object.

Return type

`int`

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

property choices: `Dict[str, int]`

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

property description: `str`

Returns the chosen name for the value this object contains.

from_bytes(*byteorder='big', *, signed=False*)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `'sys.byteorder'` as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**imag**

the imaginary part of a complex number

property is_valid_choice: `bool`

Returns whether the value for the object is a valid choice

lookup(*value=None*)

Looks up an individual value and returns the associated name.

If multiple identifiers map to the same value, the first matching identifier will be returned

Return type`str`**numerator**

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an `OverflowError` is raised.

property vol: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class Float(*context, type_name, object_info, data_format*)

Bases: `PrimitiveObject`, `float`

Primitive Object that handles double or floating point numbers.

Constructs an Object adhering to the `ObjectInterface`.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: *VolTemplateProxy***abstract classmethod child_template**(*template, child*)

Returns the template of the child member from the parent.

Return type*Template***abstract classmethod children**(*template*)

Returns the children of the template.

Return type*List[Template]***abstract classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool***abstract classmethod relative_child_offset**(*template, child*)

Returns the relative offset from the head of the parent data to the child member.

Return type*int***abstract classmethod replace_child**(*template, old_child, new_child*)

Substitutes the old_child for the new_child.

Return type*None***classmethod size**(*template*)

Returns the size of the templated object.

Return type*int***as_integer_ratio()**

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original float and with a positive denominator.

Raise OverflowError on infinities and a ValueError on NaNs.

```

>>> (10.0).as_integer_ratio()
(10, 1)
>>> (0.0).as_integer_ratio()
(0, 1)
>>> (-.25).as_integer_ratio()
(-1, 4)

```

cast(*new_type_name, **additional*)Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface***Note:** If new type name does not include a symbol table, the symbol table for the current object is used**conjugate()**

Return self, the complex conjugate of any float.

fromhex()

Create a floating-point number from a hexadecimal string.

```
>>> float.fromhex('0x1.ffffp10')
2047.984375
>>> float.fromhex('-0x1p-1074')
-5e-324
```

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

hex()

Return a hexadecimal representation of a floating-point number.

```
>>> (-0.1).hex()
'-0x1.999999999999ap-4'
>>> 3.14159.hex()
'0x1.921f9f01b866ep+1'
```

imag

the imaginary part of a complex number

is_integer()

Return True if the float is an integer.

real

the real part of a complex number

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the object into the layer of the context at the current offset.

Return type

ObjectInterface

class Function(context, type_name, object_info, **kwargs)

Bases: *ObjectInterface*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *object*

A container for proxied methods that the ObjectTemplate of this object will call. This is primarily to keep methods together for easy organization/management, there is no significant need for it to be a separate class.

The methods of this class *must* be class methods rather than standard methods, to allow for code reuse. Each method also takes a template since the templates may contain the necessary data about the yet-to-be-constructed object. It allows objects to control how their templates respond without needing to write new templates for each and every potential object type.

abstract classmethod child_template(template, child)

Returns the template of the child member from the parent.

Return type

Template

abstract classmethod children(template)

Returns the children of the template.

Return type

List[Template]

abstract classmethod has_member(template, member_name)

Returns whether the object would contain a member called member_name.

Return type

bool

abstract classmethod relative_child_offset(template, child)

Returns the relative offset from the head of the parent data to the child member.

Return type

int

abstract classmethod `replace_child(template, old_child, new_child)`

Substitutes the old_child for the new_child.

Return type

`None`

abstract classmethod `size(template)`

Returns the size of the template object.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

property `vol`: `ReadOnlyMapping`

Returns the volatility specific object information.

abstract write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class Integer(*context, type_name, object_info, data_format*)

Bases: *PrimitiveObject, int*

Primitive Object that handles standard numeric types.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

abstract classmethod child_template(*template, child*)

Returns the template of the child member from the parent.

Return type

Template

abstract classmethod children(*template*)

Returns the children of the template.

Return type

List[Template]

abstract classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

abstract classmethod relative_child_offset(*template, child*)

Returns the relative offset from the head of the parent data to the child member.

Return type

int

abstract classmethod replace_child(*template, old_child, new_child*)

Substitutes the old_child for the new_child.

Return type

None

classmethod size(*template*)

Returns the size of the templated object.

Return type

int

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(byteorder='big', *, signed=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use 'sys.byteorder' as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(length=1, byteorder='big', *, signed=False)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is ‘big’, the most significant byte is at the beginning of the byte array. If byteorder is ‘little’, the most significant byte is at the end of the byte array. To request the native byte order of the host system, use ‘`sys.byteorder`’ as the byte order value. Default is to use ‘big’.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an OverflowError is raised.

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the object into the layer of the context at the current offset.

Return type

ObjectInterface

class Pointer(context, type_name, object_info, data_format, subtype=None)

Bases: *Integer*

Pointer which points to another object.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

abstract classmethod child_template(template, child)

Returns the template of the child member from the parent.

Return type

Template

classmethod children(template)

Returns the children of the template.

Return type

List[Template]

classmethod has_member(template, member_name)

Returns whether the object would contain a member called member_name.

Return type

bool

abstract classmethod relative_child_offset(template, child)

Returns the relative offset from the head of the parent data to the child member.

Return type

int

classmethod replace_child(template, old_child, new_child)

Substitutes the old_child for the new_child.

Return type

None

classmethod size(template)

Returns the size of the template object.

Return type`int`**as_integer_ratio()**

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

dereference(layer_name=None)

Dereferences the pointer.

Layer_name identifies the appropriate layer within the context that the pointer points to. If layer_name is None, it defaults to the same layer that the pointer is currently instantiated in.

Return type*ObjectInterface*

from_bytes(*byteorder='big', *, signed=False*)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the dereferenced type has this member.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

imag

the imaginary part of a complex number

is_readable(*layer_name=None*)

Determines whether the address of this pointer can be read from memory.

Return type

`bool`

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If `byteorder` is 'big', the most significant byte is at the beginning of the byte array. If `byteorder` is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If `signed` is `False` and a negative integer is given, an `OverflowError` is raised.

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the object into the layer of the context at the current offset.

Return type

ObjectInterface

class PrimitiveObject(*context, type_name, object_info, data_format*)

Bases: *ObjectInterface*

PrimitiveObject is an interface for any objects that should simulate a Python primitive.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

abstract classmethod child_template(*template, child*)

Returns the template of the child member from the parent.

Return type

Template

abstract classmethod children(*template*)

Returns the children of the template.

Return type

List[Template]

abstract classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

abstract classmethod `relative_child_offset(template, child)`

Returns the relative offset from the head of the parent data to the child member.

Return type

`int`

abstract classmethod `replace_child(template, old_child, new_child)`

Substitutes the old_child for the new_child.

Return type

`None`

classmethod `size(template)`

Returns the size of the templated object.

Return type

`int`

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the object into the layer of the context at the current offset.

Return type

ObjectInterface

class String(*context, type_name, object_info, max_length=1, encoding='utf-8', errors='strict'*)

Bases: *PrimitiveObject, str*

Primitive Object that handles string values.

Parameters

max_length (*int*) – specifies the maximum possible length that the string could hold within memory (for multibyte characters, this will not be the maximum length of the string)

Constructs an Object adhering to the *ObjectInterface*.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

abstract classmethod child_template(*template, child*)

Returns the template of the child member from the parent.

Return type

Template

abstract classmethod children(*template*)

Returns the children of the template.

Return type

List[Template]

abstract classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

abstract classmethod relative_child_offset(*template, child*)

Returns the relative offset from the head of the parent data to the child member.

Return type

int

abstractmethod `replace_child(template, old_child, new_child)`

Substitutes the old_child for the new_child.

Return type

`None`

classmethod `size(template)`

Returns the size of the templated object.

Return type

`int`

capitalize()

Return a capitalized version of the string.

More specifically, make the first character have upper case and the rest lower case.

casefold()

Return a version of the string suitable for caseless comparisons.

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

center(*width*, *fillchar*=' ', /)

Return a centered string of length width.

Padding is done using the specified fill character (default is a space).

count(*sub*[, *start*[, *end*]]) → `int`

Return the number of non-overlapping occurrences of substring sub in string S[start:end]. Optional arguments start and end are interpreted as in slice notation.

encode(*encoding*='utf-8', *errors*='strict')

Encode the string using the codec registered for encoding.

encoding

The encoding in which to encode the string.

errors

The error handling scheme to use for encoding errors. The default is 'strict' meaning that encoding errors raise a `UnicodeEncodeError`. Other possible values are 'ignore', 'replace' and 'xmlcharrefreplace' as well as any other name registered with `codecs.register_error` that can handle `UnicodeEncodeErrors`.

endswith(*suffix*[, *start*[, *end*]]) → `bool`

Return True if S ends with the specified suffix, False otherwise. With optional start, test S beginning at that position. With optional end, stop comparing S at that position. suffix can also be a tuple of strings to try.

expandtabs(*tabsize*=8)

Return a copy where all tab characters are expanded using spaces.

If tabsize is not given, a tab size of 8 characters is assumed.

find(*sub*[, *start*[, *end*]]) → `int`

Return the lowest index in S where substring sub is found, such that sub is contained within S[start:end]. Optional arguments start and end are interpreted as in slice notation.

Return -1 on failure.

format(*args, **kwargs) → str

Return a formatted version of S, using substitutions from args and kwargs. The substitutions are identified by braces ('{' and '}').

format_map(mapping) → str

Return a formatted version of S, using substitutions from mapping. The substitutions are identified by braces ('{' and '}').

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

str

has_member(member_name)

Returns whether the object would contain a member called member_name.

Parameters

member_name (str) – Name to test whether a member exists within the type structure

Return type

bool

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (str) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (List[str]) – List of names to test as to members with those names validity

Return type

bool

index(sub[, start[, end]]) → int

Return the lowest index in S where substring sub is found, such that sub is contained within S[start:end]. Optional arguments start and end are interpreted as in slice notation.

Raises ValueError when the substring is not found.

isalnum()

Return True if the string is an alpha-numeric string, False otherwise.

A string is alpha-numeric if all characters in the string are alpha-numeric and there is at least one character in the string.

isalpha()

Return True if the string is an alphabetic string, False otherwise.

A string is alphabetic if all characters in the string are alphabetic and there is at least one character in the string.

isascii()

Return True if all characters in the string are ASCII, False otherwise.

ASCII characters have code points in the range U+0000-U+007F. Empty string is ASCII too.

isdecimal()

Return True if the string is a decimal string, False otherwise.

A string is a decimal string if all characters in the string are decimal and there is at least one character in the string.

isdigit()

Return True if the string is a digit string, False otherwise.

A string is a digit string if all characters in the string are digits and there is at least one character in the string.

isidentifier()

Return True if the string is a valid Python identifier, False otherwise.

Call `keyword.iskeyword(s)` to test whether string `s` is a reserved identifier, such as “def” or “class”.

islower()

Return True if the string is a lowercase string, False otherwise.

A string is lowercase if all cased characters in the string are lowercase and there is at least one cased character in the string.

isnumeric()

Return True if the string is a numeric string, False otherwise.

A string is numeric if all characters in the string are numeric and there is at least one character in the string.

isprintable()

Return True if the string is printable, False otherwise.

A string is printable if all of its characters are considered printable in `repr()` or if it is empty.

isspace()

Return True if the string is a whitespace string, False otherwise.

A string is whitespace if all characters in the string are whitespace and there is at least one character in the string.

istitle()

Return True if the string is a title-cased string, False otherwise.

In a title-cased string, upper- and title-case characters may only follow uncased characters and lowercase characters only cased ones.

isupper()

Return True if the string is an uppercase string, False otherwise.

A string is uppercase if all cased characters in the string are uppercase and there is at least one cased character in the string.

join(iterable, /)

Concatenate any number of strings.

The string whose method is called is inserted in between each given string. The result is returned as a new string.

Example: `'.'.join(['ab', 'pq', 'rs']) -> 'ab.pq.rs'`

ljust(width, fillchar=' ', /)

Return a left-justified string of length width.

Padding is done using the specified fill character (default is a space).

lower()

Return a copy of the string converted to lowercase.

lstrip(chars=None, /)

Return a copy of the string with leading whitespace removed.

If chars is given and not None, remove characters in chars instead.

static maketrans()

Return a translation table usable for `str.translate()`.

If there is only one argument, it must be a dictionary mapping Unicode ordinals (integers) or characters to Unicode ordinals, strings or None. Character keys will be then converted to ordinals. If there are two arguments, they must be strings of equal length, and in the resulting dictionary, each character in x will be mapped to the character at the same position in y. If there is a third argument, it must be a string, whose characters will be mapped to None in the result.

partition(sep, /)

Partition the string into three parts using the given separator.

This will search for the separator in the string. If the separator is found, returns a 3-tuple containing the part before the separator, the separator itself, and the part after it.

If the separator is not found, returns a 3-tuple containing the original string and two empty strings.

removeprefix(prefix, /)

Return a str with the given prefix string removed if present.

If the string starts with the prefix string, return `string[len(prefix):]`. Otherwise, return a copy of the original string.

removesuffix(suffix, /)

Return a str with the given suffix string removed if present.

If the string ends with the suffix string and that suffix is not empty, return `string[:-len(suffix)]`. Otherwise, return a copy of the original string.

replace(old, new, count=-1, /)

Return a copy with all occurrences of substring old replaced by new.

count

Maximum number of occurrences to replace. -1 (the default value) means replace all occurrences.

If the optional argument count is given, only the first count occurrences are replaced.

rfind(*sub*[, *start*[, *end*]]) → int

Return the highest index in *S* where substring *sub* is found, such that *sub* is contained within *S*[*start*:*end*]. Optional arguments *start* and *end* are interpreted as in slice notation.

Return -1 on failure.

rindex(*sub*[, *start*[, *end*]]) → int

Return the highest index in *S* where substring *sub* is found, such that *sub* is contained within *S*[*start*:*end*]. Optional arguments *start* and *end* are interpreted as in slice notation.

Raises `ValueError` when the substring is not found.

rjust(*width*, *fillchar*=' ', /)

Return a right-justified string of length *width*.

Padding is done using the specified fill character (default is a space).

rpartition(*sep*, /)

Partition the string into three parts using the given separator.

This will search for the separator in the string, starting at the end. If the separator is found, returns a 3-tuple containing the part before the separator, the separator itself, and the part after it.

If the separator is not found, returns a 3-tuple containing two empty strings and the original string.

rsplit(*sep*=None, *maxsplit*=-1)

Return a list of the substrings in the string, using *sep* as the separator string.

sep

The separator used to split the string.

When set to `None` (the default value), will split on any whitespace character (including `\n`, `\r`, `\t` and spaces) and will discard empty strings from the result.

maxsplit

Maximum number of splits (starting from the left). -1 (the default value) means no limit.

Splitting starts at the end of the string and works to the front.

rstrip(*chars*=None, /)

Return a copy of the string with trailing whitespace removed.

If *chars* is given and not `None`, remove characters in *chars* instead.

split(*sep*=None, *maxsplit*=-1)

Return a list of the substrings in the string, using *sep* as the separator string.

sep

The separator used to split the string.

When set to `None` (the default value), will split on any whitespace character (including `\n`, `\r`, `\t` and spaces) and will discard empty strings from the result.

maxsplit

Maximum number of splits (starting from the left). -1 (the default value) means no limit.

Note, `str.split()` is mainly useful for data that has been intentionally delimited. With natural text that includes punctuation, consider using the regular expression module.

splitlines(*keepends*=False)

Return a list of the lines in the string, breaking at line boundaries.

Line breaks are not included in the resulting list unless *keepends* is given and true.

startswith(*prefix*[, *start*[, *end*]]) → bool

Return True if S starts with the specified prefix, False otherwise. With optional start, test S beginning at that position. With optional end, stop comparing S at that position. prefix can also be a tuple of strings to try.

strip(*chars*=None, /)

Return a copy of the string with leading and trailing whitespace removed.

If chars is given and not None, remove characters in chars instead.

swapcase()

Convert uppercase characters to lowercase and lowercase characters to uppercase.

title()

Return a version of the string where each word is titlecased.

More specifically, words start with uppercased characters and all remaining cased characters have lower case.

translate(*table*, /)

Replace each character in the string using the given translation table.

table

Translation table, which must be a mapping of Unicode ordinals to Unicode ordinals, strings, or None.

The table must implement lookup/indexing via `__getitem__`, for instance a dictionary or list. If this operation raises `LookupError`, the character is left untouched. Characters mapped to None are deleted.

upper()

Return a copy of the string converted to uppercase.

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the object into the layer of the context at the current offset.

Return type

ObjectInterface

zfill(*width*, /)

Pad a numeric string with zeros on the left, to fill a field of the given width.

The string is never truncated.

class **StructType**(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: *AggregateType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (str) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class UnionType(*context, type_name, object_info, size, members*)

Bases: *AggregateType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**classmethod** `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**cast**(*new_type_name*, ***additional*)Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters**member_name** (`str`) – Name of the member to test access to determine if the member is valid or not**Return type**`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters**member_names** (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property** **vol:** `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **Void**(*context*, *type_name*, *object_info*, ***kwargs*)Bases: `ObjectInterface`

Returns an object to represent void/unknown types.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**Bases: `VolTemplateProxy`**abstract classmethod** **child_template**(*template*, *child*)

Returns the template of the child member from the parent.

Return type`Template`**abstract classmethod** **children**(*template*)

Returns the children of the template.

Return type`List[Template]`**abstract classmethod** **has_member**(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**abstract classmethod** **relative_child_offset**(*template*, *child*)

Returns the relative offset from the head of the parent data to the child member.

Return type`int`**abstract classmethod** **replace_child**(*template*, *old_child*, *new_child*)

Substitutes the old_child for the new_child.

Return type`None`

classmethod `size(template)`

Dummy size for Void objects.

According to <http://www.open-std.org/jtc1/sc22/wg14/www/docs/n1570.pdf>, void is an incomplete type, and therefore `sizeof(void)` should fail. However, we need to be able to construct voids to be able to cast them, so we return a useless size. It shouldn't cause errors, but it also shouldn't be common, it is logged at the lowest level.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

property `vol: ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Dummy method that does nothing for Void objects.

Return type

`None`

convert_data_to_value(*data*, *struct_type*, *data_format*)

Converts a series of bytes to a particular type of value.

Return type

`Union[int, float, bytes, str, bool]`

convert_value_to_data(*value*, *struct_type*, *data_format*)

Converts a particular value to a series of bytes.

Return type

`bytes`

Submodules

volatility3.framework.objects.templates module

class **ObjectTemplate**(*object_class*, *type_name*, ***arguments*)

Bases: `Template`

Factory class that produces objects that adhere to the Object interface on demand.

This is effectively a method of currying, but adds more structure to avoid abuse. It also allows inspection of information that should already be known:

- Type size
- Members
- etc

Stores the keyword arguments for later object creation.

child_template(*child*)

Returns the template of a child of the templated object (see `VolTemplateProxy`)

Return type

`Template`

property children: `List[Template]`

`~volatility.framework.interfaces.objects.ObjectInterface.VolTemplateProxy)`

Type

Returns the children of the templated object (see

Type

`class`

clone()

Returns a copy of the original Template as constructed (without *update_vol* additions having been made)

Return type

`Template`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

relative_child_offset(*child*)

Returns the relative offset of a child of the templated object (see `VolTemplateProxy`)

Return type

`int`

replace_child(*old_child*, *new_child*)

Replaces *old_child* for *new_child* in the templated object's child list (see `VolTemplateProxy`)

Return type

`None`

property size: `int`

`~volatility.framework.interfaces.objects.ObjectInterface.VolTemplateProxy`

Type

Returns the children of the templated object (see

Type

`class`

update_vol(***new_arguments*)

Updates the keyword arguments with values that will **not** be carried across to clones.

Return type

`None`

property vol: `ReadOnlyMapping`

Returns a volatility information object, much like the `ObjectInformation` provides.

class ReferenceTemplate(*type_name*, ***arguments*)

Bases: `Template`

Factory class that produces objects based on a delayed reference type.

Attempts to access any standard attributes of a resolved template will result in a `SymbolError`.

Stores the keyword arguments for later object creation.

child_template(**args*, ***kwargs*)

Referenced symbols must be appropriately resolved before they can provide information such as size This is because the size request has no context within which to determine the actual symbol structure.

Return type

`Any`

property children: `List[Template]`

The children of this template (such as member types, sub-types and base-types where they are relevant).

Used to traverse the template tree.

clone()

Returns a copy of the original Template as constructed (without *update_vol* additions having been made)

Return type

`Template`

has_member(*args, **kwargs)

Referenced symbols must be appropriately resolved before they can provide information such as size This is because the size request has no context within which to determine the actual symbol structure.

Return type

Any

relative_child_offset(*args, **kwargs)

Referenced symbols must be appropriately resolved before they can provide information such as size This is because the size request has no context within which to determine the actual symbol structure.

Return type

Any

replace_child(*args, **kwargs)

Referenced symbols must be appropriately resolved before they can provide information such as size This is because the size request has no context within which to determine the actual symbol structure.

Return type

Any

property size: *Any*

Referenced symbols must be appropriately resolved before they can provide information such as size This is because the size request has no context within which to determine the actual symbol structure.

update_vol(**new_arguments)

Updates the keyword arguments with values that will **not** be carried across to clones.

Return type

None

property vol: *ReadOnlyMapping*

Returns a volatility information object, much like the *ObjectInformation* provides.

volatility3.framework.objects.utility module

array_of_pointers(array, count, subtype, context)

Takes an object, and recasts it as an array of pointers to subtype.

Return type

ObjectInterface

array_to_string(array, count=None, errors='replace')

Takes a volatility Array of characters and returns a string.

Return type

ObjectInterface

pointer_to_string(pointer, count, errors='replace')

Takes a volatility Pointer to characters and returns a string.

volatility3.framework.plugins package

All core generic plugins.

These modules should only be imported from volatility3.plugins NOT volatility3.framework.plugins

construct_plugin(*context, automagics, plugin, base_config_path, progress_callback, open_method*)

Constructs a plugin object based on the parameters.

Clever magic figures out how to fulfill each requirement that might not be fulfilled

Parameters

- **context** (*ContextInterface*) – The volatility context to operate on
- **automagics** (*List[AutomagicInterface]*) – A list of automagic modules to run to augment the context
- **plugin** (*Type[PluginInterface]*) – The plugin to run
- **base_config_path** (*str*) – The path within the context’s config containing the plugin’s configuration
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – Callback function to provide feedback for ongoing processes
- **open_method** (*Type[FileHandlerInterface]*) – class to provide context manager for opening the file

Return type

PluginInterface

Returns

The constructed plugin object

Subpackages

Submodules

volatility3.framework.renderers package

Renderers.

Renderers display the unified output format in some manner (be it text or file or graphical output

class ColumnSortKey(*treegrid, column_name, ascending=True*)

Bases: *ColumnSortKey*

ascending: *bool* = *True*

class NotApplicableValue

Bases: *BaseAbsentValue*

Class that represents values which are empty because they don’t make sense for this node.

class NotAvailableValue

Bases: *BaseAbsentValue*

Class that represents values which cannot be provided now (but might in a future run)

This might occur when information packed with volatility (such as symbol information) is not available, but a future version or a different run may later have that information available (ie, it could be applicable, but we can't get it and it's not because it's unreadable or unparsable). Unreadable and Unparsable should be used in preference, and only if neither fits should this be used.

RowStructureConstructor(*names*)

class TreeGrid(*columns*, *generator*)

Bases: *TreeGrid*

Class providing the interface for a TreeGrid (which contains TreeNodes)

The structure of a TreeGrid is designed to maintain the structure of the tree in a single object. For this reason each TreeNode does not hold its children, they are managed by the top level object. This leaves the Nodes as simple data carries and prevents them being used to manipulate the tree as a whole. This is a data structure, and is not expected to be modified much once created.

Carrying the children under the parent makes recursion easier, but then every node is its own little tree and must have all the supporting tree functions. It also allows for a node to be present in several different trees, and to create cycles.

Constructs a TreeGrid object using a specific set of columns.

The TreeGrid itself is a root element, that can have children but no values. The TreeGrid does *not* contain any information about formatting, these are up to the renderers and plugins.

Parameters

- **columns** (`List[Tuple[str, Union[Type[int], Type[str], Type[float], Type[bytes], Type[datetime], Type[BaseAbsentValue], Type[Disassembly]]]]`) – A list of column tuples made up of (name, type).
- **generator** (`Optional[Iterable[Tuple[int, Tuple]]]`) – An iterable containing row for a tree grid, each row contains a indent level followed by the values for each column in order.

base_types: `ClassVar[Tuple] = (<class 'int'>, <class 'str'>, <class 'float'>, <class 'bytes'>, <class 'datetime.datetime'>, <class 'volatility3.framework.interfaces.renderers.Disassembly'>)`

children(*node*)

Returns the subnodes of a particular node in order.

Return type

`List[TreeNode]`

property columns: `List[Column]`

Returns the available columns and their ordering and types.

is_ancestor(*node*, *descendant*)

Returns true if descendent is a child, grandchild, etc of node.

max_depth()

Returns the maximum depth of the tree.

static path_depth(*node*)

Returns the path depth of a particular node.

Return type

`int`

path_sep = '|'

populate(*function=None, initial_accumulator=None, fail_on_errors=True*)

Populates the tree by consuming the TreeGrid's construction generator. `Func` is called on every node, so can be used to create output on demand.

This is equivalent to a one-time visit.

Parameters

- **function** (`Callable[[TreeNode, TypeVar(_Type)], TypeVar(_Type)`]) – The visitor to be called on each row of the treegrid
- **initial_accumulator** (`Any`) – The initial value for an accumulator passed to the visitor to allow it to maintain state
- **fail_on_errors** (`bool`) – A boolean defining whether exceptions should be caught or bubble up

Return type

`Optional[Exception]`

property populated: `bool`

Indicates that population has completed and the tree may now be manipulated separately.

property row_count: `int`

Returns the number of rows populated.

static sanitize_name(*text*)

Method used to sanitize column names for `TreeNodes`.

Return type

`str`

values(*node*)

Returns the values for a particular node.

The values returned are mutable,

visit(*node, function, initial_accumulator, sort_key=None*)

Visits all the nodes in a tree, calling `function` on each one.

`function` should have the signature `function(node, accumulator)` and return `new_accumulator`. If accumulators are not needed, the function must still accept a second parameter.

The order of that the nodes are visited is always depth first, however, the order children are traversed can be set based on a `sort_key` function which should accept a node's values and return something that can be sorted to receive the desired order (similar to the `sort/sorted` key).

We use the private `_find_children` function so that we don't have to re-traverse the tree for every node we descend further down

class `TreeNode`(*path, treegrid, parent, values*)

Bases: `TreeNode`

Class representing a particular node in a tree grid.

Initializes the `TreeNode`.

asdict()

Returns the contents of the node as a dictionary

Return type

`Dict[str, Any]`

count(*value*) → integer -- return number of occurrences of value

index(*value*[, *start*[, *stop*]]) → integer -- return first index of value.

Raises ValueError if the value is not present.

Supporting start and stop arguments is optional, but recommended.

property parent: `TreeNode` | `None`

Returns the parent node of this node or None.

property path: `str`

Returns a path identifying string.

This should be seen as opaque by external classes, Parsing of path locations based on this string are not guaranteed to remain stable.

path_changed(*path*, *added=False*)

Updates the path based on the addition or removal of a node higher up in the tree.

This should only be called by the containing TreeGrid and expects to only be called for affected nodes.

Return type

`None`

property path_depth: `int`

Return the path depth of the current node.

property values: `List[Type[int] | Type[str] | Type[float] | Type[bytes] | Type[datetime] | Type[BaseAbsentValue] | Type[Disassembly]]`

Returns the list of values from the particular node, based on column index.

class UnparsableValue

Bases: `BaseAbsentValue`

Class that represents values which are empty because the data cannot be interpreted correctly.

class UnreadableValue

Bases: `BaseAbsentValue`

Class that represents values which are empty because the data cannot be read.

Submodules

volatility3.framework.renderers.conversion module

convert_ipv4(*ip_as_integer*)

convert_ipv6(*packed_ip*)

convert_network_four_tuple(*family*, *four_tuple*)

Converts the connection four_tuple: (source ip, source port, dest ip, dest port)

into their string equivalents. IP addresses are expected as a tuple of unsigned shorts Ports are converted to proper endianness as well

convert_port(*port_as_integer*)

round(*addr*, *align*, *up=False*)

Round an address up or down based on an alignment.

Parameters

- **addr** (`int`) – the address
- **align** (`int`) – the alignment value
- **up** (`bool`) – Whether to round up or not

Return type

`int`

Returns

The aligned address

unixtime_to_datetime(*unixtime*)

Return type

`Union[BaseAbsentValue, datetime]`

wintime_to_datetime(*wintime*)

Return type

`Union[BaseAbsentValue, datetime]`

volatility3.framework.renderers.format_hints module

The official list of format hints that text renderers and plugins can rely upon existing within the framework.

These hints allow a plugin to indicate how they would like data from a particular column to be represented.

Text renderers should attempt to honour all hints provided in this module where possible

class Bin

Bases: `int`

A class to indicate that the integer value should be represented as a binary value.

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(*byteorder='big', *, signed=False*)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an OverflowError is raised.

class Hex

Bases: `int`

A class to indicate that the integer value should be represented as a hexadecimal value.

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(*byteorder*='big', *, *signed*=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If `byteorder` is 'big', the most significant byte is at the beginning of the byte array. If `byteorder` is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `'sys.byteorder'` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If `signed` is `False` and a negative integer is given, an `OverflowError` is raised.

class HexBytes

Bases: `bytes`

A class to indicate that the bytes should be display in an extended format showing hexadecimal and ascii printable display.

capitalize() → copy of B

Return a copy of B with only its first character capitalized (ASCII) and the rest lower-cased.

center(*width, fillchar=b' ', /*)

Return a centered string of length width.

Padding is done using the specified fill character.

count(*sub[, start[, end]]*) → int

Return the number of non-overlapping occurrences of subsection sub in bytes B[start:end]. Optional arguments start and end are interpreted as in slice notation.

decode(*encoding='utf-8', errors='strict'*)

Decode the bytes using the codec registered for encoding.

encoding

The encoding with which to decode the bytes.

errors

The error handling scheme to use for the handling of decoding errors. The default is 'strict' meaning that decoding errors raise a `UnicodeDecodeError`. Other possible values are 'ignore' and 'replace' as well as any other name registered with `codecs.register_error` that can handle `UnicodeDecodeErrors`.

endswith(*suffix*[, *start*[, *end*]]) → bool

Return True if B ends with the specified suffix, False otherwise. With optional start, test B beginning at that position. With optional end, stop comparing B at that position. *suffix* can also be a tuple of bytes to try.

expandtabs(*tabsize*=8)

Return a copy where all tab characters are expanded using spaces.

If *tabsize* is not given, a tab size of 8 characters is assumed.

find(*sub*[, *start*[, *end*]]) → int

Return the lowest index in B where subsection *sub* is found, such that *sub* is contained within B[start,end]. Optional arguments *start* and *end* are interpreted as in slice notation.

Return -1 on failure.

fromhex()

Create a bytes object from a string of hexadecimal numbers.

Spaces between two numbers are accepted. Example: `bytes.fromhex('B9 01EF') -> b'\xb9\x01\xef'`.

hex()

Create a string of hexadecimal numbers from a bytes object.

sep

An optional single character or byte to separate hex bytes.

bytes_per_sep

How many bytes between separators. Positive values count from the right, negative values count from the left.

Example: `>>> value = b'\xb9\x01\xef' >>> value.hex() 'b901ef' >>> value.hex(':') 'b9:01:ef' >>> value.hex(':', 2) 'b9:01ef' >>> value.hex(':', -2) 'b901:ef'`

index(*sub*[, *start*[, *end*]]) → int

Return the lowest index in B where subsection *sub* is found, such that *sub* is contained within B[start,end]. Optional arguments *start* and *end* are interpreted as in slice notation.

Raises `ValueError` when the subsection is not found.

isalnum() → bool

Return True if all characters in B are alphanumeric and there is at least one character in B, False otherwise.

isalpha() → bool

Return True if all characters in B are alphabetic and there is at least one character in B, False otherwise.

isascii() → bool

Return True if B is empty or all characters in B are ASCII, False otherwise.

isdigit() → bool

Return True if all characters in B are digits and there is at least one character in B, False otherwise.

islower() → bool

Return True if all cased characters in B are lowercase and there is at least one cased character in B, False otherwise.

isspace() → bool

Return True if all characters in B are whitespace and there is at least one character in B, False otherwise.

istitle() → bool

Return True if B is a titlecased string and there is at least one character in B, i.e. uppercase characters may only follow uncased characters and lowercase characters only cased ones. Return False otherwise.

isupper() → bool

Return True if all cased characters in B are uppercase and there is at least one cased character in B, False otherwise.

join(iterable_of_bytes, /)

Concatenate any number of bytes objects.

The bytes whose method is called is inserted in between each pair.

The result is returned as a new bytes object.

Example: `b'.'.join([b'ab', b'pq', b'rs']) -> b'ab.pq.rs'`.

ljust(width, fillchar=b' ', /)

Return a left-justified string of length width.

Padding is done using the specified fill character.

lower() → copy of B

Return a copy of B with all ASCII characters converted to lowercase.

lstrip(bytes=None, /)

Strip leading bytes contained in the argument.

If the argument is omitted or None, strip leading ASCII whitespace.

static maketrans(frm, to, /)

Return a translation table useable for the bytes or bytearray translate method.

The returned table will be one where each byte in frm is mapped to the byte at the same position in to.

The bytes objects frm and to must be of the same length.

partition(sep, /)

Partition the bytes into three parts using the given separator.

This will search for the separator sep in the bytes. If the separator is found, returns a 3-tuple containing the part before the separator, the separator itself, and the part after it.

If the separator is not found, returns a 3-tuple containing the original bytes object and two empty bytes objects.

removeprefix(prefix, /)

Return a bytes object with the given prefix string removed if present.

If the bytes starts with the prefix string, return `bytes[len(prefix):]`. Otherwise, return a copy of the original bytes.

removesuffix(suffix, /)

Return a bytes object with the given suffix string removed if present.

If the bytes ends with the suffix string and that suffix is not empty, return `bytes[:-len(suffix)]`. Otherwise, return a copy of the original bytes.

replace(old, new, count=-1, /)

Return a copy with all occurrences of substring old replaced by new.

count

Maximum number of occurrences to replace. -1 (the default value) means replace all occurrences.

If the optional argument count is given, only the first count occurrences are replaced.

rfind(*sub*[, *start*[, *end*]]) → int

Return the highest index in B where subsection sub is found, such that sub is contained within B[start,end]. Optional arguments start and end are interpreted as in slice notation.

Return -1 on failure.

rindex(*sub*[, *start*[, *end*]]) → int

Return the highest index in B where subsection sub is found, such that sub is contained within B[start,end]. Optional arguments start and end are interpreted as in slice notation.

Raise ValueError when the subsection is not found.

rjust(*width*, *fillchar*=b' ', /)

Return a right-justified string of length width.

Padding is done using the specified fill character.

rpartition(*sep*, /)

Partition the bytes into three parts using the given separator.

This will search for the separator sep in the bytes, starting at the end. If the separator is found, returns a 3-tuple containing the part before the separator, the separator itself, and the part after it.

If the separator is not found, returns a 3-tuple containing two empty bytes objects and the original bytes object.

rsplit(*sep*=None, *maxsplit*=-1)

Return a list of the sections in the bytes, using sep as the delimiter.

sep

The delimiter according which to split the bytes. None (the default value) means split on ASCII whitespace characters (space, tab, return, newline, formfeed, vertical tab).

maxsplit

Maximum number of splits to do. -1 (the default value) means no limit.

Splitting is done starting at the end of the bytes and working to the front.

rstrip(*bytes*=None, /)

Strip trailing bytes contained in the argument.

If the argument is omitted or None, strip trailing ASCII whitespace.

split(*sep*=None, *maxsplit*=-1)

Return a list of the sections in the bytes, using sep as the delimiter.

sep

The delimiter according which to split the bytes. None (the default value) means split on ASCII whitespace characters (space, tab, return, newline, formfeed, vertical tab).

maxsplit

Maximum number of splits to do. -1 (the default value) means no limit.

splitlines(*keepends*=False)

Return a list of the lines in the bytes, breaking at line boundaries.

Line breaks are not included in the resulting list unless keepends is given and true.

startswith(*prefix*[, *start*[, *end*]]) → bool

Return True if B starts with the specified prefix, False otherwise. With optional start, test B beginning at that position. With optional end, stop comparing B at that position. *prefix* can also be a tuple of bytes to try.

strip(*bytes=None*, /)

Strip leading and trailing bytes contained in the argument.

If the argument is omitted or None, strip leading and trailing ASCII whitespace.

swapcase() → copy of B

Return a copy of B with uppercase ASCII characters converted to lowercase ASCII and vice versa.

title() → copy of B

Return a titlecased version of B, i.e. ASCII words start with uppercase characters, all remaining cased characters have lowercase.

translate(*table*, /, *delete=b''*)

Return a copy with each character mapped by the given translation table.

table

Translation table, which must be a bytes object of length 256.

All characters occurring in the optional argument *delete* are removed. The remaining characters are mapped through the given translation table.

upper() → copy of B

Return a copy of B with all ASCII characters converted to uppercase.

zfill(*width*, /)

Pad a numeric string with zeros on the left, to fill a field of the given width.

The original string is never truncated.

class MultiTypeData(*original*, *encoding='utf-16-le'*, *split_nulls=False*, *show_hex=False*)

Bases: `bytes`

The contents are supposed to be a string, but may contain binary data.

capitalize() → copy of B

Return a copy of B with only its first character capitalized (ASCII) and the rest lower-cased.

center(*width*, *fillchar=b' '*, /)

Return a centered string of length *width*.

Padding is done using the specified fill character.

count(*sub*[, *start*[, *end*]]) → int

Return the number of non-overlapping occurrences of subsection *sub* in bytes B[start:end]. Optional arguments *start* and *end* are interpreted as in slice notation.

decode(*encoding='utf-8'*, *errors='strict'*)

Decode the bytes using the codec registered for encoding.

encoding

The encoding with which to decode the bytes.

errors

The error handling scheme to use for the handling of decoding errors. The default is 'strict' meaning that decoding errors raise a `UnicodeDecodeError`. Other possible values are 'ignore' and 'replace' as well as any other name registered with `codecs.register_error` that can handle `UnicodeDecodeErrors`.

endswith(*suffix*[, *start*[, *end*]]) → bool

Return True if B ends with the specified suffix, False otherwise. With optional start, test B beginning at that position. With optional end, stop comparing B at that position. *suffix* can also be a tuple of bytes to try.

expandtabs(*tabsize*=8)

Return a copy where all tab characters are expanded using spaces.

If *tabsize* is not given, a tab size of 8 characters is assumed.

find(*sub*[, *start*[, *end*]]) → int

Return the lowest index in B where subsection *sub* is found, such that *sub* is contained within B[start,end]. Optional arguments *start* and *end* are interpreted as in slice notation.

Return -1 on failure.

fromhex()

Create a bytes object from a string of hexadecimal numbers.

Spaces between two numbers are accepted. Example: `bytes.fromhex('B9 01EF') -> b'\xb9\x01\xef'`.

hex()

Create a string of hexadecimal numbers from a bytes object.

sep

An optional single character or byte to separate hex bytes.

bytes_per_sep

How many bytes between separators. Positive values count from the right, negative values count from the left.

Example: `>>> value = b'\xb9\x01\xef' >>> value.hex() 'b901ef' >>> value.hex(':') 'b9:01:ef' >>> value.hex(':', 2) 'b9:01ef' >>> value.hex(':', -2) 'b901:ef'`

index(*sub*[, *start*[, *end*]]) → int

Return the lowest index in B where subsection *sub* is found, such that *sub* is contained within B[start,end]. Optional arguments *start* and *end* are interpreted as in slice notation.

Raises `ValueError` when the subsection is not found.

isalnum() → bool

Return True if all characters in B are alphanumeric and there is at least one character in B, False otherwise.

isalpha() → bool

Return True if all characters in B are alphabetic and there is at least one character in B, False otherwise.

isascii() → bool

Return True if B is empty or all characters in B are ASCII, False otherwise.

isdigit() → bool

Return True if all characters in B are digits and there is at least one character in B, False otherwise.

islower() → bool

Return True if all cased characters in B are lowercase and there is at least one cased character in B, False otherwise.

isspace() → bool

Return True if all characters in B are whitespace and there is at least one character in B, False otherwise.

istitle() → bool

Return True if B is a titlecased string and there is at least one character in B, i.e. uppercase characters may only follow uncased characters and lowercase characters only cased ones. Return False otherwise.

isupper() → bool

Return True if all cased characters in B are uppercase and there is at least one cased character in B, False otherwise.

join(*iterable_of_bytes*, /)

Concatenate any number of bytes objects.

The bytes whose method is called is inserted in between each pair.

The result is returned as a new bytes object.

Example: `b'.'.join([b'ab', b'pq', b'rs']) -> b'ab.pq.rs'`.

ljust(*width*, *fillchar=b' '*, /)

Return a left-justified string of length width.

Padding is done using the specified fill character.

lower() → copy of B

Return a copy of B with all ASCII characters converted to lowercase.

lstrip(*bytes=None*, /)

Strip leading bytes contained in the argument.

If the argument is omitted or None, strip leading ASCII whitespace.

static maketrans(*frm*, *to*, /)

Return a translation table useable for the bytes or bytearray translate method.

The returned table will be one where each byte in frm is mapped to the byte at the same position in to.

The bytes objects frm and to must be of the same length.

partition(*sep*, /)

Partition the bytes into three parts using the given separator.

This will search for the separator sep in the bytes. If the separator is found, returns a 3-tuple containing the part before the separator, the separator itself, and the part after it.

If the separator is not found, returns a 3-tuple containing the original bytes object and two empty bytes objects.

removeprefix(*prefix*, /)

Return a bytes object with the given prefix string removed if present.

If the bytes starts with the prefix string, return bytes[len(prefix):]. Otherwise, return a copy of the original bytes.

removesuffix(*suffix*, /)

Return a bytes object with the given suffix string removed if present.

If the bytes ends with the suffix string and that suffix is not empty, return bytes[:-len(suffix)]. Otherwise, return a copy of the original bytes.

replace(*old*, *new*, *count=-1*, /)

Return a copy with all occurrences of substring old replaced by new.

count

Maximum number of occurrences to replace. -1 (the default value) means replace all occurrences.

If the optional argument count is given, only the first count occurrences are replaced.

rfind(*sub*[, *start*[, *end*]]) → int

Return the highest index in B where subsection sub is found, such that sub is contained within B[start,end]. Optional arguments start and end are interpreted as in slice notation.

Return -1 on failure.

rindex(*sub*[, *start*[, *end*]]) → int

Return the highest index in B where subsection sub is found, such that sub is contained within B[start,end]. Optional arguments start and end are interpreted as in slice notation.

Raise ValueError when the subsection is not found.

rjust(*width*, *fillchar*=b' ', /)

Return a right-justified string of length width.

Padding is done using the specified fill character.

rpartition(*sep*, /)

Partition the bytes into three parts using the given separator.

This will search for the separator sep in the bytes, starting at the end. If the separator is found, returns a 3-tuple containing the part before the separator, the separator itself, and the part after it.

If the separator is not found, returns a 3-tuple containing two empty bytes objects and the original bytes object.

rsplit(*sep*=None, *maxsplit*=-1)

Return a list of the sections in the bytes, using sep as the delimiter.

sep

The delimiter according which to split the bytes. None (the default value) means split on ASCII whitespace characters (space, tab, return, newline, formfeed, vertical tab).

maxsplit

Maximum number of splits to do. -1 (the default value) means no limit.

Splitting is done starting at the end of the bytes and working to the front.

rstrip(*bytes*=None, /)

Strip trailing bytes contained in the argument.

If the argument is omitted or None, strip trailing ASCII whitespace.

split(*sep*=None, *maxsplit*=-1)

Return a list of the sections in the bytes, using sep as the delimiter.

sep

The delimiter according which to split the bytes. None (the default value) means split on ASCII whitespace characters (space, tab, return, newline, formfeed, vertical tab).

maxsplit

Maximum number of splits to do. -1 (the default value) means no limit.

splitlines(*keepends*=False)

Return a list of the lines in the bytes, breaking at line boundaries.

Line breaks are not included in the resulting list unless keepends is given and true.

startswith(*prefix*[, *start*[, *end*]]) → bool

Return True if B starts with the specified prefix, False otherwise. With optional start, test B beginning at that position. With optional end, stop comparing B at that position. *prefix* can also be a tuple of bytes to try.

strip(*bytes=None*, /)

Strip leading and trailing bytes contained in the argument.

If the argument is omitted or None, strip leading and trailing ASCII whitespace.

swapcase() → copy of B

Return a copy of B with uppercase ASCII characters converted to lowercase ASCII and vice versa.

title() → copy of B

Return a titlecased version of B, i.e. ASCII words start with uppercase characters, all remaining cased characters have lowercase.

translate(*table*, /, *delete=b''*)

Return a copy with each character mapped by the given translation table.

table

Translation table, which must be a bytes object of length 256.

All characters occurring in the optional argument *delete* are removed. The remaining characters are mapped through the given translation table.

upper() → copy of B

Return a copy of B with all ASCII characters converted to uppercase.

zfill(*width*, /)

Pad a numeric string with zeros on the left, to fill a field of the given width.

The original string is never truncated.

volatility3.framework.symbols package

class SymbolSpace

Bases: *SymbolSpaceInterface*

Handles an ordered collection of SymbolTables.

This collection is ordered so that resolution of symbols can proceed down through the ranks if a namespace isn't specified.

class UnresolvedTemplate(*type_name*, ***kwargs*)

Bases: *ReferenceTemplate*

Class to highlight when missing symbols are present.

This class is identical to a reference template, but differentiable by its classname. It will output a debug log to indicate when it has been instantiated and with what name.

This class is designed to be output ONLY as part of the SymbolSpace resolution system. Individual SymbolTables that cannot resolve a symbol should still return a SymbolError to indicate this failure in resolution.

Stores the keyword arguments for later object creation.

child_template(*args, **kwargs)

Referenced symbols must be appropriately resolved before they can provide information such as size
This is because the size request has no context within which to determine the actual symbol structure.

Return type

Any

property children: *List[Template]*

The children of this template (such as member types, sub-types and base-types where they are relevant).

Used to traverse the template tree.

clone()

Returns a copy of the original Template as constructed (without *update_vol* additions having been made)

Return type

Template

has_member(*args, **kwargs)

Referenced symbols must be appropriately resolved before they can provide information such as size
This is because the size request has no context within which to determine the actual symbol structure.

Return type

Any

relative_child_offset(*args, **kwargs)

Referenced symbols must be appropriately resolved before they can provide information such as size
This is because the size request has no context within which to determine the actual symbol structure.

Return type

Any

replace_child(*args, **kwargs)

Referenced symbols must be appropriately resolved before they can provide information such as size
This is because the size request has no context within which to determine the actual symbol structure.

Return type

Any

property size: *Any*

Referenced symbols must be appropriately resolved before they can provide information such as size
This is because the size request has no context within which to determine the actual symbol structure.

update_vol(**new_arguments)

Updates the keyword arguments with values that will **not** be carried across to clones.

Return type

None

property vol: *ReadOnlyMapping*

Returns a volatility information object, much like the *ObjectInformation* provides.

append(value)

Adds a symbol_list to the end of the space.

Return type

None

clear_symbol_cache(table_name=None)

Clears the symbol cache for the specified table name. If no table name is specified, the caches of all symbol tables are cleared.

Return type`None`**free_table_name**(*prefix='layer'*)

Returns an unused table name to ensure no collision occurs when inserting a symbol table.

Return type`str`**get**(*k*, *d*) → *D*[*k*] if *k* in *D*, else *d*. *d* defaults to `None`.**get_enumeration**(*enum_name*)

Look-up a set of enumeration choices from a specific symbol table.

Return type`Template`**get_symbol**(*symbol_name*)

Look-up a symbol name across all the contained symbol spaces.

Return type`SymbolInterface`**get_symbols_by_location**(*offset*, *size=0*, *table_name=None*)

Returns all symbols that exist at a specific relative address.

Return type`Iterable[str]`**get_symbols_by_type**(*type_name*)

Returns all symbols based on the type of the symbol.

Return type`Iterable[str]`**get_type**(*type_name*)

Takes a symbol name and resolves it.

This method ensures that all referenced templates (including self-referential templates) are satisfied as `ObjectTemplates`

Return type`Template`**has_enumeration**(*name*)

Determines whether an enumeration choice exists in the contained symbol tables.

Return type`bool`**has_symbol**(*name*)

Determines whether a symbol exists in the contained symbol tables.

Return type`bool`**has_type**(*name*)

Determines whether a type exists in the contained symbol tables.

Return type`bool`

items() → a set-like object providing a view on D's items

keys() → a set-like object providing a view on D's keys

remove(*key*)

Removes a named `symbol_list` from the space.

Return type

`None`

values() → an object providing a view on D's values

verify_table_versions(*producer, validator, tables=None*)

Verifies the producer metadata and version of tables

Parameters

- **producer** (`str`) – String name of a table producer to have validation performed
- **validator** (`Callable[[Optional[Tuple], Optional[datetime], bool]`) – callable that takes an optional version and an optional datetime that returns False if table is invalid

Return type

`bool`

Returns

False if an invalid table was found or True if no invalid table was found

class SymbolType(*value, names=None, *, module=None, qualname=None, type=None, start=1, boundary=None*)

Bases: `Enum`

ENUM = 3

SYMBOL = 2

TYPE = 1

symbol_table_is_64bit(*context, symbol_table_name*)

Returns a boolean as to whether a particular symbol table within a context is 64-bit or not.

Return type

`bool`

Subpackages

volatility3.framework.symbols.generic package

class GenericIntelProcess(*context, type_name, object_info, size, members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: *VolTemplateProxy***classmethod child_template**(*template, child*)

Returns the template of a child to its parent.

Return type*Template***classmethod children**(*template*)

Method to list children of a template.

Return type*List[Template]***classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool***classmethod relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type*int***classmethod replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type*None***classmethod size**(*template*)

Method to return the size of this type.

Return type*int***cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type*str***has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool*

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.linux package

class LinuxKernelIntermedSymbols(**args, **kwargs*)

Bases: *IntermediateSymbolTable*

Instantiates a SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema. The validation can be disabled by passing validate = False, but this should almost never be done.

Parameters

- **context** – The volatility context for the symbol table
- **config_path** – The configuration path for the symbol table
- **name** – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** – A dictionary linking names referenced in the file with symbol tables in the context
- **validate** – Determines whether the ISF file will be validated against the appropriate schema
- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated
- **symbol_mask** – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache(*args, **kwargs)

Clears the symbol cache of this symbol table.

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod create(context, config_path, sub_path, filename, native_types=None, table_mapping=None, class_types=None, symbol_mask=0)

Takes a context and loads an intermediate symbol table based on a filename.

Parameters

- **context** (*ContextInterface*) – The context that the current plugin is being run within
- **config_path** (*str*) – The configuration path for reading/storing configuration information this symbol table may use
- **sub_path** (*str*) – The path under a suitable symbol path (defaults to volatility3/symbols and volatility3/framework/symbols) to check
- **filename** (*str*) – Basename of the file to find under the sub_path
- **native_types** (*Optional[NativeTableInterface]*) – Set of native types, defaults to native types read from the intermediate symbol format file
- **table_mapping** (*Optional[Dict[str, str]]*) – a dictionary of table names mentioned within the ISF file, and the tables within the context which they map to
- **symbol_mask** (*int*) – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

Return type

str

Returns

the name of the added symbol table

del_type_class(*args, **kwargs)

Removes the associated class override for a specific Symbol type.

property enumerations

Returns an iterator of the Enumeration names.

classmethod `file_symbol_url(sub_path, filename=None)`

Returns an iterator of appropriate file-scheme symbol URLs that can be opened by a ResourceAccessor class.

Filter reduces the number of results returned to only those URLs containing that string

Return type

`Generator[str, None, None]`

get_enumeration(*args, **kwargs)

classmethod `get_requirements()`

Returns a list of RequirementInterface objects required by this object.

Return type

`List[RequirementInterface]`

get_symbol(*args, **kwargs)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(offset, size=0)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(type_name)

Returns the name of all symbols in this table that have type matching type_name.

Return type

`Iterable[str]`

get_type(*args, **kwargs)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a SymbolError exception

get_type_class(*args, **kwargs)

Returns the class associated with a Symbol type.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property metadata****property natives:** `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type`bool`**property producer**

`provides = {'type': 'interface'}`

set_type_class(*args, **kwargs)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`

Parameters

- **name** – The name of the type to override the class for
- **clazz** – The actual class to override for the provided type name

property symbols

Returns an iterator of the Symbol names.

property types

Returns an iterator of the Symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]`**class LinuxUtilities**(*args, **kwargs)

Bases: `VersionableInterface`

Class with multiple useful linux functions.

classmethod container_of(*addr*, *type_name*, *member_name*, *vmlinux*)

Cast a member of a structure out to the containing structure. It mimicks the Linux kernel macro `container_of()` see `include/linux/kernel.h`

Parameters

- **addr** (`int`) – The pointer to the member.

- **type_name** (*str*) – The type of the container struct this is embedded in.
- **member_name** (*str*) – The name of the member within the struct.
- **vmlinux** (*ModuleInterface*) – The kernel symbols object

Return type*Optional[ObjectInterface]***Returns**

The constructed object or None

classmethod **do_get_path**(*rdentry, rmnt, dentry, vfmnt*)Returns a pathname of the mount point or file. It mimics the Linux kernel `prepend_path` function.**Parameters**

- **rdentry** (*dentry **) – A pointer to the root dentry
- **rmnt** (*vfsmount **) – A pointer to the root vfsmount
- **dentry** (*dentry **) – A pointer to the dentry
- **vfmnt** (*vfsmount **) – A pointer to the vfsmount

Returns

Pathname of the mount point or file

Return type*str***classmethod** **files_descriptors_for_process**(*context, symbol_table, task*)**classmethod** **generate_kernel_handler_info**(*context, kernel_module_name, mods_list*)

A helper function that gets the beginning and end address of the kernel module

Return type*List[Tuple[str, int, int]]***classmethod** **get_module_from_volobj_type**(*context, volobj*)

Get the vmlinux from a vol obj

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **volobj** (*vol object*) – A vol object

Raises**ValueError** – If it cannot obtain any module from the symbol table**Return type***ModuleInterface***Returns**

A kernel object (vmlinux)

classmethod **get_path_mnt**(*task, mnt*)

Returns the mount point pathname relative to the task's root directory.

Parameters

- **task** (*task_struct*) – A reference task

- **mnt** (*vfsmount* or *mount*) – A mounted filesystem or a mount point. - kernels < 3.3.8 type is ‘vfsmount’ - kernels >= 3.3.8 type is ‘mount’

Returns

Pathname of the mount point relative to the task’s root directory.

Return type

str

classmethod **lookup_module_address**(*kernel_module, handlers, target_address*)

Searches between the start and end address of the kernel module using *target_address*. Returns the module and symbol name of the address provided.

classmethod **mask_mods_list**(*context, layer_name, mods*)

A helper function to mask the starting and end address of kernel modules

Return type

List[Tuple[str, int, int]]

classmethod **path_for_file**(*context, task, filp*)

Returns a file (or sock pipe) pathname relative to the task’s root directory.

A ‘file’ structure doesn’t have enough information to properly restore its full path we need the root mount information from *task_struct* to determine this

Parameters

- **context** – The context to retrieve required elements (layers, symbol tables) from
- **task** (*task_struct*) – A reference task
- **filp** (*file **) – A pointer to an open file

Returns

A file (or sock pipe) pathname relative to the task’s root directory.

Return type

str

version = (2, 1, 0)

classmethod **walk_internal_list**(*vmlinux, struct_name, list_member, list_start*)

Subpackages

volatility3.framework.symbols.linux.extensions package

class **bpf_prog**(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

get_type()

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class bt_sock(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**classmethod** `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**cast**(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_protocol()**get_state()****get_symbol_table_name()**

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class cred(*context, type_name, object_info, size, members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: `VolTemplateProxy`

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod children(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

property `euid`

Returns the effective user ID

Returns

the effective user ID value

Return type

`int`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type`object`**property** `vol: ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `dentry(context, type_name, object_info, size, members)`Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`Bases: `VolTemplateProxy`**classmethod** `child_template(template, child)`

Returns the template of a child to its parent.

Return type`Template`**classmethod** `children(template)`

Method to list children of a template.

Return type`List[Template]`**classmethod** `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type`bool`**classmethod** `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**cast**(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

d_ancestor(*ancestor_dentry*)

Search for an ancestor

Returns the ancestor dentry which is a child of “ancestor_dentry”, if “ancestor_dentry” is an ancestor of “child_dentry”, else None.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_root()

Return type

`bool`

is_subdir(*old_dentry*)

Is this dentry a subdirectory of old_dentry?

Returns true if this dentry is a subdirectory of the parent (at any depth). Otherwise, it returns false.

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

path()

Based on `__dentry_path` Linux kernel function

Return type

`str`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class files_struct(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod size(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_fds()

Return type
ObjectInterface

get_max_fds()

Return type
ObjectInterface

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type
str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type
bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters
member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type
bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters
member_names (*List[str]*) – List of names to test as to members with those names validity

Return type
bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type
object

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class fs_struct(*context, type_name, object_info, size, members*)

Bases: [*StructType*](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [*VolTemplateProxy*](#)

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

[*Template*](#)

classmethod children(*template*)

Method to list children of a template.

Return type

[*List\[Template\]*](#)

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

[*bool*](#)

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

[*int*](#)

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

[*None*](#)

classmethod size(*template*)

Method to return the size of this type.

Return type

[*int*](#)

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

[*ObjectInterface*](#)

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_root_dentry()

get_root_mnt()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class inet_sock(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object

- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template*, *child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_dst_addr()

get_dst_port()

get_family()

get_protocol()

get_src_addr()

get_src_port()

get_state()

Return a string representing the sock state.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(attr='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class kernel_cap_struct(context, type_name, object_info, size, members)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: *VolTemplateProxy***classmethod child_template**(*template, child*)

Returns the template of a child to its parent.

Return type*Template***classmethod children**(*template*)

Method to list children of a template.

Return type*List[Template]***classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool***classmethod relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type*int***classmethod replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type*None***classmethod size**(*template*)

Method to return the size of this type.

Return type*int***classmethod capabilities_to_string**(*capabilities_bitfield*)

Translates a capability bitfield to a list of capability strings.

Parameters**capabilities_bitfield** (*int*) – The capability bitfield value.**Returns**

A list of capability strings.

Return type*List[str]***cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

enumerate_capabilities()

Returns the list of capability strings.

Returns

The list of capability strings.

Return type

List[str]

get_capabilities()

Returns the capability bitfield value

Returns

The capability bitfield value.

Return type

int

get_kernel_cap_full()

Return the maximum value allowed for this kernel for a capability

Returns

The capability full bitfield mask

Return type

int

classmethod get_last_cap_value()

Returns the latest capability ID supported by the framework.

Returns

The latest capability ID supported by the framework.

Return type

int

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_capability(capability)

Checks if the given capability string is enabled.

Parameters**capability** (str) – A string representing the capability i.e. dac_read_search**Raises****AttributeError** – If the given capability is unknown to the framework.**Returns**

“True” if the given capability is enabled.

Return type

bool

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class kernel_cap_t(*context, type_name, object_info, size, members*)

Bases: *kernel_cap_struct*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**classmethod** `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**classmethod** `capabilities_to_string(capabilities_bitfield)`

Translates a capability bitfield to a list of capability strings.

Parameters**capabilities_bitfield** (`int`) – The capability bitfield value.**Returns**

A list of capability strings.

Return type`List[str]`**cast**(*new_type_name*, ***additional*)Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

enumerate_capabilities()

Returns the list of capability strings.

Returns

The list of capability strings.

Return type`List[str]`**get_capabilities()**

Returns the capability bitfield value

Returns

The capability bitfield value.

Return type`int`**get_kernel_cap_full()**

Return the maximum value allowed for this kernel for a capability

Returns

The capability full bitfield mask

Return type`int`**classmethod `get_last_cap_value()`**

Returns the latest capability ID supported by the framework.

Returns

The latest capability ID supported by the framework.

Return type`int`**`get_symbol_table_name()`**

Returns the symbol table name for this particular object.

Raises

- **`ValueError`** – If the object’s symbol does not contain an explicit table
- **`KeyError`** – If the `table_name` is not valid within the object’s context

Return type`str`**`has_capability(capability)`**

Checks if the given capability string is enabled.

Parameters

`capability` (`str`) – A string representing the capability i.e. `dac_read_search`

Raises

`AttributeError` – If the given capability is unknown to the framework.

Returns

“True” if the given capability is enabled.

Return type`bool`**`has_member(member_name)`**

Returns whether the object would contain a member called `member_name`.

Return type`bool`**`has_valid_member(member_name)`**

Returns whether the dereferenced type has a valid member.

Parameters

`member_name` (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**`has_valid_members(member_names)`**

Returns whether the object has all of the members listed in `member_names`

Parameters

`member_names` (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property *vol*: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **kobject**(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**

Bases: `VolTemplateProxy`

classmethod **child_template**(*template*, *child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod **children**(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod **has_member**(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod **relative_child_offset**(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod **replace_child**(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod **size**(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

reference_count()

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `list_head`(*context, type_name, object_info, size, members*)

Bases: `StructType`, `Iterable`

Constructs an Object adhering to the `ObjectInterface`.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template`(*template, child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children`(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member`(*template, member_name*)

Returns whether the object would contain a member called `member_name`.

Return type

`bool`

classmethod `relative_child_offset`(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child`(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size`(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters**member_name** (`str`) – Name of the member to test access to determine if the member is valid or not**Return type**`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters**member_names** (`List[str]`) – List of names to test as to members with those names validity**Return type**`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**to_list**(*symbol_type*, *member*, *forward*=True, *sentinel*=True, *layer*=None)

Returns an iterator of the entries in the list.

Parameters

- **symbol_type** (`str`) – Type of the list elements
- **member** (`str`) – Name of the list_head member in the list elements
- **forward** (`bool`) – Set false to go backwards
- **sentinel** (`bool`) – Whether self is a “sentinel node”, meaning it is not embedded in a member of the list
- **https** (*Sentinel nodes are NOT yielded. See* [//en.wikipedia.org/wiki/Sentinel_node](https://en.wikipedia.org/wiki/Sentinel_node) for further reference) –
- **layer** (`Optional[str]`) – Name of layer to read from

Yields

Objects of the type specified via the “symbol_type” argument.

Return type`Iterator[ObjectInterface]`

property `vol: ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `maple_tree(context, type_name, object_info, size, members)`

Bases: [StructType](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([ContextInterface](#)) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** ([ObjectInformation](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

`MAPLE_ARANGE_64 = 3`

`MAPLE_DENSE = 0`

`MAPLE_LEAF_64 = 1`

`MAPLE_NODE_POINTER_MASK = 255`

`MAPLE_NODE_TYPE_MASK = 15`

`MAPLE_NODE_TYPE_SHIFT = 3`

`MAPLE_RANGE_64 = 2`

`MT_FLAGS_HEIGHT_MASK = 124`

`MT_FLAGS_HEIGHT_OFFSET = 2`

class `VolTemplateProxy`

Bases: [VolTemplateProxy](#)

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

[Template](#)

classmethod `children(template)`

Method to list children of a template.

Return type

[List](#)[[Template](#)]

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_slot_iter()

Parse the Maple Tree and return every non zero slot.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type`object`**property** `vol: ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `mm_struct`(*context, type_name, object_info, size, members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template`(*template, child*)

Returns the template of a child to its parent.

Return type`Template`**classmethod** `children`(*template*)

Method to list children of a template.

Return type`List[Template]`**classmethod** `has_member`(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**classmethod** `relative_child_offset`(*template, child*)

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child`(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size`(*template*)

Method to return the size of this type.

Return type`int`**cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_maple_tree_iter()

Deprecated: Use either `get_vma_iter()` or `_get_maple_tree_iter()`.

Return type

`Iterable[ObjectInterface]`

get_mmap_iter()

Deprecated: Use either `get_vma_iter()` or `_get_mmap_iter()`.

Return type

`Iterable[ObjectInterface]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the `table_name` is not valid within the object's context

Return type

`str`

get_vma_iter()

Returns an iterator for the VMAs in an `mm_struct`. Automatically choosing the `mmap` or `mm_mt` as required.

Return type

`Iterable[ObjectInterface]`

has_member(member_name)

Returns whether the object would contain a member called `member_name`.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in `member_names`

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property *vol*: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `mnt_namespace`(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template`(*template*, *child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children`(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member`(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset`(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child`(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size`(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_inode()

get_mount_points()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `module(*args, **kwargs)`

Bases: `GenericIntelProcess`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** – The context associated with the object
- **type_name** – The name of the type structure for the object
- **object_info** – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(`new_type_name, **additional`)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

`get_core_size()`

`get_elf_table_name()`

get_init_size()

get_module_base()

get_module_core()

get_module_init()

get_name()

Get the name of the module as a string

get_sections()

Get sections of the module

get_symbol(*wanted_sym_name*)

Get symbol value for a given symbol name

get_symbol_by_address(*wanted_sym_address*)

Get symbol name for a given symbol address

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

get_symbols()

Get symbols of the module

Yields

A symbol object

get_symbols_names_and_addresses()

Get names and addresses for each symbol of the module

Yields

A tuple for each symbol containing the symbol name and its corresponding value

Return type

`Tuple[str, int]`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property mod_mem_type

Return the *mod_mem_type* enum choices if available or an empty dict if not

property num_syntab

property section_strtab

property section_syntab

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class mount(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the *ObjectInterface*.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

MNT_FLAGS = {1: 'nosuid', 2: 'nodev', 4: 'noexec', 8: 'noatime', 16: 'nodiratime', 32: 'relatime'}

MNT_NOATIME = 8

MNT_NODEV = 2

MNT_NODIRATIME = 16

MNT_NOEXEC = 4

MNT_NOSUID = 1

MNT_READONLY = 64

MNT_RELATIME = 32

MNT_SHARED = 4096

MNT_SHRINKABLE = 256

MNT_UNBINDABLE = 8192

MNT_WRITE_HOLD = 512

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_dentry_current()

Returns the root of the mounted tree

Returns

A dentry pointer

get_dentry_parent()

Returns the parent root of the mounted tree

Returns

A dentry pointer

get_devname()

Return type

`str`

get_dominating_id(*root*)

Get ID of closest dominating peer group having a representative under the given root.

Return type

`int`

get_flags_access()

Return type

`str`

get_flags_opts()

Return type

`Iterable[str]`

get_mnt_flags()

get_mnt_mountpoint()

Gets the dentry of the mountpoint

Returns

A dentry pointer

get_mnt_parent()

Gets the fs where we are mounted on

Returns

A mount pointer

get_mnt_root()

get_mnt_sb()

get_parent_mount()

get_peer_under_root(*ns*, *root*)

Return true if path is reachable from root. It mimics the kernel function `is_path_reachable()`, ref: `fs/namespace.c`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the `table_name` is not valid within the object's context

Return type

`str`

get_vfsmnt_current()

Returns the fs where we are mounted on

Returns

A 'vfsmount'

get_vfsmnt_parent()

Gets the parent fs (vfsmount) to where it's mounted on

Returns

A 'vfsmount'

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_parent()

Checks if this mount has a parent

Returns

'True' if this mount has a parent

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_path_reachable(*current_dentry*, *root*)

Return true if path is reachable. It mimics the kernel function with same name, ref fs/namespace.c:

is_shared()**Return type**

`bool`

is_slave()**Return type**

`bool`

is_unbindable()

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

next_peer()

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class net(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_inode()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

property `vol: ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class netlink_sock(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_dst_portid()

get_portid()

get_protocol()

get_state()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*=‘member’)

Specifically named method for retrieving members.

Return type

`object`

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class packet_sock(*context, type_name, object_info, size, members*)

Bases: [*StructType*](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object

- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod **child_template**(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod **children**(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod **has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod **relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod **replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod **size**(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_protocol()

get_state()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property** **vol**: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **qstr**(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**

Bases: `VolTemplateProxy`

classmethod **child_template**(*template*, *child*)

Returns the template of a child to its parent.

Return type`Template`

classmethod **children**(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod **has_member**(*template*, *member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

classmethod **relative_child_offset**(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod **replace_child**(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod **size**(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the *table_name* is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

name_as_str()

Return type

str

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class sock(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**cast**(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_family()**get_inode()****get_protocol()****get_state()****get_symbol_table_name()**

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type`str`**get_type()****has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class socket(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_inode()

get_state()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property *vol*: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `struct_file`(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template`(*template*, *child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children`(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member`(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset`(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child`(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size`(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_dentry()

Return type

ObjectInterface

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

get_vfsmnt()

Returns the fs (vfsmount) where this file is mounted

Return type

ObjectInterface

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class super_block(*context, type_name, object_info, size, members*)

Bases: [*StructType*](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** ([*str*](#)) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

MINORBITS = 20

SB_DIRSYNC = 128

SB_I_VERSION = 8388608

SB_KERNMOUNT = 4194304

SB_LAZYTIME = 33554432

SB_MANDLOCK = 64

SB_NOATIME = 1024

SB_NODEV = 4

SB_NODIRATIME = 2048

SB_NOEXEC = 8

SB_NOSUID = 2

SB_OPTS = {16: 'sync', 64: 'mand', 128: 'dirsync', 33554432: 'lazytime'}

SB_POSIXACL = 65536

SB_RDONLY = 1

SB_SILENT = 32768

SB_SYNCHRONOUS = 16

class VolTemplateProxy

Bases: [*VolTemplateProxy*](#)

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

[*Template*](#)

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_flags_access()

Return type

`str`

get_flags_opts()

Return type

`Iterable[str]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

get_type()

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters**member_name** (`str`) – Name of the member to test access to determine if the member is valid or not**Return type**`bool`**has_valid_members**(*member_names*)Returns whether the object has all of the members listed in *member_names***Parameters****member_names** (`List[str]`) – List of names to test as to members with those names validity**Return type**`bool`**property major:** `int`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property minor:** `int`**property vol:** `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class task_struct(*context*, *type_name*, *object_info*, *size*, *members*)Bases: `GenericIntelProcess`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: `VolTemplateProxy`**classmethod child_template**(*template*, *child*)

Returns the template of a child to its parent.

Return type`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

add_process_layer(*config_prefix=None, preferred_name=None*)

Constructs a new layer based on the process's DTB.

Returns the name of the Layer or None.

Return type

`Optional[str]`

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_process_memory_sections(*heap_only=False*)

Returns a list of sections based on the memory manager's view of this task's virtual memory.

Return type

`Generator[Tuple[int, int], None, None]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

get_threads()

Returns a list of the task_struct based on the list_head thread_node structure.

Return type

`Iterable[ObjectInterface]`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

property is_kernel_thread: bool

Checks if this task is a kernel thread.

Returns

True, if this task is a kernel thread. Otherwise, False.

Return type

`bool`

property is_thread_group_leader: bool

Checks if this task is a thread group leader.

Returns

True, if this task is a thread group leader. Otherwise, False.

Return type

`bool`

property is_user_thread: bool

Checks if this task is a user thread.

Returns

True, if this task is a user thread. Otherwise, False.

Return type

`bool`

member(attr='member')

Specifically named method for retrieving members.

Return type`object`**property** `vol: ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `unix_sock(context, type_name, object_info, size, members)`

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type`Template`**classmethod** `children(template)`

Method to list children of a template.

Return type`List[Template]`**classmethod** `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type`bool`**classmethod** `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_inode()

get_name()

get_protocol()

get_state()

Return a string representing the sock state.

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(attr='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class `vfsmount`(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template`(*template*, *child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children`(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member`(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset`(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child`(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size`(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_dentry_current()

Returns the root of the mounted tree

Returns

A dentry pointer

get_dentry_parent()

Returns the parent root of the mounted tree

Returns

A dentry pointer

get_devname()**Return type**

`str`

get_flags_access()**Return type**

`str`

get_flags_opts()**Return type**

`Iterable[str]`

get_mnt_flags()**get_mnt_mountpoint()**

Gets the dentry of the mountpoint

Returns

A dentry pointer

get_mnt_parent()

Gets the `mnt_parent` member.

Returns

A `vfsmount` pointer For kernels $\geq 3.3.8$: A mount pointer

Return type

For kernels $< 3.3.8$

get_mnt_root()**get_mnt_sb()****get_symbol_table_name()**

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the `table_name` is not valid within the object's context

Return type

`str`

get_vfsmnt_current()

Returns the current fs where we are mounted on

Returns

A `vfsmount` pointer

get_vfsmnt_parent()

Gets the parent fs (vfsmount) to where it's mounted on

Returns

A vfsmount pointer For kernels >= 3.3.8: A vfsmount object

Return type

For kernels < 3.3.8

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_parent()**Return type**

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_equal(*vfsmount_ptr*)

Helper to make sure it is comparing two pointers to 'vfsmount'.

Depending on the kernel version, the calling object (self) could be a 'vfsmount *' (<3.3.8) or a 'vfsmount' (>=3.3.8). This way we trust in the framework "auto" dereferencing ability to assure that when we reach this point 'self' will be a 'vfsmount' already and self.vol.offset a 'vfsmount *' and not a 'vfsmount **'. The argument must be a 'vfsmount *'. Typically, it's called from do_get_path().

Parameters

vfsmount_ptr (`vfsmount *`) – A pointer to a 'vfsmount'

Raises

`exceptions.VolatilityException` – If *vfsmount_ptr* is not a 'vfsmount *'

Returns

'True' if the given argument points to the the same 'vfsmount' as 'self'.

Return type

`bool`

is_shared()

Return type

`bool`

is_slave()

Return type

`bool`

is_unbindable()

Return type

`bool`

is_valid()

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class vm_area_struct(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template*, *child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

```
extended_flags = {1: 'VM_READ', 2: 'VM_WRITE', 4: 'VM_EXEC', 8: 'VM_SHARED', 16:
'VM_MAYREAD', 32: 'VM_MAYWRITE', 64: 'VM_MAYEXEC', 128: 'VM_MAYSHARE', 256:
'VM_GROWSDOWN', 512: 'VM_NOHUGEPAGE', 1024: 'VM_PFNMAP', 2048: 'VM_DENYWRITE',
4096: 'VM_EXECUTABLE', 8192: 'VM_LOCKED', 16384: 'VM_IO', 32768: 'VM_SEQ_READ',
65536: 'VM_RAND_READ', 131072: 'VM_DONTCOPY', 262144: 'VM_DONTEXPAND', 524288:
'VM_RESERVED', 1048576: 'VM_ACCOUNT', 2097152: 'VM_NORESERVE', 4194304:
'VM_HUGETLB', 8388608: 'VM_NONLINEAR', 16777216: 'VM_MAPPED_COPY_HUGEPAGE',
33554432: 'VM_INSERTPAGE', 67108864: 'VM_ALWAYS_DUMP', 134217728:
'VM_CAN_NONLINEAR', 268435456: 'VM_MIXEDMAP', 536870912: 'VM_SAO', 1073741824:
'VM_PFN_AT_MMAP', 2147483648: 'VM_MERGEABLE'}
```

`get_flags()`

Return type

`str`

`get_name(context, task)`

`get_page_offset()`

Return type

`int`

`get_protection()`

Return type

`str`

`get_symbol_table_name()`

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type`str`**has_member**(*member_name*)Returns whether the object would contain a member called *member_name*.**Return type**`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters**member_name** (`str`) – Name of the member to test access to determine if the member is valid or not**Return type**`bool`**has_valid_members**(*member_names*)Returns whether the object has all of the members listed in *member_names***Parameters****member_names** (`List[str]`) – List of names to test as to members with those names validity**Return type**`bool`**is_suspicious**(*proclayer=None*)**member**(*attr='member'*)

Specifically named method for retrieving members.

Return type`object`**perm_flags** = {1: 'r', 2: 'w', 4: 'x'}**property vol:** [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class vsock_sock(*context, type_name, object_info, size, members*)Bases: [*StructType*](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: [*VolTemplateProxy*](#)

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_protocol()

get_state()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class xdp_sock(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**classmethod** `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**cast**(*new_type_name*, ***additional*)Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_protocol()**get_state()****get_symbol_table_name()**

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters**member_name** (`str`) – Name of the member to test access to determine if the member is valid or not**Return type**`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

Submodules**volatility3.framework.symbols.linux.extensions.bash module**

class hist_entry(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_command()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

get_time_as_integer()

get_time_object()

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_valid()

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.linux.extensions.elf module

class elf(*context, type_name, object_info, size, members*)

Bases: *StructType*

Class used to create elf objects. It overrides the typename to *Elf32_* or *Elf64_*, depending on the corresponding value on *e_ident*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_link_maps(*kernel_symbol_table_name*)

Get the ELF link map objects for the given VMA address

Parameters

kernel_symbol_table_name (*str*) – Kernel symbol table name

Yields

The ELF link map objects

get_program_headers()

get_section_headers()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

get_symbols()

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

is_valid()

Determine whether it is a valid object

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class elf_linkmap(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_name()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

property `vol`: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class `elf_phdr`(*args, **kwargs)

Bases: [*StructType*](#)

An elf program header

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** – The context associated with the object
- **type_name** – The name of the type structure for the object
- **object_info** – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: [*VolTemplateProxy*](#)

classmethod `child_template`(*template*, *child*)

Returns the template of a child to its parent.

Return type

[*Template*](#)

classmethod `children`(*template*)

Method to list children of a template.

Return type

[*List\[Template\]*](#)

classmethod `has_member`(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

[*bool*](#)

classmethod `relative_child_offset`(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

[*int*](#)

classmethod `replace_child`(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

[*None*](#)

classmethod `size`(*template*)

Method to return the size of this type.

Return type

[*int*](#)

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

[*ObjectInterface*](#)

Note: If new type name does not include a symbol table, the symbol table for the current object is used

dynamic_sections()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

get_vaddr()

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(attr='member')

Specifically named method for retrieving members.

Return type

`object`

property parent_e_type

property parent_offset

property type_prefix

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

```
class elf_sym(*args, **kwargs)
```

Bases: *StructType*

An elf symbol entry

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** – The context associated with the object
- **type_name** – The name of the type structure for the object
- **object_info** – Basic information relevant to the object (layer, offset, member_name, parent, etc)

```
class VolTemplateProxy
```

Bases: *VolTemplateProxy*

```
classmethod child_template(template, child)
```

Returns the template of a child to its parent.

Return type

Template

```
classmethod children(template)
```

Method to list children of a template.

Return type

List[Template]

```
classmethod has_member(template, member_name)
```

Returns whether the object would contain a member called member_name.

Return type

bool

```
classmethod relative_child_offset(template, child)
```

Returns the relative offset of a child to its parent.

Return type

int

```
classmethod replace_child(template, old_child, new_child)
```

Replace a child elements within the arguments handed to the template.

Return type

None

```
classmethod size(template)
```

Method to return the size of this type.

Return type

int

```
property cached_strtab
```

```
cast(new_type_name, **additional)
```

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_name()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

Submodules

volatility3.framework.symbols.linux.bash module

class `BashIntermedSymbols(*args, **kwargs)`

Bases: `IntermediateSymbolTable`

Instantiates a SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema. The validation can be disabled by passing `validate = False`, but this should almost never be done.

Parameters

- **context** – The volatility context for the symbol table
- **config_path** – The configuration path for the symbol table
- **name** – The name for the symbol table (this is used in symbols e.g. `table!symbol`)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** – A dictionary linking names referenced in the file with symbol tables in the context
- **validate** – Determines whether the ISF file will be validated against the appropriate schema
- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated
- **symbol_mask** – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

`build_configuration()`

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

clear_symbol_cache(*args, **kwargs)

Clears the symbol cache of this symbol table.

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod create(context, config_path, sub_path, filename, native_types=None, table_mapping=None, class_types=None, symbol_mask=0)

Takes a context and loads an intermediate symbol table based on a filename.

Parameters

- **context** (*ContextInterface*) – The context that the current plugin is being run within
- **config_path** (*str*) – The configuration path for reading/storing configuration information this symbol table may use
- **sub_path** (*str*) – The path under a suitable symbol path (defaults to volatility3/symbols and volatility3/framework/symbols) to check
- **filename** (*str*) – Basename of the file to find under the sub_path
- **native_types** (*Optional[NativeTableInterface]*) – Set of native types, defaults to native types read from the intermediate symbol format file
- **table_mapping** (*Optional[Dict[str, str]]*) – a dictionary of table names mentioned within the ISF file, and the tables within the context which they map to
- **symbol_mask** (*int*) – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

Return type*str***Returns**

the name of the added symbol table

del_type_class(*args, **kwargs)

Removes the associated class override for a specific Symbol type.

property enumerations

Returns an iterator of the Enumeration names.

classmethod file_symbol_url(sub_path, filename=None)

Returns an iterator of appropriate file-scheme symbol URLs that can be opened by a ResourceAccessor class.

Filter reduces the number of results returned to only those URLs containing that string

Return type*Generator[str, None, None]***get_enumeration**(*args, **kwargs)**classmethod get_requirements**()

Returns a list of RequirementInterface objects required by this object.

Return type*List[RequirementInterface]***get_symbol**(*args, **kwargs)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type*Optional[Template]***get_symbols_by_location**(offset, size=0)

Returns the name of all symbols in this table that live at a particular offset.

Return type`Iterable[str]`**get_symbols_by_type**(*type_name*)Returns the name of all symbols in this table that have type matching *type_name*.**Return type**`Iterable[str]`**get_type**(**args*, ***kwargs*)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a `SymbolError` exception**get_type_class**(**args*, ***kwargs*)

Returns the class associated with a Symbol type.

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.**Parameters**

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property metadata****property natives:** *NativeTableInterface*Returns None or a `NativeTable` for handling space specific native types.**optional_set_type_class**(*name*, *clazz*)Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: *Type[ObjectInterface]* :param clazz: The actual class to override for the provided type name**Return type**`bool`**property producer****set_type_class**(**args*, ***kwargs*)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`**Parameters**

- **name** – The name of the type to override the class for
- **clazz** – The actual class to override for the provided type name

property symbols

Returns an iterator of the Symbol names.

property types

Returns an iterator of the Symbol type names.

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

volatility3.framework.symbols.mac package**class MacKernelIntermedSymbols**(*args, **kwargs)

Bases: *IntermediateSymbolTable*

Instantiates a SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema. The validation can be disabled by passing `validate = False`, but this should almost never be done.

Parameters

- **context** – The volatility context for the symbol table
- **config_path** – The configuration path for the symbol table
- **name** – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** – A dictionary linking names referenced in the file with symbol tables in the context
- **validate** – Determines whether the ISF file will be validated against the appropriate schema
- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated
- **symbol_mask** – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache(*args, **kwargs)

Clears the symbol cache of this symbol table.

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod create(context, config_path, sub_path, filename, native_types=None, table_mapping=None, class_types=None, symbol_mask=0)

Takes a context and loads an intermediate symbol table based on a filename.

Parameters

- **context** (*ContextInterface*) – The context that the current plugin is being run within
- **config_path** (*str*) – The configuration path for reading/storing configuration information this symbol table may use
- **sub_path** (*str*) – The path under a suitable symbol path (defaults to volatility3/symbols and volatility3/framework/symbols) to check
- **filename** (*str*) – Basename of the file to find under the sub_path
- **native_types** (*Optional[NativeTableInterface]*) – Set of native types, defaults to native types read from the intermediate symbol format file
- **table_mapping** (*Optional[Dict[str, str]]*) – a dictionary of table names mentioned within the ISF file, and the tables within the context which they map to
- **symbol_mask** (*int*) – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

Return type

str

Returns

the name of the added symbol table

del_type_class(*args, **kwargs)

Removes the associated class override for a specific Symbol type.

property enumerations

Returns an iterator of the Enumeration names.

classmethod file_symbol_url(sub_path, filename=None)

Returns an iterator of appropriate file-scheme symbol URLs that can be opened by a ResourceAccessor class.

Filter reduces the number of results returned to only those URLs containing that string

Return type

Generator[str, None, None]

get_enumeration(*args, **kwargs)

classmethod `get_requirements()`

Returns a list of RequirementInterface objects required by this object.

Return type

`List[RequirementInterface]`

get_symbol(*args, **kwargs)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(offset, size=0)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(type_name)

Returns the name of all symbols in this table that have type matching type_name.

Return type

`Iterable[str]`

get_type(*args, **kwargs)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a SymbolError exception

get_type_class(*args, **kwargs)

Returns the class associated with a Symbol type.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type`bool`**property producer****provides** = {'type': 'interface'}**set_type_class**(*args, **kwargs)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`

Parameters

- **name** – The name of the type to override the class for
- **clazz** – The actual class to override for the provided type name

property symbols

Returns an iterator of the Symbol names.

property types

Returns an iterator of the Symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`**class MacUtilities**(*args, **kwargs)

Bases: `VersionableInterface`

Class with multiple useful mac functions.

classmethod files_descriptors_for_process(*context*, *symbol_table_name*, *task*)

Creates a generator for the file descriptors of a process

Parameters

- **symbol_table_name** (`str`) – The name of the symbol table associated with the process
- **context** (`ContextInterface`) –
- **task** (`ObjectInterface`) – The process structure to enumerate file descriptors from

Returns

- 1) The file's object

2) **The path referenced by the descriptor.**

The path is either empty, the full path of the file in the file system, or the formatted name for sockets, pipes, etc.

3) The file descriptor number

Return type

A 3 element tuple is yielded for each file descriptor

classmethod `generate_kernel_handler_info(context, layer_name, kernel, mods_list)`

classmethod `lookup_module_address(context, handlers, target_address, kernel_module_name=None)`

classmethod `mask_mods_list(context, layer_name, mods)`

A helper function to mask the starting and end address of kernel modules

Return type

`List[Tuple[ObjectInterface, Any, Any]]`

version = (1, 3, 0)

classmethod `walk_list_head(queue, next_member, max_elements=4096)`

Return type

`Iterable[ObjectInterface]`

classmethod `walk_slist(queue, next_member, max_elements=4096)`

Return type

`Iterable[ObjectInterface]`

classmethod `walk_tailq(queue, next_member, max_elements=4096)`

Return type

`Iterable[ObjectInterface]`

Subpackages

volatility3.framework.symbols.mac.extensions package

class `fileglob(context, type_name, object_info, size, members)`

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_fg_type()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class ifnet(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**classmethod** `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**cast**(*new_type_name*, ***additional*)Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters**member_name** (`str`) – Name of the member to test access to determine if the member is valid or not**Return type**`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters**member_names** (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

sockaddr_dl()

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class inpcb(*context, type_name, object_info, size, members*)

Bases: [*StructType*](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [*VolTemplateProxy*](#)

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

[*Template*](#)

classmethod children(*template*)

Method to list children of a template.

Return type

[*List\[Template\]*](#)

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_ipv4_info()

get_ipv6_info()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

get_tcp_state()

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class kauth_scope(*context, type_name, object_info, size, members*)

Bases: [*StructType*](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [*VolTemplateProxy*](#)

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

[*Template*](#)

classmethod children(*template*)

Method to list children of a template.

Return type

[*List\[Template\]*](#)

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

[*bool*](#)

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

[*int*](#)

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

[*None*](#)

classmethod size(*template*)

Method to return the size of this type.

Return type

[*int*](#)

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

[*ObjectInterface*](#)

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_listeners()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(attr='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: `ReadOnlyMapping`

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class proc(context, type_name, object_info, size, members)

Bases: `GenericIntelProcess`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object

- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

add_process_layer(*config_prefix=None, preferred_name=None*)

Constructs a new layer based on the process's DTB.

Returns the name of the Layer or None.

Return type

Optional[str]

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_map_iter()

Return type

Iterable[ObjectInterface]

get_process_memory_sections(*context*, *config_prefix*, *rw_no_file=False*)

Returns a list of sections based on the memory manager's view of this task's virtual memory.

Return type

`Generator[Tuple[int, int], None, None]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

get_task()

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class queue_entry(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: [*StructType*](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

walk_list(*list_head*, *member_name*, *type_name*, *max_size*=4096)

Walks a queue in a smear-aware and smear-resistant manner

smear is detected by:

- the *max_size* parameter sets an upper bound
- each seen entry is only allowed once

attempts to work around smear:

- the list is walked in both directions to help find as many elements as possible

Parameters

- **list** (*type_name* - the type of each element in the) –
- **member** (*member_name* - the name of the embedded list) –
- **list** –
- **returned** (*max_size* - the maximum amount of elements that will be) –

Return type

`Iterable[ObjectInterface]`

Returns

Each instance of the queue cast as “*type_name*” type

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class sockaddr(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_address()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(attr='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class sockaddr_dl(context, type_name, object_info, size, members)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class socket(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**classmethod** `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type`None`**classmethod** `size(template)`

Method to return the size of this type.

Return type`int`**cast**(*new_type_name*, ***additional*)Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_connection_info()**get_converted_connection_info()****get_family()****get_inpcb()****get_protocol_as_string()****get_state()****get_symbol_table_name()**

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class sysctl_oid(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_ctltype()

Returns the type of the sysctl node

Args: None

Returns

CTLTYPE_NODE CTLTYPE_INT CTLTYPE_STRING CTLTYPE_QUAD CTL-
TYPE_OPAQUE an empty string for nodes not in the above types

Return type

One of

Based on `sysctl_sysctl_debug_dump_node`

get_perms()

Returns the actions allowed on the node

Args: None

Returns

R - readable W - writeable L - self handles locking

Return type

A combination of

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class vm_map_entry(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_object()

get_offset()

get_path(*context*, *config_prefix*)

get_perms()

get_range_alias()

get_special_path()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

get_vnode(*context*, *config_prefix*)

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_suspicious(*context*, *config_prefix*)

Flags memory regions that are mapped rwx or that map an executable not back from a file on disk.

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class vm_map_object(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: `VolTemplateProxy`

classmethod child_template(*template*, *child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_map_object()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property vol:** `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class vnode(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `StructType`

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: `VolTemplateProxy`

classmethod child_template(*template*, *child*)

Returns the template of a child to its parent.

Return type`Template`**classmethod children**(*template*)

Method to list children of a template.

Return type`List[Template]`**classmethod has_member**(*template*, *member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**classmethod relative_child_offset**(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

full_path()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.windows package

class WindowsKernelIntermedSymbols(*args, **kwargs)

Bases: *IntermediateSymbolTable*

Instantiates a SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema. The validation can be disabled by passing validate = False, but this should almost never be done.

Parameters

- **context** – The volatility context for the symbol table
- **config_path** – The configuration path for the symbol table
- **name** – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** – A dictionary linking names referenced in the file with symbol tables in the context
- **validate** – Determines whether the ISF file will be validated against the appropriate schema
- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated
- **symbol_mask** – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache(*args, **kwargs)

Clears the symbol cache of this symbol table.

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod `create(context, config_path, sub_path, filename, native_types=None, table_mapping=None, class_types=None, symbol_mask=0)`

Takes a context and loads an intermediate symbol table based on a filename.

Parameters

- **context** (*ContextInterface*) – The context that the current plugin is being run within
- **config_path** (*str*) – The configuration path for reading/storing configuration information this symbol table may use
- **sub_path** (*str*) – The path under a suitable symbol path (defaults to volatility3/symbols and volatility3/framework/symbols) to check
- **filename** (*str*) – Basename of the file to find under the sub_path
- **native_types** (*Optional[NativeTableInterface]*) – Set of native types, defaults to native types read from the intermediate symbol format file
- **table_mapping** (*Optional[Dict[str, str]]*) – a dictionary of table names mentioned within the ISF file, and the tables within the context which they map to
- **symbol_mask** (*int*) – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

Return type

str

Returns

the name of the added symbol table

del_type_class(*args, **kwargs)

Removes the associated class override for a specific Symbol type.

property enumerations

Returns an iterator of the Enumeration names.

classmethod `file_symbol_url(sub_path, filename=None)`

Returns an iterator of appropriate file-scheme symbol URLs that can be opened by a ResourceAccessor class.

Filter reduces the number of results returned to only those URLs containing that string

Return type

Generator[str, None, None]

get_enumeration(*args, **kwargs)

classmethod `get_requirements()`

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(*args, **kwargs)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type`Optional[Template]`**get_symbols_by_location**(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type`Iterable[str]`**get_symbols_by_type**(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type`Iterable[str]`**get_type**(**args*, ***kwargs*)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a `SymbolError` exception

get_type_class(**args*, ***kwargs*)

Returns the class associated with a Symbol type.

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property metadata****property natives:** `NativeTableInterface`

Returns None or a `NativeTable` for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type`bool`**property producer****set_type_class**(**args*, ***kwargs*)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`

Parameters

- **name** – The name of the type to override the class for
- **clazz** – The actual class to override for the provided type name

property symbols

Returns an iterator of the Symbol names.

property types

Returns an iterator of the Symbol type names.

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

Subpackages**volatility3.framework.symbols.windows.extensions package****class CONTROL_AREA**(*context, type_name, object_info, size, members*)

Bases: `StructType`

A class for _CONTROL_AREA structures

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

PAGE_MASK = 4095

PAGE_SIZE = 4096

class VolTemplateProxy

Bases: `VolTemplateProxy`

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod children(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_available_pages()

Get the available pages that correspond to a cached file.

The tuples generated are (physical_offset, file_offset, page_size).

Return type

`Iterable[Tuple[int, int, int]]`

get_pte(*offset*)

Get a PTE object at the requested offset

Return type

`ObjectInterface`

get_subsection()

Get the Subsection object, which is found immediately after the `_CONTROL_AREA`.

Return type

`ObjectInterface`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_valid()

Determine if the object is valid.

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **DEVICE_OBJECT**(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: *StructType*, *ExecutiveObject*

A class for kernel device objects.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**

Bases: *VolTemplateProxy*

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_attached_devices()

Enumerate the attached device's objects

Return type

`Generator[ObjectInterface, None, None]`

get_device_name()

Get device's name from the object header.

Return type

`str`

get_object_header()

Return type

`OBJECT_HEADER`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class DRIVER_OBJECT(*context, type_name, object_info, size, members*)

Bases: [*StructType*](#), [*ExecutiveObject*](#)

A class for kernel driver objects.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [*VolTemplateProxy*](#)

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_devices()

Enumerate the driver's device objects

Return type

`Generator[ObjectInterface, None, None]`

get_driver_name()

Get driver's name from the object header.

Return type

`str`

get_object_header()

Return type

`OBJECT_HEADER`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (str) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (List[str]) – List of names to test as to members with those names validity

Return type

bool

is_valid()

Determine if the object is valid.

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class EPROCESS(*context, type_name, object_info, size, members*)

Bases: *GenericIntelProcess, ExecutiveObject*

A class for executive kernel processes objects.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (str) – The name of the type structure for the object

- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

add_process_layer(*config_prefix=None, preferred_name=None*)

Constructs a new layer based on the process's DirectoryTableBase.

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

environment_variables()

Generator for environment variables.

The PEB points to our env block - a series of null-terminated unicode strings. Each string cannot be more than 0x7FFF chars. End of the list is a quad-null.

get_create_time()

get_exit_time()

get_handle_count()

get_is_wow64()

get_object_header()

Return type

OBJECT_HEADER

get_peb()

Constructs a PEB object

Return type

ObjectInterface

get_session_id()

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

get_vad_root()

get_wow_64_process()

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

init_order_modules()

Generator for DLLs in the order that they were initialized

Return type

Iterable[ObjectInterface]

is_valid()

Determine if the object is valid.

Return type

`bool`

load_order_modules()

Generator for DLLs in the order that they were loaded.

Return type

`Iterable[ObjectInterface]`

mem_order_modules()

Generator for DLLs in the order that they appear in memory

Return type

`Iterable[ObjectInterface]`

member(attr='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class ETHREAD(context, type_name, object_info, size, members)

Bases: *StructType*, *ExecutiveObject*

A class for executive thread objects.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(template, child)

Returns the template of a child to its parent.

Return type

Template

classmethod children(template)

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_create_time()

get_cross_thread_flags()

Return type

`str`

get_exit_time()

get_object_header()

Return type

`OBJECT_HEADER`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

is_valid()

Determine if the object is valid.

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

owning_process()

Return the EPROCESS that owns this thread.

Return type

ObjectInterface

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class EX_FAST_REF(*context, type_name, object_info, size, members*)

Bases: *StructType*

This is a standard Windows structure that stores a pointer to an object but also leverages the least significant bits to encode additional details.

When dereferencing the pointer, we need to strip off the extra bits.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

dereference()

Return type

ObjectInterface

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class FILE_OBJECT(*context, type_name, object_info, size, members*)

Bases: *StructType, ExecutiveObject*

A class for windows file objects.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

access_string()

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

file_name_with_device()

Return type

`Union[str, BaseAbsentValue]`

get_object_header()

Return type

`OBJECT_HEADER`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters**member_name** (`str`) – Name of the member to test access to determine if the member is valid or not**Return type**`bool`**has_valid_members**(*member_names*)Returns whether the object has all of the members listed in *member_names***Parameters****member_names** (`List[str]`) – List of names to test as to members with those names validity**Return type**`bool`**is_valid**()

Determine if the object is valid.

Return type`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property** **vol**: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **KMUTANT**(*context*, *type_name*, *object_info*, *size*, *members*)Bases: *StructType*, *ExecutiveObject*

A class for windows mutant objects.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**Bases: *VolTemplateProxy***classmethod** **child_template**(*template*, *child*)

Returns the template of a child to its parent.

Return type*Template***classmethod children**(*template*)

Method to list children of a template.

Return type*List[Template]***classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool***classmethod relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type*int***classmethod replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type*None***classmethod size**(*template*)

Method to return the size of this type.

Return type*int***cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_name()

Get the object's name from the object header.

Return type*str***get_object_header**()**Return type***OBJECT_HEADER***get_symbol_table_name**()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type*str*

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_valid()

Determine if the object is valid.

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property **vol**: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **KSYSTEM_TIME**(*context, type_name, object_info, size, members*)

Bases: *StructType*

A system time structure that stores a high and low part.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**

Bases: *VolTemplateProxy*

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(new_type_name, **additional)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

get_time()

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class KTHREAD(*context, type_name, object_info, size, members*)

Bases: *StructType*

A class for thread control block objects.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_state()

Return type

`str`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

get_wait_reason()

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class LIST_ENTRY(*context, type_name, object_info, size, members*)

Bases: *StructType, Iterable*

A class for double-linked lists on Windows.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

to_list(*symbol_type*, *member*, *forward*=True, *sentinel*=True, *layer*=None)

Returns an iterator of the entries in the list.

Return type

`Iterator[ObjectInterface]`

property vol: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class MMVAD(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `MMVAD_SHORT`

A version of the process virtual memory range structure that contains additional fields necessary to map files from disk.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: `VolTemplateProxy`

classmethod child_template(*template*, *child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod children(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod relative_child_offset(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_commit_charge()

Get the VAD's commit charge (number of committed pages)

get_end()

Get the VAD's ending virtual address. This is the last accessible byte in the range.

Return type

`int`

get_file_name()

Get the name of the file mapped into the memory range (if any)

get_left_child()

Get the left child member.

get_parent()

Get the VAD's parent member.

get_private_memory()

Get the VAD's private memory setting.

get_protection(*protect_values*, *winnt_protections*)

Get the VAD's protection constants as a string.

get_right_child()

Get the right child member.

get_size()

Get the size of the VAD region. The OS ensures page granularity.

Return type

`int`

get_start()

Get the VAD's starting virtual address. This is the first accessible byte in the range.

Return type

`int`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

get_tag()**has_member(member_name)**

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(attr='member')

Specifically named method for retrieving members.

Return type

`object`

traverse(visited=None, depth=0)

Traverse the VAD tree, determining each underlying VAD node type by looking up the pool tag for the structure and then casting into a new object.

property vol: [ReadOnlyMapping](#)

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class MMVAD_SHORT(context, type_name, object_info, size, members)

Bases: [StructType](#)

A class that represents process virtual memory ranges.

Each instance is a node in a binary tree structure and is pointed to by VadRoot.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_commit_charge()

Get the VAD's commit charge (number of committed pages)

get_end()

Get the VAD's ending virtual address. This is the last accessible byte in the range.

Return type

int

get_file_name()

Only long(er) vads have mapped files.

get_left_child()

Get the left child member.

get_parent()

Get the VAD's parent member.

get_private_memory()

Get the VAD's private memory setting.

get_protection(*protect_values*, *winnt_protections*)

Get the VAD's protection constants as a string.

get_right_child()

Get the right child member.

get_size()

Get the size of the VAD region. The OS ensures page granularity.

Return type

`int`

get_start()

Get the VAD's starting virtual address. This is the first accessible byte in the range.

Return type

`int`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

get_tag()**has_member(*member_name*)**

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

traverse(*visited=None, depth=0*)

Traverse the VAD tree, determining each underlying VAD node type by looking up the pool tag for the structure and then casting into a new object.

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class OBJECT_SYMBOLIC_LINK(*context, type_name, object_info, size, members*)

Bases: *StructType, ExecutiveObject*

A class for kernel link objects.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_create_time()

get_link_name()

Return type

`str`

get_object_header()

Return type

OBJECT_HEADER

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**is_valid**()

Determine if the object is valid.

Return type`bool`**member**(*attr='member'*)

Specifically named method for retrieving members.

Return type`object`**property vol:** `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class SHARED_CACHE_MAP(*context, type_name, object_info, size, members*)

Bases: `StructType`

A class for `_SHARED_CACHE_MAP` structures

Constructs an Object adhering to the `ObjectInterface`.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

VACB_ARRAY = 128**VACB_BLOCK** = 262144**VACB_LEVEL_SHIFT** = 7**VACB_OFFSET_SHIFT** = 18**VACB_SIZE_OF_FIRST_LEVEL** = 33554432**class VolTemplateProxy**

Bases: `VolTemplateProxy`

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_available_pages()

Get the available pages that correspond to a cached file.

The lists generated are (virtual_offset, file_offset, page_size).

Return type

`List`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_valid()

Determine if the object is valid.

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

process_index_array(*array_pointer*, *level*, *limit*, *vacb_list*=None)

Recursively process the sparse multilevel VACB index array.

Parameters

- **array_pointer** (`ObjectInterface`) – The address of a possible index array
- **level** (`int`) – The current level
- **limit** (`int`) – The level where we abandon all hope. Ideally this is 7
- **vacb_list** (`Optional[List]`) – An array of collected VACBs

Return type

`List`

Returns

Collected VACBs

save_vacb(*vacb_obj*, *vacb_list*)

property vol: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **TOKEN**(*context, type_name, object_info, size, members*)

Bases: *StructType*

A class for process etoken object.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**

Bases: *VolTemplateProxy*

classmethod **child_template**(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod **children**(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod **has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod **relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod **replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod **size**(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_sids()

Yield a sid for the current token object.

Return type

`Iterable[str]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

privileges()

Return a list of privileges for the current token object.

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class UNICODE_STRING(*context, type_name, object_info, size, members*)

Bases: *StructType*

A class for Windows unicode string structures.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

property String: *ObjectInterface*

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_string()

Return type

ObjectInterface

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(attr='member')

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class VACB(context, type_name, object_info, size, members)

Bases: *StructType*

A class for _VACB structures

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

FILEOFFSET_MASK = 18446744073709486080

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_file_offset()

Return type

int

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (str) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (List[str]) – List of names to test as to members with those names validity

Return type

bool

member(*attr*='member')

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

Submodules

volatility3.framework.symbols.windows.extensions.crash module

class **SUMMARY_DUMP**(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (str) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: *VolTemplateProxy***classmethod child_template**(*template, child*)

Returns the template of a child to its parent.

Return type*Template***classmethod children**(*template*)

Method to list children of a template.

Return type*List[Template]***classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool***classmethod relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type*int***classmethod replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type*None***classmethod size**(*template*)

Method to return the size of this type.

Return type*int***cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_buffer(*sub_type, count*)**Return type***ObjectInterface***get_buffer_char**()**Return type***ObjectInterface***get_buffer_long**()**Return type***ObjectInterface***get_symbol_table_name**()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.windows.extensions.kdbg module

class **KDDEBUGGER_DATA64**(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: *VolTemplateProxy***classmethod child_template**(*template, child*)

Returns the template of a child to its parent.

Return type*Template***classmethod children**(*template*)

Method to list children of a template.

Return type*List[Template]***classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool***classmethod relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type*int***classmethod replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type*None***classmethod size**(*template*)

Method to return the size of this type.

Return type*int***cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_build_lab()

Returns the NT build lab string from the KDBG.

get_csdversion()

Returns the CSDVersion as an integer (i.e. Service Pack number)

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type*str*

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.windows.extensions.mbr module

class **PARTITION_ENTRY**(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: [*StructType*](#)

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**

Bases: [*VolTemplateProxy*](#)

classmethod **child_template**(*template*, *child*)

Returns the template of a child to its parent.

Return type

[*Template*](#)

classmethod children(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod size(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_bootable_flag()

Get Bootable Flag.

Return type

`int`

get_ending_chs()

Get Ending CHS (Cylinder Header Sector) Address.

Return type

`int`

get_ending_cylinder()

Get Ending Cylinder.

Return type

`int`

get_ending_sector()

Get Ending Sector.

Return type

`int`

get_partition_type()

Get Partition Type.

Return type

`str`

get_size_in_sectors()

Get Size in Sectors.

Return type

`int`

get_starting_chs()

Get Starting CHS (Cylinder Header Sector) Address.

Return type

`int`

get_starting_cylinder()

Get Starting Cylinder.

Return type

`int`

get_starting_lba()

Get Starting LBA (Logical Block Addressing).

Return type

`int`

get_starting_sector()

Get Starting Sector.

Return type

`int`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

is_bootable()

Check Bootable Partition.

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class PARTITION_TABLE(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

bool

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_disk_signature()

Get Disk Signature (GUID).

Return type

`str`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.windows.extensions.mft module

class MFTAttribute(*context, type_name, object_info, size, members*)

Bases: *StructType*

This represents an MFT ATTRIBUTE

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_resident_filecontent()

Return type

`bytes`

get_resident_filename()

Return type

`str`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property** **vol:** `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **MFTEntry**(*context*, *type_name*, *object_info*, *size*, *members*)Bases: `StructType`

This represents the base MFT Record

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**Bases: `VolTemplateProxy`**classmethod** **child_template**(*template*, *child*)

Returns the template of a child to its parent.

Return type`Template`**classmethod** **children**(*template*)

Method to list children of a template.

Return type`List[Template]`**classmethod** **has_member**(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**classmethod** **relative_child_offset**(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type`int`**classmethod** **replace_child**(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_signature()

Return type

`str`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

`object`

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class MFTFileName(*context, type_name, object_info, size, members*)

Bases: [*StructType*](#)

This represents an MFT \$FILE_NAME Attribute

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [*VolTemplateProxy*](#)

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

[*Template*](#)

classmethod children(*template*)

Method to list children of a template.

Return type

[*List\[Template\]*](#)

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

[*ObjectInterface*](#)

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_full_name()

Return type

`str`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

member(attr='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.windows.extensions.network module

inet_ntop(*address_family*, *packed_ip*)

Return type
str

volatility3.framework.symbols.windows.extensions.pe module

class IMAGE_DOS_HEADER(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template*, *child*)

Returns the template of a child to its parent.

Return type
Template

classmethod children(*template*)

Method to list children of a template.

Return type
List[Template]

classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called member_name.

Return type
bool

classmethod relative_child_offset(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type
int

classmethod replace_child(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type
None

classmethod size(*template*)

Method to return the size of this type.

Return type
int

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

fix_image_base(*raw_data*, *nt_header*)

Fix the _OPTIONAL_HEADER.ImageBase value (which is either an unsigned long for 32-bit PE's or unsigned long long for 64-bit PE's) to match the address where the PE file was carved out of memory.

Parameters

- **raw_data** (*bytes*) – a bytes object of the PE's data
- **nt_header** (*ObjectInterface*) – <_IMAGE_NT_HEADERS> or <_IMAGE_NT_HEADERS64> instance

Return type

bytes

Returns

<bytes> patched with the correct address

get_nt_header()

Carve out the NT header from this DOS header. This reflects on the PE file's Machine type to create a 32- or 64-bit NT header structure.

Return type

ObjectInterface

Returns

<_IMAGE_NT_HEADERS> or <_IMAGE_NT_HEADERS64> instance

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List*[*str*]) – List of names to test as to members with those names validity

Return type

bool

member(*attr*='member')

Specifically named method for retrieving members.

Return type

object

reconstruct()

This method generates the content necessary to reconstruct a PE file from memory. It preserves slack space (similar to the old –memory) and automatically fixes the ImageBase in the output PE file.

Return type

Generator[*Tuple*[*int*, *bytes*], *None*, *None*]

Returns

<tuple> of (<int> offset, <bytes> data)

replace_header_field(*sect*, *header*, *item*, *value*)

Replaces a member in an _IMAGE_SECTION_HEADER structure.

Parameters

- **sect** (*ObjectInterface*) – the section instance
- **header** (*bytes*) – raw data for the section
- **item** (*ObjectInterface*) – the member of the section to replace
- **value** (*int*) – new value for the member

Return type

bytes

Returns

The raw data with the replaced header field

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class IMAGE_NT_HEADERS(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_sections()

Iterate through the section headers for this PE file.

Yields

<_IMAGE_SECTION_HEADER> objects

Return type

Generator[ObjectInterface, None, None]

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property** **vol**: `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.windows.extensions.pool module**class** **ExecutiveObject**(*context*, *type_name*, *object_info*, ***kwargs*)

Bases: `ObjectInterface`

This is used as a “mixin” that provides all kernel executive objects with a means of finding their own object header.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: `object`

A container for proxied methods that the ObjectTemplate of this object will call. This is primarily to keep methods together for easy organization/management, there is no significant need for it to be a separate class.

The methods of this class *must* be class methods rather than standard methods, to allow for code reuse. Each method also takes a template since the templates may contain the necessary data about the yet-to-be-constructed object. It allows objects to control how their templates respond without needing to write new templates for each and every potential object type.

abstract classmethod child_template(*template, child*)

Returns the template of the child member from the parent.

Return type`Template`**abstract classmethod children**(*template*)

Returns the children of the template.

Return type`List[Template]`**abstract classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type`bool`**abstract classmethod relative_child_offset**(*template, child*)

Returns the relative offset from the head of the parent data to the child member.

Return type`int`**abstract classmethod replace_child**(*template, old_child, new_child*)

Substitutes the old_child for the new_child.

Return type`None`**abstract classmethod size**(*template*)

Returns the size of the template object.

Return type`int`**cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_object_header()**Return type**`OBJECT_HEADER`**get_symbol_table_name**()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Parameters

member_name (`str`) – Name to test whether a member exists within the type structure

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**property vol:** `ReadOnlyMapping`

Returns the volatility specific object information.

abstract write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class OBJECT_HEADER(*context, type_name, object_info, size, members*)

Bases: `StructType`

A class for the headers for executive kernel objects, which contains quota information, ownership details, naming data, and ACLs.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

property NameInfo: `ObjectInterface`**class VolTemplateProxy**

Bases: `VolTemplateProxy`

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_object_type(*type_map*, *cookie=None*)

Across all Windows versions, the _OBJECT_HEADER embeds details on the type of object (i.e. process, file) but the way its embedded differs between versions.

This API abstracts away those details.

Return type

`Optional[str]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_valid()

Determine if the object is valid.

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property **vol**: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **POOL_HEADER**(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: *StructType*

A kernel pool allocation header.

Exists at the base of the allocation and provides a tag that we can scan for.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod size(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_object(*constraint, use_top_down, kernel_symbol_table=None, native_layer_name=None*)

Carve an object or data structure from a kernel pool allocation

Parameters

- **constraint** (*PoolConstraint*) – a PoolConstraint object used to get the pool allocation header object
- **use_top_down** (*bool*) – for delineating how a windows version finds the size of the object body
- **kernel_symbol_table** (*Optional[str]*) – in case objects of a different symbol table are scanned for
- **native_layer_name** (*Optional[str]*) – the name of the layer where the data originally lived

Return type

Optional[ObjectInterface]

Returns

An object as found from a POOL_HEADER

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(member_name)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(member_name)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(member_names)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_free_pool()**is_nonpaged_pool()****is_paged_pool()****member(attr='member')**

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(value)

Writes the new value into the format at the offset the object currently resides at.

class `POOL_HEADER_VISTA`(*context, type_name, object_info, size, members*)

Bases: `POOL_HEADER`

A kernel pool allocation header, updated for Vista and later.

Exists at the base of the allocation and provides a tag that we can scan for.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class `VolTemplateProxy`

Bases: `VolTemplateProxy`

classmethod `child_template`(*template, child*)

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children`(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member`(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset`(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child`(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size`(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_object(*constraint*, *use_top_down*, *kernel_symbol_table=None*, *native_layer_name=None*)

Carve an object or data structure from a kernel pool allocation

Parameters

- **constraint** (*PoolConstraint*) – a PoolConstraint object used to get the pool allocation header object
- **use_top_down** (*bool*) – for delineating how a windows version finds the size of the object body
- **kernel_symbol_table** (*Optional[str]*) – in case objects of a different symbol table are scanned for
- **native_layer_name** (*Optional[str]*) – the name of the layer where the data originally lived

Return type

Optional[ObjectInterface]

Returns

An object as found from a POOL_HEADER

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in member_names

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

is_free_pool()

is_nonpaged_pool()

is_paged_pool()

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: [*ReadOnlyMapping*](#)

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class POOL_TRACKER_BIG_PAGES(*context, type_name, object_info, size, members*)

Bases: [*StructType*](#)

A kernel big page pool tracker.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** ([*ContextInterface*](#)) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** ([*ObjectInformation*](#)) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: [*VolTemplateProxy*](#)

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

[*Template*](#)

classmethod children(*template*)

Method to list children of a template.

Return type

[*List\[Template\]*](#)

classmethod has_member(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod relative_child_offset(*template, child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod replace_child(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_key()

Returns the Key value as a 4 character string

Return type

`str`

get_number_of_bytes()

Returns the NumberOfBytes value on applicable systems

Return type

`Union[int, BaseAbsentValue]`

get_pool_type()

Returns the enum name for the PoolType value on applicable systems

Return type

`Union[str, BaseAbsentValue]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

is_free()

Returns if the allocation is freed (True) or in-use (False)

Return type

bool

is_valid()

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

pool_type_lookup: *Dict[str, str]* = {}

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

volatility3.framework.symbols.windows.extensions.registry module

class CMHIVE(*context, type_name, object_info, size, members*)

Bases: *StructType*

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

`List[Template]`

classmethod has_member(*template*, *member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

classmethod relative_child_offset(*template*, *child*)

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod replace_child(*template*, *old_child*, *new_child*)

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod size(*template*)

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_name()

Determine a name for the hive.

Note that some attributes are unpredictably blank across different OS versions while others are populated, so we check all possibilities and take the first one that's not empty

Return type

`Optional[ObjectInterface]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the *table_name* is not valid within the object's context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

is_valid()

Determine if the object is valid.

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property name: *ObjectInterface* | *None*

Determine a name for the hive.

Note that some attributes are unpredictably blank across different OS versions while others are populated, so we check all possibilities and take the first one that's not empty

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class CM_KEY_BODY(*context, type_name, object_info, size, members*)

Bases: *StructType*

This represents an open handle to a registry key and is not tied to the registry hive file format on disk.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_full_key_name()

Return type

`str`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object’s symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object’s context

Return type

`str`

has_member(*member_name*)

Returns whether the object would contain a member called member_name.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class CM_KEY_NODE(*context, type_name, object_info, size, members*)

Bases: *StructType*

Extension to allow traversal of registry keys.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod child_template(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod children(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: `ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_key_path()

Return type

`str`

get_name()

Gets the name for the current key node

Return type

`ObjectInterface`

get_subkeys()

Returns a list of the key nodes.

Return type

`Iterable[ObjectInterface]`

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

`str`

get_values()

Returns a list of the Value nodes for a key.

Return type`Iterable[ObjectInterface]`**get_volatile()****Return type**`bool`**has_member**(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property** **vol:** `ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **CM_KEY_VALUE**(*context*, *type_name*, *object_info*, *size*, *members*)

Bases: `StructType`

Extensions to extract data from CM_KEY_VALUE nodes.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxyBases: *VolTemplateProxy***classmethod child_template**(*template, child*)

Returns the template of a child to its parent.

Return type*Template***classmethod children**(*template*)

Method to list children of a template.

Return type*List[Template]***classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool***classmethod relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type*int***classmethod replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type*None***classmethod size**(*template*)

Method to return the size of this type.

Return type*int***cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

decode_data()

Properly decodes the data associated with the value node

Return type*Union[int, bytes]***get_name()**

Gets the name for the current key value

Return type*ObjectInterface***get_symbol_table_name()**

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table

- **KeyError** – If the `table_name` is not valid within the object's context

Return type`str`**has_member**(*member_name*)

Returns whether the object would contain a member called `member_name`.

Return type`bool`**has_valid_member**(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members**(*member_names*)

Returns whether the object has all of the members listed in `member_names`

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**member**(*attr*='member')

Specifically named method for retrieving members.

Return type`object`**property** `vol: ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class **HMAP_ENTRY**(*context, type_name, object_info, size, members*)

Bases: `StructType`

Constructs an Object adhering to the `ObjectInterface`.

Parameters

- **context** (`ContextInterface`) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (`ObjectInformation`) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class **VolTemplateProxy**

Bases: `VolTemplateProxy`

classmethod **child_template**(*template, child*)

Returns the template of a child to its parent.

Return type*Template***classmethod children**(*template*)

Method to list children of a template.

Return type*List[Template]***classmethod has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool***classmethod relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type*int***classmethod replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type*None***classmethod size**(*template*)

Method to return the size of this type.

Return type*int***cast**(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

ObjectInterface

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_block_offset()**Return type***int***get_symbol_table_name**()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type*str***has_member**(*member_name*)

Returns whether the object would contain a member called member_name.

Return type*bool*

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (*str*) – Name of the member to test access to determine if the member is valid or not

Return type

bool

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (*List[str]*) – List of names to test as to members with those names validity

Return type

bool

member(*attr='member'*)

Specifically named method for retrieving members.

Return type

object

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class RegKeyFlags(*value, names=None, *, module=None, qualname=None, type=None, start=1, boundary=None*)

Bases: *IntEnum*

KEY_COMP_NAME = 32

KEY_HIVE_ENTRY = 4

KEY_HIVE_EXIT = 2

KEY_IS_VOLATILE = 1

KEY_NO_DELETE = 8

KEY_PREFEF_HANDLE = 64

KEY_SYM_LINK = 16

KEY_VIRTUAL_STORE = 512

KEY_VIRT_MIRRORED = 128

KEY_VIRT_TARGET = 256

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(byteorder='big', *, signed=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If `byteorder` is 'big', the most significant byte is at the beginning of the byte array. If `byteorder` is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If `signed` is `False` and a negative integer is given, an `OverflowError` is raised.

class RegValueTypes(*value, names=None, *, module=None, qualname=None, type=None, start=1, boundary=None*)

Bases: `Enum`

`REG_BINARY = 3`

`REG_DWORD = 4`

`REG_DWORD_BIG_ENDIAN = 5`

`REG_EXPAND_SZ = 2`

`REG_FULL_RESOURCE_DESCRIPTOR = 9`

`REG_LINK = 6`

`REG_MULTI_SZ = 7`

`REG_NONE = 0`

`REG_QWORD = 11`

`REG_RESOURCE_LIST = 8`

`REG_RESOURCE_REQUIREMENTS_LIST = 10`

`REG_SZ = 1`

`REG_UNKNOWN = 99999`

volatility3.framework.symbols.windows.extensions.services module

class SERVICE_HEADER(*context, type_name, object_info, size, members*)

Bases: `StructType`

A service header structure.

Constructs an Object adhering to the `ObjectInterface`.

Parameters

- **context** (`ContextInterface`) – The context associated with the object

- **type_name** (*str*) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod **child_template**(*template, child*)

Returns the template of a child to its parent.

Return type

Template

classmethod **children**(*template*)

Method to list children of a template.

Return type

List[Template]

classmethod **has_member**(*template, member_name*)

Returns whether the object would contain a member called member_name.

Return type

bool

classmethod **relative_child_offset**(*template, child*)

Returns the relative offset of a child to its parent.

Return type

int

classmethod **replace_child**(*template, old_child, new_child*)

Replace a child elements within the arguments handed to the template.

Return type

None

classmethod **size**(*template*)

Method to return the size of this type.

Return type

int

cast(*new_type_name, **additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype: *ObjectInterface*

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_symbol_table_name()

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type

str

has_member(*member_name*)

Returns whether the object would contain a member called *member_name*.

Return type

`bool`

has_valid_member(*member_name*)

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type

`bool`

has_valid_members(*member_names*)

Returns whether the object has all of the members listed in *member_names*

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type

`bool`

is_valid()

Determine if the structure is valid.

Return type

`bool`

member(*attr*='member')

Specifically named method for retrieving members.

Return type

`object`

property vol: *ReadOnlyMapping*

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

class SERVICE_RECORD(*context, type_name, object_info, size, members*)

Bases: *StructType*

A service record structure.

Constructs an Object adhering to the ObjectInterface.

Parameters

- **context** (*ContextInterface*) – The context associated with the object
- **type_name** (`str`) – The name of the type structure for the object
- **object_info** (*ObjectInformation*) – Basic information relevant to the object (layer, offset, member_name, parent, etc)

class VolTemplateProxy

Bases: *VolTemplateProxy*

classmethod `child_template(template, child)`

Returns the template of a child to its parent.

Return type

`Template`

classmethod `children(template)`

Method to list children of a template.

Return type

`List[Template]`

classmethod `has_member(template, member_name)`

Returns whether the object would contain a member called member_name.

Return type

`bool`

classmethod `relative_child_offset(template, child)`

Returns the relative offset of a child to its parent.

Return type

`int`

classmethod `replace_child(template, old_child, new_child)`

Replace a child elements within the arguments handed to the template.

Return type

`None`

classmethod `size(template)`

Method to return the size of this type.

Return type

`int`

cast(*new_type_name*, ***additional*)

Returns a new object at the offset and from the layer that the current object inhabits. :rtype:

`ObjectInterface`

Note: If new type name does not include a symbol table, the symbol table for the current object is used

get_binary()

Returns the binary associated with the service.

Return type

`Union[str, BaseAbsentValue]`

get_display()

Returns the service display.

Return type

`Union[str, BaseAbsentValue]`

get_name()

Returns the service name.

Return type

`Union[str, BaseAbsentValue]`

get_pid()

Return the pid of the process, if any.

Return type`Union[int, BaseAbsentValue]`**get_symbol_table_name()**

Returns the symbol table name for this particular object.

Raises

- **ValueError** – If the object's symbol does not contain an explicit table
- **KeyError** – If the table_name is not valid within the object's context

Return type`str`**get_type()**

Returns the binary types.

Return type`str`**has_member(member_name)**

Returns whether the object would contain a member called member_name.

Return type`bool`**has_valid_member(member_name)**

Returns whether the dereferenced type has a valid member.

Parameters

member_name (`str`) – Name of the member to test access to determine if the member is valid or not

Return type`bool`**has_valid_members(member_names)**

Returns whether the object has all of the members listed in member_names

Parameters

member_names (`List[str]`) – List of names to test as to members with those names validity

Return type`bool`**is_valid()**

Determine if the structure is valid.

Return type`bool`**member(attr='member')**

Specifically named method for retrieving members.

Return type`object`**traverse()**

Generator that enumerates other services.

property `vol: ReadOnlyMapping`

Returns the volatility specific object information.

write(*value*)

Writes the new value into the format at the offset the object currently resides at.

Submodules

volatility3.framework.symbols.windows.pdbconv module

class `ForwardArrayCount`(*size, element_type*)

Bases: `object`

class `PdbReader`(*context, location, database_name=None, progress_callback=None*)

Bases: `object`

Class to read Microsoft PDB files.

This reads the various streams according to various sources as to how pdb should be read. These sources include:

<https://docs.rs/crate/pdb/0.5.0/source/src/> <https://github.com/moyix/pdbparse> <https://llvm.org/docs/PDB/index.html> <https://github.com/Microsoft/microsoft-pdb/>

In order to generate ISF files, we need the type stream (2), and the symbols stream (variable). The MultiStream Format wrapper is handled as a volatility layer, which constructs sublayers for each stream. The streams can then be read contiguously allowing the data to be accessed.

Volatility's type system is strong when everything must be laid out in advance, but PDB data is reasonably dynamic, particularly when it comes to names. We must therefore parse it after we've collected other information already. This is in comparison to something such as Construct/pdbparse which can use just-parsed data to determine dynamically sized data following.

consume_padding(*layer_name, offset*)

Returns the amount of padding used between fields.

Return type

`int`

consume_type(*module, offset, length*)

Returns a (leaf_type, name, object) Tuple for a type, and the number of bytes consumed.

Return type

`Tuple[Tuple[Optional[ObjectInterface], Optional[str], Union[None, List, ObjectInterface]], int]`

property `context`

convert_bytes_to_guid(*original*)

Convert the bytes to the correct ordering for a GUID.

Return type

`str`

convert_fields(*fields*)

Converts a field list into a list of fields.

Return type

`Dict[Optional[str], Dict[str, Any]]`

determine_extended_value(*leaf_type, value, module, length*)

Reads a value and potentially consumes more data to construct the value.

Return type

`Tuple[str, ObjectInterface, int]`

get_json()

Returns the intermediate format JSON data from this pdb file.

get_size_from_index(*index*)

Returns the size of the structure based on the type index provided.

Return type

`int`

get_type_from_index(*index*)

Takes a type index and returns appropriate dictionary.

Return type

`Union[List[Any], Dict[str, Any]]`

classmethod load_pdb_layer(*context, location*)

Loads a PDB file into a layer within the context and returns the name of the new layer.

Note: the context may be changed by this method

Return type

`Tuple[str, ContextInterface]`

name_strip(*name*)

Strips unnecessary components from the start of a symbol name.

omap_lookup(*address*)

Looks up an address using the omap mapping.

static parse_string(*structure, parse_as_pascal=False, size=0*)

Consumes either a c-string or a pascal string depending on the leaf_type.

Return type

`str`

property pdb_layer_name

process_types(*type_references*)

Reads the TPI and symbol streams to populate the reader's variables.

Return type

`None`

read_dbi_stream()

Reads the DBI Stream.

Return type

`None`

read_ipi_stream()

read_necessary_streams()

Read streams to populate the various internal components for a PDB table.

read_pdb_info_stream()

Reads in the pdb information stream.

read_symbol_stream()

Reads in the symbol stream.

read_tpi_stream()

Reads the TPI type steam.

Return type

`None`

replace_forward_references(*types, type_references*)

Finds all ForwardArrayCounts and calculates them once ForwardReferences have been resolved.

reset()

```
type_handlers = {'LF_ARGLIST': ('LF_ENUM', True, None), 'LF_ARRAY': ('LF_ARRAY',
True, 'size'), 'LF_ARRAY_ST': ('LF_ARRAY', True, 'size'), 'LF_BITFIELD':
('LF_BITFIELD', False, None), 'LF_BUILDINFO': ('LF_BUILDINFO', False, None),
'LF_CLASS': ('LF_STRUCTURE', True, 'size'), 'LF_CLASS_ST': ('LF_STRUCTURE', True,
'size'), 'LF_CLASS_VS19': ('LF_STRUCTURE_VS19', True, 'size'), 'LF_ENUM':
('LF_ENUM', True, None), 'LF_ENUMERATE': ('LF_ENUMERATE', True, 'value'),
'LF_FIELDLIST': ('LF_FIELDLIST', False, None), 'LF_FUNC_ID': ('LF_FUNC_ID', True,
None), 'LF_INTERFACE': ('LF_STRUCTURE', True, 'size'), 'LF_MEMBER': ('LF_MEMBER',
True, 'offset'), 'LF_MEMBER_ST': ('LF_MEMBER', True, 'offset'), 'LF_MODIFIER':
('LF_MODIFIER', False, None), 'LF_POINTER': ('LF_POINTER', False, None),
'LF_PROCEDURE': ('LF_PROCEDURE', False, None), 'LF_STRIDED_ARRAY': ('LF_ARRAY',
True, 'size'), 'LF_STRING_ID': ('LF_STRING_ID', True, None), 'LF_STRUCTURE':
('LF_STRUCTURE', True, 'size'), 'LF_STRUCTURE_ST': ('LF_STRUCTURE', True, 'size'),
'LF_STRUCTURE_VS19': ('LF_STRUCTURE_VS19', True, 'size'), 'LF_UDT_MOD_SRC_LINE':
('LF_UDT_MOD_SRC_LINE', False, None), 'LF_UDT_SRC_LINE': ('LF_UDT_SRC_LINE', False,
None), 'LF_UNION': ('LF_UNION', True, None)}
```

class PdbRetreiver

Bases: `object`

retreive_pdb(*guid, file_name, progress_callback=None*)

Return type

`Optional[str]`

volatility3.framework.symbols.windows.pdbutil module

class PDBUtility(*args, **kwargs)

Bases: `VersionableInterface`

Class to handle and manage all getting symbols based on MZ header

classmethod download_pdb_isf(*context, guid, age, pdb_name, progress_callback=None*)

Attempts to download the PDB file, convert it to an ISF file and save it to one of the symbol locations.

Return type

`None`

classmethod `get_guid_from_mz(context, layer_name, offset)`

Takes the offset to an MZ header, locates any available pdb headers, and extracts the guid, age and pdb_name from them

Parameters

- **context** (*ContextInterface*) – The context on which to operate
- **layer_name** (*str*) – The name of the (contiguous) layer within the context that contains the MZ file
- **offset** (*int*) – The offset in the layer at which the MZ file begins

Return type

Optional[*Tuple*[*str*, *int*, *str*]]

Returns

A tuple of the guid, age and pdb_name, or None if no PDB record can be found

classmethod `load_windows_symbol_table(context, guid, age, pdb_name, symbol_table_class, config_path='pdbutility', progress_callback=None)`

Loads (downloading if necessary) a windows symbol table

classmethod `module_from_pdb(context, config_path, layer_name, pdb_name, module_offset=None, module_size=None)`

Creates a module in the specified layer_name based on a pdb name.

Searches the memory section of the loaded module for its PDB GUID and loads the associated symbol table into the symbol space.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **config_path** (*str*) – The config path where to find symbol files
- **layer_name** (*str*) – The name of the layer on which to operate
- **module_offset** (*int*) – This memory dump's module image offset
- **module_size** (*int*) – The size of the module for this dump

Return type

str

Returns

The name of the constructed and loaded symbol table

classmethod `pdbname_scan(ctx, layer_name, page_size, pdb_names, progress_callback=None, start=None, end=None, maximum_invalid_count=100)`

Scans through *layer_name* at *ctx* looking for RSDS headers that indicate one of four common pdb kernel names (as listed in *self.pdb_names*) and returns the tuple (GUID, age, pdb_name, signature_offset, mz_offset) :rtype: *Generator*[*Dict*[*str*, *Union*[*bytes*, *str*, *int*, *None*]], *None*, *None*]

Note: This is automagical and therefore not guaranteed to provide correct results.

The UI should always provide the user an opportunity to specify the appropriate types and PDB values themselves :type layer_name: *str* :param layer_name: The layer name to scan :type page_size: *int* :param page_size: Size of page constant :type pdb_names: *List*[*bytes*] :param pdb_names: List of pdb names to scan :type progress_callback: *Optional*[*Callable*[[*float*, *str*], *None*]] :param progress_callback:

Means of providing the user with feedback during long processes :type start: `Optional[int]` :param start: Start address to start scanning from the pdb_names :type end: `Optional[int]` :param end: Minimum address to scan the pdb_names :type maximum_invalid_count: `int` :param maximum_invalid_count: Amount of pages that can be invalid during scanning before aborting signature search

```
classmethod symbol_table_from_offset(context, layer_name, offset, symbol_table_class='volatility3.framework.symbols.intermed.IntermediateSymbolTable',
                                     config_path=None, progress_callback=None)
```

Produces the name of a symbol table loaded from the offset for an MZ header

Parameters

- **context** (`ContextInterface`) – The context on which to operate
- **layer_name** (`str`) – The name of the (contiguous) layer within the context that contains the MZ file
- **offset** (`int`) – The offset in the layer at which the MZ file begins
- **symbol_table_class** (`str`) – The class to use when constructing the SymbolTable
- **config_path** (`str`) – New path for the produced symbol table configuration with the config tree
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – Callable called to update ongoing progress

Return type

`Optional[str]`

Returns

None if no pdb information can be determined, else returned the name of the loaded symbols for the MZ

```
classmethod symbol_table_from_pdb(context, config_path, layer_name, pdb_name,
                                  module_offset=None, module_size=None)
```

Creates symbol table for a module in the specified layer_name.

Searches the memory section of the loaded module for its PDB GUID and loads the associated symbol table into the symbol space.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **config_path** (`str`) – The config path where to find symbol files
- **layer_name** (`str`) – The name of the layer on which to operate
- **module_offset** (`int`) – This memory dump's module image offset
- **module_size** (`int`) – The size of the module for this dump

Return type

`str`

Returns

The name of the constructed and loaded symbol table

version = (1, 0, 1)

class `PdbSignatureScanner`(*pdb_names*)

Bases: `ScannerInterface`

A `ScannerInterface` based scanner use to identify Windows PDB records.

Parameters

pdb_names (`List[bytes]`) – A list of bytestrings, used to match pdb signatures against the pdb names within the records.

Note: The `pdb_names` must be a list of byte strings, unicode strs will not match against the data scanned

property context: `ContextInterface` | `None`

property layer_name: `str` | `None`

overlap = 16384

The size of overlap needed for the signature to ensure data cannot hide between two scanned chunks

thread_safe = `True`

Determines whether the scanner accesses global variables in a thread safe manner (for use with `multiprocessing`)

version = (`0`, `0`, `0`)

volatility3.framework.symbols.windows.versions module

class `OsDistinguisher`(*version_check*, *fallback_checks*)

Bases: `object`

Distinguishes a symbol table as being above a particular version or point.

This will primarily check the version metadata first and foremost. If that metadata isn't available then each item in the `fallback_checks` is tested. If `invert` is specified then the result will be true if the version is less than that specified, or in the case of fallback, if any of the fallback checks is successful.

A fallback check is made up of:

- a symbol or type name
- a member name (implying that the value before was a type name)
- whether that symbol, type or member must be present or absent for the symbol table to be more above the required point

Note: Specifying that a member must not be present includes the whole type not being present too (ie, either will pass the test)

Parameters

- **version_check** (`Callable[[Tuple[int, ...], bool]]`) – Function that takes a 4-tuple version and returns whether whether the provided version is above a particular point
- **fallback_checks** (`List[Tuple[str, Optional[str], bool]]`) – A list of symbol/types/members of types, and whether they must be present to be above the required point

Returns

A function that takes a context and a symbol table name and determines whether that symbol table passes the distinguishing checks

Submodules**volatility3.framework.symbols.intermed module**

class ISFormatTable(*context, config_path, name, json_object, native_types=None, table_mapping=None*)

Bases: *SymbolTableInterface*

Provide a base class to identify all subclasses.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (*ContextInterface*) – The volatility context for the symbol table
- **config_path** (*str*) – The configuration path for the symbol table
- **name** (*str*) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (*NativeTableInterface*) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (*Optional[Dict[str, str]]*) – A dictionary linking names referenced in the file with symbol tables in the context
- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(*name*)

Removes the associated class override for a specific Symbol type.

Return type

`None`

property enumerations: `Iterable[Any]`

Returns an iterator of the Enumeration names.

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

`List[RequirementInterface]`

get_symbol(*name*)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

Return type

`SymbolInterface`

get_symbol_type(*name*)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching type_name.

Return type

`Iterable[str]`

get_type(*name*)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a SymbolError exception

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration

- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface` | `None`

Returns a metadata object containing information about the symbol table.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: `ProducerMetadata` | `None`

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type

`None`

property symbols: `Iterable[str]`

Returns an iterator of the Symbol names.

property types: `Iterable[str]`

Returns an iterator of the Symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

```
version = (0, 0, 0)
```

```
class IntermediateSymbolTable(context, config_path, name, isf_url, native_types=None,
                              table_mapping=None, validate=True, class_types=None, symbol_mask=0)
```

Bases: *SymbolTableInterface*

The IntermediateSymbolTable class reads a JSON file and conducts common tasks such as validation, construction by looking up a JSON file from the available files and ensuring the appropriate version of the schema and proxy are chosen.

The JSON format itself is made up of various groups (symbols, user_types, base_types, enums and metadata)

- Symbols link a name to a particular offset relative to the start of a section of memory
- Base types define the simplest primitive data types, these can make more complex structure
- User types define the more complex types by specifying members at a relative offset from the start of the type
- Enums can specify a list of names and values and a type inside which the numeric encoding will fit
- Metadata defines information about the originating file

These are documented in JSONSchema JSON files located in volatility3/schemas.

Instantiates a SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema. The validation can be disabled by passing validate = False, but this should almost never be done.

Parameters

- **context** (*ContextInterface*) – The volatility context for the symbol table
- **config_path** (*str*) – The configuration path for the symbol table
- **name** (*str*) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** (*str*) – The URL pointing to the ISF file location
- **native_types** (*NativeTableInterface*) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (*Optional[Dict[str, str]]*) – A dictionary linking names referenced in the file with symbol tables in the context
- **validate** (*bool*) – Determines whether the ISF file will be validated against the appropriate schema
- **class_types** (*Optional[Mapping[str, Type[ObjectInterface]]]*) – A dictionary of type names and classes that override StructType when they are instantiated
- **symbol_mask** (*int*) – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache(*args, **kwargs)

Clears the symbol cache of this symbol table.

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod create(context, config_path, sub_path, filename, native_types=None, table_mapping=None, class_types=None, symbol_mask=0)

Takes a context and loads an intermediate symbol table based on a filename.

Parameters

- **context** (*ContextInterface*) – The context that the current plugin is being run within
- **config_path** (*str*) – The configuration path for reading/storing configuration information this symbol table may use
- **sub_path** (*str*) – The path under a suitable symbol path (defaults to volatility3/symbols and volatility3/framework/symbols) to check
- **filename** (*str*) – Basename of the file to find under the sub_path
- **native_types** (*Optional[NativeTableInterface]*) – Set of native types, defaults to native types read from the intermediate symbol format file
- **table_mapping** (*Optional[Dict[str, str]]*) – a dictionary of table names mentioned within the ISF file, and the tables within the context which they map to
- **symbol_mask** (*int*) – An address mask used for all returned symbol offsets from this table (a mask of 0 disables masking)

Return type

str

Returns

the name of the added symbol table

del_type_class(*args, **kwargs)

Removes the associated class override for a specific Symbol type.

property enumerations

Returns an iterator of the Enumeration names.

classmethod file_symbol_url(sub_path, filename=None)

Returns an iterator of appropriate file-scheme symbol URLs that can be opened by a ResourceAccessor class.

Filter reduces the number of results returned to only those URLs containing that string

Return type

Generator[str, None, None]

get_enumeration(*args, **kwargs)

classmethod `get_requirements()`

Returns a list of RequirementInterface objects required by this object.

Return type

`List[RequirementInterface]`

get_symbol(*args, **kwargs)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a SymbolError exception

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(offset, size=0)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(type_name)

Returns the name of all symbols in this table that have type matching type_name.

Return type

`Iterable[str]`

get_type(*args, **kwargs)

Resolves a symbol name into an object template.

If the symbol isn't found it raises a SymbolError exception

get_type_class(*args, **kwargs)

Returns the class associated with a Symbol type.

classmethod `make_subconfig`(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type`bool`**property producer****set_type_class**(**args*, ***kwargs*)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`

Parameters

- **name** – The name of the type to override the class for
- **clazz** – The actual class to override for the provided type name

property symbols

Returns an iterator of the Symbol names.

property types

Returns an iterator of the Symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`**class Version1Format**(*context*, *config_path*, *name*, *json_object*, *native_types=None*, *table_mapping=None*)

Bases: `ISFormatTable`

Class for storing intermediate debugging data as objects and classes.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (`ContextInterface`) – The volatility context for the symbol table
- **config_path** (`str`) – The configuration path for the symbol table
- **name** (`str`) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (`NativeTableInterface`) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (`Optional[Dict[str, str]]`) – A dictionary linking names referenced in the file with symbol tables in the context

- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the available enumerations.

get_enumeration(enum_name)

Resolves an individual enumeration.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(name)

Returns the location offset given by the symbol name.

Return type

SymbolInterface

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

Optional[Template]

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves an individual symbol.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface` | `None`

Returns a metadata object containing information about the symbol table.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: `ProducerMetadata` | `None`

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (*str*) – The name of the type to override the class for
- **clazz** (*Type[ObjectInterface]*) – The actual class to override for the provided type name

Return type

None

property symbols: *Iterable[str]*

Returns an iterator of the symbol names.

property types: *Iterable[str]*

Returns an iterator of the symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 1)

class Version2Format(*context*, *config_path*, *name*, *json_object*, *native_types=None*, *table_mapping=None*)

Bases: *Version1Format*

Class for storing intermediate debugging data as objects and classes.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (*ContextInterface*) – The volatility context for the symbol table
- **config_path** (*str*) – The configuration path for the symbol table
- **name** (*str*) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (*NativeTableInterface*) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (*Optional[Dict[str, str]]*) – A dictionary linking names referenced in the file with symbol tables in the context
- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the available enumerations.

get_enumeration(enum_name)

Resolves an individual enumeration.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(name)

Returns the location offset given by the symbol name.

Return type

SymbolInterface

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

Optional[Template]

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves an individual symbol.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface` | `None`

Returns a metadata object containing information about the symbol table.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: `ProducerMetadata` | `None`

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (*str*) – The name of the type to override the class for
- **clazz** (*Type[ObjectInterface]*) – The actual class to override for the provided type name

Return type

None

property symbols: *Iterable[str]*

Returns an iterator of the symbol names.

property types: *Iterable[str]*

Returns an iterator of the symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (2, 0, 0)

class Version3Format(*context*, *config_path*, *name*, *json_object*, *native_types=None*, *table_mapping=None*)

Bases: *Version2Format*

Class for storing intermediate debugging data as objects and classes.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (*ContextInterface*) – The volatility context for the symbol table
- **config_path** (*str*) – The configuration path for the symbol table
- **name** (*str*) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (*NativeTableInterface*) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (*Optional[Dict[str, str]]*) – A dictionary linking names referenced in the file with symbol tables in the context
- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the available enumerations.

get_enumeration(enum_name)

Resolves an individual enumeration.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(name)

Returns the symbol given by the symbol name.

Return type

SymbolInterface

get_symbol_type(name)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

Optional[Template]

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves an individual symbol.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface` | `None`

Returns a metadata object containing information about the symbol table.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: `ProducerMetadata` | `None`

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (*str*) – The name of the type to override the class for
- **clazz** (*Type[ObjectInterface]*) – The actual class to override for the provided type name

Return type

None

property symbols: *Iterable[str]*

Returns an iterator of the symbol names.

property types: *Iterable[str]*

Returns an iterator of the symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (2, 1, 0)

class Version4Format(*context*, *config_path*, *name*, *json_object*, *native_types=None*, *table_mapping=None*)

Bases: *Version3Format*

Class for storing intermediate debugging data as objects and classes.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (*ContextInterface*) – The volatility context for the symbol table
- **config_path** (*str*) – The configuration path for the symbol table
- **name** (*str*) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (*NativeTableInterface*) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (*Optional[Dict[str, str]]*) – A dictionary linking names referenced in the file with symbol tables in the context
- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the available enumerations.

```
format_mapping = {'bool': <class 'volatility3.framework.objects.Boolean'>, 'char':
<class 'volatility3.framework.objects.Char'>, 'float': <class
'volatility3.framework.objects.Float'>, 'int': <class
'volatility3.framework.objects.Integer'>, 'void': <class
'volatility3.framework.objects.Integer'>}
```

get_enumeration(enum_name)

Resolves an individual enumeration.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(name)

Returns the symbol given by the symbol name.

Return type

SymbolInterface

get_symbol_type(*name*)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves an individual symbol.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface | None`

Returns a metadata object containing information about the symbol table.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: *ProducerMetadata* | *None*

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (*str*) – The name of the type to override the class for
- **clazz** (*Type[ObjectInterface]*) – The actual class to override for the provided type name

Return type

None

property symbols: *Iterable[str]*

Returns an iterator of the symbol names.

property types: *Iterable[str]*

Returns an iterator of the symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (4, 0, 0)

class Version5Format(*context*, *config_path*, *name*, *json_object*, *native_types=None*, *table_mapping=None*)

Bases: *Version4Format*

Class for storing intermediate debugging data as objects and classes.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (*ContextInterface*) – The volatility context for the symbol table
- **config_path** (*str*) – The configuration path for the symbol table
- **name** (*str*) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (*NativeTableInterface*) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (*Optional[Dict[str, str]]*) – A dictionary linking names referenced in the file with symbol tables in the context

- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the available enumerations.

```
format_mapping = {'bool': <class 'volatility3.framework.objects.Boolean'>, 'char':  
<class 'volatility3.framework.objects.Char'>, 'float': <class  
'volatility3.framework.objects.Float'>, 'int': <class  
'volatility3.framework.objects.Integer'>, 'void': <class  
'volatility3.framework.objects.Integer'>}
```

get_enumeration(enum_name)

Resolves an individual enumeration.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(name)

Returns the symbol given by the symbol name.

Return type

SymbolInterface

get_symbol_type(*name*)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves an individual symbol.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface | None`

Returns a metadata object containing information about the symbol table.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: `ProducerMetadata | None`

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type

`None`

property symbols: `Iterable[str]`

Returns an iterator of the symbol names.

property types: `Iterable[str]`

Returns an iterator of the symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (4, 1, 0)

class Version6Format(*context*, *config_path*, *name*, *json_object*, *native_types=None*, *table_mapping=None*)

Bases: `Version5Format`

Class for storing intermediate debugging data as objects and classes.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (`ContextInterface`) – The volatility context for the symbol table
- **config_path** (`str`) – The configuration path for the symbol table
- **name** (`str`) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (`NativeTableInterface`) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (`Optional[Dict[str, str]]`) – A dictionary linking names referenced in the file with symbol tables in the context

- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the available enumerations.

```
format_mapping = {'bool': <class 'volatility3.framework.objects.Boolean'>, 'char':
<class 'volatility3.framework.objects.Char'>, 'float': <class
'volatility3.framework.objects.Float'>, 'int': <class
'volatility3.framework.objects.Integer'>, 'void': <class
'volatility3.framework.objects.Integer'>}
```

get_enumeration(enum_name)

Resolves an individual enumeration.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(name)

Returns the symbol given by the symbol name.

Return type

SymbolInterface

get_symbol_type(*name*)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves an individual symbol.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface` | `None`

Returns a MetadataInterface object.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: `ProducerMetadata` | `None`

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type

`None`

property symbols: `Iterable[str]`

Returns an iterator of the symbol names.

property types: `Iterable[str]`

Returns an iterator of the symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (6, 0, 0)

class Version7Format(*context*, *config_path*, *name*, *json_object*, *native_types=None*, *table_mapping=None*)

Bases: `Version6Format`

Class for storing intermediate debugging data as objects and classes.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (`ContextInterface`) – The volatility context for the symbol table
- **config_path** (`str`) – The configuration path for the symbol table
- **name** (`str`) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (`NativeTableInterface`) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (`Optional[Dict[str, str]]`) – A dictionary linking names referenced in the file with symbol tables in the context

- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the available enumerations.

```
format_mapping = {'bool': <class 'volatility3.framework.objects.Boolean'>, 'char':  
<class 'volatility3.framework.objects.Char'>, 'float': <class  
'volatility3.framework.objects.Float'>, 'int': <class  
'volatility3.framework.objects.Integer'>, 'void': <class  
'volatility3.framework.objects.Integer'>}
```

get_enumeration(enum_name)

Resolves an individual enumeration.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(name)

Returns the symbol given by the symbol name.

Return type

SymbolInterface

get_symbol_type(*name*)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves an individual symbol.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface` | `None`

Returns a MetadataInterface object.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: `ProducerMetadata | None`

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type

`None`

property symbols: `Iterable[str]`

Returns an iterator of the symbol names.

property types: `Iterable[str]`

Returns an iterator of the symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (6, 1, 0)

class Version8Format(*context*, *config_path*, *name*, *json_object*, *native_types=None*, *table_mapping=None*)

Bases: `Version7Format`

Class for storing intermediate debugging data as objects and classes.

Instantiates an SymbolTable based on an IntermediateSymbolFormat JSON file. This is validated against the appropriate schema.

Parameters

- **context** (`ContextInterface`) – The volatility context for the symbol table
- **config_path** (`str`) – The configuration path for the symbol table
- **name** (`str`) – The name for the symbol table (this is used in symbols e.g. table!symbol)
- **isf_url** – The URL pointing to the ISF file location
- **native_types** (`NativeTableInterface`) – The NativeSymbolTable that contains the native types for this symbol table
- **table_mapping** (`Optional[Dict[str, str]]`) – A dictionary linking names referenced in the file with symbol tables in the context

- **class_types** – A dictionary of type names and classes that override StructType when they are instantiated

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

clear_symbol_cache()

Clears the symbol cache of the symbol table.

Return type

None

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

del_type_class(name)

Removes the associated class override for a specific Symbol type.

Return type

None

property enumerations: *Iterable[str]*

Returns an iterator of the available enumerations.

```
format_mapping = {'bool': <class 'volatility3.framework.objects.Boolean'>, 'char':
<class 'volatility3.framework.objects.Char'>, 'float': <class
'volatility3.framework.objects.Float'>, 'int': <class
'volatility3.framework.objects.Integer'>, 'void': <class
'volatility3.framework.objects.Integer'>}
```

get_enumeration(enum_name)

Resolves an individual enumeration.

Return type

Template

classmethod get_requirements()

Returns a list of RequirementInterface objects required by this object.

Return type

List[RequirementInterface]

get_symbol(name)

Returns the symbol given by the symbol name.

Return type

SymbolInterface

get_symbol_type(*name*)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(*offset*, *size=0*)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves an individual symbol.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property metadata: `MetadataInterface` | `None`

Returns a MetadataInterface object.

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

property producer: `ProducerMetadata | None`

Returns a metadata object containing information about the symbol table.

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in self.types

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type

`None`

property symbols: `Iterable[str]`

Returns an iterator of the symbol names.

property types: `Iterable[str]`

Returns an iterator of the symbol type names.

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (6, 2, 0)

volatility3.framework.symbols.metadata module

class LinuxMetadata(*json_data*)

Bases: `MetadataInterface`

Class to handle the metadata from a Linux symbol table.

Constructor that accepts json_data.

class ProducerMetadata(*json_data*)

Bases: `MetadataInterface`

Class to handle the Producer metadata from an ISF

Constructor that accepts json_data.

property datetime: `datetime | None`

Returns a timestamp for when the file was produced

property name: `str | None`

property version: `Tuple[int] | None`

Returns the version of the ISF file producer

class WindowsMetadata(*json_data*)

Bases: `MetadataInterface`

Class to handle the metadata from a Windows symbol table.

Constructor that accepts *json_data*.

property pdb_age: `int | None`

property pdb_guid: `str | None`

property pe_version: `Tuple[int, int, int] | Tuple[int, int, int, int] | None`

property pe_version_string: `str | None`

volatility3.framework.symbols.native module

class NativeTable(*name, native_dictionary*)

Bases: `NativeTableInterface`

Symbol List that handles Native types.

Parameters

- **name** (`str`) – Name of the symbol table
- **native_types** – The native symbol table used to resolve any base/native types
- **table_mapping** – A dictionary mapping names of tables (which when present within the table will be changed to the mapped table)
- **class_types** – A dictionary of types and classes that should be instantiated instead of Struct to construct them

clear_symbol_cache()

Clears the symbol cache of this symbol table.

Return type

`None`

del_type_class(*name*)

Removes the associated class override for a specific Symbol type.

Return type

`None`

property enumerations: `Iterable[str]`

Returns an iterator of the Enumeration names.

get_enumeration(*name*)

Return type

`Template`

get_symbol(*name*)

Resolves a symbol name into a symbol object.

If the symbol isn't found, it raises a `SymbolError` exception

Return type

`SymbolInterface`

get_symbol_type(*name*)

Resolves a symbol name into a symbol and then resolves the symbol's type.

Return type

`Optional[Template]`

get_symbols_by_location(*offset*, *size*=0)

Returns the name of all symbols in this table that live at a particular offset.

Return type

`Iterable[str]`

get_symbols_by_type(*type_name*)

Returns the name of all symbols in this table that have type matching *type_name*.

Return type

`Iterable[str]`

get_type(*type_name*)

Resolves a symbol name into an object template.

This always construct a new python object, rather than using a cached value otherwise changes made later may affect the cached copy. Calling clone after every native type construction was extremely slow.

Return type

`Template`

get_type_class(*name*)

Returns the class associated with a Symbol type.

Return type

`Type[ObjectInterface]`

property natives: `NativeTableInterface`

Returns None or a NativeTable for handling space specific native types.

optional_set_type_class(*name*, *clazz*)

Calls the `set_type_class` function but does not throw an exception. Returns whether setting the type class was successful. :type name: `str` :param name: The name of the type to override the class for :type clazz: `Type[ObjectInterface]` :param clazz: The actual class to override for the provided type name

Return type

`bool`

set_type_class(*name*, *clazz*)

Overrides the object class for a specific Symbol type.

Name *must* be present in `self.types`

Parameters

- **name** (`str`) – The name of the type to override the class for
- **clazz** (`Type[ObjectInterface]`) – The actual class to override for the provided type name

Return type`None`**property symbols:** `Iterable[str]`

Returns an iterator of the Symbol names.

property types: `Iterable[str]`

Returns an iterator of the symbol type names.

volatility3.framework.symbols.wrappers module**class** `Flags(choices)`Bases: `object`

Object that converts an integer into a set of flags based on their masks.

property choices: `ReadOnlyMapping`**Submodules****volatility3.framework.exceptions module**

A list of potential exceptions that volatility can throw.

These include exceptions that can be thrown on errors by the symbol space or symbol tables, and by layers when an address is invalid. The `PagedInvalidAddressException` contains information about the size of the invalid page.

exception `InvalidAddressException(layer_name, invalid_address, *args)`Bases: `LayerException`

Thrown when an address is not valid in the layer it was requested.

add_note()

Exception.add_note(note) – add a note to the exception

args**with_traceback()**

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `LayerException(layer_name, *args)`Bases: `VolatilityException`

Thrown when an error occurs dealing with memory and layers.

add_note()

Exception.add_note(note) – add a note to the exception

args**with_traceback()**

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `MissingModuleException(module, *args)`Bases: `VolatilityException`

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception OfflineException(url, *args)

Bases: [VolatilityException](#)

Throw when a remote resource is requested but Volatility is in offline mode

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception PagedInvalidAddressException(layer_name, invalid_address, invalid_bits, entry, *args)

Bases: [InvalidAddressException](#)

Thrown when an address is not valid in the paged space in which it was request. This is a subclass of [InvalidAddressException](#) and is only thrown from a paged layer. In most circumstances [InvalidAddressException](#) is the correct exception to throw, since this will catch all invalid mappings (including paged ones).

Includes the invalid address and the number of bits of the address that are invalid

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception PluginRequirementException

Bases: [VolatilityException](#)

Class to allow plugins to indicate that a requirement has not been fulfilled.

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception PluginVersionException

Bases: [VolatilityException](#)

Class to allow determining that a required plugin has an invalid version.

add_note()

Exception.add_note(note) – add a note to the exception

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception SwappedInvalidAddressException(*layer_name, invalid_address, invalid_bits, entry, swap_offset, *args*)

Bases: [*PagedInvalidAddressException*](#)

Thrown when an address is not valid in the paged layer in which it was requested, but expected to be in an associated swap layer.

Includes the swap lookup, as well as the invalid address and the bits of the lookup that were invalid.

add_note()

Exception.add_note(note) – add a note to the exception

args**with_traceback()**

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception SymbolError(*symbol_name, table_name, *args*)

Bases: [*VolatilityException*](#)

Thrown when a symbol lookup has failed.

add_note()

Exception.add_note(note) – add a note to the exception

args**with_traceback()**

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception SymbolSpaceError

Bases: [*VolatilityException*](#)

Thrown when an error occurs dealing with Symbolspaces and SymbolTables.

add_note()

Exception.add_note(note) – add a note to the exception

args**with_traceback()**

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception UnsatisfiedException(*unsatisfied*)

Bases: [*VolatilityException*](#)

add_note()

Exception.add_note(note) – add a note to the exception

args**with_traceback()**

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception VolatilityException

Bases: [*Exception*](#)

Class to allow filtering of all VolatilityExceptions.

add_note()

Exception.add_note(note) – add a note to the exception

args**with_traceback()**

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

10.1.3 volatility3.plugins package

Defines the plugin architecture.

This is the namespace for all volatility plugins, and determines the path for loading plugins

NOTE: This file is important for core plugins to run (which certain components such as the windows registry layers) are dependent upon, please DO NOT alter or remove this file unless you know the consequences of doing so.

The framework is configured this way to allow plugin developers/users to override any plugin functionality whether existing or new.

Subpackages

volatility3.plugins.linux package

All Linux-related plugins.

NOTE: This file is important for core plugins to run (which certain components such as the windows registry layers) are dependent upon, please DO NOT alter or remove this file unless you know the consequences of doing so.

The framework is configured this way to allow plugin developers/users to override any plugin functionality whether existing or new.

When overriding the plugins directory, you must include a file like this in any subdirectories that may be necessary.

Submodules

volatility3.plugins.linux.bash module

A module containing a collection of plugins that produce data typically found in Linux's /proc file system.

class Bash(context, config_path, progress_callback=None)

Bases: [PluginInterface](#), [TimeLinerInterface](#)

Recovers bash command history from memory.

Parameters

- **context** ([ContextInterface](#)) – The context that the plugin will operate within
- **config_path** ([str](#)) – The path to configuration data within the context configuration data
- **progress_callback** ([Optional](#)[[Callable](#)[[[float](#), [str](#)], [None](#)]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.capabilities module

class Capabilities(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Lists process capabilities

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `get_task_capabilities(task)`

Returns a tuple with the task basic information along with its capabilities

Parameters

task (*ObjectInterface*) – A task object from where to get the fields.

Return type

`Tuple[TaskData, CapabilitiesData]`

Returns

A tuple with the task basic information and its capabilities

classmethod `get_tasks_capabilities(tasks)`

Yields a tuple for each task containing the task's basic information along with its capabilities

Parameters

tasks (*List[ObjectInterface]*) – An iterable with the tasks to process.

Yields

A tuple for each task containing the task's basic information and its capabilities

Return type

`Iterable[Tuple[TaskData, CapabilitiesData]]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod **unsatisfied**(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 0, 0)

class **CapabilitiesData**(*cap_inheritable*, *cap_permitted*, *cap_effective*, *cap_bset*, *cap_ambient*)

Bases: `object`

Stores each set of capabilities for a task

astuple()

Returns a shallow copy of the capability sets in a tuple.

Otherwise, when `dataclasses.astuple()` performs a deep-copy recursion on `ObjectInterface` will take a substantial amount of time.

Return type

`Tuple`

cap_ambient: `ObjectInterface`

cap_bset: `ObjectInterface`

cap_effective: `ObjectInterface`

cap_inheritable: `ObjectInterface`

cap_permitted: `ObjectInterface`

class **TaskData**(*comm*, *pid*, *tgid*, *ppid*, *euid*)

Bases: `object`

Stores basic information about a task

comm: `str`

euid: `int`

pid: `int`

ppid: `int`

tgid: `int`

volatility3.plugins.linux.check_afinfo module

A module containing a collection of plugins that produce data typically found in Linux's /proc file system.

class **Check_afinfo**(*context*, *config_path*, *progress_callback*=None)

Bases: *PluginInterface*

Verifies the operation function pointers of network protocols.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], None]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[*RequirementInterface*]

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.check_creds module

class Check_creds(context, config_path, progress_callback=None)

Bases: *PluginInterface*

Checks if any processes are sharing credential structures

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type*None***classmethod unsatisfied**(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]``version = (0, 0, 0)`**volatility3.plugins.linux.check_idt module****class** `Check_idt(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Checks if the IDT has been altered

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`**classmethod make_subconfig(context, base_config_path, **kwargs)**

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration

- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.check_modules module

class Check_modules(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Compares module list to sysfs info, if available

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data

- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_kset_modules(*context, vmlinux_name*)

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.check_syscall module

A module containing a collection of plugins that produce data typically found in Linux's /proc file system.

class Check_syscall(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Check system call table for hooks.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

`version = (0, 0, 0)`

volatility3.plugins.linux.elfs module

A module containing a collection of plugins that produce data typically found in Linux's /proc file system.

class `Elf`(*context*, *config_path*, *progress_callback*=None)

Bases: `PluginInterface`

Lists all memory mapped ELF files for all processes.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

`build_configuration()`

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `elf_dump`(*context*, *layer_name*, *elf_table_name*, *vma*, *task*, *open_method*)

Extracts an ELF as a FileHandlerInterface :type context: `ContextInterface` :param context: the context to operate upon :type layer_name: `str` :param layer_name: The name of the layer on which to operate :type elf_table_name: `str` :param elf_table_name: the name for the symbol table containing the symbols for ELF-files :type vma: `ObjectInterface` :param vma: virtual memory allocation of ELF :type task: `ObjectInterface` :param task: the task object whose memory should be output :type open_method: `Type[FileHandlerInterface]` :param open_method: class to provide context manager for opening the file

Return type

`Optional[FileHandlerInterface]`

Returns

An open FileHandlerInterface object containing the complete data for the task or None in the case of failure

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (2, 0, 1)

volatility3.plugins.linux.envvars module**class** **Envvars**(*context, config_path, progress_callback=None*)Bases: *PluginInterface*

Lists processes with their environment variables

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.iomem module**class IOMem(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Generates an output similar to /proc/iomem on a running system.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

classmethod parse_resource(*context, vmlinux_module_name, resource_offset, seen={}, depth=0*)

Recursively parse from a root resource to find details about all related resources.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **vmlinux_module_name** (*str*) – The name of the kernel module on which to operate
- **resource_offset** (*int*) – The offset to the resource to be parsed
- **seen** (*set*) – The set of resource offsets that have already been parsed
- **depth** (*int*) – How deep into the resource structure we are

Yields

Each row of output

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 0, 1)

volatility3.plugins.linux.keyboard_notifiers module**class Keyboard_notifiers(context, config_path, progress_callback=None)**

Bases: `PluginInterface`

Parses the keyboard notifier call chain

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: HierarchicalDict

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: str

The configuration path on which this configurable lives.

property context: ContextInterface

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.kmsg module**class** **ABCKmsg**(*context, config*)Bases: **ABC**

Kernel log buffer reader

FACILITIES = ('kern', 'user', 'mail', 'daemon', 'auth', 'syslog', 'lpr', 'news', 'uucp', 'cron', 'authpriv', 'ftp')**LEVELS** = ('emerg', 'alert', 'crit', 'err', 'warn', 'notice', 'info', 'debug')**get_caller**(*obj*)**get_caller_text**(*caller_id*)**classmethod** **get_facility_text**(*facility*)**Return type****str****classmethod** **get_level_text**(*level*)**Return type****str****get_prefix**(*obj*)**Return type****Tuple**[**int**, **int**, **str**, **str**]**get_string**(*addr, length*)**Return type****str****get_timestamp_in_sec_str**(*obj*)**Return type****str****nsec_to_sec_str**(*nsec*)**Return type****str****abstract** **run**()

Walks through the specific kernel implementation.

Returns

facility [**str**]: The log facility: kern, user, etc. See **FACILITIES** level [**str**]: The log level: info, debug, etc. See **LEVELS** timestamp [**str**]: The message timestamp. See **nsec_to_sec_str**() caller [**str**]: The caller ID: CPU(1) or Task(1234). See **get_caller**() line [**str**]: The log message.

Return type**tuple****classmethod** **run_all**(*context, config*)It calls each subclass **symtab_checks**() to test the required conditions to that specific kernel implementation.**Parameters**

- **context** (*ContextInterface*) – The volatility3 context on which to operate
- **config** (*HierarchicalDict*) – Core configuration

Yields

The kmsg records. Same as run()

Return type

Iterator[*Tuple*[*str*, *str*, *str*, *str*, *str*]]

abstract classmethod symtab_checks(*vmlinux*)

This method on each subclass will be called to evaluate if the kernel being analyzed fulfill the type & symbols requirements for the implementation. The first class returning True will be instantiated and called via the run() method.

Returns

True if the kernel being analyzed fulfill the class requirements.

Return type

bool

class DescStateEnum(*value*, *names=None*, *, *module=None*, *qualname=None*, *type=None*, *start=1*, *boundary=None*)

Bases: *Enum*

desc_committed = 1

desc_finalized = 2

desc_miss = -1

desc_reserved = 0

desc_reusable = 3

class Kmsg(*context*, *config_path*, *progress_callback=None*)

Bases: *PluginInterface*

Kernel log buffer reader

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (1, 0, 2)``class Kmsg_3_11_to_5_10(context, config)`Bases: `Kmsg_3_5_to_3_11`

Starting from version 3.11, the struct 'log' was renamed to 'printk_log'. While 'log_buf' is declared as a pointer and '__log_buf' as a char array, it essentially holds an array of 'printk_log' structs.

`FACILITIES = ('kern', 'user', 'mail', 'daemon', 'auth', 'syslog', 'lpr', 'news', 'uucp', 'cron', 'authpriv', 'ftp')``LEVELS = ('emerg', 'alert', 'crit', 'err', 'warn', 'notice', 'info', 'debug')``get_caller(obj)``get_caller_text(caller_id)``get_dict_lines(msg)`**Return type**`Generator[str, None, None]``classmethod get_facility_text(facility)`**Return type**`str``classmethod get_level_text(level)`**Return type**`str``get_log_lines(msg)`**Return type**`Generator[str, None, None]``get_prefix(obj)`**Return type**`Tuple[int, int, str, str]``get_string(addr, length)`**Return type**`str``get_text_from_log(msg)`**Return type**`str``get_timestamp_in_sec_str(obj)`**Return type**`str`

nsec_to_sec_str(*nsec*)

Return type

str

run()

Walks through the specific kernel implementation.

Returns

facility [str]: The log facility: kern, user, etc. See FACILITIES level [str]: The log level: info, debug, etc. See LEVELS timestamp [str]: The message timestamp. See nsec_to_sec_str() caller [str]: The caller ID: CPU(1) or Task(1234). See get_caller() line [str]: The log message.

Return type

tuple

classmethod run_all(*context, config*)

It calls each subclass symtab_checks() to test the required conditions to that specific kernel implementation.

Parameters

- **context** (*ContextInterface*) – The volatility3 context on which to operate
- **config** (*HierarchicalDict*) – Core configuration

Yields

The kmsg records. Same as run()

Return type

Iterator[Tuple[str, str, str, str, str]]

classmethod symtab_checks(*vmlinux*)

This method on each subclass will be called to evaluate if the kernel being analyzed fulfill the type & symbols requirements for the implementation. The first class returning True will be instantiated and called via the run() method.

Returns

True if the kernel being analyzed fulfill the class requirements.

Return type

bool

class Kmsg_3_5_to_3_11(*context, config*)

Bases: *ABCKmsg*

While 'log_buf' is declared as a pointer and '__log_buf' as a char array, it essentially holds an array of 'log' structs.

FACILITIES = ('kern', 'user', 'mail', 'daemon', 'auth', 'syslog', 'lpr', 'news', 'uucp', 'cron', 'authpriv', 'ftp')

LEVELS = ('emerg', 'alert', 'crit', 'err', 'warn', 'notice', 'info', 'debug')

get_caller(*obj*)

get_caller_text(*caller_id*)

get_dict_lines(*msg*)

Return type

Generator[str, None, None]

classmethod `get_facility_text(facility)`

Return type

`str`

classmethod `get_level_text(level)`

Return type

`str`

get_log_lines(msg)

Return type

`Generator[str, None, None]`

get_prefix(obj)

Return type

`Tuple[int, int, str, str]`

get_string(addr, length)

Return type

`str`

get_text_from_log(msg)

Return type

`str`

get_timestamp_in_sec_str(obj)

Return type

`str`

nsec_to_sec_str(nsec)

Return type

`str`

run()

Walks through the specific kernel implementation.

Returns

facility [str]: The log facility: kern, user, etc. See FACILITIES level [str]: The log level: info, debug, etc. See LEVELS timestamp [str]: The message timestamp. See nsec_to_sec_str() caller [str]: The caller ID: CPU(1) or Task(1234). See get_caller() line [str]: The log message.

Return type

`tuple`

classmethod `run_all(context, config)`

It calls each subclass `symtab_checks()` to test the required conditions to that specific kernel implementation.

Parameters

- **context** (*ContextInterface*) – The volatility3 context on which to operate
- **config** (*HierarchicalDict*) – Core configuration

Yields

The kmsg records. Same as `run()`

Return type`Iterator[Tuple[str, str, str, str, str]]`**classmethod `syntab_checks`**(*vmlinux*)

This method on each subclass will be called to evaluate if the kernel being analyzed fulfill the type & symbols requirements for the implementation. The first class returning True will be instantiated and called via the `run()` method.

Returns

True if the kernel being analyzed fulfill the class requirements.

Return type`bool`**class `Kmsg_5_10_to_`**(*context, config*)

Bases: `ABCKmsg`

In 5.10 the kernel ring buffer implementation changed. Previously only one process should read `/proc/kmsg` and it is permanently open and periodically read by the syslog daemon. A high level structure 'printk_ringbuffer' was added to represent the printk ring buffer which actually contains two ring buffers. The descriptor ring 'desc_ring' contains the records' metadata, text offsets and states. The data block ring 'text_data_ring' contains the records' text strings. A pointer to the high level structure is kept in the prb pointer which is initialized to a static ring buffer.

```
static struct printk_ringbuffer *prb = &printk_rb_static;
```

In SMP systems with more than 64 CPUs this ring buffer size is dynamically allocated according the number of CPUs based on the value of `CONFIG_LOG_CPU_MAX_BUF_SHIFT`. The prb pointer is updated consequently to this dynamic ring buffer in `setup_log_buf()`.

```
prb = &printk_rb_dynamic;
```

Behind scenes, 'log_buf' is still used as external buffer. When the static 'printk_ringbuffer' struct is initialized, `_DEFINE_PRINTKRB` sets `text_data_ring.data` pointer to the address in 'log_buf' which points to the static buffer '___log_buf'. If a dynamic ring buffer takes place, `setup_log_buf()` sets `text_data_ring.data` of 'printk_rb_dynamic' to the new allocated external buffer via the 'prb_init' function. In that case, the original external static buffer in '___log_buf' and 'printk_rb_static' are unused.

```
new_log_buf = memblock_alloc(new_log_buf_len, LOG_ALIGN);
prb_init(&printk_rb_dynamic, new_log_buf, ...);
log_buf = new_log_buf;
prb = &printk_rb_dynamic;
```

See `printk.c` and `printk_ringbuffer.c` in `kernel/printk/` folder for more details.

```
FACILITIES = ('kern', 'user', 'mail', 'daemon', 'auth', 'syslog', 'lpr', 'news',
             'uucp', 'cron', 'authpriv', 'ftp')
```

```
LEVELS = ('emerg', 'alert', 'crit', 'err', 'warn', 'notice', 'info', 'debug')
```

```
get_caller(obj)
```

```
get_caller_text(caller_id)
```

```
get_dict_lines(info)
```

Return type`Generator[str, None, None]`

classmethod `get_facility_text(facility)`

Return type

`str`

classmethod `get_level_text(level)`

Return type

`str`

get_log_lines(*text_data_ring*, *desc*, *info*)

Return type

`Generator[str, None, None]`

get_prefix(*obj*)

Return type

`Tuple[int, int, str, str]`

get_string(*addr*, *length*)

Return type

`str`

get_text_from_data_ring(*text_data_ring*, *desc*, *info*)

Return type

`str`

get_timestamp_in_sec_str(*obj*)

Return type

`str`

nsec_to_sec_str(*nsec*)

Return type

`str`

run()

Walks through the specific kernel implementation.

Returns

facility [`str`]: The log facility: kern, user, etc. See FACILITIES
level [`str`]: The log level: info, debug, etc. See LEVELS
timestamp [`str`]: The message timestamp. See `nsec_to_sec_str()`
caller [`str`]: The caller ID: CPU(1) or Task(1234). See `get_caller()`
line [`str`]: The log message.

Return type

`tuple`

classmethod `run_all(context, config)`

It calls each subclass `symtab_checks()` to test the required conditions to that specific kernel implementation.

Parameters

- **context** (*ContextInterface*) – The volatility3 context on which to operate
- **config** (*HierarchicalDict*) – Core configuration

Yields

The kmsg records. Same as `run()`

Return type`Iterator[Tuple[str, str, str, str, str]]`**classmethod `syntab_checks`**(*vmlinux*)

This method on each subclass will be called to evaluate if the kernel being analyzed fulfill the type & symbols requirements for the implementation. The first class returning True will be instantiated and called via the `run()` method.

Returns

True if the kernel being analyzed fulfill the class requirements.

Return type`bool`**class `Kmsg_pre_3_5`**(*context, config*)

Bases: `ABCKmsg`

The kernel ring buffer (`log_buf`) is a char array that sequentially stores log lines, each separated by newline (LF) characters. i.e:

```
<6>[ 9565.250411] line1!n<6>[ 9565.250412] line2n...
```

```
FACILITIES = ('kern', 'user', 'mail', 'daemon', 'auth', 'syslog', 'lpr', 'news',
'uucp', 'cron', 'authpriv', 'ftp')
```

```
LEVELS = ('emerg', 'alert', 'crit', 'err', 'warn', 'notice', 'info', 'debug')
```

```
get_caller(obj)
```

```
get_caller_text(caller_id)
```

```
classmethod get_facility_text(facility)
```

Return type`str`

```
classmethod get_level_text(level)
```

Return type`str`

```
get_prefix(obj)
```

Return type`Tuple[int, int, str, str]`

```
get_string(addr, length)
```

Return type`str`

```
get_timestamp_in_sec_str(obj)
```

Return type`str`

```
nsec_to_sec_str(nsec)
```

Return type`str`

run()

Walks through the specific kernel implementation.

Returns

facility [str]: The log facility: kern, user, etc. See FACILITIES level [str]: The log level: info, debug, etc. See LEVELS timestamp [str]: The message timestamp. See nsec_to_sec_str() caller [str]: The caller ID: CPU(1) or Task(1234). See get_caller() line [str]: The log message.

Return type

tuple

classmethod run_all(context, config)

It calls each subclass symtab_checks() to test the required conditions to that specific kernel implementation.

Parameters

- **context** (*ContextInterface*) – The volatility3 context on which to operate
- **config** (*HierarchicalDict*) – Core configuration

Yields

The kmsg records. Same as run()

Return type

Iterator[Tuple[str, str, str, str, str]]

classmethod symtab_checks(vmlinux)

This method on each subclass will be called to evaluate if the kernel being analyzed fulfill the type & symbols requirements for the implementation. The first class returning True will be instantiated and called via the run() method.

Returns

True if the kernel being analyzed fulfill the class requirements.

Return type

bool

volatility3.plugins.linux.library_list module**class LibraryList(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Enumerate libraries loaded into processes

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (str) – The path to configuration data within the context configuration data
- **progress_callback** (Optional[Callable[[float, str], None]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type*None***classmethod unsatisfied**(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

`version = (1, 0, 0)`

volatility3.plugins.linux.lsmmod module

A module containing a collection of plugins that produce data typically found in Linux's /proc file system.

class `Lsmmod`(*context*, *config_path*, *progress_callback=None*)

Bases: `PluginInterface`

Lists loaded kernel modules.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod list_modules(*context*, *vmlinux_module_name*)

Lists all the modules in the primary layer.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from

- **layer_name** – The name of the layer on which to operate
- **vmlinux_symbols** – The name of the table containing the kernel symbols

Yields

The modules present in the *layer_name* layer's modules list

Return type

`Iterable[ObjectInterface]`

This function will throw a `SymbolError` exception if kernel module support is not enabled.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from `kwargs`.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like `open`

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A `TreeGrid` object that can then be passed to a `Renderer`.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return `[]`, it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (2, 0, 0)`**volatility3.plugins.linux.lsof module**

A module containing a collection of plugins that produce data typically found in Linux's /proc file system.

class `Lsof`(*context*, *config_path*, *progress_callback*=None)

Bases: `PluginInterface`

Lists all memory maps for all processes.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`

classmethod `list_fds`(*context*, *symbol_table*, *filter_func*=<function Lsof.<lambda>>)

classmethod `make_subconfig`(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration

- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 1, 0)

volatility3.plugins.linux.malfind module

class Malfind(context, config_path, progress_callback=None)

Bases: `PluginInterface`

Lists process memory ranges that potentially contain injected code.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.mountinfo module

class MountInfo(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Lists mount points on processes mount namespaces

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_mountinfo(mnt, task)`

Extract various information about a mount point. It mimics the Linux kernel `show_mountinfo` function.

Return type

`Optional[Tuple[int, int, str, str, str, List[str], List[str], str, str, List[str]]]`

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from `kwargs`.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like `open`

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a `Renderer`.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return `[]`, it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```


Return type`Dict[str, RequirementInterface]`**version** = (1, 0, 0)

class MountInfoData(*mnt_id, parent_id, st_dev, mnt_root_path, path_root, mnt_opts, fields, mnt_type, devname, sb_opts*)

Bases: `tuple`

Create new instance of MountInfoData(*mnt_id, parent_id, st_dev, mnt_root_path, path_root, mnt_opts, fields, mnt_type, devname, sb_opts*)

count(*value, /*)

Return number of occurrences of value.

devname

Alias for field number 8

fields

Alias for field number 6

index(*value, start=0, stop=9223372036854775807, /*)

Return first index of value.

Raises ValueError if the value is not present.

mnt_id

Alias for field number 0

mnt_opts

Alias for field number 5

mnt_root_path

Alias for field number 3

mnt_type

Alias for field number 7

parent_id

Alias for field number 1

path_root

Alias for field number 4

sb_opts

Alias for field number 9

st_dev

Alias for field number 2

volatility3.plugins.linux.proc module

A module containing a collection of plugins that produce data typically found in Linux's /proc file system.

class **Maps**(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Lists all memory maps for all processes.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

MAXSIZE_DEFAULT = 1073741824

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod list_vmas(*task, filter_func=<function Maps.<lambda>>*)

Lists the Virtual Memory Areas of a specific process.

Parameters

- **task** (*ObjectInterface*) – task object from which to list the vma
- **filter_func** (*Callable[[ObjectInterface], bool]*) – Function to take a vma and return False if it should be filtered out

Return type

Generator[ObjectInterface, None, None]

Returns

Yields vmass based on the task and filtered based on the filter function

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

classmethod vma_dump(context, task, vm_start, vm_end, open_method, maxsize=1073741824)

Extracts the complete data for VMA as a FileInterface.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **task** (*ObjectInterface*) – an task_struct instance
- **vm_start** (*int*) – The start virtual address from the vma to dump
- **vm_end** (*int*) – The end virtual address from the vma to dump

- **open_method** (`Type[FileHandlerInterface]`) – class to provide context manager for opening the file
- **maxsize** (`int`) – Max size of VMA section (default MAXSIZE_DEFAULT)

Return type`Optional[FileHandlerInterface]`**Returns**

An open FileInterface object containing the complete data for the task or None in the case of failure

volatility3.plugins.linux.psaux module

class PsAux(*context, config_path, progress_callback=None*)

Bases: `PluginInterface`

Lists processes with their command line arguments

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration

- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.linux.pslist module

class PsList(context, config_path, progress_callback=None)

Bases: `PluginInterface`

Lists the processes present in a particular linux memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod create_pid_filter(*pid_list=None*)

Constructs a filter function for process IDs.

Parameters

pid_list (*List[int]*) – List of process IDs that are acceptable (or None if all are acceptable)

Return type

Callable[[Any], bool]

Returns

Function which, when provided a process object, returns True if the process is to be filtered out of the list

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod get_task_fields(*task, decorate_comm=False*)

Extract the fields needed for the final output

Parameters

- **task** (*ObjectInterface*) – A task object from where to get the fields.
- **decorate_comm** (*bool*) – If True, it decorates the comm string of user threads in curly brackets, and of Kernel threads in square brackets. Defaults to False.

Return type

Tuple[int, int, int, str]

Returns

A tuple with the fields to show in the plugin output.

classmethod list_tasks(*context, vmlinux_module_name, filter_func=<function PsList.<lambda>>, include_threads=False*)

Lists all the tasks in the primary layer.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from

- **vmlinux_module_name** (*str*) – The name of the kernel module on which to operate
- **filter_func** (*Callable[[int], bool]*) – A function which takes a process object and returns True if the process should be ignored/filtered
- **include_threads** (*bool*) – If True, it will also return user threads.

Yields

Task objects

Return type

Iterable[ObjectInterface]

classmethod **make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property **open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod **unsatisfied**(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (2, 2, 1)`**volatility3.plugins.linux.psscan module**

```
class DescExitStateEnum(value, names=None, *, module=None, qualname=None, type=None, start=1, boundary=None)
```

Bases: `Enum`

Enum for linux task exit_state as defined in include/linux/sched.h

`EXIT_DEAD = 16``EXIT_TRACE = 48``EXIT_ZOMBIE = 32``TASK_RUNNING = 0`

```
class PsScan(context, config_path, progress_callback=None)
```

Bases: `PluginInterface`

Scans for processes present in a particular linux image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod `scan_tasks(context, vmlinux_module_name, kernel_layer_name)`

Scans for tasks in the memory layer.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **vmlinux_module_name** (*str*) – The name of the kernel module on which to operate
- **kernel_layer_name** (*str*) – The name for the kernel layer

Yields

Task objects

Return type

Iterable[ObjectInterface]

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

`version = (1, 0, 1)`

volatility3.plugins.linux.pstree module

class `PsTree(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Plugin for listing processes in a tree based on their parent process ID.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

find_level(pid)

Finds how deep the PID is in the tasks hierarchy.

Parameters

pid (`int`) – PID to find the level in the hierarchy

Return type

`None`

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.sockstat module**class SockHandlers**(*vmlinux, task*)Bases: *VersionableInterface*

Handles several socket families extracting the sockets information.

process_sock(*sock*)Takes a kernel generic *sock* object and processes it with its respective socket family**Parameters****sock** (*StructType*) – Kernel generic *sock* object**Return type***Tuple[StructType, Tuple[str, str, str], Dict]***Returns a tuple with:**

sock: The respective kernel's *_sock object for that socket family
sock_stat: A tuple with the source and destination (address and port) along with its state string
socket_filter: A dictionary with information about the socket filter

version = (1, 0, 0)**class Sockstat**(*context, config_path, progress_callback=None*)Bases: *PluginInterface*

Lists all network connections for all processes.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod `list_sockets(context, symbol_table, filter_func=<function Sockstat.<lambda>>)`

Returns every single socket descriptor

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **symbol_table** (*str*) – The name of the kernel module on which to operate
- **filter_func** (*Callable[[int], bool]*) – A function which takes a task object and returns True if the task should be ignored/filtered

Yields

task – Kernel’s task object *netns_id*: Network namespace ID *fd_num*: File descriptor number *family*: Socket family string (AF_UNIX, AF_INET, etc) *sock_type*: Socket type string (STREAM, DGRAM, etc) *protocol*: Protocol string (UDP, TCP, etc) *sock_fields*: A tuple with the **_sock* object, the sock stats and the extended info dictionary

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

`version = (1, 0, 0)`

volatility3.plugins.linux.tty_check module

class `tty_check(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Checks tty devices for hooks

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration

- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.linux.vmayarascan module

class VmaYaraScan(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Scans all virtual memory areas for tasks using yara.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data

- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

static get_vma_maps(task)

Creates a map of start/end addresses for each virtual memory area in a task.

Parameters

task (`ObjectInterface`) – The task object of which to read the vmas from

Return type

`Iterable[Tuple[int, int]]`

Returns

An iterable of tuples containing start and end addresses for each descriptor

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.mac package

All Mac-related plugins.

NOTE: This file is important for core plugins to run (which certain components such as the windows registry layers) are dependent upon, please DO NOT alter or remove this file unless you know the consequences of doing so.

The framework is configured this way to allow plugin developers/users to override any plugin functionality whether existing or new.

When overriding the plugins directory, you must include a file like this in any subdirectories that may be necessary.

Submodules**volatility3.plugins.mac.bash module**

A module containing a collection of plugins that produce data typically found in mac's /proc file system.

class Bash(context, config_path, progress_callback=None)

Bases: *PluginInterface*, *TimeLinerInterface*

Recovers bash command history from memory.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.mac.check_syscall module**class Check_syscall(context, config_path, progress_callback=None)**

Bases: `PluginInterface`

Check system call table for hooks.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: HierarchicalDict

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: str

The configuration path on which this configurable lives.

property context: ContextInterface

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.mac.check_sysctl module**class** `Check_sysctl(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Check sysctl handlers for hooks.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`**classmethod make_subconfig(context, base_config_path, **kwargs)**

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.mac.check_trap_table module**class Check_trap_table(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Check mach trap table for hooks.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

`version = (0, 0, 0)`

volatility3.plugins.mac.dmesg module

class `Dmesg(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Prints the kernel log buffer.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_kernel_log_buffer(context, kernel_module_name)

Online documentation :

- <https://github.com/apple-open-source/macos/blob/master/xnu/bsd/sys/msgbuf.h>
- https://github.com/apple-open-source/macos/blob/ea4cd5a06831aca49e33df829d2976d6de5316ec/xnu/bsd/kern/subr_log.c#L751

Volatility 2 plugin :

- <https://github.com/volatilityfoundation/volatility/blob/master/volatility/plugins/mac/dmesg.py>

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.mac.ifconfig module**class Ifconfig**(*context, config_path, progress_callback=None*)Bases: *PluginInterface*

Lists network interface information for all devices

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.mac.kauth_listeners module**class Kauth_listeners(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Lists kauth listeners and their status

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: [*HierarchicalDict*](#)

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: [*str*](#)

The configuration path on which this configurable lives.

property context: [*ContextInterface*](#)

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** ([*ContextInterface*](#)) – The context in which to store the new configuration
- **base_config_path** ([*str*](#)) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

[*str*](#)

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

[*None*](#)

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (0, 0, 0)`**volatility3.plugins.mac.kauth_scopes module****class** `Kauth_scopes`(*context, config_path, progress_callback=None*)Bases: `PluginInterface`

Lists kauth scopes and their status

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod list_kauth_scopes(*context, kernel_module_name, filter_func=<function Kauth_scopes.<lambda>>>*)

Enumerates the registered kauth scopes and yields each object. Uses smear-safe enumeration API

Return type`Iterable[ObjectInterface]`**classmethod make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration

- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (2, 0, 0)

volatility3.plugins.mac.kevents module**class Kevents(context, config_path, progress_callback=None)**

Bases: `PluginInterface`

Lists event handlers registered by processes

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

```
all_filters = {4: [('NOTE_DELETE', 1), ('NOTE_WRITE', 2), ('NOTE_EXTEND', 4),
('NOTE_ATTRIB', 8), ('NOTE_LINK', 16), ('NOTE_RENAME', 32), ('NOTE_REVOKE', 64)], 5:
[('NOTE_EXIT', 2147483648), ('NOTE_EXITSTATUS', 67108864), ('NOTE_FORK',
1073741824), ('NOTE_EXEC', 536870912), ('NOTE_SIGNAL', 134217728), ('NOTE_REAP',
268435456)], 7: [('NOTE_SECONDS', 1), ('NOTE_USECONDS', 2), ('NOTE_NSECONDS', 4),
('NOTE_ABSOLUTE', 8)]}
```

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

```
event_types = {1: 'EVFILT_READ', 2: 'EVFILT_WRITE', 3: 'EVFILT_AIO', 4:
'EVFILT_VNODE', 5: 'EVFILT_PROC', 6: 'EVFILT_SIGNAL', 7: 'EVFILT_TIMER', 8:
'EVFILT_MACHPORT', 9: 'EVFILT_FS', 10: 'EVFILT_USER', 12: 'EVFILT_VM'}
```

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod list_kernel_events(*context, kernel_module_name, filter_func=<function Kevents.<lambda>>*)

Returns the kernel event filters registered

Return type

Iterable[Tuple[ObjectInterface, ObjectInterface, ObjectInterface]]

Return values:

A tuple of 3 elements:

- 1) The name of the process that registered the filter
- 2) The process ID of the process that registered the filter
- 3) The object of the associated kernel event filter

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration

- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

```
proc_filters = [('NOTE_EXIT', 2147483648), ('NOTE_EXITSTATUS', 67108864),
('NOTE_FORK', 1073741824), ('NOTE_EXEC', 536870912), ('NOTE_SIGNAL', 134217728),
('NOTE_REAP', 268435456)]
```

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

```
timer_filters = [('NOTE_SECONDS', 1), ('NOTE_USECONDS', 2), ('NOTE_NSECONDS', 4),
('NOTE_ABSOLUTE', 8)]
```

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

```
version = (1, 0, 0)
```

```
vnode_filters = [('NOTE_DELETE', 1), ('NOTE_WRITE', 2), ('NOTE_EXTEND', 4),
('NOTE_ATTRIB', 8), ('NOTE_LINK', 16), ('NOTE_RENAME', 32), ('NOTE_REVOKE', 64)]
```


volatility3.plugins.mac.list_files module**class List_Files**(context, config_path, progress_callback=None)Bases: *PluginInterface*

Lists all open file descriptors for all processes.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (Optional[Callable[[float, str], None]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod list_files(context, kernel_module_name)**Return type***Iterable[ObjectInterface]***classmethod make_subconfig**(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str*

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.mac.lsmodule module

A module containing a collection of plugins that produce data typically found in Mac's lsmodule command.

class Lsmodule(context, config_path, progress_callback=None)

Bases: `PluginInterface`

Lists loaded kernel modules.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod list_modules(*context, darwin_module_name*)

Lists all the modules in the primary layer.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** – The name of the layer on which to operate
- **darwin_symbols** – The name of the table containing the kernel symbols

Returns

A list of modules from the *layer_name* layer

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (2, 0, 0)

volatility3.plugins.mac.lsof module

class Lsof(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Lists all open file descriptors for all processes.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.mac.malfind module**class Malfind**(*context, config_path, progress_callback=None*)Bases: *PluginInterface*

Lists process memory ranges that potentially contain injected code.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.mac.mount module

A module containing a collection of plugins that produce data typically found in Mac's mount command.

class Mount(context, config_path, progress_callback=None)

Bases: *PluginInterface*

A module containing a collection of plugins that produce data typically found in Mac's mount command

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod list_mounts(*context, kernel_module_name*)

Lists all the mount structures in the primary layer.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** – The name of the layer on which to operate
- **darwin_symbols** – The name of the table containing the kernel symbols

Returns

A list of mount structures from the *layer_name* layer

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod **unsatisfied**(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (2, 0, 0)

volatility3.plugins.mac.netstat module

class **Netstat**(*context*, *config_path*, *progress_callback*=None)

Bases: `PluginInterface`

Lists all network connections for all processes.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property **config**: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property **config_path**: `str`

The configuration path on which this configurable lives.

property **context**: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod **get_requirements**()

Returns a list of Requirement objects for this plugin.

classmethod `list_sockets(context, kernel_module_name, filter_func=<function Netstat.<lambda>>)`

Returns the open socket descriptors of a process

Return type

`Iterable[Tuple[ObjectInterface, ObjectInterface, ObjectInterface]]`

Return values:

A tuple of 3 elements:

- 1) The name of the process that opened the socket
- 2) The process ID of the process that opened the socket
- 3) The address of the associated socket structure

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type

`Dict[str, RequirementInterface]`

`version = (0, 0, 0)`

volatility3.plugins.mac.proc_maps module

class `Maps(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Lists process memory ranges that potentially contain injected code.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

`MAXSIZE_DEFAULT = 1073741824`

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property `config`: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path`: `str`

The configuration path on which this configurable lives.

property `context`: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `list_vmas(task, filter_func=<function Maps.<lambda>>)`

Lists the Virtual Memory Areas of a specific process.

Parameters

- **task** (`ObjectInterface`) – task object from which to list the vma
- **filter_func** (`Callable[[ObjectInterface], bool]`) – Function to take a vma and return False if it should be filtered out

Return type`Generator[ObjectInterface, None, None]`**Returns**

Yields vmas based on the task and filtered based on the filter function

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`

version = (1, 1, 0)

classmethod `vma_dump(context, task, vm_start, vm_end, open_method, maxsize=1073741824)`

Extracts the complete data for VMA as a FileInterface.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **task** (*ObjectInterface*) – an task_struct instance
- **vm_start** (*int*) – The start virtual address from the vma to dump
- **vm_end** (*int*) – The end virtual address from the vma to dump
- **open_method** (*Type[FileHandlerInterface]*) – class to provide context manager for opening the file
- **maxsize** (*int*) – Max size of VMA section (default MAXSIZE_DEFAULT)

Return type

Optional[FileHandlerInterface]

Returns

An open FileInterface object containing the complete data for the task or None in the case of failure

volatility3.plugins.mac.psaux module

In-memory artifacts from OSX systems.

class `Psaux(context, config_path, progress_callback=None)`

Bases: *PluginInterface*

Recovers program command line arguments.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

`build_configuration()`

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: [`ContextInterface`](#)

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

[`List\[RequirementInterface\]`](#)

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** ([`ContextInterface`](#)) – The context in which to store the new configuration
- **base_config_path** ([`str`](#)) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

[`str`](#)

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Return type

[`TreeGrid`](#)

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

[`None`](#)

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (0, 0, 0)`**volatility3.plugins.mac.pslist module****class** `PsList(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Lists the processes present in a particular mac memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod create_pid_filter(`pid_list=None`)**Return type**`Callable[[int], bool]`**classmethod get_list_tasks**(`method`)

Returns the list_tasks method based on the selector

Parameters**method** (`str`) – Must be one of the available methods in get_task_choices**Return type**`Callable[[ContextInterface, str, Callable[[int], bool], Iterable[ObjectInterface]]`**Returns**

list_tasks method for listing tasks

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `list_tasks_allproc(context, kernel_module_name, filter_func=<function PsList.<lambda>>)`

Lists all the processes in the primary layer based on the allproc method

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **kernel_module_name** (*str*) – The name of the the kernel module on which to operate
- **filter_func** (*Callable[[int], bool]*) – A function which takes a process object and returns True if the process should be ignored/filtered

Return type

Iterable[ObjectInterface]

Returns

The list of process objects from the processes linked list after filtering

classmethod `list_tasks_pid_hash_table(context, kernel_module_name, filter_func=<function PsList.<lambda>>)`

Lists all the tasks in the primary layer using the pid hash table

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **kernel_module_name** (*str*) – The name of the the kernel module on which to operate
- **filter_func** (*Callable[[int], bool]*) – A function which takes a task object and returns True if the task should be ignored/filtered

Return type

Iterable[ObjectInterface]

Returns

The list of task objects from the *layer_name* layer's *tasks* list after filtering

classmethod `list_tasks_process_group(context, kernel_module_name, filter_func=<function PsList.<lambda>>)`

Lists all the tasks in the primary layer using process groups

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **kernel_module_name** (*str*) – The name of the the kernel module on which to operate
- **filter_func** (*Callable[[int], bool]*) – A function which takes a task object and returns True if the task should be ignored/filtered

Return type

Iterable[ObjectInterface]

Returns

The list of task objects from the *layer_name* layer's *tasks* list after filtering


```
classmethod list_tasks_sessions(context, kernel_module_name, filter_func=<function  
                                PsList.<lambda>>>)
```

Lists all the tasks in the primary layer using sessions

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **kernel_module_name** (*str*) – The name of the the kernel module on which to operate
- **filter_func** (*Callable[[int], bool]*) – A function which takes a task object and returns True if the task should be ignored/filtered

Return type

Iterable[ObjectInterface]

Returns

The list of task objects from the *layer_name* layer's *tasks* list after filtering

```
classmethod list_tasks_tasks(context, kernel_module_name, filter_func=<function  
                             PsList.<lambda>>>)
```

Lists all the tasks in the primary layer based on the tasks queue

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **kernel_module_name** (*str*) – The name of the the kernel module on which to operate
- **filter_func** (*Callable[[int], bool]*) – A function which takes a task object and returns True if the task should be ignored/filtered

Return type

Iterable[ObjectInterface]

Returns

The list of task objects from the *layer_name* layer's *tasks* list after filtering

```
classmethod make_subconfig(context, base_config_path, **kwargs)
```

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

```
pslist_methods = ['tasks', 'allproc', 'process_group', 'sessions', 'pid_hash_table']
```

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (3, 0, 0)

volatility3.plugins.mac.pstree module**class PsTree(*args, **kwargs)**

Bases: *PluginInterface*

Plugin for listing processes in a tree based on their parent process ID.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type

HierarchicalDict

property config: [*HierarchicalDict*](#)

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: [*str*](#)

The configuration path on which this configurable lives.

property context: [*ContextInterface*](#)

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** ([*ContextInterface*](#)) – The context in which to store the new configuration
- **base_config_path** ([*str*](#)) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

[*str*](#)

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

[*None*](#)

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (0, 0, 0)`**volatility3.plugins.mac.socket_filters module****class** `Socket_filters(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Enumerates kernel socket filters.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`**classmethod make_subconfig(context, base_config_path, **kwargs)**

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type`None`**classmethod unsatisfied(context, config_path)**

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.mac.timers module

class Timers(context, config_path, progress_callback=None)

Bases: [*PluginInterface*](#)

Check for malicious kernel timers.

Parameters

- **context** ([*ContextInterface*](#)) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** ([*Optional*](#)[[*Callable*](#)[[`float`, `str`], `None`]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.mac.trustedbsd module

class Trustedbsd(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Checks for malicious trustedbsd modules

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.mac.vfsevents module**class VFSevents**(context, config_path, progress_callback=None)Bases: *PluginInterface*

Lists processes that are filtering file system events

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional*[Callable[[float, str], None]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

```
event_types = ['CREATE_FILE', 'DELETE', 'STAT_CHANGED', 'RENAME',
               'CONTENT_MODIFIED', 'EXCHANGE', 'FINDER_INFO_CHANGED', 'CREATE_DIR', 'CHOWN',
               'XATTR_MODIFIED', 'XATTR_REMOVED', 'DOCID_CREATED', 'DOCID_CHANGED']
```

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str*

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows package

All Windows OS plugins.

NOTE: This file is important for core plugins to run (which certain components such as the windows registry layers) are dependent upon, please DO NOT alter or remove this file unless you know the consequences of doing so.

The framework is configured this way to allow plugin developers/users to override any plugin functionality whether existing or new.

When overriding the plugins directory, you must include a file like this in any subdirectories that may be necessary.

Subpackages

volatility3.plugins.windows.registry package

Windows registry plugins.

NOTE: This file is important for core plugins to run (which certain components such as the windows registry layers) are dependent upon, please DO NOT alter or remove this file unless you know the consequences of doing so.

The framework is configured this way to allow plugin developers/users to override any plugin functionality whether existing or new.

When overriding the plugins directory, you must include a file like this in any subdirectories that may be necessary.

Submodules

volatility3.plugins.windows.registry.hivelist module

class `HiveGenerator`(*cmhive*, *forward=True*)

Bases: `object`

Walks the registry HiveList linked list in a given direction and stores an invalid offset if it's unable to fully walk the list

property `invalid`: `int` | `None`

class `HiveList`(*context*, *config_path*, *progress_callback=None*)

Bases: `PluginInterface`

Lists the registry hives present in a particular memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property `config`: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path`: `str`

The configuration path on which this configurable lives.

property `context`: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `list_hive_objects(context, layer_name, symbol_table, filter_string=None)`

Lists all the hives in the primary layer.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (`str`) – The name of the layer on which to operate
- **symbol_table** (`str`) – The name of the table containing the kernel symbols
- **filter_string** (`str`) – A string which must be present in the hive name if specified

Return type

`Iterator[ObjectInterface]`

Returns

The list of registry hives from the *layer_name* layer as filtered against using the *filter_string*

classmethod `list_hives(context, base_config_path, layer_name, symbol_table, filter_string=None, hive_offsets=None)`

Walks through a registry, hive by hive returning the constructed registry layer name.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **base_config_path** (`str`) – The configuration path for any settings required by the new table
- **layer_name** (`str`) – The name of the layer on which to operate
- **symbol_table** (`str`) – The name of the table containing the kernel symbols
- **filter_string** (`Optional[str]`) – An optional string which must be present in the hive name if specified
- **offset** – An optional offset to specify a specific hive to iterate over (takes precedence over *filter_string*)

Yields

A registry hive layer name

Return type

`Iterable[RegistryHive]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration

- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Return type

`TreeGrid`

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 0, 0)

volatility3.plugins.windows.registry.hivescan module

class HiveScan(context, config_path, progress_callback=None)

Bases: `PluginInterface`

Scans for registry hives present in a particular windows memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data

- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod `scan_hives(context, layer_name, symbol_table)`

Scans for hives using the poolscanner module and constraints or bigpools module with tag.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type

Iterable[ObjectInterface]

Returns

A list of Hive objects as found from the *layer_name* layer based on Hive pool signatures

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.registry.printkey module

class `PrintKey(context, config_path, progress_callback=None)`

Bases: *PluginInterface*

Lists the registry keys under a hive or specific key value.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type*List[RequirementInterface]***classmethod key_iterator**(*hive, node_path=None, recurse=False*)

Walks through a set of nodes from a given node (last one in *node_path*). Avoids loops by not traversing into nodes already present in the *node_path*.

Parameters

- **hive** (*RegistryHive*) – The registry hive to walk
- **node_path** (*Sequence[StructType]*) – The list of nodes that make up the
- **recurse** (*bool*) – Traverse down the node tree or stay only on the same level

Yields

A tuple of results (depth, is_key, last write time, path, volatile, and the node).

Return type*Iterable[Tuple[int, bool, datetime, str, bool, ObjectInterface]]***classmethod make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.registry.userassist module**class UserAssist(*args, **kwargs)**

Bases: *PluginInterface*

Print userassist registry keys and information.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: HierarchicalDict

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

list_userassist(*hive*)

Generate userassist data for a registry hive.

Return type

`Generator[Tuple[int, Tuple], None, None]`

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

parse_userassist_data(*reg_val*)

Reads the raw data of a _CM_KEY_VALUE and returns a dict of userassist fields.

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

Submodules

volatility3.plugins.windows.bigpools module

class `BigPools(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

List big page pools.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `list_big_pools(context, layer_name, symbol_table, tags=None, show_free=False)`

Returns the big page pool objects from the kernel PoolBigPageTable array.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **tags** (*Optional[list]*) – An optional list of pool tags to filter big page pool tags by

Yields

A big page pool object

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]``version = (1, 1, 0)`**volatility3.plugins.windows.cachedump module****class** `Cachedump`(*context, config_path, progress_callback=None*)Bases: `PluginInterface`

Dumps lsa secrets from memory

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

static decrypt_hash(*edata, nlkm, ch, xp*)**static get_nlkm**(*sechive, lsakey, is_vista_or_later*)**classmethod get_requirements()**

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration

- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

static parse_cache_entry(*cache_data*)**Return type**

Tuple[*int*, *int*, *int*, *bytes*, *bytes*]

static parse_decrypted_cache(*dec_data*, *uname_len*, *domain_len*, *domain_name_len*)

Get the data from the cache and separate it into the username, domain name, and hash data

Return type

Tuple[*str*, *str*, *str*, *bytes*]

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[*str*, *RequirementInterface*]

version = (1, 0, 0)

volatility3.plugins.windows.callbacks module

class `Callbacks(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Lists kernel callbacks and notification routines.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

static create_callback_table(context, symbol_table, config_path)

Creates a symbol table for a set of callbacks.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **symbol_table** (`str`) – The name of an existing symbol table containing the kernel symbols
- **config_path** (`str`) – The configuration path within the context of the symbol table to create

Return type

`str`

Returns

The name of the constructed callback table

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `list_bugcheck_callbacks(context, layer_name, symbol_table, callback_table_name)`

Lists all kernel bugcheck callbacks.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **callback_table_name** (*str*) – The name of the table containing the callback symbols

Yields

A name, location and optional detail string

Return type

Iterable[*Tuple*[*str*, *int*, *str*]]

classmethod `list_bugcheck_reason_callbacks(context, layer_name, symbol_table, callback_table_name)`

Lists all kernel bugcheck reason callbacks.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **callback_table_name** (*str*) – The name of the table containing the callback symbols

Yields

A name, location and optional detail string

Return type

Iterable[*Tuple*[*str*, *int*, *str*]]

classmethod `list_notify_routines(context, layer_name, symbol_table, callback_table_name)`

Lists all kernel notification routines.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **callback_table_name** (*str*) – The name of the table containing the callback symbols

Yields

A name, location and optional detail string

Return type

Iterable[*Tuple*[*str*, *int*, *Optional*[*str*]]]

classmethod `list_registry_callbacks(context, layer_name, symbol_table, callback_table_name)`

Lists all registry callbacks.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **callback_table_name** (*str*) – The name of the table containing the callback symbols

Yields

A name, location and optional detail string

Return type

`Iterable[Tuple[str, int, Optional[str]]]`

classmethod **make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod **unsatisfied**(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (1, 0, 0)`**volatility3.plugins.windows.cmdline module****class** `CmdLine(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Lists process command line arguments.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_cmdline(context, kernel_table_name, proc)`

Extracts the cmdline from PEB

Parameters

- **context** (`ContextInterface`) – the context to operate upon
- **kernel_table_name** (`str`) – the name for the symbol table containing the kernel's symbols
- **proc** – the process object

Returns

A string with the command line

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.crashinfo module**class** **Crashinfo**(*context, config_path, progress_callback=None*)Bases: *PluginInterface*

Lists the information from a Windows crash dump.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows.devicetree module**class DeviceTree(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Listing tree based on drivers and attached devices in a particular windows memory image.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Return type

TreeGrid

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]``version = (1, 0, 1)`**volatility3.plugins.windows.dlllist module****class** `DllList(context, config_path, progress_callback=None)`Bases: `PluginInterface`, `TimeLinerInterface`

Lists the loaded modules in a particular windows memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod dump_pe(context, pe_table_name, dll_entry, open_method, layer_name=None, prefix="")

Extracts the complete data for a process as a FileInterface

Parameters

- **context** (`ContextInterface`) – the context to operate upon
- **pe_table_name** (`str`) – the name for the symbol table containing the PE format symbols
- **dll_entry** (`ObjectInterface`) – the object representing the module
- **layer_name** (`str`) – the layer that the DLL lives within
- **open_method** (`Type[FileHandlerInterface]`) – class for constructing output files

Return type`Optional[FileHandlerInterface]`**Returns**

An open FileHandlerInterface object containing the complete data for the DLL or None in the case of failure

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`**classmethod make_subconfig(context, base_config_path, **kwargs)**

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type`None`**classmethod unsatisfied(context, config_path)**

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:


```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type

`Dict[str, RequirementInterface]`

`version = (2, 0, 0)`

volatility3.plugins.windows.driverirp module

class `DriverIrp(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

List IRPs for drivers in a particular windows memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

`build_configuration()`

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.windows.drivermodule module

class DriverModule(context, config_path, progress_callback=None)

Bases: *PluginInterface*

Determines if any loaded drivers were hidden by a rootkit

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional*[Callable[[float, str], None]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Return type

TreeGrid

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.driverscan module

class DriverScan(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Scans for drivers present in a particular windows memory image.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_names_for_driver(driver)`

Convenience method for getting the commonly used names associated with a driver

Parameters

driver – A Eriver object

Returns

A tuple of strings of (driver name, service key, driver alt. name)

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod `scan_drivers(context, layer_name, symbol_table)`

Scans for drivers using the poolscanner module and constraints.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type

Iterable[ObjectInterface]

Returns

A list of Driver objects as found from the *layer_name* layer based on Driver pool signatures

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.dumpfiles module

class DumpFiles(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Dumps cached file contents from Windows memory samples.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod `dump_file_producer(file_object, memory_object, open_method, layer, desired_file_name)`

Produce a file from the memory object's `get_available_pages()` interface.

Parameters

- **file_object** (*ObjectInterface*) – the parent `_FILE_OBJECT`
- **memory_object** (*ObjectInterface*) – the `_CONTROL_AREA` or `_SHARED_CACHE_MAP`
- **open_method** (*Type[FileHandlerInterface]*) – class for constructing output files
- **layer** (*DataLayerInterface*) – the memory layer to read from
- **desired_file_name** (*str*) – name of the output file

Return type

Optional[FileHandlerInterface]

Returns

result status

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

classmethod `process_file_object(context, primary_layer_name, open_method, file_obj)`

Given a `FILE_OBJECT`, dump data to separate files for each of the three file caches.

Parameters

- **context** (*ContextInterface*) – the context to operate upon
- **primary_layer_name** (*str*) – primary/virtual layer to operate on
- **open_method** (*Type[FileHandlerInterface]*) – class for constructing output files
- **file_obj** (*ObjectInterface*) – the `FILE_OBJECT`

Return type

Generator[Tuple, None, None]

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.envvars module**class Envvars(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Display process environment variables

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

`version = (1, 0, 0)`

volatility3.plugins.windows.filescan module

class `FileScan(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Scans for file objects present in a particular windows memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod scan_files(context, layer_name, symbol_table)

Scans for file objects using the poolscanner module and constraints.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (`str`) – The name of the layer on which to operate
- **symbol_table** (`str`) – The name of the table containing the kernel symbols

Return type

Iterable[ObjectInterface]

Returns

A list of File objects as found from the *layer_name* layer based on File pool signatures

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows.getservicesids module**class** `GetServiceSIDs(*args, **kwargs)`Bases: `PluginInterface`

Lists process token sids.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`**classmethod make_subconfig(context, base_config_path, **kwargs)**

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)**createservicesid(svc)**

Calculate the Service SID

Return type

str

volatility3.plugins.windows.getsids module**class GetSIDs(*args, **kwargs)**

Bases: *PluginInterface*

Print the SIDs owning each process

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type*List[RequirementInterface]***lookup_user_sids()**

Enumerate the registry for all the users.

Returns

user name}

Return type

An dictionary of {sid

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod **unsatisfied**(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 0, 0)

find_sid_re(*sid_string*, *sid_re_list*)

Return type

`Union[str, BaseAbsentValue]`

volatility3.plugins.windows.handles module

class **Handles**(*args, **kwargs)

Bases: `PluginInterface`

Lists process open handles.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `find_cookie(context, layer_name, symbol_table)`

Find the ObHeaderCookie value (if it exists)

Return type

`Optional[ObjectInterface]`

find_sar_value()

Locate ObpCaptureHandleInformationEx if it exists in the sample.

Once found, parse it for the SAR value that we need to decode pointers in the `_HANDLE_TABLE_ENTRY` which allows us to find the associated `_OBJECT_HEADER`.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `get_type_map(context, layer_name, symbol_table)`

List the executive object types (`_OBJECT_TYPE`) using the `ObTypeIndexTable` or `ObpObjectTypes` symbol (differs per OS). This method will be necessary for determining what type of object we have given an object header.

Note: The object type index map was hard coded into profiles in previous versions of volatility. It is now generated dynamically.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (`str`) – The name of the layer on which to operate
- **symbol_table** (`str`) – The name of the table containing the kernel symbols

Return type

`Dict[int, str]`

Returns

A mapping of type indices to type names

handles(*handle_table*)

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type`None`**classmethod unsatisfied(context, config_path)**

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`

version = (1, 0, 0)

volatility3.plugins.windows.hashdump module**class Hashdump(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Dumps user hashes from memory

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional*[Callable[[float, str], None]]) – A callable that can provide feedback at progress points

almpassword = `b'LMPASSWORD\x00'`

antpassword = `b'NTPASSWORD\x00'`

```
anum = b'\0123456789012345678901234567890123456789\x00'
```

```
aqwerty = b'!@#$$%^&*()qwertyUIOPAzxcvbnmQQQQQQQQQQ)(*@&%\x00'
```

```
bootkey_perm_table = [8, 5, 4, 2, 11, 9, 13, 3, 0, 6, 1, 12, 14, 10, 15, 7]
```

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod decrypt_single_hash(rid, hbootkey, enc_hash, lmntstr)

classmethod decrypt_single_saltred_hash(rid, hbootkey, enc_hash, _lmntstr, salt)

Return type

Optional[bytes]

```
empty_lm = b'\xaa\xd3\xb45\xb5\x14\x04\xee\xaa\xd3\xb45\xb5\x14\x04\xee'
```

```
empty_nt = b'1\xd6\xcf\xe0\xd1j\xe91\xb7<Y\xd7\xe0\xc0\x89\xc0'
```

classmethod get_bootkey(syshive)

Return type

Optional[bytes]

classmethod get_hbootkey(samhive, bootkey)

Return type

Optional[bytes]

classmethod get_hive_key(hive, key)

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod get_user_hashes(user, samhive, hbootkey)

Return type

Optional[Tuple[bytes, bytes]]

classmethod get_user_keys(samhive)

Return type

List[ObjectInterface]

classmethod `get_user_name(user, samhive)`

Return type

`Optional[bytes]`

`lmkey = b'KGS!@#$$'`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

```
odd_parity = [1, 1, 2, 2, 4, 4, 7, 7, 8, 8, 11, 11, 13, 13, 14, 14, 16, 16, 19, 19,
21, 21, 22, 22, 25, 25, 26, 26, 28, 28, 31, 31, 32, 32, 35, 35, 37, 37, 38, 38, 41,
41, 42, 42, 44, 44, 47, 47, 49, 49, 50, 50, 52, 52, 55, 55, 56, 56, 59, 59, 61, 61,
62, 62, 64, 64, 67, 67, 69, 69, 70, 70, 73, 73, 74, 74, 76, 76, 79, 79, 81, 81, 82,
82, 84, 84, 87, 87, 88, 88, 91, 91, 93, 93, 94, 94, 97, 97, 98, 98, 100, 100, 103,
103, 104, 104, 107, 107, 109, 109, 110, 110, 112, 112, 115, 115, 117, 117, 118, 118,
121, 121, 122, 122, 124, 124, 127, 127, 128, 128, 131, 131, 133, 133, 134, 134, 137,
137, 138, 138, 140, 140, 143, 143, 145, 145, 146, 146, 148, 148, 151, 151, 152, 152,
155, 155, 157, 157, 158, 158, 161, 161, 162, 162, 164, 164, 167, 167, 168, 168, 171,
171, 173, 173, 174, 174, 176, 176, 179, 179, 181, 181, 182, 182, 185, 185, 186, 186,
188, 188, 191, 191, 193, 193, 194, 194, 196, 196, 199, 199, 200, 200, 203, 203, 205,
205, 206, 206, 208, 208, 211, 211, 213, 213, 214, 214, 217, 217, 218, 218, 220, 220,
223, 223, 224, 224, 227, 227, 229, 229, 230, 230, 233, 233, 234, 234, 236, 236, 239,
239, 241, 241, 242, 242, 244, 244, 247, 247, 248, 248, 251, 251, 253, 253, 254, 254]
```

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type`None`**classmethod** `sid_to_key(sid)`

Takes rid of a user and converts it to a key to be used by the DES cipher

Return type`Tuple[bytes, bytes]`**classmethod** `sidbytes_to_key(s)`

Builds final DES key from the strings generated in `sid_to_key`

Return type`bytes`**classmethod** `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`**version** = (1, 1, 0)**volatility3.plugins.windows.iat module****class** `IAT(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Extract Import Address Table to list API (functions) used by a program contained in external libraries

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property** `config`: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

```
version = (0, 0, 0)
```

volatility3.plugins.windows.info module

class `Info(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Show OS & kernel details of the memory sample being analyzed.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

`build_configuration()`

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_depends(`context, layer_name, index=0`)

List the dependencies of a given layer.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required layers from
- **layer_name** (`str`) – the name of the starting layer
- **index** (`int`) – the index/order of the layer

Return type

`Iterable[Tuple[int, DataLayerInterface]]`

Returns

An iterable containing the levels and layer objects for all dependent layers

classmethod get_kdbg_structure(`context, config_path, layer_name, symbol_table`)

Returns the KDDEBUGGER_DATA64 structure for a kernel

Return type

`ObjectInterface`

classmethod `get_kernel_module(context, layer_name, symbol_table)`

Returns the kernel module based on the layer and symbol_table

classmethod `get_kuser_structure(context, layer_name, symbol_table)`

Returns the _KUSER_SHARED_DATA structure for a kernel

Return type

ObjectInterface

classmethod `get_ntheadr_structure(context, config_path, layer_name)`

Gets the ntheadr structure for the kernel of the specified layer

Return type

ObjectInterface

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod `get_version_structure(context, layer_name, symbol_table)`

Returns the KdVersionBlock information from a kernel

Return type

ObjectInterface

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod **unsatisfied**(*context*, *config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 0, 0)

volatility3.plugins.windows.joblinks module

class **JobLinks**(*context*, *config_path*, *progress_callback*=None)

Bases: `PluginInterface`

Print process job link information

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Return type

`TreeGrid`

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

```
version = (1, 0, 0)
```

volatility3.plugins.windows.ldrmodules module

class `LdrModules`(*context, config_path, progress_callback=None*)

Bases: `PluginInterface`

Lists the loaded modules in a particular windows memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

`build_configuration()`

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.lsadump module

class Lsadump(context, config_path, progress_callback=None)

Bases: *PluginInterface*

Dumps lsa secrets from memory

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (str) – The path to configuration data within the context configuration data
- **progress_callback** (Optional[Callable[[float, str], None]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod decrypt_aes(*secret, key*)

Based on code from <http://lab.mediaservice.net/code/cachedump.rb>

Return type*bytes***classmethod decrypt_secret**(*secret, key*)

Python implementation of SystemFunction005.

Decrypts a block of data with DES using given key. Note that key can be longer than 7 bytes.

classmethod get_lsa_key(*sechive, bootkey, vista_or_later*)**Return type***Optional[bytes]***classmethod get_requirements**()

Returns a list of Requirement objects for this plugin.

classmethod get_secret_by_name(*sechive, name, lsakey, is_vista_or_later*)**classmethod make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 0, 0)

volatility3.plugins.windows.malfind module**class Malfind(context, config_path, progress_callback=None)**

Bases: `PluginInterface`

Lists process memory ranges that potentially contain injected code.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: HierarchicalDict

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: str

The configuration path on which this configurable lives.

property context: ContextInterface

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `is_vad_empty(proc_layer, vad)`

Check if a VAD region is either entirely unavailable due to paging, entirely consisting of zeros, or a combination of the two. This helps ignore false positives whose VAD flags match task._injection_filter requirements but there's no data and thus not worth reporting it.

Parameters

- **proc_layer** – the process layer
- **vad** – the MMVAD structure to test

Returns

A boolean indicating whether a vad is empty or not

classmethod `list_injections(context, kernel_layer_name, symbol_table, proc)`

Generate memory regions for a process that may contain injected code.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **kernel_layer_name** (*str*) – The name of the kernel layer from which to read the VAD protections
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **proc** (*ObjectInterface*) – an _EPROCESS instance

Return type

Iterable[*Tuple*[*ObjectInterface*, *bytes*]]

Returns

An iterable of VAD instances and the first 64 bytes of data containing in that region

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows.mbrscan module**class MBRScan(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Scans for and parses potential Master Boot Records (MBRs)

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_hash(*data*)

Return type

str

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Return type

TreeGrid

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 0, 0)

volatility3.plugins.windows.memmap module

class `Memmap(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Prints the memory map

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows.mftscan module**class** `ADS(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Scans for Alternate Data Stream

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

class MFTScan(context, config_path, progress_callback=None)

Bases: *PluginInterface, TimeLinerInterface*

Scans for MFT FILE objects present in a particular windows memory image.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

`version = (0, 0, 0)`

volatility3.plugins.windows.modscan module

class `ModScan(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Scans for modules present in a particular windows memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod find_session_layer(context, session_layers, base_address)

Given a base address and a list of layer names, find a layer that can access the specified address.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** – The name of the layer on which to operate
- **symbol_table** – The name of the table containing the kernel symbols
- **session_layers** (`Iterable[str]`) – A list of session layer names
- **base_address** (`int`) – The base address to identify the layers that can access it

Returns

Layer name or None if no layers that contain the base address can be found

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `get_session_layers(context, layer_name, symbol_table, pids=None)`

Build a cache of possible virtual layers, in priority starting with the primary/kernel layer. Then keep one layer per session by cycling through the process list.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **pids** (*List[int]*) – A list of process identifiers to include exclusively or None for no filter

Return type

Generator[str, None, None]

Returns

A list of session layer names

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod `scan_modules(context, layer_name, symbol_table)`

Scans for modules using the poolscanner module and constraints.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type

Iterable[ObjectInterface]

Returns

A list of Driver objects as found from the *layer_name* layer based on Driver pool signatures

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.modules module

class `Modules(context, config_path, progress_callback=None)`

Bases: *PluginInterface*

Lists the loaded kernel modules.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod find_session_layer(*context, session_layers, base_address*)

Given a base address and a list of layer names, find a layer that can access the specified address.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** – The name of the layer on which to operate
- **symbol_table** – The name of the table containing the kernel symbols
- **session_layers** (*Iterable[str]*) – A list of session layer names
- **base_address** (*int*) – The base address to identify the layers that can access it

Returns

Layer name or None if no layers that contain the base address can be found

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type*List[RequirementInterface]***classmethod get_session_layers**(*context, layer_name, symbol_table, pids=None*)

Build a cache of possible virtual layers, in priority starting with the primary/kernel layer. Then keep one layer per session by cycling through the process list.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **pids** (*List[int]*) – A list of process identifiers to include exclusively or None for no filter

Return type*Generator[str, None, None]***Returns**

A list of session layer names

classmethod list_modules(*context, layer_name, symbol_table*)

Lists all the modules in the primary layer.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type*Iterable[ObjectInterface]***Returns**

A list of Modules as retrieved from PsLoadedModuleList

classmethod **make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property** **open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type*None***classmethod** **unsatisfied**(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (1, 1, 0)`**volatility3.plugins.windows.mutantscan module****class** `MutantScan(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Scans for mutexes present in a particular windows memory image.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(`context, base_config_path, **kwargs`)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod scan_mutants(*context, layer_name, symbol_table*)

Scans for mutants using the poolscanner module and constraints.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type

Iterable[ObjectInterface]

Returns

A list of Mutant objects found by scanning memory for the Mutant pool signatures

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows.netscan module

class NetScan(*context*, *config_path*, *progress_callback*=None)

Bases: [PluginInterface](#), [TimeLinerInterface](#)

Scans for network objects present in a particular windows memory image.

Parameters

- **context** ([ContextInterface](#)) – The context that the plugin will operate within
- **config_path** ([str](#)) – The path to configuration data within the context configuration data
- **progress_callback** ([Optional](#)[[Callable](#)[[[float](#), [str](#)], None]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

[HierarchicalDict](#)

property config: [HierarchicalDict](#)

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: [str](#)

The configuration path on which this configurable lives.

property context: [ContextInterface](#)

The context object that this configurable belongs to/configuration is stored in.

static create_netscan_constraints(*context*, *symbol_table*)

Creates a list of Pool Tag Constraints for network objects.

Parameters

- **context** ([ContextInterface](#)) – The context to retrieve required elements (layers, symbol tables) from
- **symbol_table** ([str](#)) – The name of an existing symbol table containing the symbols / types

Return type

[List](#)[[PoolConstraint](#)]

Returns

The list containing the built constraints.

classmethod create_netscan_symbol_table(*context*, *layer_name*, *nt_symbol_table*, *config_path*)

Creates a symbol table for TCP Listeners and TCP/UDP Endpoints.

Parameters

- **context** ([ContextInterface](#)) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** ([str](#)) – The name of the layer on which to operate
- **nt_symbol_table** ([str](#)) – The name of the table containing the kernel symbols

- **config_path** (*str*) – The config path where to find symbol files

Return type*str***Returns**

The name of the constructed symbol table

classmethod **determine_tcpip_version**(*context, layer_name, nt_symbol_table*)

Tries to determine which symbol filename to use for the image's tcpip driver. The logic is partially taken from the info plugin.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **nt_symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type*Tuple[str, Type]***Returns**

The filename of the symbol table to use.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod **get_requirements**()

Returns a list of Requirement objects for this plugin.

classmethod **make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str*

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod `scan(context, layer_name, nt_symbol_table, netscan_symbol_table)`

Scans for network objects using the poolscanner module and constraints.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **nt_symbol_table** (*str*) – The name of the table containing the kernel symbols
- **netscan_symbol_table** (*str*) – The name of the table containing the network object symbols (_TCP_LISTENER etc.)

Return type

Iterable[ObjectInterface]

Returns

A list of network objects found by scanning the *layer_name* layer for network pool signatures

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.netstat module

class `NetStat(context, config_path, progress_callback=None)`

Bases: *PluginInterface, TimeLinerInterface*

Traverses network tracking structures present in a particular windows memory image.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod create_tcpip_symbol_table(*context, config_path, layer_name, tcpip_module_offset, tcpip_module_size*)

DEPRECATED: Use PDBUtility.symbol_table_from_pdb instead

Creates symbol table for the current image's tcpip.sys driver.

Searches the memory section of the loaded tcpip.sys module for its PDB GUID and loads the associated symbol table into the symbol space.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **config_path** (*str*) – The config path where to find symbol files
- **layer_name** (*str*) – The name of the layer on which to operate
- **tcpip_module_offset** (*int*) – This memory dump's tcpip.sys image offset
- **tcpip_module_size** (*int*) – The size of *tcpip.sys* for this dump

Return type

str

Returns

The name of the constructed and loaded symbol table

classmethod enumerate_structures_by_port(*context, layer_name, net_symbol_table, port, port_pool_addr, proto='tcp'*)

Lists all UDP Endpoints and TCP Listeners by parsing UdpPortPool and TcpPortPool.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **net_symbol_table** (*str*) – The name of the table containing the tcpip types
- **port** (*int*) – Current port as integer to lookup the associated object.
- **port_pool_addr** (*int*) – Address of port pool object

- **proto** – Either “tcp” or “udp” to decide which types to use.

Return type`Iterable[ObjectInterface]`**Returns**

The list of network objects from this image’s TCP and UDP *PortPools*

classmethod `find_port_pools(context, layer_name, net_symbol_table, tcpip_symbol_table, tcpip_module_offset)`

Finds the given image’s port pools. Older Windows versions (presumably < Win10 build 14251) use driver symbols called *UdpPortPool* and *TcpPortPool* which point towards the pools. Newer Windows versions use *UdpCompartmentSet* and *TcpCompartmentSet*, which we first have to translate into the port pool address. See also: <http://redplait.blogspot.com/2016/06/tcpip-port-pools-in-fresh-windows-10.html>

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (`str`) – The name of the layer on which to operate
- **net_symbol_table** (`str`) – The name of the table containing the tcpip types
- **tcpip_module_offset** (`int`) – This memory dump’s tcpip.sys image offset
- **tcpip_symbol_table** (`str`) – The name of the table containing the tcpip driver symbols

Return type`Tuple[int, int]`**Returns**

The tuple containing the address of the UDP and TCP port pool respectively.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `get_tcpip_module(context, layer_name, nt_symbols)`

Uses *windows.modules* to find tcpip.sys in memory.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (`str`) – The name of the layer on which to operate
- **nt_symbols** (`str`) – The name of the table containing the kernel symbols

Return type`Optional[ObjectInterface]`**Returns**

The constructed tcpip.sys module object.

classmethod `list_sockets(context, layer_name, nt_symbols, net_symbol_table, tcpip_module_offset, tcpip_symbol_table)`

Lists all UDP Endpoints, TCP Listeners and TCP Endpoints in the primary layer that are in tcpip.sys’s *UdpPortPool*, *TcpPortPool* and TCP Endpoint partition table, respectively.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **nt_symbols** (*str*) – The name of the table containing the kernel symbols
- **net_symbol_table** (*str*) – The name of the table containing the tcpip types
- **tcpip_module_offset** (*int*) – Offset of *tcpip.sys*'s PE image in memory
- **tcpip_symbol_table** (*str*) – The name of the table containing the tcpip driver symbols

Return type*Iterable[ObjectInterface]***Returns**

The list of network objects from the *layer_name* layer's *PartitionTable* and *PortPools*

classmethod **make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from *kwargs*.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property** **open**

Returns a context manager and thus can be called like *open*

classmethod **parse_bitmap**(*context, layer_name, bitmap_offset, bitmap_size_in_byte*)

Parses a given bitmap and looks for each occurrence of a 1.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **bitmap_offset** (*int*) – Start address of bitmap
- **bitmap_size_in_byte** (*int*) – Bitmap size in Byte, not in bit.

Return type*list***Returns**

The list of indices at which a 1 was found.

classmethod `parse_hashtable(context, layer_name, ht_offset, ht_length, alignment, net_symbol_table)`

Parses a hashtable quick and dirty.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **ht_offset** (*int*) – Beginning of the hash table
- **ht_length** (*int*) – Length of the hash table

Return type

Generator[ObjectInterface, None, None]

Returns

The hash table entries which are `_not_` empty

classmethod `parse_partitions(context, layer_name, net_symbol_table, tcpip_symbol_table, tcpip_module_offset)`

Parses tcpip.sys's PartitionTable containing established TCP connections. The amount of Partition depends on the value of the symbol *PartitionCount* and correlates with the maximum processor count (refer to Art of Memory Forensics, chapter 11).

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **net_symbol_table** (*str*) – The name of the table containing the tcpip types
- **tcpip_symbol_table** (*str*) – The name of the table containing the tcpip driver symbols
- **tcpip_module_offset** (*int*) – The offset of the tcpip module

Return type

Iterable[ObjectInterface]

Returns

The list of TCP endpoint objects from the *layer_name* layer's *PartitionTable*

classmethod `read_pointer(context, layer_name, offset, length)`

Reads a pointer at a given offset and returns the address it points to.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **offset** (*int*) – Offset of pointer
- **length** (*int*) – Pointer length

Return type

int

Returns

The value the pointer points to.

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.poolscanner module

class PoolConstraint(tag, type_name, object_type=None, page_type=None, size=None, index=None, alignment=1, skip_type_test=False, additional_structures=None)

Bases: `object`

Class to maintain tag/size/index/type information about Pool header tags.

class PoolHeaderScanner(module, constraint_lookup, alignment)

Bases: `ScannerInterface`

property context: `ContextInterface` | None

property layer_name: `str` | None

thread_safe = False

version = (0, 0, 0)

class PoolScanner(context, config_path, progress_callback=None)

Bases: `PluginInterface`

A generic pool scanner plugin.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

static builtin_constraints(symbol_table, tags_filter=None)

Get built-in PoolConstraints given a list of pool tags.

The tags_filter is a list of pool tags, and the associated PoolConstraints are returned. If tags_filter is empty or not supplied, then all builtin constraints are returned.

Parameters

- **symbol_table** (*str*) – The name of the symbol table to prepend to the types used
- **tags_filter** (*List[bytes]*) – List of tags to return or None to return all

Return type

List[PoolConstraint]

Returns

A list of well-known constructed PoolConstraints that match the provided tags

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod generate_pool_scan(context, layer_name, symbol_table, constraints)

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **constraints** (*List[PoolConstraint]*) – List of pool constraints used to limit the scan results

Return type

Generator[Tuple[PoolConstraint, ObjectInterface, ObjectInterface], None, None]

Returns

Iterable of tuples, containing the constraint that matched, the object from memory, the object header used to determine the object

classmethod `get_pool_header_table(context, symbol_table)`

Returns the appropriate symbol_table containing a _POOL_HEADER type, even if the original symbol table doesn't contain one.

Parameters

- **context** (*ContextInterface*) – The context that the symbol tables does (or will) reside in
- **symbol_table** (*str*) – The expected symbol_table to contain the _POOL_HEADER type

Return type

str

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

classmethod `pool_scan(context, layer_name, symbol_table, pool_constraints, alignment=8, progress_callback=None)`

Returns the _POOL_HEADER object (based on the symbol_table template) after scanning through layer_name returning all headers that match any of the constraints provided. Only one constraint can be provided per tag.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **pool_constraints** (*List[PoolConstraint]*) – List of pool constraints used to limit the scan results

- **alignment** (`int`) – An optional value that all pool headers will be aligned to
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – An optional function to provide progress feedback whilst scanning

Return type

`Generator[Tuple[PoolConstraint, ObjectInterface], None, None]`

Returns

An Iterable of pool constraints and the pool headers associated with them

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Return type

`TreeGrid`

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 0, 0)

class PoolType(*value, names=None, *, module=None, qualname=None, type=None, start=1, boundary=None*)

Bases: `IntFlag`

Class to maintain the different possible PoolTypes The values must be integer powers of 2.

FREE = 4

NONPAGED = 2

PAGED = 1

as_integer_ratio()

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(byteorder='big', *, signed=False)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use 'sys.byteorder' as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An `OverflowError` is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If `byteorder` is 'big', the most significant byte is at the beginning of the byte array. If `byteorder` is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If `signed` is `False` and a negative integer is given, an `OverflowError` is raised.

volatility3.plugins.windows.privileges module**class Privs**(*args, **kwargs)

Bases: [*PluginInterface*](#)

Lists process token privileges

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a `HierarchicalDictionary` of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too.

Return type

[*HierarchicalDict*](#)

property config: [*HierarchicalDict*](#)

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: [*ContextInterface*](#)

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 2, 0)

volatility3.plugins.windows.pslist module

class PsList(*context*, *config_path*, *progress_callback*=None)

Bases: [PluginInterface](#), [TimeLinerInterface](#)

Lists the processes present in a particular windows memory image.

Parameters

- **context** ([ContextInterface](#)) – The context that the plugin will operate within
- **config_path** ([str](#)) – The path to configuration data within the context configuration data
- **progress_callback** ([Optional](#)[[Callable](#)[[[float](#), [str](#)], None]]) – A callable that can provide feedback at progress points

PHYSICAL_DEFAULT = False

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

[HierarchicalDict](#)

property config: [HierarchicalDict](#)

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: [str](#)

The configuration path on which this configurable lives.

property context: [ContextInterface](#)

The context object that this configurable belongs to/configuration is stored in.

classmethod create_name_filter(*name_list*=None, *exclude*=False)

A factory for producing filter functions that filter based on a list of process names.

Parameters

- **name_list** ([List](#)[[str](#)]) – A list of process names that are acceptable, all other processes will be filtered out
- **exclude** ([bool](#)) – Accept only tasks that are not in name_list

Return type

[Callable](#)[[[ObjectInterface](#)], [bool](#)]

Returns

Filter function for passing to the *list_processes* method

classmethod create_pid_filter(*pid_list*=None, *exclude*=False)

A factory for producing filter functions that filter based on a list of process IDs.

Parameters

- **pid_list** ([List](#)[[int](#)]) – A list of process IDs that are acceptable, all other processes will be filtered out
- **exclude** ([bool](#)) – Accept only tasks that are not in pid_list

Return type`Callable[[ObjectInterface], bool]`**Returns**

Filter function for passing to the *list_processes* method

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod list_processes(context, layer_name, symbol_table, filter_func=<function PsList.<lambda>>)

Lists all the processes in the primary layer that are in the pid config option.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **filter_func** (`Callable[[ObjectInterface], bool]`) – A function which takes an EPROCESS object and returns True if the process should be ignored/filtered

Return type`Iterable[ObjectInterface]`**Returns**

The list of EPROCESS objects from the *layer_name* layer's PsActiveProcessHead list after filtering

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

classmethod process_dump(context, kernel_table_name, pe_table_name, proc, open_method)

Extracts the complete data for a process as a FileHandlerInterface

Parameters

- **context** (*ContextInterface*) – the context to operate upon
- **kernel_table_name** (*str*) – the name for the symbol table containing the kernel’s symbols
- **pe_table_name** (*str*) – the name for the symbol table containing the PE format symbols
- **proc** (*ObjectInterface*) – the process object whose memory should be output
- **open_method** (*Type[FileHandlerInterface]*) – class to provide context manager for opening the file

Return type*FileHandlerInterface***Returns**

An open FileHandlerInterface object containing the complete data for the process or None in the case of failure

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type*None***classmethod unsatisfied(context, config_path)**

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type*Dict[str, RequirementInterface]*

version = (2, 0, 0)

volatility3.plugins.windows.psscan module**class PsScan**(*context, config_path, progress_callback=None*)Bases: *PluginInterface, TimeLinerInterface*

Scans for processes present in a particular windows memory image.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod create_offset_filter(*context, layer_name, offset=None, physical=True, exclude=False*)

A factory for producing filter functions that filter based on the physical offset of the process.

Parameters

- **offset** (*int*) – A number that is the physical offset to be filtered out
- **exclude** (*bool*) – Accept only tasks that are not the offset argument

Return type*Callable[[ObjectInterface], bool]***Returns**

Filter function to be passed to the list of processes.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_osversion(*context, layer_name, symbol_table*)

Returns the complete OS version (MAJ,MIN,BUILD)

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from

- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type*Tuple*[*int*, *int*, *int*]**Returns**

A tuple with (MAJ,MIN,BUILD)

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property** `open`

Returns a context manager and thus can be called like open

classmethod `physical_offset_from_virtual(context, layer_name, proc)`

Calculate the physical offset from the virtual offset of a process.

Parameters

- **context** – The context containing layers and modules information.
- **layer_name** – The name of the layer containing the process memory.
- **proc** – The process object for which to calculate the physical offset.

Returns

The physical offset of the process.

Return type*int***Raises****TypeError** – If the primary layer is not an Intel layer.**run()**

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod `scan_processes(context, layer_name, symbol_table, filter_func=<function PsScan.<lambda>>)`

Scans for processes using the poolscanner module and constraints.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type

Iterable[ObjectInterface]

Returns

A list of processes found by scanning the *layer_name* layer for process pool signatures

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 1, 0)

classmethod `virtual_process_from_physical(context, layer_name, symbol_table, proc)`

Returns a virtual process from a physical addressed one

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols
- **proc** (*ObjectInterface*) – the process object with physical address

Return type

Optional[ObjectInterface]

Returns

A process object on virtual address layer

volatility3.plugins.windows.pstree module**class PsTree(*args, **kwargs)**Bases: *PluginInterface*

Plugin for listing processes in a tree based on their parent process ID.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

find_level(pid, filter_func=<function PsTree.<lambda>>)

Finds how deep the pid is in the processes list.

Return type*None***classmethod get_requirements()**

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str*

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows.sessions module**class Sessions(context, config_path, progress_callback=None)**

Bases: *PluginInterface, TimeLinerInterface*

lists Processes with Session information extracted from Environmental Variables

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type*None*

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.windows.skeleton_key_check module

class `Skeleton_Key_Check(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Looks for signs of Skeleton Key malware

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration

- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows.ssdt module

class SSDT(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Lists the system call table.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data

- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

classmethod build_module_collection(context, layer_name, symbol_table)

Builds a collection of modules.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (`str`) – The name of the layer on which to operate
- **symbol_table** (`str`) – The name of the table containing the kernel symbols

Return type

ModuleCollection

Returns

A Module collection of available modules based on *Modules.list_modules*

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Return type`TreeGrid`**Returns**

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type`None`**classmethod unsatisfied(context, config_path)**

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`

version = (1, 0, 0)

volatility3.plugins.windows.strings module

class Strings(context, config_path, progress_callback=None)

Bases: `PluginInterface`

Reads output from the strings command and indicates which process(es) each string belongs to.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod generate_mapping(*context, layer_name, symbol_table, progress_callback=None, pid_list=None*)

Creates a reverse mapping between virtual addresses and physical addresses.

Parameters

- **context** (*ContextInterface*) – the context for the method to run against
- **layer_name** (*str*) – the layer to map against the string lines
- **symbol_table** (*str*) – the name of the symbol table for the provided layer
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – an optional callable to display progress
- **pid_list** (*Optional[List[int]]*) – a list of process IDs to consider when generating the reverse map

Return type

Dict[int, Set[Tuple[str, int]]]

Returns

A mapping of virtual offsets to strings and physical offsets

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

```
strings_pattern = re.compile(b'^(?:\\W*)([0-9]+)(?:\\W*)(\\w[\\w\\W]+)\\n?')
```

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

```
version = (1, 2, 0)
```

volatility3.plugins.windows.svcscan module**class ServiceBinaryInfo(dll, binary)**

Bases: `tuple`

Create new instance of ServiceBinaryInfo(dll, binary)

binary: `Union[str, BaseAbsentValue]`

Alias for field number 1

count(value, /)

Return number of occurrences of value.

dll: `Union[str, BaseAbsentValue]`

Alias for field number 0

index(*value*, *start*=0, *stop*=9223372036854775807, /)

Return first index of value.

Raises ValueError if the value is not present.

class `SvcScan(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Scans for windows services.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

static create_service_table(*context*, *symbol_table*, *config_path*)

Constructs a symbol table containing the symbols for services depending upon the operating system in use.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **symbol_table** (`str`) – The name of the table containing the kernel symbols
- **config_path** (`str`) – The configuration path for any settings required by the new table

Return type

`str`

Returns

A symbol table containing the symbols necessary for services

static get_record_tuple(*service_record*, *binary_info*)

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (2, 0, 0)

volatility3.plugins.windows.symlinkscan module**class SymlinkScan**(*context, config_path, progress_callback=None*)Bases: *PluginInterface, TimeLinerInterface*

Scans for links present in a particular windows memory image.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str*

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod scan_symlinks(*context, layer_name, symbol_table*)

Scans for links using the poolscanner module and constraints.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type

Iterable[ObjectInterface]

Returns

A list of symlink objects found by scanning memory for the Symlink pool signatures

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.windows.thrdscan module**class** `ThrdScan(context, config_path, progress_callback=None)`Bases: `PluginInterface`, `TimeLinerInterface`

Scans for windows threads.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

classmethod make_subconfig(`context, base_config_path, **kwargs`)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod scan_threads(*context, layer_name, symbol_table*)

Scans for threads using the poolscanner module and constraints.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type

Iterable[ObjectInterface]

Returns

A list of _ETHREAD objects found by scanning memory for the “Thre” / “ThrxE5” pool signatures

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.truecrypt module**class** **Passphrase**(*context, config_path, progress_callback=None*)Bases: *PluginInterface*

TrueCrypt Cached Passphrase Finder

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type*List[RequirementInterface]***classmethod make_subconfig**(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type*str***property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Return type

TreeGrid

Returns

A TreeGrid object that can then be passed to a Renderer.

scan_module(module_base, layer_name)

Scans the TrueCrypt kernel module for cached passphrases.

Parameters

- **module_base** (*int*) – the module’s DLL base
- **layer_name** (*str*) – the name of the layer in which the module resides

Return type

Generator[Tuple[int, str], None, None]

Generates:

A tuple of the offset at which a password is found, and the password

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 1, 0)

volatility3.plugins.windows.vadinfo module**class VadInfo(*args, **kwargs)**Bases: *PluginInterface*

Lists process memory ranges.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

MAXSIZE_DEFAULT = 1073741824**build_configuration()**

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type*List[RequirementInterface]***classmethod list_vads(proc, filter_func=<function VadInfo.<lambda>>)**

Lists the Virtual Address Descriptors of a specific process.

Parameters

- **proc** (*ObjectInterface*) – _EPROCESS object from which to list the VADs
- **filter_func** (*Callable[[ObjectInterface], bool]*) – Function to take a virtual address descriptor value and return True if it should be filtered out

Return type*Generator[ObjectInterface, None, None]***Returns**

A list of virtual address descriptors based on the process and filtered based on the filter function

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

classmethod protect_values(*context, layer_name, symbol_table*)

Look up the array of memory protection constants from the memory sample. These don't change often, but if they do in the future, then finding them dynamically versus hard-coding here will ensure we parse them properly.

Parameters

- **context** (*ContextInterface*) – The context to retrieve required elements (layers, symbol tables) from
- **layer_name** (*str*) – The name of the layer on which to operate
- **symbol_table** (*str*) – The name of the table containing the kernel symbols

Return type

Iterable[int]

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(*handler*)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(*context, config_path*)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`**classmethod** `vad_dump(context, proc, vad, open_method, maxsize=1073741824)`

Extracts the complete data for Vad as a FileInterface.

Parameters

- **context** (`ContextInterface`) – The context to retrieve required elements (layers, symbol tables) from
- **proc** (`ObjectInterface`) – an `_EPROCESS` instance
- **vad** (`ObjectInterface`) – The suspected VAD to extract (`ObjectInterface`)
- **open_method** (`Type[FileHandlerInterface]`) – class to provide context manager for opening the file
- **maxsize** (`int`) – Max size of VAD section (default `MAXSIZE_DEFAULT`)

Return type`Optional[FileHandlerInterface]`**Returns**

An open FileInterface object containing the complete data for the process or None in the case of failure

version = (2, 0, 0)**volatility3.plugins.windows.vadwalk module****class** `VadWalk(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Walk the VAD tree.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: [`ContextInterface`](#)

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

[`List\[RequirementInterface\]`](#)

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** ([`ContextInterface`](#)) – The context in which to store the new configuration
- **base_config_path** ([`str`](#)) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

[`str`](#)

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Return type

[`TreeGrid`](#)

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

[`None`](#)

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]``version = (1, 0, 0)`**volatility3.plugins.windows.vadyarascan module****class** `VadYaraScan(context, config_path, progress_callback=None)`Bases: `PluginInterface`

Scans all the Virtual Address Descriptor memory maps using yara.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`**static get_vad_maps(task)**

Creates a map of start/end addresses within a virtual address descriptor tree.

Parameters

task (`ObjectInterface`) – The EPROCESS object of which to traverse the vad tree

Return type`Iterable[Tuple[int, int]]`**Returns**

An iterable of tuples containing start and end addresses for each descriptor

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 1)

volatility3.plugins.windows.verinfo module**class VerInfo**(context, config_path, progress_callback=None)Bases: *PluginInterface*

Lists version information from PE files.

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional*[*Callable*[[*float*, *str*], *None*]]) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type*HierarchicalDict***property config:** *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod find_version_info(context, layer_name, filename)

Searches for an original filename, then tracks back to find the VS_VERSION_INFO and read the fixed version information structure

Return type*Optional*[*Tuple*[*int*, *int*, *int*, *int*]]**classmethod get_requirements()**

Returns a list of Requirement objects for this plugin.

Return type*List*[*RequirementInterface*]**classmethod get_version_information**(context, pe_table_name, layer_name, base_address)

Get File and Product version information from PE files.

Parameters

- **context** (*ContextInterface*) – volatility context on which to operate
- **pe_table_name** (*str*) – name of the PE table
- **layer_name** (*str*) – name of the layer containing the PE file
- **base_address** (*int*) – base address of the PE (where MZ is found)

Return type*Tuple*[*int*, *int*, *int*, *int*]

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (1, 0, 0)

volatility3.plugins.windows.virtmap module**class** `VirtMap`(*context*, *config_path*, *progress_callback*=None)Bases: `PluginInterface`

Lists virtual mapped sections.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod determine_map(*module*)

Returns the virtual map from a windows kernel module.

Return type`Dict[str, List[Tuple[int, int]]]`**classmethod get_requirements()**

Returns a list of Requirement objects for this plugin.

Return type`List[RequirementInterface]`**classmethod make_subconfig**(*context*, *base_config_path*, ***kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

classmethod scannable_sections(module)**Return type**`Generator[Tuple[int, int], None, None]`**set_open_method(handler)**

Sets the file handler to be used by this plugin.

Return type`None`**classmethod unsatisfied(context, config_path)**

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type`Dict[str, RequirementInterface]`

version = (0, 0, 0)

Submodules

volatility3.plugins.banners module

class Banners(context, config_path, progress_callback=None)

Bases: `PluginInterface`

Attempts to identify potential linux banners in an image

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data

- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod locate_banners(*context, layer_name*)

Identifies banners from a memory image

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.configwriter module**class ConfigWriter(context, config_path, progress_callback=None)**

Bases: `PluginInterface`

Runs the automagics and both prints and outputs configuration in the output directory.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: HierarchicalDict

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: str

The configuration path on which this configurable lives.

property context: ContextInterface

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.frameworkinfo module

class FrameworkInfo(*context, config_path, progress_callback=None*)

Bases: *PluginInterface*

Plugin to list the various modular components of Volatility

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod make_subconfig(*context, base_config_path, **kwargs*)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod unsatisfied(context, config_path)

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (0, 0, 0)

volatility3.plugins.isfinfo module**class IsfInfo(context, config_path, progress_callback=None)**

Bases: *PluginInterface*

Determines information about the currently available ISF files, or a specific one

Parameters

- **context** (*ContextInterface*) – The context that the plugin will operate within
- **config_path** (*str*) – The path to configuration data within the context configuration data
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

HierarchicalDict

property config: *HierarchicalDict*

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: *str*

The configuration path on which this configurable lives.

property context: *ContextInterface*

The context object that this configurable belongs to/configuration is stored in.

classmethod get_requirements()

Returns a list of Requirement objects for this plugin.

Return type

List[RequirementInterface]

classmethod list_all_isf_files()

Lists all the ISF files that can be found

Return type

Generator[str, None, None]

classmethod make_subconfig(context, base_config_path, **kwargs)

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (2, 0, 0)

volatility3.plugins.layerwriter module

class `LayerWriter(context, config_path, progress_callback=None)`

Bases: `PluginInterface`

Runs the automagics and writes out the primary layer produced by the stacker.

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built. Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type

`HierarchicalDict`

property config: `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property config_path: `str`

The configuration path on which this configurable lives.

property context: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

default_block_size = 5242880

classmethod `get_requirements()`

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (*ContextInterface*) – The context in which to store the new configuration
- **base_config_path** (*str*) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

str

property open

Returns a context manager and thus can be called like open

run()

Executes the functionality of the code.

Note: This method expects *self.validate* to have been called to ensure all necessary options have been provided

Returns

A TreeGrid object that can then be passed to a Renderer.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

None

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

Dict[str, RequirementInterface]

version = (2, 0, 0)

classmethod `write_layer(context, layer_name, preferred_name, open_method, chunk_size=None, progress_callback=None)`

Produces a FileHandler from the named layer in the provided context or None on failure

Parameters

- **context** (*ContextInterface*) – the context from which to read the memory layer
- **layer_name** (*str*) – the name of the layer to write out
- **preferred_name** (*str*) – a string with the preferred filename for hte file
- **chunk_size** (*Optional[int]*) – an optional size for the chunks that should be written (defaults to 0x500000)
- **open_method** (*Type[FileHandlerInterface]*) – class for creating FileHandler context managers
- **progress_callback** (*Optional[Callable[[float, str], None]]*) – an optional function that takes a percentage and a string that displays output

Return type*Optional[FileHandlerInterface]***volatility3.plugins.timeliner module****class TimeLinerInterface**Bases: *object*

Interface defining methods that timeliner will use to generate a body file.

abstract generate_timeline()

Method generates Tuples of (description, timestamp_type, timestamp)

These need not be generated in any particular order, sorting will be done later

Return type*Generator[Tuple[str, TimeLinerType, datetime], None, None]***class TimeLinerType**(*value, names=None, *, module=None, qualname=None, type=None, start=1, boundary=None*)Bases: *IntEnum***ACCESSED** = 3**CHANGED** = 4**CREATED** = 1**MODIFIED** = 2**as_integer_ratio()**

Return integer ratio.

Return a pair of integers, whose ratio is exactly equal to the original int and with a positive denominator.

```
>>> (10).as_integer_ratio()
(10, 1)
>>> (-10).as_integer_ratio()
(-10, 1)
>>> (0).as_integer_ratio()
(0, 1)
```

bit_count()

Number of ones in the binary representation of the absolute value of self.

Also known as the population count.

```
>>> bin(13)
'0b1101'
>>> (13).bit_count()
3
```

bit_length()

Number of bits necessary to represent self in binary.

```
>>> bin(37)
'0b100101'
>>> (37).bit_length()
6
```

conjugate()

Returns self, the complex conjugate of any int.

denominator

the denominator of a rational number in lowest terms

from_bytes(*byteorder='big', *, signed=False*)

Return the integer represented by the given array of bytes.

bytes

Holds the array of bytes to convert. The argument must either support the buffer protocol or be an iterable object producing bytes. Bytes and bytearray are examples of built-in objects that support the buffer protocol.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use 'sys.byteorder' as the byte order value. Default is to use 'big'.

signed

Indicates whether two's complement is used to represent the integer.

imag

the imaginary part of a complex number

numerator

the numerator of a rational number in lowest terms

real

the real part of a complex number

to_bytes(*length=1, byteorder='big', *, signed=False*)

Return an array of bytes representing an integer.

length

Length of bytes object to use. An OverflowError is raised if the integer is not representable with the given number of bytes. Default is length 1.

byteorder

The byte order used to represent the integer. If byteorder is 'big', the most significant byte is at the beginning of the byte array. If byteorder is 'little', the most significant byte is at the end of the byte array. To request the native byte order of the host system, use `sys.byteorder` as the byte order value. Default is to use 'big'.

signed

Determines whether two's complement is used to represent the integer. If signed is False and a negative integer is given, an OverflowError is raised.

class `Timeliner(*args, **kwargs)`

Bases: `PluginInterface`

Runs all relevant plugins that provide time related information and orders the results by time.

Parameters

- **context** – The context that the plugin will operate within
- **config_path** – The path to configuration data within the context configuration data
- **progress_callback** – A callable that can provide feedback at progress points

build_configuration()

Builds the configuration to save for the plugin such that it can be reconstructed.

property **config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property **config_path:** `str`

The configuration path on which this configurable lives.

property **context:** `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod **get_requirements()**

Returns a list of Requirement objects for this plugin.

Return type

`List[RequirementInterface]`

classmethod **get_usable_plugins(selected_list=None)**

Return type

`List[Type]`

classmethod **make_subconfig(context, base_config_path, **kwargs)**

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from kwargs.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type`str`**property open**

Returns a context manager and thus can be called like open

run()

Isolate each plugin and run it.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type`None`**classmethod unsatisfied(context, config_path)**

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```

unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))

```

Return type`Dict[str, RequirementInterface]`

version = (0, 0, 0)

volatility3.plugins.yarascan module**class YaraScan(context, config_path, progress_callback=None)**

Bases: `PluginInterface`

Scans kernel memory using yara rules (string or file).

Parameters

- **context** (`ContextInterface`) – The context that the plugin will operate within
- **config_path** (`str`) – The path to configuration data within the context configuration data
- **progress_callback** (`Optional[Callable[[float, str], None]]`) – A callable that can provide feedback at progress points

build_configuration()

Constructs a HierarchicalDictionary of all the options required to build this component in the current context.

Ensures that if the class has been created, it can be recreated using the configuration built Inheriting classes must override this to ensure any dependent classes update their configurations too

Return type`HierarchicalDict`**property config:** `HierarchicalDict`

The Hierarchical configuration Dictionary for this Configurable object.

property `config_path`: `str`

The configuration path on which this configurable lives.

property `context`: `ContextInterface`

The context object that this configurable belongs to/configuration is stored in.

classmethod `get_requirements()`

Returns the requirements needed to run yarascan directly, combining the `TranslationLayerRequirement` and the requirements from `get_yarascan_option_requirements`.

Return type

`List[RequirementInterface]`

classmethod `get_yarascan_option_requirements()`

Returns the requirements needed for the command lines options used by yarascan. This can then also be used by other plugins that are using yarascan. This does not include a `TranslationLayerRequirement` or a `ModuleRequirement`.

Return type

`List[RequirementInterface]`

classmethod `make_subconfig(context, base_config_path, **kwargs)`

Convenience function to allow constructing a new randomly generated sub-configuration path, containing each element from `kwargs`.

Parameters

- **context** (`ContextInterface`) – The context in which to store the new configuration
- **base_config_path** (`str`) – The base configuration path on which to build the new configuration
- **kwargs** – Keyword arguments that are used to populate the new configuration path

Returns

The newly generated full configuration path

Return type

`str`

property `open`

Returns a context manager and thus can be called like `open`

classmethod `process_yara_options(config)`

run()

Executes the functionality of the code.

Note: This method expects `self.validate` to have been called to ensure all necessary options have been provided

Returns

A `TreeGrid` object that can then be passed to a `Renderer`.

set_open_method(handler)

Sets the file handler to be used by this plugin.

Return type

`None`

classmethod `unsatisfied(context, config_path)`

Returns a list of the names of all unsatisfied requirements.

Since a satisfied set of requirements will return [], it can be used in tests as follows:

```
unmet = configurable.unsatisfied(context, config_path)
if unmet:
    raise RuntimeError("Unsatisfied requirements: {}".format(unmet))
```

Return type

`Dict[str, RequirementInterface]`

version = (1, 2, 0)

class `YaraScanner(rules)`

Bases: `ScannerInterface`

property `context`: `ContextInterface` | `None`

property `layer_name`: `str` | `None`

thread_safe = `False`

version = (2, 0, 0)

10.1.4 volatility3.schemas package

create_json_hash(*input*, *schema=None*)

Constructs the hash of the input and schema to create a unique identifier for a particular JSON file.

Return type

`Optional[str]`

load_cached_validations()

Loads up the list of successfully cached json objects, so we don't need to revalidate them.

Return type

`Set[str]`

record_cached_validations(*validations*)

Record the cached validations, so we don't need to revalidate them in future.

Return type

`None`

valid(*input*, *schema*, *use_cache=True*)

Validates a json schema.

Return type

`bool`

validate(*input*, *use_cache=True*)

Validates an input JSON file based upon.

Return type

`bool`

10.1.5 volatility3.symbols package

Defines the symbols architecture.

This is the namespace for all volatility symbols, and determines the path for loading symbol ISF files

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

V

volatility3, 47
volatility3.cli, 48
volatility3.cli.text_filter, 64
volatility3.cli.text_renderer, 64
volatility3.cli.volargparse, 68
volatility3.cli.volshell, 49
volatility3.cli.volshell.generic, 51
volatility3.cli.volshell.linux, 55
volatility3.cli.volshell.mac, 58
volatility3.cli.volshell.windows, 61
volatility3.framework, 69
volatility3.framework.automagic, 70
volatility3.framework.automagic.construct_layers, 71
volatility3.framework.automagic.linux, 73
volatility3.framework.automagic.mac, 75
volatility3.framework.automagic.module, 78
volatility3.framework.automagic.pdbscan, 79
volatility3.framework.automagic.stacker, 83
volatility3.framework.automagic.symbol_cache, 86
volatility3.framework.automagic.symbol_finder, 91
volatility3.framework.automagic.windows, 93
volatility3.framework.configuration, 96
volatility3.framework.configuration.requirements, 96
volatility3.framework.constants, 120
volatility3.framework.constants.linux, 124
volatility3.framework.constants.windows, 127
volatility3.framework.contexts, 127
volatility3.framework.exceptions, 564
volatility3.framework.interfaces, 139
volatility3.framework.interfaces.automagic, 139
volatility3.framework.interfaces.configuration, 141
volatility3.framework.interfaces.context, 153
volatility3.framework.interfaces.layers, 158
volatility3.framework.interfaces.objects, 165
volatility3.framework.interfaces.plugins, 169
volatility3.framework.interfaces.renderers, 173
volatility3.framework.interfaces.symbols, 176
volatility3.framework.layers, 185
volatility3.framework.layers.avml, 186
volatility3.framework.layers.cloudstorage, 189
volatility3.framework.layers.codecs, 185
volatility3.framework.layers.crash, 189
volatility3.framework.layers.elf, 196
volatility3.framework.layers.intel, 199
volatility3.framework.layers.leechcore, 219
volatility3.framework.layers.lime, 219
volatility3.framework.layers.linear, 222
volatility3.framework.layers.msf, 225
volatility3.framework.layers.physical, 230
volatility3.framework.layers.qemu, 235
volatility3.framework.layers.registry, 238
volatility3.framework.layers.resources, 242
volatility3.framework.layers.scanners, 185
volatility3.framework.layers.scanners.multiregexp, 186
volatility3.framework.layers.segmented, 244
volatility3.framework.layers.vmware, 248
volatility3.framework.layers.xen, 251
volatility3.framework.objects, 254
volatility3.framework.objects.templates, 303
volatility3.framework.objects.utility, 305
volatility3.framework.plugins, 306
volatility3.framework.renderers, 306
volatility3.framework.renderers.conversion, 309
volatility3.framework.renderers.format_hints, 310
volatility3.framework.symbols, 321
volatility3.framework.symbols.generic, 324
volatility3.framework.symbols.intermed, 531
volatility3.framework.symbols.linux, 326
volatility3.framework.symbols.linux.bash, 405
volatility3.framework.symbols.linux.extensions, 331
volatility3.framework.symbols.linux.extensions.bash,

395
volatility3.framework.symbols.linux.extensions, 397
volatility3.framework.symbols.mac, 408
volatility3.framework.symbols.mac.extensions, 412
volatility3.framework.symbols.metadata, 561
volatility3.framework.symbols.native, 562
volatility3.framework.symbols.windows, 437
volatility3.framework.symbols.windows.extensions, 440
volatility3.framework.symbols.windows.extensions.linux, 478
volatility3.framework.symbols.windows.extensions.macos, 480
volatility3.framework.symbols.windows.extensions.macos.lldb, 482
volatility3.framework.symbols.windows.extensions.macos.lldb.lldb, 487
volatility3.framework.symbols.windows.extensions.macos.lldb.lldb.mach, 493
volatility3.framework.symbols.windows.extensions.macos.lldb.lldb.mach.mach, 493
volatility3.framework.symbols.windows.extensions.macos.lldb.lldb.mach.mach.mach, 497
volatility3.framework.symbols.windows.extensions.macos.lldb.lldb.mach.mach.mach.mach, 508
volatility3.framework.symbols.windows.extensions.macos.lldb.lldb.mach.mach.mach.mach.mach, 520
volatility3.framework.symbols.windows.pdbconv, 525
volatility3.framework.symbols.windows.pdbutil, 527
volatility3.framework.symbols.windows.versions, 530
volatility3.framework.symbols.wrappers, 564
volatility3.plugins, 567
volatility3.plugins.banners, 775
volatility3.plugins.configwriter, 777
volatility3.plugins.frameworkinfo, 779
volatility3.plugins.isinfo, 780
volatility3.plugins.layerwriter, 782
volatility3.plugins.linux, 567
volatility3.plugins.linux.bash, 567
volatility3.plugins.linux.capabilities, 569
volatility3.plugins.linux.check_afinfo, 572
volatility3.plugins.linux.check_creds, 573
volatility3.plugins.linux.check_idt, 575
volatility3.plugins.linux.check_modules, 576
volatility3.plugins.linux.check_syscall, 578
volatility3.plugins.linux.elfs, 580
volatility3.plugins.linux.envvars, 582
volatility3.plugins.linux.iomem, 583
volatility3.plugins.linux.keyboard_notifiers, 585
volatility3.plugins.linux.kmsg, 587
volatility3.plugins.linux.library_list, 596
volatility3.plugins.linux.lsmmod, 598
volatility3.plugins.linux.lsof, 600
volatility3.plugins.linux.malfind, 601
volatility3.plugins.linux.mountinfo, 603
volatility3.plugins.linux.proc, 606
volatility3.plugins.linux.psaux, 608
volatility3.plugins.linux.pslist, 609
volatility3.plugins.linux.psscan, 612
volatility3.plugins.linux.pstree, 614
volatility3.plugins.linux.sockstat, 616
volatility3.plugins.linux.tty_check, 618
volatility3.plugins.linux.vmayarascan, 619
volatility3.plugins.mac, 621
volatility3.plugins.mac.bash, 621
volatility3.plugins.mac.check_syscall, 623
volatility3.plugins.mac.check_sysctl, 625
volatility3.plugins.mac.check_trap_table, 626
volatility3.plugins.mac.dmesg, 628
volatility3.plugins.mac.ifconfig, 630
volatility3.plugins.mac.kauth_listeners, 631
volatility3.plugins.mac.kauth_scopes, 633
volatility3.plugins.mac.kevents, 634
volatility3.plugins.mac.list_files, 637
volatility3.plugins.mac.lsmmod, 638
volatility3.plugins.mac.lsof, 640
volatility3.plugins.mac.malfind, 642
volatility3.plugins.mac.mount, 643
volatility3.plugins.mac.netstat, 645
volatility3.plugins.mac.proc_maps, 647
volatility3.plugins.mac.psaux, 649
volatility3.plugins.mac.pslist, 651
volatility3.plugins.mac.pstree, 654
volatility3.plugins.mac.socket_filters, 656
volatility3.plugins.mac.timers, 657
volatility3.plugins.mac.trustedbsd, 659
volatility3.plugins.mac.vfsevents, 661
volatility3.plugins.timeliner, 784
volatility3.plugins.windows, 662
volatility3.plugins.windows.bigpools, 671
volatility3.plugins.windows.cachedump, 673
volatility3.plugins.windows.callbacks, 675
volatility3.plugins.windows.cmdline, 678
volatility3.plugins.windows.crashinfo, 680
volatility3.plugins.windows.devicetree, 681
volatility3.plugins.windows.dlllist, 683
volatility3.plugins.windows.driverirp, 685
volatility3.plugins.windows.drivermodule, 686
volatility3.plugins.windows.driverscan, 688
volatility3.plugins.windows.dumpfiles, 690
volatility3.plugins.windows.envvars, 692
volatility3.plugins.windows.filescan, 694

volatility3.plugins.windows.getservicesids,
696

volatility3.plugins.windows.getsids, 697

volatility3.plugins.windows.handles, 699

volatility3.plugins.windows.hashdump, 701

volatility3.plugins.windows.iat, 704

volatility3.plugins.windows.info, 706

volatility3.plugins.windows.joblinks, 708

volatility3.plugins.windows.ldrmodules, 710

volatility3.plugins.windows.lsadump, 711

volatility3.plugins.windows.malfind, 713

volatility3.plugins.windows.mbrscan, 715

volatility3.plugins.windows.memmap, 717

volatility3.plugins.windows.mftscan, 719

volatility3.plugins.windows.modscan, 722

volatility3.plugins.windows.modules, 724

volatility3.plugins.windows.mutantscan, 727

volatility3.plugins.windows.netscan, 729

volatility3.plugins.windows.netstat, 731

volatility3.plugins.windows.poolscanner, 736

volatility3.plugins.windows.privileges, 741

volatility3.plugins.windows.pslist, 743

volatility3.plugins.windows.psscan, 746

volatility3.plugins.windows.pstree, 749

volatility3.plugins.windows.registry, 663

volatility3.plugins.windows.registry.hivelist,
663

volatility3.plugins.windows.registry.hivescan,
665

volatility3.plugins.windows.registry.printkey,
667

volatility3.plugins.windows.registry.userassist,
669

volatility3.plugins.windows.sessions, 750

volatility3.plugins.windows.skeleton_key_check,
752

volatility3.plugins.windows.ssd, 753

volatility3.plugins.windows.strings, 755

volatility3.plugins.windows.svcscan, 757

volatility3.plugins.windows.symblinkscan, 760

volatility3.plugins.windows.thrdscan, 762

volatility3.plugins.windows.truecrypt, 764

volatility3.plugins.windows.vadinfo, 766

volatility3.plugins.windows.vadwalk, 768

volatility3.plugins.windows.vadyarascan, 770

volatility3.plugins.windows.verinfo, 772

volatility3.plugins.windows.virtmap, 774

volatility3.plugins.yarascan, 787

volatility3.schemas, 789

volatility3.symbols, 790

A

- ABCKmsg (class in volatility3.plugins.linux.kmsg), 587
- access_string() (FILE_OBJECT method), 454
- ACCESSED (TimeLinerType attribute), 784
- add_argument() (HelpfulArgParser method), 68
- add_argument_group() (HelpfulArgParser method), 68
- add_identifier() (CacheManagerInterface method), 86
- add_identifier() (SqliteCache method), 88
- add_layer() (Context method), 130
- add_layer() (ContextInterface method), 153
- add_layer() (LayerContainer method), 161
- add_module() (Context method), 130
- add_module() (ContextInterface method), 153
- add_module() (ModuleCollection method), 135
- add_module() (ModuleContainer method), 155
- add_mutually_exclusive_group() (HelpfulArgParser method), 68
- add_note() (ElfFormatException method), 199
- add_note() (InvalidAddressException method), 564
- add_note() (LayerException method), 564
- add_note() (LimeFormatException method), 219
- add_note() (MissingModuleException method), 564
- add_note() (OfflineException method), 565
- add_note() (PagedInvalidAddressException method), 565
- add_note() (PDBFormatException method), 225
- add_note() (PluginRequirementException method), 565
- add_note() (PluginVersionException method), 565
- add_note() (RegistryFormatException method), 238
- add_note() (RegistryInvalidIndex method), 242
- add_note() (SnappyException method), 189
- add_note() (SwappedInvalidAddressException method), 566
- add_note() (SymbolError method), 566
- add_note() (SymbolSpaceError method), 566
- add_note() (UnsatisfiedException method), 566
- add_note() (VmwareFormatException method), 248
- add_note() (VolatilityException method), 566
- add_note() (WindowsCrashDumpFormatException method), 195
- add_parent() (JarHandler method), 242
- add_parent() (OfflineHandler method), 242
- add_parent() (VolatilityHandler method), 243
- add_parser() (HelpfulSubparserAction method), 69
- add_pattern() (MultiRegexp method), 186
- add_process_layer() (EPROCESS method), 447
- add_process_layer() (proc method), 420
- add_process_layer() (task_struct method), 382
- add_requirement() (BooleanRequirement method), 97
- add_requirement() (BytesRequirement method), 98
- add_requirement() (ChoiceRequirement method), 99
- add_requirement() (ClassRequirement method), 142
- add_requirement() (ComplexListRequirement method), 100
- add_requirement() (ConfigurableRequirementInterface method), 144
- add_requirement() (ConstructableRequirementInterface method), 146
- add_requirement() (IntRequirement method), 102
- add_requirement() (LayerListRequirement method), 104
- add_requirement() (ListRequirement method), 106
- add_requirement() (ModuleRequirement method), 107
- add_requirement() (MultiRequirement method), 109
- add_requirement() (PluginRequirement method), 110
- add_requirement() (RequirementInterface method), 149
- add_requirement() (SimpleTypeRequirement method), 151
- add_requirement() (StringRequirement method), 112
- add_requirement() (SymbolTableRequirement method), 114
- add_requirement() (TranslationLayerRequirement method), 115
- add_requirement() (URIRequirement method), 117
- add_requirement() (VersionRequirement method), 118
- add_subparsers() (HelpfulArgParser method), 68
- address (SymbolInterface property), 180
- address_mask (AVMLLayer property), 186
- address_mask (BufferDataLayer property), 230
- address_mask (DataLayerInterface property), 158
- address_mask (Elf64Layer property), 196

- `address_mask` (*FileLayer* property), 232
 - `address_mask` (*Intel* property), 199
 - `address_mask` (*Intel32e* property), 202
 - `address_mask` (*IntelPAE* property), 205
 - `address_mask` (*LimeLayer* property), 219
 - `address_mask` (*LinearlyMappedLayer* property), 222
 - `address_mask` (*NonLinearlySegmentedLayer* property), 244
 - `address_mask` (*PdbMSFStream* property), 225
 - `address_mask` (*PdbMultiStreamFormat* property), 227
 - `address_mask` (*QemuSuspendLayer* property), 236
 - `address_mask` (*RegistryHive* property), 239
 - `address_mask` (*SegmentedLayer* property), 246
 - `address_mask` (*TranslationLayerInterface* property), 163
 - `address_mask` (*VmwareLayer* property), 248
 - `address_mask` (*WindowsCrashDump32Layer* property), 189
 - `address_mask` (*WindowsCrashDump64Layer* property), 192
 - `address_mask` (*WindowsIntel* property), 207
 - `address_mask` (*WindowsIntel32e* property), 210
 - `address_mask` (*WindowsIntelPAE* property), 213
 - `address_mask` (*WindowsMixin* property), 216
 - `address_mask` (*XenCoreDumpLayer* property), 251
 - `ADS` (class in *volatility3.plugins.windows.mftscan*), 719
 - `AggregateType` (class in *volatility3.framework.objects*), 254
 - `AggregateType.VolTemplateProxy` (class in *volatility3.framework.objects*), 254
 - `all_filters` (*Kevents* attribute), 634
 - `almpassword` (*Hashdump* attribute), 701
 - `antpassword` (*Hashdump* attribute), 701
 - `anum` (*Hashdump* attribute), 701
 - `append()` (*SymbolSpace* method), 322
 - `append()` (*SymbolSpaceInterface* method), 181
 - `aqwerty` (*Hashdump* attribute), 702
 - `args` (*ElfFormatException* attribute), 199
 - `args` (*InvalidAddressException* attribute), 564
 - `args` (*LayerException* attribute), 564
 - `args` (*LimeFormatException* attribute), 219
 - `args` (*MissingModuleException* attribute), 565
 - `args` (*OfflineException* attribute), 565
 - `args` (*PagedInvalidAddressException* attribute), 565
 - `args` (*PDBFormatException* attribute), 225
 - `args` (*PluginRequirementException* attribute), 565
 - `args` (*PluginVersionException* attribute), 565
 - `args` (*RegistryFormatException* attribute), 238
 - `args` (*RegistryInvalidIndex* attribute), 242
 - `args` (*SnappyException* attribute), 189
 - `args` (*SwappedInvalidAddressException* attribute), 566
 - `args` (*SymbolError* attribute), 566
 - `args` (*SymbolSpaceError* attribute), 566
 - `args` (*UnsatisfiedException* attribute), 566
 - `args` (*VmwareFormatException* attribute), 248
 - `args` (*VolatilityException* attribute), 567
 - `args` (*WindowsCrashDumpFormatException* attribute), 195
 - `Array` (class in *volatility3.framework.objects*), 256
 - `Array.VolTemplateProxy` (class in *volatility3.framework.objects*), 256
 - `array_of_pointers()` (in module *volatility3.framework.objects.utility*), 305
 - `array_to_string()` (in module *volatility3.framework.objects.utility*), 305
 - `as_integer_ratio()` (*Bin* method), 310
 - `as_integer_ratio()` (*BitField* method), 259
 - `as_integer_ratio()` (*Boolean* method), 262
 - `as_integer_ratio()` (*Char* method), 270
 - `as_integer_ratio()` (*ELF_CLASS* method), 124
 - `as_integer_ratio()` (*ELF_IDENT* method), 126
 - `as_integer_ratio()` (*Enumeration* method), 276
 - `as_integer_ratio()` (*Float* method), 279
 - `as_integer_ratio()` (*Hex* method), 312
 - `as_integer_ratio()` (*Integer* method), 283
 - `as_integer_ratio()` (*Parallelism* method), 122
 - `as_integer_ratio()` (*Pointer* method), 287
 - `as_integer_ratio()` (*PoolType* method), 739
 - `as_integer_ratio()` (*RegKeyFlags* method), 518
 - `as_integer_ratio()` (*TimeLinerType* method), 784
 - `ascending` (*ColumnSortKey* attribute), 173, 306
 - `asdict()` (*TreeNode* method), 308
 - `astuple()` (*CapabilitiesData* method), 571
 - `AUTOMAGIC_CONFIG_PATH` (in module *volatility3.framework.constants*), 120
 - `AutomagicInterface` (class in *volatility3.framework.interfaces.automagic*), 139
 - `available()` (in module *volatility3.framework.automagic*), 70
 - `AVMLLayer` (class in *volatility3.framework.layers.avml*), 186
 - `AVMLStacker` (class in *volatility3.framework.layers.avml*), 188
- ## B
- `BANG` (in module *volatility3.framework.constants*), 120
 - `banner_config_key` (*LinuxSymbolFinder* attribute), 73
 - `banner_config_key` (*MacSymbolFinder* attribute), 76
 - `banner_config_key` (*SymbolFinder* attribute), 91
 - `Banners` (class in *volatility3.plugins.banners*), 775
 - `banners` (*LinuxSymbolFinder* property), 73
 - `banners` (*MacSymbolFinder* property), 76
 - `banners` (*SymbolFinder* property), 91
 - `base_types` (*TreeGrid* attribute), 174, 307
 - `BaseAbsentValue` (class in *volatility3.framework.interfaces.renderers*), 173
 - `BaseSymbolTableInterface` (class in *volatility3.framework.interfaces.symbols*), 176

- Bash (class in volatility3.plugins.linux.bash), 567
- Bash (class in volatility3.plugins.mac.bash), 621
- BashIntermedSymbols (class in volatility3.framework.symbols.linux.bash), 405
- BigPools (class in volatility3.plugins.windows.bigpools), 671
- Bin (class in volatility3.framework.renderers.format_hints), 310
- binary (ServiceBinaryInfo attribute), 757
- bit_count() (Bin method), 310
- bit_count() (BitField method), 259
- bit_count() (Boolean method), 262
- bit_count() (Char method), 271
- bit_count() (ELF_CLASS method), 124
- bit_count() (ELF_IDENT method), 126
- bit_count() (Enumeration method), 276
- bit_count() (Hex method), 312
- bit_count() (Integer method), 284
- bit_count() (Parallelism method), 122
- bit_count() (Pointer method), 287
- bit_count() (PoolType method), 740
- bit_count() (RegKeyFlags method), 519
- bit_count() (TimeLinerType method), 784
- bit_length() (Bin method), 311
- bit_length() (BitField method), 259
- bit_length() (Boolean method), 262
- bit_length() (Char method), 271
- bit_length() (ELF_CLASS method), 124
- bit_length() (ELF_IDENT method), 126
- bit_length() (Enumeration method), 276
- bit_length() (Hex method), 312
- bit_length() (Integer method), 284
- bit_length() (Parallelism method), 122
- bit_length() (Pointer method), 287
- bit_length() (PoolType method), 740
- bit_length() (RegKeyFlags method), 519
- bit_length() (TimeLinerType method), 785
- BitField (class in volatility3.framework.objects), 258
- BitField.VolTemplateProxy (class in volatility3.framework.objects), 258
- bits_per_register (Intel attribute), 199
- bits_per_register (Intel32e attribute), 202
- bits_per_register (IntelPAE attribute), 205
- bits_per_register (WindowsIntel attribute), 208
- bits_per_register (WindowsIntel32e attribute), 210
- bits_per_register (WindowsIntelPAE attribute), 213
- bits_per_register (WindowsMixin attribute), 216
- Boolean (class in volatility3.framework.objects), 261
- Boolean.VolTemplateProxy (class in volatility3.framework.objects), 261
- BooleanRequirement (class in volatility3.framework.configuration.requirements), 96
- bootkey_perm_table (Hashdump attribute), 702
- bpf_prog (class in volatility3.framework.symbols.linux.extensions), 331
- bpf_prog.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 331
- branch() (HierarchicalDict method), 148
- bt_sock (class in volatility3.framework.symbols.linux.extensions), 333
- bt_sock.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 333
- BufferDataLayer (class in volatility3.framework.layers.physical), 230
- build_configuration() (ADS method), 719
- build_configuration() (AutomagicInterface method), 139
- build_configuration() (AVMLLayer method), 186
- build_configuration() (Banners method), 776
- build_configuration() (Bash method), 567, 622
- build_configuration() (BashIntermedSymbols method), 405
- build_configuration() (BigPools method), 671
- build_configuration() (BufferDataLayer method), 230
- build_configuration() (Cachedump method), 673
- build_configuration() (Callbacks method), 675
- build_configuration() (Capabilities method), 569
- build_configuration() (Check_afinfo method), 572
- build_configuration() (Check_creds method), 573
- build_configuration() (Check_idt method), 575
- build_configuration() (Check_modules method), 577
- build_configuration() (Check_syscall method), 578, 623
- build_configuration() (Check_sysctl method), 625
- build_configuration() (Check_trap_table method), 626
- build_configuration() (CmdLine method), 678
- build_configuration() (ComplexListRequirement method), 101
- build_configuration() (ConfigurableInterface method), 143
- build_configuration() (ConfigurableModule method), 127
- build_configuration() (ConfigurableRequirementInterface method), 144
- build_configuration() (ConfigWriter method), 777
- build_configuration() (ConstructionMagic method), 71
- build_configuration() (Crashinfo method), 680
- build_configuration() (DataLayerInterface method), 158

`build_configuration()` (*DeviceTree method*), 681
`build_configuration()` (*DllList method*), 683
`build_configuration()` (*Dmesg method*), 628
`build_configuration()` (*DriverIrp method*), 685
`build_configuration()` (*DriverModule method*), 686
`build_configuration()` (*DriverScan method*), 688
`build_configuration()` (*DumpFiles method*), 690
`build_configuration()` (*Elf64Layer method*), 196
`build_configuration()` (*Elfs method*), 580
`build_configuration()` (*Envvars method*), 582, 692
`build_configuration()` (*FileLayer method*), 232
`build_configuration()` (*FileScan method*), 694
`build_configuration()` (*FrameworkInfo method*), 779
`build_configuration()` (*GetServiceSIDs method*), 696
`build_configuration()` (*GetSIDs method*), 697
`build_configuration()` (*Handles method*), 699
`build_configuration()` (*Hashdump method*), 702
`build_configuration()` (*HiveList method*), 663
`build_configuration()` (*HiveScan method*), 666
`build_configuration()` (*IAT method*), 704
`build_configuration()` (*Ifconfig method*), 630
`build_configuration()` (*Info method*), 706
`build_configuration()` (*Intel method*), 199
`build_configuration()` (*Intel32e method*), 202
`build_configuration()` (*IntelPAE method*), 205
`build_configuration()` (*IntermediateSymbolTable method*), 534
`build_configuration()` (*IOMem method*), 583
`build_configuration()` (*IsfInfo method*), 780
`build_configuration()` (*ISFormatTable method*), 531
`build_configuration()` (*JobLinks method*), 708
`build_configuration()` (*Kauth_listeners method*), 631
`build_configuration()` (*Kauth_scopes method*), 633
`build_configuration()` (*KernelModule method*), 78
`build_configuration()` (*KernelPDBScanner method*), 79
`build_configuration()` (*Kevents method*), 635
`build_configuration()` (*Keyboard_notifiers method*), 585
`build_configuration()` (*Kmsg method*), 588
`build_configuration()` (*LayerListRequirement method*), 104
`build_configuration()` (*LayerStacker method*), 83
`build_configuration()` (*LayerWriter method*), 782
`build_configuration()` (*LdrModules method*), 710
`build_configuration()` (*LibraryList method*), 596
`build_configuration()` (*LimeLayer method*), 219
`build_configuration()` (*LinearlyMappedLayer method*), 222
`build_configuration()` (*LinuxKernelIntermedSymbols method*), 327
`build_configuration()` (*LinuxSymbolFinder method*), 73
`build_configuration()` (*List_Files method*), 637
`build_configuration()` (*Lsadbump method*), 711
`build_configuration()` (*Lsmmod method*), 598, 638
`build_configuration()` (*Lsof method*), 600, 640
`build_configuration()` (*MacKernelIntermedSymbols method*), 408
`build_configuration()` (*MacSymbolFinder method*), 76
`build_configuration()` (*Malfind method*), 601, 642, 713
`build_configuration()` (*Maps method*), 606, 647
`build_configuration()` (*MBRScan method*), 715
`build_configuration()` (*Memmap method*), 717
`build_configuration()` (*MFTScan method*), 720
`build_configuration()` (*ModScan method*), 722
`build_configuration()` (*Module method*), 132
`build_configuration()` (*ModuleInterface method*), 155
`build_configuration()` (*ModuleRequirement method*), 107
`build_configuration()` (*Modules method*), 724
`build_configuration()` (*Mount method*), 643
`build_configuration()` (*MountInfo method*), 603
`build_configuration()` (*MutantScan method*), 727
`build_configuration()` (*NetScan method*), 729
`build_configuration()` (*NetStat method*), 731
`build_configuration()` (*Netstat method*), 645
`build_configuration()` (*NonLinearlySegmented-Layer method*), 244
`build_configuration()` (*Passphrase method*), 764
`build_configuration()` (*PdbMSFStream method*), 225
`build_configuration()` (*PdbMultiStreamFormat method*), 227
`build_configuration()` (*PluginInterface method*), 171
`build_configuration()` (*PoolScanner method*), 737
`build_configuration()` (*PrintKey method*), 667
`build_configuration()` (*Privs method*), 741
`build_configuration()` (*PsAux method*), 608
`build_configuration()` (*Psaux method*), 649
`build_configuration()` (*PsList method*), 609, 651, 743
`build_configuration()` (*PsScan method*), 612, 746
`build_configuration()` (*PsTree method*), 614, 654, 749
`build_configuration()` (*QemuSuspendLayer method*), 236
`build_configuration()` (*RegistryHive method*), 239
`build_configuration()` (*SegmentedLayer method*), 246
`build_configuration()` (*Sessions method*), 750

- `build_configuration()` (*SizedModule method*), 136
 - `build_configuration()` (*Skeleton_Key_Check method*), 752
 - `build_configuration()` (*Socket_filters method*), 656
 - `build_configuration()` (*Sockstat method*), 616
 - `build_configuration()` (*SSDT method*), 754
 - `build_configuration()` (*Strings method*), 755
 - `build_configuration()` (*SvcScan method*), 758
 - `build_configuration()` (*SymbolCacheMagic method*), 89
 - `build_configuration()` (*SymbolFinder method*), 91
 - `build_configuration()` (*SymbolTableInterface method*), 182
 - `build_configuration()` (*SymbolTableRequirement method*), 114
 - `build_configuration()` (*SymlinkScan method*), 760
 - `build_configuration()` (*ThrdScan method*), 762
 - `build_configuration()` (*Timeliner method*), 786
 - `build_configuration()` (*Timers method*), 657
 - `build_configuration()` (*TranslationLayerInterface method*), 163
 - `build_configuration()` (*TranslationLayerRequirement method*), 115
 - `build_configuration()` (*Trustedbsd method*), 659
 - `build_configuration()` (*tty_check method*), 618
 - `build_configuration()` (*UserAssist method*), 669
 - `build_configuration()` (*VadInfo method*), 766
 - `build_configuration()` (*VadWalk method*), 768
 - `build_configuration()` (*VadYaraScan method*), 770
 - `build_configuration()` (*VerInfo method*), 772
 - `build_configuration()` (*Version1Format method*), 538
 - `build_configuration()` (*Version2Format method*), 540
 - `build_configuration()` (*Version3Format method*), 543
 - `build_configuration()` (*Version4Format method*), 546
 - `build_configuration()` (*Version5Format method*), 550
 - `build_configuration()` (*Version6Format method*), 553
 - `build_configuration()` (*Version7Format method*), 556
 - `build_configuration()` (*Version8Format method*), 559
 - `build_configuration()` (*VFSevents method*), 661
 - `build_configuration()` (*VirtMap method*), 774
 - `build_configuration()` (*VmaYaraScan method*), 620
 - `build_configuration()` (*VmwareLayer method*), 249
 - `build_configuration()` (*Volshell method*), 53, 55, 58, 61
 - `build_configuration()` (*WindowsCrash-Dump32Layer method*), 189
 - `build_configuration()` (*WindowsCrash-Dump64Layer method*), 192
 - `build_configuration()` (*WindowsIntel method*), 208
 - `build_configuration()` (*WindowsIntel32e method*), 210
 - `build_configuration()` (*WindowsIntelPAE method*), 213
 - `build_configuration()` (*WindowsKernelInter-medSymbols method*), 437
 - `build_configuration()` (*WindowsMixin method*), 216
 - `build_configuration()` (*WinSwapLayers method*), 94
 - `build_configuration()` (*XenCoreDumpLayer method*), 251
 - `build_configuration()` (*YaraScan method*), 787
 - `build_module_collection()` (*SSDT class method*), 754
 - `builtin_constraints()` (*PoolScanner static method*), 737
 - `byteorder` (*DataFormatInfo attribute*), 274
 - `Bytes` (*class in volatility3.framework.objects*), 264
 - `Bytes.VolTemplateProxy` (*class in volatility3.framework.objects*), 264
 - `BytesRequirement` (*class in volatility3.framework.configuration.requirements*), 98
 - `BytesScanner` (*class in volatility3.framework.layers.scanners*), 185
- ## C
- `CACHE_PATH` (*in module volatility3.framework.constants*), 120
 - `CACHE_SQLITE_SCHEMA_VERSION` (*in module volatility3.framework.constants*), 120
 - `cached_strtab` (*elf_sym property*), 403
 - `Cachedump` (*class in volatility3.plugins.windows.cachedump*), 673
 - `CacheManagerInterface` (*class in volatility3.framework.automagic.symbol_cache*), 86
 - `Callbacks` (*class in volatility3.plugins.windows.callbacks*), 675
 - `canonicalize()` (*Intel method*), 199
 - `canonicalize()` (*Intel32e method*), 202
 - `canonicalize()` (*IntelPAE method*), 205
 - `canonicalize()` (*WindowsIntel method*), 208
 - `canonicalize()` (*WindowsIntel32e method*), 210
 - `canonicalize()` (*WindowsIntelPAE method*), 213
 - `canonicalize()` (*WindowsMixin method*), 216
 - `cap_ambient` (*CapabilitiesData attribute*), 571
 - `cap_bset` (*CapabilitiesData attribute*), 571
 - `cap_effective` (*CapabilitiesData attribute*), 571
 - `cap_inheritable` (*CapabilitiesData attribute*), 571
 - `cap_permitted` (*CapabilitiesData attribute*), 571

Capabilities (class in volatility3.plugins.linux.capabilities), 569

capabilities_to_string() (kernel_cap_struct class method), 345

capabilities_to_string() (kernel_cap_t class method), 348

CapabilitiesData (class in volatility3.plugins.linux.capabilities), 571

capitalize() (Bytes method), 265

capitalize() (HexBytes method), 313

capitalize() (MultiTypeData method), 317

capitalize() (String method), 292

cascadeCloseFile() (in module volatility3.framework.layers.resources), 243

casefold() (String method), 292

cast() (AggregateType method), 255

cast() (Array method), 257

cast() (BitField method), 259

cast() (Boolean method), 262

cast() (bpf_prog method), 332

cast() (bt_sock method), 334

cast() (Bytes method), 265

cast() (Char method), 271

cast() (ClassType method), 273

cast() (CM_KEY_BODY method), 511

cast() (CM_KEY_NODE method), 513

cast() (CM_KEY_VALUE method), 515

cast() (CMHIVE method), 509

cast() (CONTROL_AREA method), 441

cast() (cred method), 336

cast() (dentry method), 337

cast() (DEVICE_OBJECT method), 443

cast() (DRIVER_OBJECT method), 445

cast() (elf method), 398

cast() (elf_linkmap method), 400

cast() (elf_phdr method), 401

cast() (elf_sym method), 403

cast() (Enumeration method), 276

cast() (EPROCESS method), 447

cast() (ETHREAD method), 450

cast() (EX_FAST_REF method), 452

cast() (ExecutiveObject method), 498

cast() (FILE_OBJECT method), 454

cast() (fileglob method), 413

cast() (files_struct method), 339

cast() (Float method), 279

cast() (fs_struct method), 341

cast() (Function method), 282

cast() (GenericIntelProcess method), 325

cast() (hist_entry method), 396

cast() (HMAP_ENTRY method), 517

cast() (ifnet method), 415

cast() (IMAGE_DOS_HEADER method), 493

cast() (IMAGE_NT_HEADERS method), 496

cast() (inet_sock method), 343

cast() (inpcb method), 417

cast() (Integer method), 284

cast() (kauth_scope method), 418

cast() (KDDEBUGGER_DATA64 method), 481

cast() (kernel_cap_struct method), 345

cast() (kernel_cap_t method), 348

cast() (KMUTANT method), 456

cast() (kobject method), 350

cast() (KSYSTEM_TIME method), 458

cast() (KTHREAD method), 460

cast() (LIST_ENTRY method), 462

cast() (list_head method), 352

cast() (maple_tree method), 355

cast() (MFTAttribute method), 488

cast() (MFTEntry method), 490

cast() (MFTFileName method), 491

cast() (mm_struct method), 356

cast() (MMVAD method), 464

cast() (MMVAD_SHORT method), 466

cast() (mnt_namespace method), 358

cast() (module method), 360

cast() (mount method), 363

cast() (net method), 367

cast() (netlink_sock method), 368

cast() (OBJECT_HEADER method), 500

cast() (OBJECT_SYMBOLIC_LINK method), 469

cast() (ObjectInterface method), 167

cast() (packet_sock method), 370

cast() (PARTITION_ENTRY method), 483

cast() (PARTITION_TABLE method), 486

cast() (Pointer method), 287

cast() (POOL_HEADER method), 502

cast() (POOL_HEADER_VISTA method), 504

cast() (POOL_TRACKER_BIG_PAGES method), 507

cast() (PrimitiveObject method), 290

cast() (proc method), 420

cast() (qstr method), 372

cast() (queue_entry method), 422

cast() (SERVICE_HEADER method), 521

cast() (SERVICE_RECORD method), 523

cast() (SHARED_CACHE_MAP method), 471

cast() (sock method), 374

cast() (sockaddr method), 424

cast() (sockaddr_dl method), 426

cast() (socket method), 376, 428

cast() (String method), 292

cast() (struct_file method), 377

cast() (StructType method), 298

cast() (SUMMARY_DUMP method), 479

cast() (super_block method), 380

cast() (sysctl_oid method), 430

cast() (task_struct method), 382

cast() (TOKEN method), 473

- `cast()` (*UNICODE_STRING* method), 475
- `cast()` (*UnionType* method), 300
- `cast()` (*unix_sock* method), 384
- `cast()` (*VACB* method), 477
- `cast()` (*yfsmount* method), 386
- `cast()` (*vm_area_struct* method), 390
- `cast()` (*vm_map_entry* method), 432
- `cast()` (*vm_map_object* method), 434
- `cast()` (*vnode* method), 436
- `cast()` (*Void* method), 302
- `cast()` (*vsock_sock* method), 392
- `cast()` (*xdp_sock* method), 394
- `center()` (*Bytes* method), 265
- `center()` (*HexBytes* method), 313
- `center()` (*MultiTypeData* method), 317
- `center()` (*String* method), 292
- `change_kernel()` (*Volshell* method), 53, 56, 58, 61
- `change_layer()` (*Volshell* method), 53, 56, 58, 61
- `change_process()` (*Volshell* method), 61
- `change_symbol_table()` (*Volshell* method), 53, 56, 59, 61
- `change_task()` (*Volshell* method), 56, 59
- `CHANGED` (*TimeLinerType* attribute), 784
- Char* (class in *volatility3.framework.objects*), 270
- Char.VolTemplateProxy* (class in *volatility3.framework.objects*), 270
- Check_afinfo* (class in *volatility3.plugins.linux.check_afinfo*), 572
- Check_creds* (class in *volatility3.plugins.linux.check_creds*), 573
- `check_cycles()` (*LayerContainer* method), 161
- `check_header()` (*WindowsCrashDump32Layer* class method), 190
- `check_header()` (*WindowsCrashDump64Layer* class method), 192
- Check_idt* (class in *volatility3.plugins.linux.check_idt*), 575
- `check_kernel_offset()` (*KernelPDBScanner* method), 80
- Check_modules* (class in *volatility3.plugins.linux.check_modules*), 576
- Check_syscall* (class in *volatility3.plugins.linux.check_syscall*), 578
- Check_syscall* (class in *volatility3.plugins.mac.check_syscall*), 623
- Check_sysctl* (class in *volatility3.plugins.mac.check_sysctl*), 625
- Check_trap_table* (class in *volatility3.plugins.mac.check_trap_table*), 626
- `child_template()` (*AggregateType.VolTemplateProxy* class method), 254
- `child_template()` (*Array.VolTemplateProxy* class method), 256
- `child_template()` (*BitField.VolTemplateProxy* class method), 258
- `child_template()` (*Boolean.VolTemplateProxy* class method), 261
- `child_template()` (*bpf_prog.VolTemplateProxy* class method), 332
- `child_template()` (*bt_sock.VolTemplateProxy* class method), 333
- `child_template()` (*Bytes.VolTemplateProxy* class method), 264
- `child_template()` (*Char.VolTemplateProxy* class method), 270
- `child_template()` (*ClassType.VolTemplateProxy* class method), 273
- `child_template()` (*CM_KEY_BODY.VolTemplateProxy* class method), 510
- `child_template()` (*CM_KEY_NODE.VolTemplateProxy* class method), 512
- `child_template()` (*CM_KEY_VALUE.VolTemplateProxy* class method), 515
- `child_template()` (*CMHIVE.VolTemplateProxy* class method), 508
- `child_template()` (*CONTROL_AREA.VolTemplateProxy* class method), 440
- `child_template()` (*cred.VolTemplateProxy* class method), 335
- `child_template()` (*dentry.VolTemplateProxy* class method), 337
- `child_template()` (*DEVICE_OBJECT.VolTemplateProxy* class method), 442
- `child_template()` (*DRIVER_OBJECT.VolTemplateProxy* class method), 444
- `child_template()` (*elf.VolTemplateProxy* class method), 397
- `child_template()` (*elf_linkmap.VolTemplateProxy* class method), 399
- `child_template()` (*elf_phdr.VolTemplateProxy* class method), 401
- `child_template()` (*elf_sym.VolTemplateProxy* class method), 403
- `child_template()` (*Enumeration.VolTemplateProxy* class method), 275
- `child_template()` (*EPROCESS.VolTemplateProxy* class method), 447
- `child_template()` (*ETHREAD.VolTemplateProxy* class method), 449
- `child_template()` (*EX_FAST_REF.VolTemplateProxy* class method), 452
- `child_template()` (*ExecutiveObject.VolTemplateProxy* class method), 498
- `child_template()` (*FILE_OBJECT.VolTemplateProxy* class method), 453
- `child_template()` (*fileglob.VolTemplateProxy* class method), 258

method), 412

child_template() (*files_struct.VolTemplateProxy* class method), 339

child_template() (*Float.VolTemplateProxy* class method), 279

child_template() (*fs_struct.VolTemplateProxy* class method), 341

child_template() (*Function.VolTemplateProxy* class method), 281

child_template() (*GenericIntelProcess.VolTemplateProxy* class method), 325

child_template() (*hist_entry.VolTemplateProxy* class method), 395

child_template() (*HMAP_ENTRY.VolTemplateProxy* class method), 516

child_template() (*ifnet.VolTemplateProxy* class method), 414

child_template() (*IMAGE_DOS_HEADER.VolTemplateProxy* class method), 493

child_template() (*IMAGE_NT_HEADERS.VolTemplateProxy* class method), 496

child_template() (*inet_sock.VolTemplateProxy* class method), 343

child_template() (*inpcb.VolTemplateProxy* class method), 416

child_template() (*Integer.VolTemplateProxy* class method), 283

child_template() (*kauth_scope.VolTemplateProxy* class method), 418

child_template() (*KDDEBUGGER_DATA64.VolTemplateProxy* class method), 481

child_template() (*kernel_cap_struct.VolTemplateProxy* class method), 345

child_template() (*kernel_cap_t.VolTemplateProxy* class method), 347

child_template() (*KMUTANT.VolTemplateProxy* class method), 455

child_template() (*kobject.VolTemplateProxy* class method), 350

child_template() (*KSYSTEM_TIME.VolTemplateProxy* class method), 457

child_template() (*KTHREAD.VolTemplateProxy* class method), 459

child_template() (*LIST_ENTRY.VolTemplateProxy* class method), 461

child_template() (*list_head.VolTemplateProxy* class method), 352

child_template() (*maple_tree.VolTemplateProxy* class method), 354

child_template() (*MFTAttribute.VolTemplateProxy* class method), 487

child_template() (*MFTEntry.VolTemplateProxy* class method), 489

child_template() (*MFTFileName.VolTemplateProxy* class method), 491

child_template() (*mm_struct.VolTemplateProxy* class method), 356

child_template() (*MMVAD.VolTemplateProxy* class method), 463

child_template() (*MMVAD_SHORT.VolTemplateProxy* class method), 466

child_template() (*mnt_namespace.VolTemplateProxy* class method), 358

child_template() (*module.VolTemplateProxy* class method), 360

child_template() (*mount.VolTemplateProxy* class method), 363

child_template() (*net.VolTemplateProxy* class method), 366

child_template() (*netlink_sock.VolTemplateProxy* class method), 368

child_template() (*OBJECT_HEADER.VolTemplateProxy* class method), 499

child_template() (*OBJECT_SYMBOLIC_LINK.VolTemplateProxy* class method), 468

child_template() (*ObjectInterface.VolTemplateProxy* class method), 166

child_template() (*ObjectTemplate* method), 303

child_template() (*packet_sock.VolTemplateProxy* class method), 370

child_template() (*PARTITION_ENTRY.VolTemplateProxy* class method), 482

child_template() (*PARTITION_TABLE.VolTemplateProxy* class method), 485

child_template() (*Pointer.VolTemplateProxy* class method), 286

child_template() (*POOL_HEADER.VolTemplateProxy* class method), 502

child_template() (*POOL_HEADER_VISTA.VolTemplateProxy* class method), 504

child_template() (*POOL_TRACKER_BIG_PAGES.VolTemplateProxy* class method), 506

child_template() (*PrimitiveObject.VolTemplateProxy* class method), 289

child_template() (*proc.VolTemplateProxy* class method), 420

child_template() (*qstr.VolTemplateProxy* class method), 371

[child_template\(\)](#) (*queue_entry.VolTemplateProxy class method*), 422
[child_template\(\)](#) (*ReferenceTemplate method*), 304
[child_template\(\)](#) (*SER-VICE_HEADER.VolTemplateProxy class method*), 521
[child_template\(\)](#) (*SER-VICE_RECORD.VolTemplateProxy class method*), 522
[child_template\(\)](#) (*SHARED_CACHE_MAP.VolTemplateProxy class method*), 470
[child_template\(\)](#) (*sock.VolTemplateProxy class method*), 373
[child_template\(\)](#) (*sockaddr.VolTemplateProxy class method*), 424
[child_template\(\)](#) (*sockaddr_dl.VolTemplateProxy class method*), 426
[child_template\(\)](#) (*socket.VolTemplateProxy class method*), 375, 427
[child_template\(\)](#) (*String.VolTemplateProxy class method*), 291
[child_template\(\)](#) (*struct_file.VolTemplateProxy class method*), 377
[child_template\(\)](#) (*StructType.VolTemplateProxy class method*), 298
[child_template\(\)](#) (*SUM-MARY_DUMP.VolTemplateProxy class method*), 479
[child_template\(\)](#) (*super_block.VolTemplateProxy class method*), 379
[child_template\(\)](#) (*SymbolSpace.UnresolvedTemplate method*), 321
[child_template\(\)](#) (*sysctl_oid.VolTemplateProxy class method*), 429
[child_template\(\)](#) (*task_struct.VolTemplateProxy class method*), 381
[child_template\(\)](#) (*Template method*), 168
[child_template\(\)](#) (*TOKEN.VolTemplateProxy class method*), 473
[child_template\(\)](#) (*UNI-CODE_STRING.VolTemplateProxy class method*), 475
[child_template\(\)](#) (*UnionType.VolTemplateProxy class method*), 299
[child_template\(\)](#) (*unix_sock.VolTemplateProxy class method*), 384
[child_template\(\)](#) (*VACB.VolTemplateProxy class method*), 477
[child_template\(\)](#) (*vfsmount.VolTemplateProxy class method*), 386
[child_template\(\)](#) (*vm_area_struct.VolTemplateProxy class method*), 389
[child_template\(\)](#) (*vm_map_entry.VolTemplateProxy class method*), 431
[child_template\(\)](#) (*vm_map_object.VolTemplateProxy class method*), 433
[child_template\(\)](#) (*vnnode.VolTemplateProxy class method*), 435
[child_template\(\)](#) (*Void.VolTemplateProxy class method*), 301
[child_template\(\)](#) (*vsock_sock.VolTemplateProxy class method*), 391
[child_template\(\)](#) (*xdp_sock.VolTemplateProxy class method*), 393
[children](#) (*ObjectTemplate property*), 303
[children](#) (*ReferenceTemplate property*), 304
[children](#) (*SymbolSpace.UnresolvedTemplate property*), 322
[children](#) (*Template property*), 169
[children\(\)](#) (*AggregateType.VolTemplateProxy class method*), 254
[children\(\)](#) (*Array.VolTemplateProxy class method*), 256
[children\(\)](#) (*BitField.VolTemplateProxy class method*), 258
[children\(\)](#) (*Boolean.VolTemplateProxy class method*), 261
[children\(\)](#) (*bpf_prog.VolTemplateProxy class method*), 332
[children\(\)](#) (*bt_sock.VolTemplateProxy class method*), 333
[children\(\)](#) (*Bytes.VolTemplateProxy class method*), 264
[children\(\)](#) (*Char.VolTemplateProxy class method*), 270
[children\(\)](#) (*ClassType.VolTemplateProxy class method*), 273
[children\(\)](#) (*CM_KEY_BODY.VolTemplateProxy class method*), 511
[children\(\)](#) (*CM_KEY_NODE.VolTemplateProxy class method*), 512
[children\(\)](#) (*CM_KEY_VALUE.VolTemplateProxy class method*), 515
[children\(\)](#) (*CMHIVE.VolTemplateProxy class method*), 508
[children\(\)](#) (*CONTROL_AREA.VolTemplateProxy class method*), 440
[children\(\)](#) (*cred.VolTemplateProxy class method*), 335
[children\(\)](#) (*dentry.VolTemplateProxy class method*), 337
[children\(\)](#) (*DEVICE_OBJECT.VolTemplateProxy class method*), 443
[children\(\)](#) (*DRIVER_OBJECT.VolTemplateProxy class method*), 445
[children\(\)](#) (*elf.VolTemplateProxy class method*), 397
[children\(\)](#) (*elf_linkmap.VolTemplateProxy class method*), 399
[children\(\)](#) (*elf_phdr.VolTemplateProxy class method*), 401

`children()` (*elf_sym.VolTemplateProxy* class method), 403

`children()` (*Enumeration.VolTemplateProxy* class method), 275

`children()` (*EPROCESS.VolTemplateProxy* class method), 447

`children()` (*ETHREAD.VolTemplateProxy* class method), 449

`children()` (*EX_FAST_REF.VolTemplateProxy* class method), 452

`children()` (*ExecutiveObject.VolTemplateProxy* class method), 498

`children()` (*FILE_OBJECT.VolTemplateProxy* class method), 453

`children()` (*fileglob.VolTemplateProxy* class method), 413

`children()` (*files_struct.VolTemplateProxy* class method), 339

`children()` (*Float.VolTemplateProxy* class method), 279

`children()` (*fs_struct.VolTemplateProxy* class method), 341

`children()` (*Function.VolTemplateProxy* class method), 281

`children()` (*GenericIntelProcess.VolTemplateProxy* class method), 325

`children()` (*hist_entry.VolTemplateProxy* class method), 395

`children()` (*HMAP_ENTRY.VolTemplateProxy* class method), 517

`children()` (*ifnet.VolTemplateProxy* class method), 414

`children()` (*IMAGE_DOS_HEADER.VolTemplateProxy* class method), 493

`children()` (*IMAGE_NT_HEADERS.VolTemplateProxy* class method), 496

`children()` (*inet_sock.VolTemplateProxy* class method), 343

`children()` (*inpcb.VolTemplateProxy* class method), 416

`children()` (*Integer.VolTemplateProxy* class method), 283

`children()` (*kauth_scope.VolTemplateProxy* class method), 418

`children()` (*KDDEBUGGER_DATA64.VolTemplateProxy* class method), 481

`children()` (*kernel_cap_struct.VolTemplateProxy* class method), 345

`children()` (*kernel_cap_t.VolTemplateProxy* class method), 347

`children()` (*KMUTANT.VolTemplateProxy* class method), 456

`children()` (*kobject.VolTemplateProxy* class method), 350

`children()` (*KSYSTEM_TIME.VolTemplateProxy* class method), 458

`children()` (*KTHREAD.VolTemplateProxy* class method), 459

`children()` (*LIST_ENTRY.VolTemplateProxy* class method), 461

`children()` (*list_head.VolTemplateProxy* class method), 352

`children()` (*maple_tree.VolTemplateProxy* class method), 354

`children()` (*MFTAttribute.VolTemplateProxy* class method), 487

`children()` (*MFTEntry.VolTemplateProxy* class method), 489

`children()` (*MFTFileName.VolTemplateProxy* class method), 491

`children()` (*mm_struct.VolTemplateProxy* class method), 356

`children()` (*MMVAD.VolTemplateProxy* class method), 463

`children()` (*MMVAD_SHORT.VolTemplateProxy* class method), 466

`children()` (*mnt_namespace.VolTemplateProxy* class method), 358

`children()` (*module.VolTemplateProxy* class method), 360

`children()` (*mount.VolTemplateProxy* class method), 363

`children()` (*net.VolTemplateProxy* class method), 366

`children()` (*netlink_sock.VolTemplateProxy* class method), 368

`children()` (*OBJECT_HEADER.VolTemplateProxy* class method), 500

`children()` (*OBJECT_SYMBOLIC_LINK.VolTemplateProxy* class method), 468

`children()` (*ObjectInterface.VolTemplateProxy* class method), 166

`children()` (*packet_sock.VolTemplateProxy* class method), 370

`children()` (*PARTITION_ENTRY.VolTemplateProxy* class method), 482

`children()` (*PARTITION_TABLE.VolTemplateProxy* class method), 485

`children()` (*Pointer.VolTemplateProxy* class method), 286

`children()` (*POOL_HEADER.VolTemplateProxy* class method), 502

`children()` (*POOL_HEADER_VISTA.VolTemplateProxy* class method), 504

`children()` (*POOL_TRACKER_BIG_PAGES.VolTemplateProxy* class method), 506

`children()` (*PrimitiveObject.VolTemplateProxy* class method), 289

`children()` (*proc.VolTemplateProxy* class method), 420

- `children()` (*qstr.VolTemplateProxy* class method), 371
- `children()` (*queue_entry.VolTemplateProxy* class method), 422
- `children()` (*SERVICE_HEADER.VolTemplateProxy* class method), 521
- `children()` (*SERVICE_RECORD.VolTemplateProxy* class method), 523
- `children()` (*SHARED_CACHE_MAP.VolTemplateProxy* class method), 471
- `children()` (*sock.VolTemplateProxy* class method), 373
- `children()` (*sockaddr.VolTemplateProxy* class method), 424
- `children()` (*sockaddr_dl.VolTemplateProxy* class method), 426
- `children()` (*socket.VolTemplateProxy* class method), 375, 427
- `children()` (*String.VolTemplateProxy* class method), 291
- `children()` (*struct_file.VolTemplateProxy* class method), 377
- `children()` (*StructType.VolTemplateProxy* class method), 298
- `children()` (*SUMMARY_DUMP.VolTemplateProxy* class method), 479
- `children()` (*super_block.VolTemplateProxy* class method), 379
- `children()` (*sysctl_oid.VolTemplateProxy* class method), 429
- `children()` (*task_struct.VolTemplateProxy* class method), 381
- `children()` (*TOKEN.VolTemplateProxy* class method), 473
- `children()` (*TreeGrid* method), 174, 307
- `children()` (*UNICODE_STRING.VolTemplateProxy* class method), 475
- `children()` (*UnionType.VolTemplateProxy* class method), 299
- `children()` (*unix_sock.VolTemplateProxy* class method), 384
- `children()` (*VACB.VolTemplateProxy* class method), 477
- `children()` (*vfsmount.VolTemplateProxy* class method), 386
- `children()` (*vm_area_struct.VolTemplateProxy* class method), 389
- `children()` (*vm_map_entry.VolTemplateProxy* class method), 431
- `children()` (*vm_map_object.VolTemplateProxy* class method), 433
- `children()` (*vnnode.VolTemplateProxy* class method), 435
- `children()` (*Void.VolTemplateProxy* class method), 301
- `children()` (*vsock_sock.VolTemplateProxy* class method), 392
- `children()` (*xdp_sock.VolTemplateProxy* class method), 393
- `ChoiceRequirement` (class in *volatility3.framework.configuration.requirements*), 99
- `choices` (*Enumeration* property), 276
- `choices` (*Flags* property), 564
- `choose_automagic()` (in module *volatility3.framework.automagic*), 70
- `choose_os_stackercs()` (in module *volatility3.framework.automagic.stackercs*), 86
- `class_subclasses()` (in module *volatility3.framework*), 69
- `classproperty` (class in *volatility3*), 47
- `ClassRequirement` (class in *volatility3.framework.interfaces.configuration*), 141
- `ClassType` (class in *volatility3.framework.objects*), 273
- `ClassType.VolTemplateProxy` (class in *volatility3.framework.objects*), 273
- `clear_cache()` (in module *volatility3.framework*), 69
- `clear_symbol_cache()` (*BaseSymbolTableInterface* method), 177
- `clear_symbol_cache()` (*BashIntermedSymbols* method), 405
- `clear_symbol_cache()` (*IntermediateSymbolTable* method), 534
- `clear_symbol_cache()` (*ISFormatTable* method), 531
- `clear_symbol_cache()` (*LinuxKernelIntermedSymbols* method), 327
- `clear_symbol_cache()` (*MacKernelIntermedSymbols* method), 408
- `clear_symbol_cache()` (*NativeTable* method), 562
- `clear_symbol_cache()` (*NativeTableInterface* method), 178
- `clear_symbol_cache()` (*SymbolSpace* method), 322
- `clear_symbol_cache()` (*SymbolSpaceInterface* method), 181
- `clear_symbol_cache()` (*SymbolTableInterface* method), 182
- `clear_symbol_cache()` (*Version1Format* method), 538
- `clear_symbol_cache()` (*Version2Format* method), 541
- `clear_symbol_cache()` (*Version3Format* method), 544
- `clear_symbol_cache()` (*Version4Format* method), 547
- `clear_symbol_cache()` (*Version5Format* method), 550
- `clear_symbol_cache()` (*Version6Format* method), 553
- `clear_symbol_cache()` (*Version7Format* method), 556
- `clear_symbol_cache()` (*Version8Format* method), 559
- `clear_symbol_cache()` (*WindowsKernelIntermedSymbols* method), 437
- `CLI_NAME` (*CommandLine* attribute), 48
- `CLI_NAME` (*VolShell* attribute), 49
- `CLIFilter` (class in *volatility3.cli.text_filter*), 64
- `CLIRenderer` (class in *volatility3.cli.text_renderer*), 64

`clone()` (*Context method*), 131
`clone()` (*ContextInterface method*), 153
`clone()` (*HierarchicalDict method*), 148
`clone()` (*ObjectTemplate method*), 303
`clone()` (*ReferenceTemplate method*), 304
`clone()` (*SymbolSpace.UnresolvedTemplate method*), 322
`clone()` (*Template method*), 169
`close()` (*FileHandlerInterface method*), 169
`close()` (*JarHandler method*), 242
`close()` (*NullFileHandler method*), 51
`close()` (*OfflineHandler method*), 242
`close()` (*VolatilityHandler method*), 243
`closed` (*FileHandlerInterface attribute*), 170
`closed` (*NullFileHandler attribute*), 51
`cls` (*ClassRequirement property*), 142
`CM_KEY_BODY` (class in *volatility3.framework.symbols.windows.extensions.registered_symbols*), 510
`CM_KEY_BODY.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.registered_symbols*), 510
`CM_KEY_NODE` (class in *volatility3.framework.symbols.windows.extensions.registered_symbols*), 512
`CM_KEY_NODE.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.registered_symbols*), 512
`CM_KEY_VALUE` (class in *volatility3.framework.symbols.windows.extensions.registered_symbols*), 514
`CM_KEY_VALUE.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.registered_symbols*), 514
`CmdLine` (class in *volatility3.plugins.windows.cmdline*), 678
`CMHIVE` (class in *volatility3.framework.symbols.windows.extensions.registered_symbols*), 508
`CMHIVE.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.registered_symbols*), 508
`Column` (class in *volatility3.framework.interfaces.renderers*), 173
`ColumnFilter` (class in *volatility3.cli.text_filter*), 64
`columns` (*TreeGrid property*), 174, 307
`ColumnSortKey` (class in *volatility3.framework.interfaces.renderers*), 173
`ColumnSortKey` (class in *volatility3.framework.renderers*), 306
`comm` (*TaskData attribute*), 571
`CommandLine` (class in *volatility3.cli*), 48
`ComplexListRequirement` (class in *volatility3.framework.configuration.requirements*), 100
`config` (*ADS property*), 719
`config` (*AutomagicInterface property*), 139
`config` (*AVMLLayer property*), 186
`config` (*Banners property*), 776
`config` (*Bash property*), 568, 622
`config` (*BashIntermedSymbols property*), 405
`config` (*BigPools property*), 671
`config` (*BufferDataLayer property*), 230
`config` (*Cachedump property*), 673
`config` (*Callbacks property*), 675
`config` (*Capabilities property*), 569
`config` (*Check_afinfo property*), 572
`config` (*Check_creds property*), 574
`config` (*Check_idt property*), 575
`config` (*Check_modules property*), 577
`config` (*Check_syscall property*), 578, 623
`config` (*Check_sysctl property*), 625
`config` (*Check_trap_table property*), 626
`config` (*CmdLine property*), 678
`config` (*ConfigurableInterface property*), 143
`config` (*ConfigurableModule property*), 128
`config` (*ConfigWriter property*), 777
`config` (*ConstructionMagic property*), 71
`config` (*Context property*), 131
`config` (*ContextInterface property*), 154
`config` (*Crashinfo property*), 680
`config` (*DataLayerInterface property*), 159
`config` (*DeviceTree property*), 681
`config` (*DllList property*), 683
`config` (*Dmesg property*), 628
`config` (*DriverIrp property*), 685
`config` (*DriverModule property*), 687
`config` (*DriverScan property*), 688
`config` (*DumpFiles property*), 690
`config` (*Elf64Layer property*), 196
`config` (*Elfs property*), 580
`config` (*Envvars property*), 582, 692
`config` (*FileLayer property*), 233
`config` (*FileScan property*), 694
`config` (*FrameworkInfo property*), 779
`config` (*GetServiceSIDs property*), 696
`config` (*GetSIDs property*), 698
`config` (*Handles property*), 699
`config` (*Hashdump property*), 702
`config` (*HiveList property*), 663
`config` (*HiveScan property*), 666
`config` (*IAT property*), 704
`config` (*Ifconfig property*), 630
`config` (*Info property*), 706
`config` (*Intel property*), 199
`config` (*Intel32e property*), 202
`config` (*IntelPAE property*), 205
`config` (*IntermediateSymbolTable property*), 535

- config (*IOMem* property), 583
- config (*IsfInfo* property), 780
- config (*ISFormatTable* property), 531
- config (*JobLinks* property), 708
- config (*Kauth_listeners* property), 631
- config (*Kauth_scopes* property), 633
- config (*KernelModule* property), 78
- config (*KernelPDBScanner* property), 80
- config (*Kevents* property), 635
- config (*Keyboard_notifiers* property), 585
- config (*Kmsg* property), 588
- config (*LayerStacker* property), 83
- config (*LayerWriter* property), 782
- config (*LdrModules* property), 710
- config (*LibraryList* property), 597
- config (*LimeLayer* property), 219
- config (*LinearlyMappedLayer* property), 222
- config (*LinuxKernelIntermedSymbols* property), 327
- config (*LinuxSymbolFinder* property), 74
- config (*List_Files* property), 637
- config (*Lsadbump* property), 712
- config (*Lsmode* property), 598, 639
- config (*Lsof* property), 600, 640
- config (*MacKernelIntermedSymbols* property), 409
- config (*MacSymbolFinder* property), 76
- config (*Malfind* property), 602, 642, 713
- config (*Maps* property), 606, 647
- config (*MBRScan* property), 715
- config (*Memmap* property), 717
- config (*MFTScan* property), 720
- config (*ModScan* property), 722
- config (*Module* property), 132
- config (*ModuleInterface* property), 155
- config (*Modules* property), 725
- config (*Mount* property), 643
- config (*MountInfo* property), 603
- config (*MutantScan* property), 727
- config (*NetScan* property), 729
- config (*NetStat* property), 732
- config (*Netstat* property), 645
- config (*NonLinearlySegmentedLayer* property), 244
- config (*Passphrase* property), 764
- config (*PdbMSFStream* property), 225
- config (*PdbMultiStreamFormat* property), 228
- config (*PluginInterface* property), 172
- config (*PoolScanner* property), 737
- config (*PrintKey* property), 668
- config (*Privs* property), 741
- config (*PsAux* property), 608
- config (*Psaux* property), 649
- config (*PsList* property), 610, 651, 743
- config (*PsScan* property), 612, 746
- config (*PsTree* property), 614, 654, 749
- config (*QemuSuspendLayer* property), 236
- config (*RegistryHive* property), 239
- config (*SegmentedLayer* property), 246
- config (*Sessions* property), 751
- config (*SizedModule* property), 136
- config (*Skeleton_Key_Check* property), 752
- config (*Socket_filters* property), 656
- config (*Sockstat* property), 616
- config (*SSDT* property), 754
- config (*Strings* property), 756
- config (*SvcScan* property), 758
- config (*SymbolCacheMagic* property), 90
- config (*SymbolFinder* property), 92
- config (*SymbolTableInterface* property), 182
- config (*SymlinkScan* property), 760
- config (*ThrdScan* property), 762
- config (*Timeliner* property), 786
- config (*Timers* property), 658
- config (*TranslationLayerInterface* property), 163
- config (*Trustedbsd* property), 659
- config (*tty_check* property), 618
- config (*UserAssist* property), 669
- config (*VadInfo* property), 766
- config (*VadWalk* property), 768
- config (*VadYaraScan* property), 770
- config (*VerInfo* property), 772
- config (*Version1Format* property), 538
- config (*Version2Format* property), 541
- config (*Version3Format* property), 544
- config (*Version4Format* property), 547
- config (*Version5Format* property), 550
- config (*Version6Format* property), 553
- config (*Version7Format* property), 556
- config (*Version8Format* property), 559
- config (*VFSevents* property), 661
- config (*VirtMap* property), 774
- config (*VmaYaraScan* property), 620
- config (*VmwareLayer* property), 249
- config (*Volshell* property), 53, 56, 59, 61
- config (*WindowsCrashDump32Layer* property), 190
- config (*WindowsCrashDump64Layer* property), 193
- config (*WindowsIntel* property), 208
- config (*WindowsIntel32e* property), 211
- config (*WindowsIntelPAE* property), 213
- config (*WindowsKernelIntermedSymbols* property), 437
- config (*WindowsMixin* property), 216
- config (*WinSwapLayers* property), 94
- config (*XenCoreDumpLayer* property), 251
- config (*YaraScan* property), 787
- config_path (*ADS* property), 719
- config_path (*AutomagicInterface* property), 139
- config_path (*AVMLLayer* property), 186
- config_path (*Banners* property), 776
- config_path (*Bash* property), 568, 622
- config_path (*BashIntermedSymbols* property), 405

`config_path` (*BigPools* property), 671
`config_path` (*BufferDataLayer* property), 230
`config_path` (*Cachedump* property), 673
`config_path` (*Callbacks* property), 675
`config_path` (*Capabilities* property), 569
`config_path` (*Check_afinfo* property), 572
`config_path` (*Check_creds* property), 574
`config_path` (*Check_idt* property), 575
`config_path` (*Check_modules* property), 577
`config_path` (*Check_syscall* property), 578, 623
`config_path` (*Check_sysctl* property), 625
`config_path` (*Check_trap_table* property), 627
`config_path` (*CmdLine* property), 678
`config_path` (*ConfigurableInterface* property), 143
`config_path` (*ConfigurableModule* property), 128
`config_path` (*ConfigWriter* property), 777
`config_path` (*ConstructionMagic* property), 71
`config_path` (*Crashinfo* property), 680
`config_path` (*DataLayerInterface* property), 159
`config_path` (*DeviceTree* property), 682
`config_path` (*DllList* property), 683
`config_path` (*Dmesg* property), 628
`config_path` (*DriverIrp* property), 685
`config_path` (*DriverModule* property), 687
`config_path` (*DriverScan* property), 688
`config_path` (*DumpFiles* property), 690
`config_path` (*Elf64Layer* property), 196
`config_path` (*Elfs* property), 580
`config_path` (*Envvars* property), 582, 693
`config_path` (*FileLayer* property), 233
`config_path` (*FileScan* property), 694
`config_path` (*FrameworkInfo* property), 779
`config_path` (*GetServiceSIDs* property), 696
`config_path` (*GetSIDs* property), 698
`config_path` (*Handles* property), 699
`config_path` (*Hashdump* property), 702
`config_path` (*HiveList* property), 663
`config_path` (*HiveScan* property), 666
`config_path` (*IAT* property), 704
`config_path` (*Ifconfig* property), 630
`config_path` (*Info* property), 706
`config_path` (*Intel* property), 199
`config_path` (*Intel32e* property), 202
`config_path` (*IntelPAE* property), 205
`config_path` (*IntermediateSymbolTable* property), 535
`config_path` (*IOMem* property), 584
`config_path` (*IsfInfo* property), 781
`config_path` (*ISFormatTable* property), 531
`config_path` (*JobLinks* property), 708
`config_path` (*Kauth_listeners* property), 632
`config_path` (*Kauth_scopes* property), 633
`config_path` (*KernelModule* property), 78
`config_path` (*KernelPDBScanner* property), 80
`config_path` (*Kevents* property), 635
`config_path` (*Keyboard_notifiers* property), 585
`config_path` (*Kmsg* property), 588
`config_path` (*LayerStacker* property), 83
`config_path` (*LayerWriter* property), 782
`config_path` (*LdrModules* property), 710
`config_path` (*LibraryList* property), 597
`config_path` (*LimeLayer* property), 219
`config_path` (*LinearlyMappedLayer* property), 222
`config_path` (*LinuxKernelIntermedSymbols* property), 327
`config_path` (*LinuxSymbolFinder* property), 74
`config_path` (*List_Files* property), 637
`config_path` (*Lsadump* property), 712
`config_path` (*Lsmmod* property), 598, 639
`config_path` (*Lsof* property), 600, 640
`config_path` (*MacKernelIntermedSymbols* property), 409
`config_path` (*MacSymbolFinder* property), 76
`config_path` (*Malfind* property), 602, 642, 713
`config_path` (*Maps* property), 606, 647
`config_path` (*MBRScan* property), 716
`config_path` (*Memmap* property), 717
`config_path` (*MFTScan* property), 720
`config_path` (*ModScan* property), 722
`config_path` (*Module* property), 132
`config_path` (*ModuleInterface* property), 156
`config_path` (*Modules* property), 725
`config_path` (*Mount* property), 644
`config_path` (*MountInfo* property), 603
`config_path` (*MutantScan* property), 727
`config_path` (*NetScan* property), 729
`config_path` (*NetStat* property), 732
`config_path` (*Netstat* property), 645
`config_path` (*NonLinearlySegmentedLayer* property), 244
`config_path` (*Passphrase* property), 764
`config_path` (*PdbMSFStream* property), 225
`config_path` (*PdbMultiStreamFormat* property), 228
`config_path` (*PluginInterface* property), 172
`config_path` (*PoolScanner* property), 737
`config_path` (*PrintKey* property), 668
`config_path` (*Privs* property), 741
`config_path` (*PsAux* property), 608
`config_path` (*Psaux* property), 649
`config_path` (*PsList* property), 610, 651, 743
`config_path` (*PsScan* property), 612, 746
`config_path` (*PsTree* property), 614, 655, 749
`config_path` (*QemuSuspendLayer* property), 236
`config_path` (*RegistryHive* property), 239
`config_path` (*SegmentedLayer* property), 246
`config_path` (*Sessions* property), 751
`config_path` (*SizedModule* property), 136
`config_path` (*Skeleton_Key_Check* property), 752
`config_path` (*Socket_filters* property), 656

- `config_path` (*Sockstat property*), 616
- `config_path` (*SSDT property*), 754
- `config_path` (*Strings property*), 756
- `config_path` (*SvcScan property*), 758
- `config_path` (*SymbolCacheMagic property*), 90
- `config_path` (*SymbolFinder property*), 92
- `config_path` (*SymbolTableInterface property*), 183
- `config_path` (*SymlinkScan property*), 760
- `config_path` (*ThrdScan property*), 762
- `config_path` (*Timeliner property*), 786
- `config_path` (*Timers property*), 658
- `config_path` (*TranslationLayerInterface property*), 163
- `config_path` (*Trustedbsd property*), 659
- `config_path` (*tty_check property*), 618
- `config_path` (*UserAssist property*), 669
- `config_path` (*VadInfo property*), 766
- `config_path` (*VadWalk property*), 768
- `config_path` (*VadYaraScan property*), 770
- `config_path` (*VerInfo property*), 772
- `config_path` (*Version1Format property*), 538
- `config_path` (*Version2Format property*), 541
- `config_path` (*Version3Format property*), 544
- `config_path` (*Version4Format property*), 547
- `config_path` (*Version5Format property*), 550
- `config_path` (*Version6Format property*), 553
- `config_path` (*Version7Format property*), 556
- `config_path` (*Version8Format property*), 559
- `config_path` (*VFSevents property*), 661
- `config_path` (*VirtMap property*), 774
- `config_path` (*VmaYaraScan property*), 620
- `config_path` (*VmwareLayer property*), 249
- `config_path` (*Volshell property*), 53, 56, 59, 62
- `config_path` (*WindowsCrashDump32Layer property*), 190
- `config_path` (*WindowsCrashDump64Layer property*), 193
- `config_path` (*WindowsIntel property*), 208
- `config_path` (*WindowsIntel32e property*), 211
- `config_path` (*WindowsIntelPAE property*), 213
- `config_path` (*WindowsKernelIntermedSymbols property*), 437
- `config_path` (*WindowsMixin property*), 216
- `config_path` (*WinSwapLayers property*), 94
- `config_path` (*XenCoreDumpLayer property*), 252
- `config_path` (*YaraScan property*), 787
- `CONFIG_SEPARATOR` (in module `volatility3.framework.interfaces.configuration`), 141
- `config_value()` (*BooleanRequirement method*), 97
- `config_value()` (*BytesRequirement method*), 98
- `config_value()` (*ChoiceRequirement method*), 99
- `config_value()` (*ClassRequirement method*), 142
- `config_value()` (*ComplexListRequirement method*), 101
- `config_value()` (*ConfigurableRequirementInterface method*), 145
- `config_value()` (*ConstructableRequirementInterface method*), 146
- `config_value()` (*IntRequirement method*), 102
- `config_value()` (*LayerListRequirement method*), 104
- `config_value()` (*ListRequirement method*), 106
- `config_value()` (*ModuleRequirement method*), 107
- `config_value()` (*MultiRequirement method*), 109
- `config_value()` (*PluginRequirement method*), 111
- `config_value()` (*RequirementInterface method*), 150
- `config_value()` (*SimpleTypeRequirement method*), 151
- `config_value()` (*StringRequirement method*), 112
- `config_value()` (*SymbolTableRequirement method*), 114
- `config_value()` (*TranslationLayerRequirement method*), 116
- `config_value()` (*URIRequirement method*), 117
- `config_value()` (*VersionRequirement method*), 119
- `ConfigurableInterface` (class in `volatility3.framework.interfaces.configuration`), 143
- `ConfigurableModule` (class in `volatility3.framework.contexts`), 127
- `ConfigurableRequirementInterface` (class in `volatility3.framework.interfaces.configuration`), 144
- `ConfigWriter` (class in `volatility3.plugins.configwriter`), 777
- `conjugate()` (*Bin method*), 311
- `conjugate()` (*BitField method*), 259
- `conjugate()` (*Boolean method*), 262
- `conjugate()` (*Char method*), 271
- `conjugate()` (*ELF_CLASS method*), 124
- `conjugate()` (*ELF_IDENT method*), 126
- `conjugate()` (*Enumeration method*), 276
- `conjugate()` (*Float method*), 279
- `conjugate()` (*Hex method*), 312
- `conjugate()` (*Integer method*), 284
- `conjugate()` (*Parallelism method*), 122
- `conjugate()` (*Pointer method*), 287
- `conjugate()` (*PoolType method*), 740
- `conjugate()` (*RegKeyFlags method*), 519
- `conjugate()` (*TimeLinerType method*), 785
- `constant_data` (*SymbolInterface property*), 180
- `construct()` (*ComplexListRequirement method*), 101
- `construct()` (*ConstructableRequirementInterface method*), 147
- `construct()` (*LayerListRequirement method*), 104
- `construct()` (*ModuleRequirement method*), 108
- `construct()` (*SymbolTableRequirement method*), 114
- `construct()` (*TranslationLayerRequirement method*), 116
- `construct_locals()` (*Volshell method*), 53, 56, 59, 62

`construct_plugin()` (in module `volatility3.framework.plugins`), 306

`ConstructableRequirementInterface` (class in `volatility3.framework.interfaces.configuration`), 146

`ConstructionMagic` (class in `volatility3.framework.automagic.construct_layers`), 71

`consume_padding()` (*PdbReader* method), 525

`consume_type()` (*PdbReader* method), 525

`container_of()` (*LinuxUtilities* class method), 329

`context` (*ADS* property), 719

`context` (*AutomagicInterface* property), 139

`context` (*AVMLLayer* property), 187

`context` (*Banners* property), 776

`context` (*Bash* property), 568, 622

`context` (*BashIntermedSymbols* property), 405

`context` (*BigPools* property), 671

`context` (*BufferDataLayer* property), 230

`context` (*BytesScanner* property), 185

`context` (*Cachedump* property), 673

`context` (*Callbacks* property), 675

`context` (*Capabilities* property), 569

`context` (*Check_afinfo* property), 572

`context` (*Check_creds* property), 574

`context` (*Check_idt* property), 575

`context` (*Check_modules* property), 577

`context` (*Check_syscall* property), 578, 623

`context` (*Check_sysctl* property), 625

`context` (*Check_trap_table* property), 627

`Context` (class in `volatility3.framework.contexts`), 130

`context` (*CmdLine* property), 678

`context` (*ConfigurableInterface* property), 143

`context` (*ConfigurableModule* property), 128

`context` (*ConfigWriter* property), 777

`context` (*ConstructionMagic* property), 71

`context` (*Crashinfo* property), 680

`context` (*DataLayerInterface* property), 159

`context` (*DeviceTree* property), 682

`context` (*DllList* property), 683

`context` (*Dmesg* property), 628

`context` (*DriverIrp* property), 685

`context` (*DriverModule* property), 687

`context` (*DriverScan* property), 688

`context` (*DumpFiles* property), 690

`context` (*Elf64Layer* property), 196

`context` (*Elfs* property), 580

`context` (*Envvars* property), 582, 693

`context` (*FileLayer* property), 233

`context` (*FileScan* property), 694

`context` (*FrameworkInfo* property), 779

`context` (*GetServiceSIDs* property), 696

`context` (*GetSIDs* property), 698

`context` (*Handles* property), 699

`context` (*Hashdump* property), 702

`context` (*HiveList* property), 663

`context` (*HiveScan* property), 666

`context` (*IAT* property), 705

`context` (*Ifconfig* property), 630

`context` (*Info* property), 706

`context` (*Intel* property), 199

`context` (*Intel32e* property), 202

`context` (*IntelPAE* property), 205

`context` (*IntermediateSymbolTable* property), 535

`context` (*IOMem* property), 584

`context` (*IsfInfo* property), 781

`context` (*ISFormatTable* property), 531

`context` (*JobLinks* property), 708

`context` (*Kauth_listeners* property), 632

`context` (*Kauth_scopes* property), 633

`context` (*KernelModule* property), 78

`context` (*KernelPDBScanner* property), 80

`context` (*Kevents* property), 635

`context` (*Keyboard_notifiers* property), 585

`context` (*Kmsg* property), 589

`context` (*LayerStacker* property), 83

`context` (*LayerWriter* property), 782

`context` (*LdrModules* property), 710

`context` (*LibraryList* property), 597

`context` (*LimeLayer* property), 219

`context` (*LinearlyMappedLayer* property), 222

`context` (*LinuxKernelIntermedSymbols* property), 327

`context` (*LinuxSymbolFinder* property), 74

`context` (*List_Files* property), 637

`context` (*Lsadbump* property), 712

`context` (*Lsmdb* property), 598, 639

`context` (*Lsof* property), 600, 640

`context` (*MacKernelIntermedSymbols* property), 409

`context` (*MacSymbolFinder* property), 76

`context` (*Malfind* property), 602, 642, 713

`context` (*Maps* property), 606, 647

`context` (*MBRScan* property), 716

`context` (*Memmap* property), 717

`context` (*MFTScan* property), 721

`context` (*ModScan* property), 722

`context` (*Module* property), 132

`context` (*ModuleInterface* property), 156

`context` (*Modules* property), 725

`context` (*Mount* property), 644

`context` (*MountInfo* property), 603

`context` (*MultiStringScanner* property), 185

`context` (*MutantScan* property), 727

`context` (*NetScan* property), 729

`context` (*NetStat* property), 732

`context` (*Netstat* property), 645

`context` (*NonLinearlySegmentedLayer* property), 244

`context` (*PageMapScanner* property), 94

`context` (*Passphrase* property), 764

context (*PdbMSFStream property*), 225
 context (*PdbMultiStreamFormat property*), 228
 context (*PdbReader property*), 525
 context (*PdbSignatureScanner property*), 530
 context (*PluginInterface property*), 172
 context (*PoolHeaderScanner property*), 736
 context (*PoolScanner property*), 737
 context (*PrintKey property*), 668
 context (*Privs property*), 741
 context (*PsAux property*), 608
 context (*Psaux property*), 649
 context (*PsList property*), 610, 651, 743
 context (*PsScan property*), 612, 746
 context (*PsTree property*), 614, 655, 749
 context (*QemuSuspendLayer property*), 236
 context (*RegExScanner property*), 185
 context (*RegistryHive property*), 239
 context (*ScannerInterface property*), 163
 context (*SegmentedLayer property*), 246
 context (*Sessions property*), 751
 context (*SizedModule property*), 136
 context (*Skeleton_Key_Check property*), 752
 context (*Socket_filters property*), 656
 context (*Sockstat property*), 616
 context (*SSDT property*), 754
 context (*Strings property*), 756
 context (*SvcScan property*), 758
 context (*SymbolCacheMagic property*), 90
 context (*SymbolFinder property*), 92
 context (*SymbolTableInterface property*), 183
 context (*SymlinkScan property*), 760
 context (*ThrdScan property*), 762
 context (*Timeliner property*), 786
 context (*Timers property*), 658
 context (*TranslationLayerInterface property*), 163
 context (*Trustedbsd property*), 659
 context (*tty_check property*), 618
 context (*UserAssist property*), 670
 context (*VadInfo property*), 766
 context (*VadWalk property*), 768
 context (*VadYaraScan property*), 770
 context (*VerInfo property*), 772
 context (*Version1Format property*), 538
 context (*Version2Format property*), 541
 context (*Version3Format property*), 544
 context (*Version4Format property*), 547
 context (*Version5Format property*), 550
 context (*Version6Format property*), 553
 context (*Version7Format property*), 556
 context (*Version8Format property*), 559
 context (*VFSevents property*), 661
 context (*VirtMap property*), 774
 context (*VmaYaraScan property*), 620
 context (*VmwareLayer property*), 249

context (*Volshell property*), 53, 56, 59, 62
 context (*WindowsCrashDump32Layer property*), 190
 context (*WindowsCrashDump64Layer property*), 193
 context (*WindowsIntel property*), 208
 context (*WindowsIntel32e property*), 211
 context (*WindowsIntelPAE property*), 213
 context (*WindowsKernelIntermedSymbols property*), 437
 context (*WindowsMixin property*), 216
 context (*WinSwapLayers property*), 94
 context (*XenCoreDumpLayer property*), 252
 context (*YaraScan property*), 788
 context (*YaraScanner property*), 789
 ContextInterface (class in *volatility3.framework.interfaces.context*), 153
 CONTROL_AREA (class in *volatility3.framework.symbols.windows.extensions*), 440
 CONTROL_AREA.VolTemplateProxy (class in *volatility3.framework.symbols.windows.extensions*), 440
 convert_arg_line_to_args() (*HelpfulArgParser method*), 68
 convert_bytes_to_guid() (*PdbReader method*), 525
 convert_data_to_value() (in module *volatility3.framework.objects*), 303
 convert_fields() (*PdbReader method*), 525
 convert_ipv4() (in module *volatility3.framework.renderers.conversion*), 309
 convert_ipv6() (in module *volatility3.framework.renderers.conversion*), 309
 convert_network_four_tuple() (in module *volatility3.framework.renderers.conversion*), 309
 convert_port() (in module *volatility3.framework.renderers.conversion*), 309
 convert_value_to_data() (in module *volatility3.framework.objects*), 303
 count (*Array property*), 257
 count() (*Bytes method*), 265
 count() (*Column method*), 173
 count() (*DataFormatInfo method*), 275
 count() (*HexBytes method*), 313
 count() (*MountInfoData method*), 605
 count() (*MultiTypeData method*), 317
 count() (*ServiceBinaryInfo method*), 757
 count() (*String method*), 292
 count() (*TreeNode method*), 176, 308
 crashdump_json (*WindowsCrashDump32Layer attribute*), 190
 crashdump_json (*WindowsCrashDump64Layer attribute*), 193
 Crashinfo (class in *volatility3.plugins.windows.crashinfo*), 680
 create() (*BashIntermedSymbols class method*), 405

`create()` (*ConfigurableModule* class method), 128
`create()` (*IntermediateSymbolTable* class method), 535
`create()` (*LinuxKernelIntermedSymbols* class method), 327
`create()` (*MacKernelIntermedSymbols* class method), 409
`create()` (*Module* class method), 132
`create()` (*SizedModule* class method), 136
`create()` (*WindowsKernelIntermedSymbols* class method), 437
`create_callback_table()` (*Callbacks* static method), 675
`create_configurable()` (*Volshell* method), 53, 56, 59, 62
`create_json_hash()` (in module *volatility3.schemas*), 789
`create_name_filter()` (*PsList* class method), 743
`create_netscan_constraints()` (*NetScan* static method), 729
`create_netscan_symbol_table()` (*NetScan* class method), 729
`create_offset_filter()` (*PsScan* class method), 746
`create_pid_filter()` (*PsList* class method), 610, 651, 743
`create_service_table()` (*SvcScan* static method), 758
`create_stackers_list()` (*LayerStacker* method), 83
`create_stream_from_pages()` (*PdbMultiStreamFormat* method), 228
`create_tcpip_symbol_table()` (*NetStat* class method), 732
`CREATED` (*TimeLinerType* attribute), 784
`createservicesid()` (in module *volatility3.plugins.windows.getservicesids*), 697
`cred` (class in *volatility3.framework.symbols.linux.extensions*), 335
`cred.VolTemplateProxy` (class in *volatility3.framework.symbols.linux.extensions*), 335
`CSVRenderer` (class in *volatility3.cli.text_renderer*), 65
`current_kernel_name` (*Volshell* property), 53, 56, 59, 62
`current_layer` (*Volshell* property), 53, 56, 59, 62
`current_symbol_table` (*Volshell* property), 53, 56, 59, 62

D

`d_ancestor()` (*dentry* method), 338
`data` (*HierarchicalDict* property), 148
`DataFormatInfo` (class in *volatility3.framework.objects*), 274
`DataLayerInterface` (class in *volatility3.framework.interfaces.layers*), 158
`datetime` (*ProducerMetadata* property), 561
`decanonicalize()` (*Intel* method), 199
`decanonicalize()` (*Intel32e* method), 202
`decanonicalize()` (*IntelPAE* method), 205
`decanonicalize()` (*WindowsIntel* method), 208
`decanonicalize()` (*WindowsIntel32e* method), 211
`decanonicalize()` (*WindowsIntelPAE* method), 214
`decanonicalize()` (*WindowsMixin* method), 216
`decode()` (*Bytes* method), 265
`decode()` (*HexBytes* method), 313
`decode()` (*MultiTypeData* method), 317
`decode_data()` (*CM_KEY_VALUE* method), 515
`decrypt_aes()` (*Lsadump* class method), 712
`decrypt_hash()` (*Cachedump* static method), 673
`decrypt_secret()` (*Lsadump* class method), 712
`decrypt_single_hash()` (*Hashdump* class method), 702
`decrypt_single_saltied_hash()` (*Hashdump* class method), 702
`deduplicate()` (*ModuleCollection* method), 135
`default` (*BooleanRequirement* property), 97
`default` (*BytesRequirement* property), 98
`default` (*ChoiceRequirement* property), 99
`default` (*ClassRequirement* property), 142
`default` (*ComplexListRequirement* property), 101
`default` (*ConfigurableRequirementInterface* property), 145
`default` (*ConstructableRequirementInterface* property), 147
`default` (*IntRequirement* property), 103
`default` (*LayerListRequirement* property), 104
`default` (*ListRequirement* property), 106
`default` (*ModuleRequirement* property), 108
`default` (*MultiRequirement* property), 109
`default` (*PluginRequirement* property), 111
`default` (*RequirementInterface* property), 150
`default` (*SimpleTypeRequirement* property), 151
`default` (*StringRequirement* property), 113
`default` (*SymbolTableRequirement* property), 114
`default` (*TranslationLayerRequirement* property), 116
`default` (*URIRequirement* property), 117
`default` (*VersionRequirement* property), 119
`default_block_size` (*LayerWriter* attribute), 782
`default_open()` (*JarHandler* static method), 242
`default_open()` (*OfflineHandler* static method), 242
`del_layer()` (*LayerContainer* method), 161
`del_type_class()` (*BaseSymbolTableInterface* method), 177
`del_type_class()` (*BashIntermedSymbols* method), 406
`del_type_class()` (*IntermediateSymbolTable* method), 535
`del_type_class()` (*ISFormatTable* method), 531

- `del_type_class()` (*LinuxKernelIntermedSymbols* method), 327
- `del_type_class()` (*MacKernelIntermedSymbols* method), 409
- `del_type_class()` (*NativeTable* method), 562
- `del_type_class()` (*NativeTableInterface* method), 179
- `del_type_class()` (*SymbolTableInterface* method), 183
- `del_type_class()` (*Version1Format* method), 538
- `del_type_class()` (*Version2Format* method), 541
- `del_type_class()` (*Version3Format* method), 544
- `del_type_class()` (*Version4Format* method), 547
- `del_type_class()` (*Version5Format* method), 550
- `del_type_class()` (*Version6Format* method), 553
- `del_type_class()` (*Version7Format* method), 556
- `del_type_class()` (*Version8Format* method), 559
- `del_type_class()` (*WindowsKernelIntermedSymbols* method), 438
- `deleter()` (*classproperty* method), 47
- `denominator` (*Bin* attribute), 311
- `denominator` (*BitField* attribute), 259
- `denominator` (*Boolean* attribute), 262
- `denominator` (*Char* attribute), 271
- `denominator` (*ELF_CLASS* attribute), 124
- `denominator` (*ELF_IDENT* attribute), 126
- `denominator` (*Enumeration* attribute), 277
- `denominator` (*Hex* attribute), 312
- `denominator` (*Integer* attribute), 284
- `denominator` (*Parallelism* attribute), 122
- `denominator` (*Pointer* attribute), 287
- `denominator` (*PoolType* attribute), 740
- `denominator` (*RegKeyFlags* attribute), 519
- `denominator` (*TimeLinerType* attribute), 785
- `dentry` (class in *volatility3.framework.symbols.linux.extensions*), 337
- `dentry.VolTemplateProxy` (class in *volatility3.framework.symbols.linux.extensions*), 337
- `dependencies` (*AVMLLayer* property), 187
- `dependencies` (*BufferDataLayer* property), 230
- `dependencies` (*DataLayerInterface* property), 159
- `dependencies` (*Elf64Layer* property), 196
- `dependencies` (*FileLayer* property), 233
- `dependencies` (*Intel* property), 200
- `dependencies` (*Intel32e* property), 202
- `dependencies` (*IntelPAE* property), 205
- `dependencies` (*LimeLayer* property), 219
- `dependencies` (*LinearlyMappedLayer* property), 222
- `dependencies` (*NonLinearlySegmentedLayer* property), 244
- `dependencies` (*PdbMSFStream* property), 225
- `dependencies` (*PdbMultiStreamFormat* property), 228
- `dependencies` (*QemuSuspendLayer* property), 236
- `dependencies` (*RegistryHive* property), 239
- `dependencies` (*SegmentedLayer* property), 246
- `dependencies` (*TranslationLayerInterface* property), 163
- `dependencies` (*VmwareLayer* property), 249
- `dependencies` (*WindowsCrashDump32Layer* property), 190
- `dependencies` (*WindowsCrashDump64Layer* property), 193
- `dependencies` (*WindowsIntel* property), 208
- `dependencies` (*WindowsIntel32e* property), 211
- `dependencies` (*WindowsIntelPAE* property), 214
- `dependencies` (*WindowsMixin* property), 216
- `dependencies` (*XenCoreDumpLayer* property), 252
- `dereference()` (*EX_FAST_REF* method), 452
- `dereference()` (*Pointer* method), 287
- `desc_committed` (*DescStateEnum* attribute), 588
- `desc_finalized` (*DescStateEnum* attribute), 588
- `desc_miss` (*DescStateEnum* attribute), 588
- `desc_reserved` (*DescStateEnum* attribute), 588
- `desc_reusable` (*DescStateEnum* attribute), 588
- `DescExitStateEnum` (class in *volatility3.plugins.linux.psscan*), 612
- `description` (*BooleanRequirement* property), 97
- `description` (*BytesRequirement* property), 98
- `description` (*ChoiceRequirement* property), 99
- `description` (*ClassRequirement* property), 142
- `description` (*ComplexListRequirement* property), 101
- `description` (*ConfigurableRequirementInterface* property), 145
- `description` (*ConstructableRequirementInterface* property), 147
- `description` (*Enumeration* property), 277
- `description` (*IntRequirement* property), 103
- `description` (*LayerListRequirement* property), 104
- `description` (*ListRequirement* property), 106
- `description` (*ModuleRequirement* property), 108
- `description` (*MultiRequirement* property), 109
- `description` (*PluginRequirement* property), 111
- `description` (*RequirementInterface* property), 150
- `description` (*SimpleTypeRequirement* property), 151
- `description` (*StringRequirement* property), 113
- `description` (*SymbolTableRequirement* property), 114
- `description` (*TranslationLayerRequirement* property), 116
- `description` (*URIRequirement* property), 117
- `description` (*VersionRequirement* property), 119
- `DescStateEnum` (class in *volatility3.plugins.linux.kmsg*), 588
- `destroy()` (*AVMLLayer* method), 187
- `destroy()` (*BufferDataLayer* method), 231
- `destroy()` (*DataLayerInterface* method), 159
- `destroy()` (*Elf64Layer* method), 196
- `destroy()` (*FileLayer* method), 233

- `destroy()` (*Intel method*), 200
 - `destroy()` (*Intel32e method*), 202
 - `destroy()` (*IntelPAE method*), 205
 - `destroy()` (*LimeLayer method*), 220
 - `destroy()` (*LinearlyMappedLayer method*), 222
 - `destroy()` (*NonLinearlySegmentedLayer method*), 244
 - `destroy()` (*PdbMSFStream method*), 225
 - `destroy()` (*PdbMultiStreamFormat method*), 228
 - `destroy()` (*QemuSuspendLayer method*), 236
 - `destroy()` (*RegistryHive method*), 239
 - `destroy()` (*SegmentedLayer method*), 246
 - `destroy()` (*TranslationLayerInterface method*), 163
 - `destroy()` (*VmwareLayer method*), 249
 - `destroy()` (*WindowsCrashDump32Layer method*), 190
 - `destroy()` (*WindowsCrashDump64Layer method*), 193
 - `destroy()` (*WindowsIntel method*), 208
 - `destroy()` (*WindowsIntel32e method*), 211
 - `destroy()` (*WindowsIntelPAE method*), 214
 - `destroy()` (*WindowsMixin method*), 217
 - `destroy()` (*XenCoreDumpLayer method*), 252
 - `detach()` (*NullFileHandler method*), 51
 - `determine_extended_value()` (*PdbReader method*), 525
 - `determine_map()` (*VirtMap class method*), 774
 - `determine_tcpip_version()` (*NetScan class method*), 730
 - `determine_valid_kernel()` (*KernelPDBScanner method*), 80
 - `DEVICE_OBJECT` (class in *volatility3.framework.symbols.windows.extensions*), 442
 - `DEVICE_OBJECT.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions*), 442
 - `DeviceTree` (class in *volatility3.plugins.windows.devicetree*), 681
 - `devname` (*MountInfoData attribute*), 605
 - `disassemble()` (*Volshell method*), 53, 56, 59, 62
 - `Disassembly` (class in *volatility3.framework.interfaces.renderers*), 173
 - `display_bytes()` (*Volshell method*), 53, 56, 59, 62
 - `display_disassembly()` (in module *volatility3.cli.text_renderer*), 67
 - `display_doublewords()` (*Volshell method*), 53, 56, 59, 62
 - `display_plugin_output()` (*Volshell method*), 53, 56, 59, 62
 - `display_quadwords()` (*Volshell method*), 54, 56, 59, 62
 - `display_symbols()` (*Volshell method*), 54, 56, 59, 62
 - `display_type()` (*Volshell method*), 54, 56, 59, 62
 - `display_words()` (*Volshell method*), 54, 57, 59, 62
 - `distro_re` (*QemuSuspendLayer attribute*), 236
 - `dll` (*ServiceBinaryInfo attribute*), 757
 - `DllList` (class in *volatility3.plugins.windows.dlllist*), 683
 - `Dmesg` (class in *volatility3.plugins.mac.dmesg*), 628
 - `do_get_path()` (*LinuxUtilities class method*), 330
 - `download_pdb_isf()` (*PDBUtility class method*), 527
 - `DRIVER_OBJECT` (class in *volatility3.framework.symbols.windows.extensions*), 444
 - `DRIVER_OBJECT.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions*), 444
 - `DriverIrp` (class in *volatility3.plugins.windows.driverirp*), 685
 - `DriverModule` (class in *volatility3.plugins.windows.drivermodule*), 686
 - `DriverScan` (class in *volatility3.plugins.windows.driverscan*), 688
 - `DtbSelfRef32bit` (class in *volatility3.framework.automagic.windows*), 93
 - `DtbSelfRef64bit` (class in *volatility3.framework.automagic.windows*), 93
 - `DtbSelfRef64bitOldWindows` (class in *volatility3.framework.automagic.windows*), 93
 - `DtbSelfReferential` (class in *volatility3.framework.automagic.windows*), 93
 - `DtbSelfRefPae` (class in *volatility3.framework.automagic.windows*), 93
 - `DummyLock` (class in *volatility3.framework.layers.physical*), 232
 - `DummyProgress` (class in *volatility3.framework.interfaces.layers*), 161
 - `dump_file_producer()` (*DumpFiles class method*), 690
 - `dump_header_name` (*WindowsCrashDump32Layer attribute*), 190
 - `dump_header_name` (*WindowsCrashDump64Layer attribute*), 193
 - `dump_pe()` (*DllList class method*), 683
 - `DumpFiles` (class in *volatility3.plugins.windows.dumpfiles*), 690
 - `dynamic_sections()` (*elf_phdr method*), 402
- ## E
- `EI_CLASS` (*ELF_IDENT attribute*), 125
 - `EI_DATA` (*ELF_IDENT attribute*), 125
 - `EI_MAG0` (*ELF_IDENT attribute*), 125
 - `EI_MAG1` (*ELF_IDENT attribute*), 125
 - `EI_MAG2` (*ELF_IDENT attribute*), 125
 - `EI_MAG3` (*ELF_IDENT attribute*), 125
 - `EI_OSABI` (*ELF_IDENT attribute*), 125
 - `EI_PAD` (*ELF_IDENT attribute*), 126
 - `EI_VERSION` (*ELF_IDENT attribute*), 126
 - `elf` (class in *volatility3.framework.symbols.linux.extensions.elf*), 397

- `elf.VolTemplateProxy` (class in `volatility3.framework.symbols.linux.extensions.elf`), 397
- `Elf64Layer` (class in `volatility3.framework.layers.elf`), 196
- `Elf64Stacker` (class in `volatility3.framework.layers.elf`), 198
- `ELF_CLASS` (class in `volatility3.framework.constants.linux`), 124
- `ELF_CLASS` (`Elf64Layer` attribute), 196
- `ELF_CLASS` (`XenCoreDumpLayer` attribute), 251
- `elf_dump()` (`Elfs` class method), 580
- `ELF_IDENT` (class in `volatility3.framework.constants.linux`), 125
- `elf_linkmap` (class in `volatility3.framework.symbols.linux.extensions.elf`), 399
- `elf_linkmap.VolTemplateProxy` (class in `volatility3.framework.symbols.linux.extensions.elf`), 399
- `elf_phdr` (class in `volatility3.framework.symbols.linux.extensions.elf`), 401
- `elf_phdr.VolTemplateProxy` (class in `volatility3.framework.symbols.linux.extensions.elf`), 401
- `elf_sym` (class in `volatility3.framework.symbols.linux.extensions.elf`), 402
- `elf_sym.VolTemplateProxy` (class in `volatility3.framework.symbols.linux.extensions.elf`), 403
- `ELFCLASS32` (`ELF_CLASS` attribute), 124
- `ELFCLASS64` (`ELF_CLASS` attribute), 124
- `ELFCLASSNONE` (`ELF_CLASS` attribute), 124
- `ElfFormatException`, 199
- `Elfs` (class in `volatility3.plugins.linux.elfs`), 580
- `empty_lm` (`Hashdump` attribute), 702
- `empty_nt` (`Hashdump` attribute), 702
- `encode()` (`String` method), 292
- `endswith()` (`Bytes` method), 265
- `endswith()` (`HexBytes` method), 313
- `endswith()` (`MultiTypeData` method), 318
- `endswith()` (`String` method), 292
- `ENUM` (`SymbolType` attribute), 324
- `enumerate_capabilities()` (`kernel_cap_struct` method), 345
- `enumerate_capabilities()` (`kernel_cap_t` method), 348
- `enumerate_structures_by_port()` (`NetStat` class method), 732
- `Enumeration` (class in `volatility3.framework.objects`), 275
- `Enumeration.VolTemplateProxy` (class in `volatility3.framework.objects`), 275
- `enumerations` (`BaseSymbolTableInterface` property), 177
- `enumerations` (`BashIntermedSymbols` property), 406
- `enumerations` (`IntermediateSymbolTable` property), 535
- `enumerations` (`ISFormatTable` property), 532
- `enumerations` (`LinuxKernelIntermedSymbols` property), 327
- `enumerations` (`MacKernelIntermedSymbols` property), 409
- `enumerations` (`NativeTable` property), 562
- `enumerations` (`NativeTableInterface` property), 179
- `enumerations` (`SymbolTableInterface` property), 183
- `enumerations` (`Version1Format` property), 538
- `enumerations` (`Version2Format` property), 541
- `enumerations` (`Version3Format` property), 544
- `enumerations` (`Version4Format` property), 547
- `enumerations` (`Version5Format` property), 550
- `enumerations` (`Version6Format` property), 553
- `enumerations` (`Version7Format` property), 556
- `enumerations` (`Version8Format` property), 559
- `enumerations` (`WindowsKernelIntermedSymbols` property), 438
- `Envvars` (class in `volatility3.plugins.linux.envvars`), 582
- `Envvars` (class in `volatility3.plugins.windows.envvars`), 692
- environment variable
 - `PYTHONPATH`, 23
- `environment_variables()` (`EPROCESS` method), 447
- `EPROCESS` (class in `volatility3.framework.symbols.windows.extensions`), 446
- `EPROCESS.VolTemplateProxy` (class in `volatility3.framework.symbols.windows.extensions`), 447
- `error()` (`HelpfulArgParser` method), 68
- `ETHREAD` (class in `volatility3.framework.symbols.windows.extensions`), 449
- `ETHREAD.VolTemplateProxy` (class in `volatility3.framework.symbols.windows.extensions`), 449
- `euid` (`cred` property), 336
- `euid` (`TaskData` attribute), 571
- `event_types` (`Kevents` attribute), 635
- `event_types` (`VFSevents` attribute), 661
- `EX_FAST_REF` (class in `volatility3.framework.symbols.windows.extensions`), 451
- `EX_FAST_REF.VolTemplateProxy` (class in `volatility3.framework.symbols.windows.extensions`), 451
- `exclusion_list` (`AutomagicInterface` attribute), 140
- `exclusion_list` (`AVMLStacker` attribute), 188
- `exclusion_list` (`ConstructionMagic` attribute), 71

exclusion_list (*Elf64Stacker attribute*), 198
exclusion_list (*KernelModule attribute*), 78
exclusion_list (*KernelPDBScanner attribute*), 80
exclusion_list (*LayerStacker attribute*), 84
exclusion_list (*LimeStacker attribute*), 221
exclusion_list (*LinuxIntelStacker attribute*), 73
exclusion_list (*LinuxSymbolFinder attribute*), 74
exclusion_list (*MacIntelStacker attribute*), 75
exclusion_list (*MacSymbolFinder attribute*), 76
exclusion_list (*QemuStacker attribute*), 235
exclusion_list (*StackerLayerInterface attribute*), 141
exclusion_list (*SymbolCacheMagic attribute*), 90
exclusion_list (*SymbolFinder attribute*), 92
exclusion_list (*VmwareStacker attribute*), 251
exclusion_list (*WindowsCrashDumpStacker attribute*), 195
exclusion_list (*WindowsIntelStacker attribute*), 96
exclusion_list (*WinSwapLayers attribute*), 94
exclusion_list (*XenCoreDumpStacker attribute*), 254
ExecutiveObject (class in volatility3.framework.symbols.windows.extensions.pool), 497
ExecutiveObject.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.pool), 497
exit() (*HelpfulArgParser method*), 68
EXIT_DEAD (*DescExitStateEnum attribute*), 612
EXIT_TRACE (*DescExitStateEnum attribute*), 612
EXIT_ZOMBIE (*DescExitStateEnum attribute*), 612
expandtabs() (*Bytes method*), 265
expandtabs() (*HexBytes method*), 314
expandtabs() (*MultiTypeData method*), 318
expandtabs() (*String method*), 292
extended_flags (*vm_area_struct attribute*), 390
extract_data() (*QemuSuspendLayer method*), 236

F

FACILITIES (*ABCKmsg attribute*), 587
FACILITIES (*Kmsg_3_11_to_5_10 attribute*), 590
FACILITIES (*Kmsg_3_5_to_3_11 attribute*), 591
FACILITIES (*Kmsg_5_10_to_ attribute*), 593
FACILITIES (*Kmsg_pre_3_5 attribute*), 595
fdel (*classproperty attribute*), 47
fget (*classproperty attribute*), 47
fields (*MountInfoData attribute*), 605
file_handler_class_factory() (*CommandLine method*), 48
file_handler_class_factory() (*VolShell method*), 49
file_name_with_device() (*FILE_OBJECT method*), 454
FILE_OBJECT (class in volatility3.framework.symbols.windows.extensions),

453
FILE_OBJECT.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions), 453
file_symbol_url() (*BashIntermedSymbols class method*), 406
file_symbol_url() (*IntermediateSymbolTable class method*), 535
file_symbol_url() (*LinuxKernelIntermedSymbols class method*), 327
file_symbol_url() (*MacKernelIntermedSymbols class method*), 409
file_symbol_url() (*WindowsKernelIntermedSymbols class method*), 438
fileglob (class in volatility3.framework.symbols.mac.extensions), 412
fileglob.VolTemplateProxy (class in volatility3.framework.symbols.mac.extensions), 412
FileHandlerInterface (class in volatility3.framework.interfaces.plugins), 169
FileLayer (class in volatility3.framework.layers.physical), 232
fileno() (*FileHandlerInterface method*), 170
fileno() (*NullFileHandler method*), 51
FILEOFFSET_MASK (*VACB attribute*), 477
files_descriptors_for_process() (*LinuxUtilities class method*), 330
files_descriptors_for_process() (*MacUtilities class method*), 411
files_struct (class in volatility3.framework.symbols.linux.extensions), 339
files_struct.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 339
FileScan (class in volatility3.plugins.windows.filescan), 694
filter (*CLIRenderer attribute*), 64
filter (*CSVRenderer attribute*), 65
filter (*JsonLinesRenderer attribute*), 65
filter (*JsonRenderer attribute*), 66
filter (*NoneRenderer attribute*), 66
filter (*PrettyTextRenderer attribute*), 66
filter (*QuickTextRenderer attribute*), 67
filter() (*CLIFilter method*), 64
find() (*Bytes method*), 265
find() (*ColumnFilter method*), 64
find() (*HexBytes method*), 314
find() (*MultiTypeData method*), 318
find() (*String method*), 292
find_aslr (*SymbolFinder attribute*), 92
find_aslr() (*LinuxIntelStacker class method*), 73
find_aslr() (*LinuxSymbolFinder method*), 74
find_aslr() (*MacIntelStacker class method*), 75

- `find_aslr()` (*MacSymbolFinder* class method), 76
 - `find_cookie()` (*Handles* class method), 699
 - `find_level()` (*PsTree* method), 614, 749
 - `find_location()` (*CacheManagerInterface* method), 86
 - `find_location()` (*SqliteCache* method), 88
 - `find_module()` (*WarningFindSpec* method), 47
 - `find_port_pools()` (*NetStat* class method), 733
 - `find_requirements()` (*AutomagicInterface* method), 140
 - `find_requirements()` (*ConstructionMagic* method), 72
 - `find_requirements()` (*KernelModule* method), 78
 - `find_requirements()` (*KernelPDBScanner* method), 80
 - `find_requirements()` (*LayerStacker* method), 84
 - `find_requirements()` (*LinuxSymbolFinder* method), 74
 - `find_requirements()` (*MacSymbolFinder* method), 76
 - `find_requirements()` (*SymbolCacheMagic* method), 90
 - `find_requirements()` (*SymbolFinder* method), 92
 - `find_requirements()` (*WinSwapLayers* method), 94
 - `find_sar_value()` (*Handles* method), 700
 - `find_session_layer()` (*ModScan* class method), 722
 - `find_session_layer()` (*Modules* class method), 725
 - `find_sid_re()` (in module *volatility3.plugins.windows.getsids*), 699
 - `find_spec()` (*WarningFindSpec* static method), 47
 - `find_suitable_requirements()` (*LayerStacker* class method), 84
 - `find_swap_requirement()` (*WinSwapLayers* static method), 95
 - `find_version_info()` (*VerInfo* class method), 772
 - `find_virtual_layers_from_req()` (*KernelPDBScanner* method), 81
 - `fix_image_base()` (*IMAGE_DOS_HEADER* method), 494
 - Flags** (class in *volatility3.framework.symbols.wrappers*), 564
 - Float** (class in *volatility3.framework.objects*), 278
 - Float.VolTemplateProxy** (class in *volatility3.framework.objects*), 278
 - `flush()` (*FileHandlerInterface* method), 170
 - `flush()` (*NullFileHandler* method), 51
 - `format()` (*String* method), 292
 - `format_help()` (*HelpfulArgParser* method), 68
 - `format_map()` (*String* method), 293
 - `format_mapping` (*Version4Format* attribute), 547
 - `format_mapping` (*Version5Format* attribute), 550
 - `format_mapping` (*Version6Format* attribute), 553
 - `format_mapping` (*Version7Format* attribute), 556
 - `format_mapping` (*Version8Format* attribute), 559
 - `format_usage()` (*HelpfulArgParser* method), 68
 - `format_usage()` (*HelpfulSubparserAction* method), 69
 - ForwardArrayCount** (class in *volatility3.framework.symbols.windows.pdbconv*), 525
 - `found()` (*ColumnFilter* method), 64
 - FrameworkInfo** (class in *volatility3.plugins.frameworkinfo*), 779
 - FREE** (*PoolType* attribute), 739
 - `free_layer_name()` (*LayerContainer* method), 161
 - `free_module_name()` (*ModuleCollection* method), 135
 - `free_module_name()` (*ModuleContainer* method), 155
 - `free_table_name()` (*SymbolSpace* method), 323
 - `free_table_name()` (*SymbolSpaceInterface* method), 181
 - `from_bytes()` (*Bin* method), 311
 - `from_bytes()` (*BitField* method), 259
 - `from_bytes()` (*Boolean* method), 262
 - `from_bytes()` (*Char* method), 271
 - `from_bytes()` (*ELF_CLASS* method), 124
 - `from_bytes()` (*ELF_IDENT* method), 126
 - `from_bytes()` (*Enumeration* method), 277
 - `from_bytes()` (*Hex* method), 312
 - `from_bytes()` (*Integer* method), 284
 - `from_bytes()` (*Parallelism* method), 122
 - `from_bytes()` (*Pointer* method), 287
 - `from_bytes()` (*PoolType* method), 740
 - `from_bytes()` (*RegKeyFlags* method), 519
 - `from_bytes()` (*TimeLinerType* method), 785
 - `fromhex()` (*Bytes* method), 266
 - `fromhex()` (*Float* method), 279
 - `fromhex()` (*HexBytes* method), 314
 - `fromhex()` (*MultiTypeData* method), 318
 - fs_struct** (class in *volatility3.framework.symbols.linux.extensions*), 341
 - fs_struct.VolTemplateProxy** (class in *volatility3.framework.symbols.linux.extensions*), 341
 - `fset` (classproperty attribute), 47
 - `full_path()` (*vnode* method), 436
 - Function** (class in *volatility3.framework.objects*), 281
 - Function.VolTemplateProxy** (class in *volatility3.framework.objects*), 281
- ## G
- `generate()` (*WindowsIdentifier* class method), 91
 - `generate_kernel_handler_info()` (*LinuxUtilities* class method), 330
 - `generate_kernel_handler_info()` (*MacUtilities* class method), 412
 - `generate_mapping()` (*Strings* class method), 756
 - `generate_pool_scan()` (*PoolScanner* class method), 737
 - `generate_timeline()` (*Bash* method), 568, 622

`generate_timeline()` (*DllList method*), 684
`generate_timeline()` (*MFTScan method*), 721
`generate_timeline()` (*NetScan method*), 730
`generate_timeline()` (*NetStat method*), 733
`generate_timeline()` (*PsList method*), 744
`generate_timeline()` (*PsScan method*), 746
`generate_timeline()` (*Sessions method*), 751
`generate_timeline()` (*SymlinkScan method*), 760
`generate_timeline()` (*ThrdScan method*), 762
`generate_timeline()` (*TimeLinerInterface method*), 784
`generate_treegrid()` (*Volshell method*), 54, 57, 59, 62
`generator()` (*HierarchicalDict method*), 148
`GenericIntelProcess` (class in *volatility3.framework.symbols.generic*), 324
`GenericIntelProcess.VolTemplateProxy` (class in *volatility3.framework.symbols.generic*), 325
`get()` (*HierarchicalDict method*), 149
`get()` (*LayerContainer method*), 162
`get()` (*ModuleCollection method*), 135
`get()` (*ModuleContainer method*), 155
`get()` (*ObjectInformation method*), 166
`get()` (*ReadOnlyMapping method*), 168
`get()` (*SymbolSpace method*), 323
`get()` (*SymbolSpaceInterface method*), 181
`get_absolute_symbol_address()` (*Configurable-Module method*), 128
`get_absolute_symbol_address()` (*Module method*), 132
`get_absolute_symbol_address()` (*ModuleInterface method*), 156
`get_absolute_symbol_address()` (*SizedModule method*), 136
`get_address()` (*sockaddr method*), 424
`get_attached_devices()` (*DEVICE_OBJECT method*), 443
`get_available_pages()` (*CONTROL_AREA method*), 441
`get_available_pages()` (*SHARED_CACHE_MAP method*), 471
`get_binary()` (*SERVICE_RECORD method*), 523
`get_block_offset()` (*HMAP_ENTRY method*), 517
`get_bootable_flag()` (*PARTITION_ENTRY method*), 483
`get_bootkey()` (*Hashdump class method*), 702
`get_buffer()` (*SUMMARY_DUMP method*), 479
`get_buffer_char()` (*SUMMARY_DUMP method*), 479
`get_buffer_long()` (*SUMMARY_DUMP method*), 479
`get_build_lab()` (*KDDEBUGGER_DATA64 method*), 481
`get_caller()` (*ABCKmsg method*), 587
`get_caller()` (*Kmsg_3_11_to_5_10 method*), 590
`get_caller()` (*Kmsg_3_5_to_3_11 method*), 591
`get_caller()` (*Kmsg_5_10_to_ method*), 593
`get_caller_text()` (*ABCKmsg method*), 587
`get_caller_text()` (*Kmsg_3_11_to_5_10 method*), 590
`get_caller_text()` (*Kmsg_3_5_to_3_11 method*), 591
`get_caller_text()` (*Kmsg_5_10_to_ method*), 593
`get_capabilities()` (*kernel_cap_struct method*), 346
`get_capabilities()` (*kernel_cap_t method*), 348
`get_cell()` (*RegistryHive method*), 239
`get_cmdline()` (*CmdLine class method*), 678
`get_command()` (*hist_entry method*), 396
`get_commit_charge()` (*MMVAD method*), 464
`get_commit_charge()` (*MMVAD_SHORT method*), 466
`get_connection_info()` (*socket method*), 428
`get_converted_connection_info()` (*socket method*), 428
`get_core_size()` (*module method*), 360
`get_create_time()` (*EPROCESS method*), 447
`get_create_time()` (*ETHREAD method*), 450
`get_create_time()` (*OBJECT_SYMBOLIC_LINK method*), 469
`get_cross_thread_flags()` (*ETHREAD method*), 450
`get_csdversion()` (*KDDEBUGGER_DATA64 method*), 481
`get_ctltype()` (*sysctl_oid method*), 430
`get_default()` (*HelpfulArgParser method*), 68
`get_dentry()` (*struct_file method*), 378
`get_dentry_current()` (*mount method*), 363
`get_dentry_current()` (*vfsmount method*), 386
`get_dentry_parent()` (*mount method*), 363
`get_dentry_parent()` (*vfsmount method*), 387
`get_depends()` (*Info class method*), 706
`get_device_name()` (*DEVICE_OBJECT method*), 443
`get_devices()` (*DRIVER_OBJECT method*), 445
`get_devname()` (*mount method*), 364
`get_devname()` (*vfsmount method*), 387
`get_dict_lines()` (*Kmsg_3_11_to_5_10 method*), 590
`get_dict_lines()` (*Kmsg_3_5_to_3_11 method*), 591
`get_dict_lines()` (*Kmsg_5_10_to_ method*), 593
`get_disk_signature()` (*PARTITION_TABLE method*), 486
`get_display()` (*SERVICE_RECORD method*), 523
`get_dominating_id()` (*mount method*), 364
`get_driver_name()` (*DRIVER_OBJECT method*), 445
`get_dst_addr()` (*inet_sock method*), 343
`get_dst_port()` (*inet_sock method*), 343
`get_dst_portid()` (*netlink_sock method*), 368
`get_elf_table_name()` (*module method*), 360
`get_end()` (*MMVAD method*), 464
`get_end()` (*MMVAD_SHORT method*), 466
`get_ending_chs()` (*PARTITION_ENTRY method*), 483

`get_ending_cylinder()` (*PARTITION_ENTRY method*), 483
`get_ending_sector()` (*PARTITION_ENTRY method*), 483
`get_enumeration()` (*BashIntermedSymbols method*), 406
`get_enumeration()` (*ConfigurableModule method*), 128
`get_enumeration()` (*IntermediateSymbolTable method*), 535
`get_enumeration()` (*LinuxKernelIntermedSymbols method*), 328
`get_enumeration()` (*MacKernelIntermedSymbols method*), 409
`get_enumeration()` (*Module method*), 132
`get_enumeration()` (*ModuleInterface method*), 156
`get_enumeration()` (*NativeTable method*), 562
`get_enumeration()` (*NativeTableInterface method*), 179
`get_enumeration()` (*SizedModule method*), 136
`get_enumeration()` (*SymbolSpace method*), 323
`get_enumeration()` (*SymbolSpaceInterface method*), 181
`get_enumeration()` (*Version1Format method*), 538
`get_enumeration()` (*Version2Format method*), 541
`get_enumeration()` (*Version3Format method*), 544
`get_enumeration()` (*Version4Format method*), 547
`get_enumeration()` (*Version5Format method*), 550
`get_enumeration()` (*Version6Format method*), 553
`get_enumeration()` (*Version7Format method*), 556
`get_enumeration()` (*Version8Format method*), 559
`get_enumeration()` (*WindowsKernelIntermedSymbols method*), 438
`get_exit_time()` (*EPROCESS method*), 447
`get_exit_time()` (*ETHREAD method*), 450
`get_facility_text()` (*ABCKmsg class method*), 587
`get_facility_text()` (*Kmsg_3_11_to_5_10 class method*), 590
`get_facility_text()` (*Kmsg_3_5_to_3_11 class method*), 591
`get_facility_text()` (*Kmsg_5_10_to_ class method*), 593
`get_facility_text()` (*Kmsg_pre_3_5 class method*), 595
`get_family()` (*inet_sock method*), 343
`get_family()` (*sock method*), 374
`get_family()` (*socket method*), 428
`get_fds()` (*files_struct method*), 340
`get_fg_type()` (*fileglob method*), 413
`get_file_name()` (*MMVAD method*), 464
`get_file_name()` (*MMVAD_SHORT method*), 466
`get_file_offset()` (*VACB method*), 477
`get_flags()` (*vm_area_struct method*), 390
`get_flags_access()` (*mount method*), 364
`get_flags_access()` (*super_block method*), 380
`get_flags_access()` (*vfsmount method*), 387
`get_flags_opts()` (*mount method*), 364
`get_flags_opts()` (*super_block method*), 380
`get_flags_opts()` (*vfsmount method*), 387
`get_full_key_name()` (*CM_KEY_BODY method*), 511
`get_full_name()` (*MFTFileName method*), 492
`get_guid_from_mz()` (*PDBUtility class method*), 527
`get_handle_count()` (*EPROCESS method*), 447
`get_hash()` (*CacheManagerInterface method*), 86
`get_hash()` (*MBRScan class method*), 716
`get_hash()` (*SqliteCache method*), 88
`get_hbootkey()` (*Hashdump class method*), 702
`get_header()` (*WindowsCrashDump32Layer method*), 190
`get_header()` (*WindowsCrashDump64Layer method*), 193
`get_hive_key()` (*Hashdump class method*), 702
`get_identifier()` (*CacheManagerInterface method*), 86
`get_identifier()` (*IdentifierProcessor class method*), 87
`get_identifier()` (*LinuxIdentifier class method*), 87
`get_identifier()` (*MacIdentifier class method*), 87
`get_identifier()` (*SqliteCache method*), 88
`get_identifier()` (*WindowsIdentifier class method*), 91
`get_identifier_dictionary()` (*CacheManagerInterface method*), 86
`get_identifier_dictionary()` (*SqliteCache method*), 88
`get_identifiers()` (*CacheManagerInterface method*), 86
`get_identifiers()` (*SqliteCache method*), 89
`get_init_size()` (*module method*), 360
`get_inode()` (*mnt_namespace method*), 359
`get_inode()` (*net method*), 367
`get_inode()` (*sock method*), 374
`get_inode()` (*socket method*), 376
`get_inode()` (*unix_sock method*), 385
`get_inpcb()` (*socket method*), 428
`get_ipv4_info()` (*inpcb method*), 417
`get_ipv6_info()` (*inpcb method*), 417
`get_is_wow64()` (*EPROCESS method*), 447
`get_json()` (*PdbReader method*), 526
`get_kdbg_structure()` (*Info class method*), 706
`get_kernel_cap_full()` (*kernel_cap_struct method*), 346
`get_kernel_cap_full()` (*kernel_cap_t method*), 348
`get_kernel_log_buffer()` (*Dmsg class method*), 628
`get_kernel_module()` (*Info class method*), 706
`get_key()` (*POOL_TRACKER_BIG_PAGES method*), 507
`get_key()` (*RegistryHive method*), 239

`get_key_path()` (*CM_KEY_NODE* method), 513
`get_kset_modules()` (*Check_modules* class method), 577
`get_kuser_structure()` (*Info* class method), 707
`get_last_cap_value()` (*kernel_cap_struct* class method), 346
`get_last_cap_value()` (*kernel_cap_t* class method), 349
`get_left_child()` (*MMVAD* method), 464
`get_left_child()` (*MMVAD_SHORT* method), 467
`get_level_text()` (*ABCKmsg* class method), 587
`get_level_text()` (*Kmsg_3_11_to_5_10* class method), 590
`get_level_text()` (*Kmsg_3_5_to_3_11* class method), 592
`get_level_text()` (*Kmsg_5_10_to_* class method), 594
`get_level_text()` (*Kmsg_pre_3_5* class method), 595
`get_link_maps()` (*elf* method), 398
`get_link_name()` (*OBJECT_SYMBOLIC_LINK* method), 469
`get_list_tasks()` (*PsList* class method), 651
`get_listeners()` (*kauth_scope* method), 418
`get_local_locations()` (*CacheManagerInterface* method), 87
`get_local_locations()` (*SqliteCache* method), 89
`get_location_statistics()` (*CacheManagerInterface* method), 87
`get_location_statistics()` (*SqliteCache* method), 89
`get_log_lines()` (*Kmsg_3_11_to_5_10* method), 590
`get_log_lines()` (*Kmsg_3_5_to_3_11* method), 592
`get_log_lines()` (*Kmsg_5_10_to_* method), 594
`get_lsa_key()` (*Lsadump* class method), 712
`get_map_iter()` (*proc* method), 420
`get_map_object()` (*vm_map_object* method), 434
`get_maple_tree_iter()` (*mm_struct* method), 357
`get_max_fds()` (*files_struct* method), 340
`get_mmap_iter()` (*mm_struct* method), 357
`get_mnt_flags()` (*mount* method), 364
`get_mnt_flags()` (*vfsmount* method), 387
`get_mnt_mountpoint()` (*mount* method), 364
`get_mnt_mountpoint()` (*vfsmount* method), 387
`get_mnt_parent()` (*mount* method), 364
`get_mnt_parent()` (*vfsmount* method), 387
`get_mnt_root()` (*mount* method), 364
`get_mnt_root()` (*vfsmount* method), 387
`get_mnt_sb()` (*mount* method), 364
`get_mnt_sb()` (*vfsmount* method), 387
`get_module_base()` (*module* method), 361
`get_module_core()` (*module* method), 361
`get_module_from_vobj_type()` (*LinuxUtilities* class method), 330
`get_module_init()` (*module* method), 361
`get_module_symbols_by_absolute_location()` (*ModuleCollection* method), 135
`get_module_wrapper()` (*in module volatility3.framework.contexts*), 138
`get_modules_by_symbol_tables()` (*ModuleCollection* method), 135
`get_modules_by_symbol_tables()` (*ModuleContainer* method), 155
`get_mount_points()` (*mnt_namespace* method), 359
`get_mountinfo()` (*MountInfo* class method), 603
`get_name()` (*CM_KEY_NODE* method), 513
`get_name()` (*CM_KEY_VALUE* method), 515
`get_name()` (*CMHIVE* method), 509
`get_name()` (*elf_linkmap* method), 400
`get_name()` (*elf_sym* method), 403
`get_name()` (*KMUTANT* method), 456
`get_name()` (*module* method), 361
`get_name()` (*RegistryHive* method), 239
`get_name()` (*SERVICE_RECORD* method), 523
`get_name()` (*unix_sock* method), 385
`get_name()` (*vm_area_struct* method), 390
`get_names_for_driver()` (*DriverScan* class method), 688
`get_nlk()` (*Cachedump* static method), 673
`get_node()` (*RegistryHive* method), 239
`get_nt_header()` (*IMAGE_DOS_HEADER* method), 494
`get_nthead_struct()` (*Info* class method), 707
`get_number_of_bytes()` (*POOL_TRACKER_BIG_PAGES* method), 507
`get_object()` (*POOL_HEADER* method), 502
`get_object()` (*POOL_HEADER_VISTA* method), 504
`get_object()` (*vm_map_entry* method), 432
`get_object_header()` (*DEVICE_OBJECT* method), 443
`get_object_header()` (*DRIVER_OBJECT* method), 445
`get_object_header()` (*EPROCESS* method), 448
`get_object_header()` (*ETHREAD* method), 450
`get_object_header()` (*ExecutiveObject* method), 498
`get_object_header()` (*FILE_OBJECT* method), 454
`get_object_header()` (*KMUTANT* method), 456
`get_object_header()` (*OBJECT_SYMBOLIC_LINK* method), 469
`get_object_type()` (*OBJECT_HEADER* method), 500
`get_offset()` (*vm_map_entry* method), 432
`get_osversion()` (*PsScan* class method), 746
`get_page_offset()` (*vm_area_struct* method), 390
`get_parent()` (*MMVAD* method), 464
`get_parent()` (*MMVAD_SHORT* method), 467
`get_parent_mount()` (*mount* method), 364
`get_partition_type()` (*PARTITION_ENTRY* method), 483

- `get_path()` (*vm_map_entry* method), 432
- `get_path_mnt()` (*LinuxUtilities* class method), 330
- `get_peb()` (*EPROCESS* method), 448
- `get_peer_under_root()` (*mount* method), 364
- `get_perms()` (*sysctl_oid* method), 430
- `get_perms()` (*vm_map_entry* method), 432
- `get_physical_layer_name()` (*KernelPDBScanner* method), 81
- `get_pid()` (*SERVICE_RECORD* method), 523
- `get_pool_header_table()` (*PoolScanner* class method), 738
- `get_pool_type()` (*POOL_TRACKER_BIG_PAGES* method), 507
- `get_portid()` (*netlink_sock* method), 368
- `get_prefix()` (*ABCKmsg* method), 587
- `get_prefix()` (*Kmsg_3_11_to_5_10* method), 590
- `get_prefix()` (*Kmsg_3_5_to_3_11* method), 592
- `get_prefix()` (*Kmsg_5_10_to_* method), 594
- `get_prefix()` (*Kmsg_pre_3_5* method), 595
- `get_private_memory()` (*MMVAD* method), 464
- `get_private_memory()` (*MMVAD_SHORT* method), 467
- `get_process_memory_sections()` (*proc* method), 420
- `get_process_memory_sections()` (*task_struct* method), 382
- `get_program_headers()` (*elf* method), 398
- `get_protection()` (*MMVAD* method), 464
- `get_protection()` (*MMVAD_SHORT* method), 467
- `get_protection()` (*vm_area_struct* method), 390
- `get_protocol()` (*bt_sock* method), 334
- `get_protocol()` (*inet_sock* method), 343
- `get_protocol()` (*netlink_sock* method), 369
- `get_protocol()` (*packet_sock* method), 370
- `get_protocol()` (*sock* method), 374
- `get_protocol()` (*unix_sock* method), 385
- `get_protocol()` (*vsock_sock* method), 392
- `get_protocol()` (*xdp_sock* method), 394
- `get_protocol_as_string()` (*socket* method), 428
- `get_pte()` (*CONTROL_AREA* method), 441
- `get_range_alias()` (*vm_map_entry* method), 432
- `get_record_tuple()` (*SvcScan* static method), 758
- `get_render_options()` (*CLIRenderer* method), 64
- `get_render_options()` (*CSVRenderer* method), 65
- `get_render_options()` (*JsonLinesRenderer* method), 65
- `get_render_options()` (*JsonRenderer* method), 66
- `get_render_options()` (*NoneRenderer* method), 66
- `get_render_options()` (*PrettyTextRenderer* method), 66
- `get_render_options()` (*QuickTextRenderer* method), 67
- `get_render_options()` (*Renderer* method), 174
- `get_requirements()` (*ADS* class method), 719
- `get_requirements()` (*AutomagicInterface* class method), 140
- `get_requirements()` (*AVMLLayer* class method), 187
- `get_requirements()` (*Banners* class method), 776
- `get_requirements()` (*Bash* class method), 568, 622
- `get_requirements()` (*BashIntermedSymbols* class method), 406
- `get_requirements()` (*BigPools* class method), 671
- `get_requirements()` (*BufferDataLayer* class method), 231
- `get_requirements()` (*Cachedump* class method), 673
- `get_requirements()` (*Callbacks* class method), 675
- `get_requirements()` (*Capabilities* class method), 569
- `get_requirements()` (*Check_afinfo* class method), 572
- `get_requirements()` (*Check_creds* class method), 574
- `get_requirements()` (*Check_idt* class method), 575
- `get_requirements()` (*Check_modules* class method), 577
- `get_requirements()` (*Check_syscall* class method), 578, 623
- `get_requirements()` (*Check_sysctl* class method), 625
- `get_requirements()` (*Check_trap_table* class method), 627
- `get_requirements()` (*CmdLine* class method), 678
- `get_requirements()` (*ComplexListRequirement* class method), 101
- `get_requirements()` (*ConfigurableInterface* class method), 143
- `get_requirements()` (*ConfigurableModule* class method), 128
- `get_requirements()` (*ConfigWriter* class method), 777
- `get_requirements()` (*ConstructionMagic* class method), 72
- `get_requirements()` (*Crashinfo* class method), 680
- `get_requirements()` (*DataLayerInterface* class method), 159
- `get_requirements()` (*DeviceTree* class method), 682
- `get_requirements()` (*DllList* class method), 684
- `get_requirements()` (*Dmesg* class method), 628
- `get_requirements()` (*DriverIrp* class method), 685
- `get_requirements()` (*DriverModule* class method), 687
- `get_requirements()` (*DriverScan* class method), 689
- `get_requirements()` (*DumpFiles* class method), 691
- `get_requirements()` (*Elf64Layer* class method), 196
- `get_requirements()` (*Elfs* class method), 580
- `get_requirements()` (*Envvars* class method), 582, 693
- `get_requirements()` (*FileLayer* class method), 233
- `get_requirements()` (*FileScan* class method), 694
- `get_requirements()` (*FrameworkInfo* class method), 779
- `get_requirements()` (*GetServiceSIDs* class method), 696
- `get_requirements()` (*GetSIDs* class method), 698

`get_requirements()` (*Handles class method*), 700
`get_requirements()` (*Hashdump class method*), 702
`get_requirements()` (*HiveList class method*), 663
`get_requirements()` (*HiveScan class method*), 666
`get_requirements()` (*IAT class method*), 705
`get_requirements()` (*Ifconfig class method*), 630
`get_requirements()` (*Info class method*), 707
`get_requirements()` (*Intel class method*), 200
`get_requirements()` (*Intel32e class method*), 203
`get_requirements()` (*IntelPAE class method*), 205
`get_requirements()` (*IntermediateSymbolTable class method*), 535
`get_requirements()` (*IOMem class method*), 584
`get_requirements()` (*IsfInfo class method*), 781
`get_requirements()` (*ISFormatTable class method*), 532
`get_requirements()` (*JobLinks class method*), 708
`get_requirements()` (*Kauth_listeners class method*), 632
`get_requirements()` (*Kauth_scopes class method*), 633
`get_requirements()` (*KernelModule class method*), 78
`get_requirements()` (*KernelPDBScanner class method*), 81
`get_requirements()` (*Kevents class method*), 635
`get_requirements()` (*Keyboard_notifiers class method*), 585
`get_requirements()` (*Kmsg class method*), 589
`get_requirements()` (*LayerListRequirement class method*), 104
`get_requirements()` (*LayerStacker class method*), 84
`get_requirements()` (*LayerWriter class method*), 782
`get_requirements()` (*LdrModules class method*), 710
`get_requirements()` (*LibraryList class method*), 597
`get_requirements()` (*LimeLayer class method*), 220
`get_requirements()` (*LinearlyMappedLayer class method*), 223
`get_requirements()` (*LinuxKernelIntermedSymbols class method*), 328
`get_requirements()` (*LinuxSymbolFinder class method*), 74
`get_requirements()` (*List_Files class method*), 637
`get_requirements()` (*Lsadbump class method*), 712
`get_requirements()` (*Lsmod class method*), 598, 639
`get_requirements()` (*Lsof class method*), 600, 640
`get_requirements()` (*MacKernelIntermedSymbols class method*), 409
`get_requirements()` (*MacSymbolFinder class method*), 77
`get_requirements()` (*Malfind class method*), 602, 642, 713
`get_requirements()` (*Maps class method*), 606, 647
`get_requirements()` (*MBRScan class method*), 716
`get_requirements()` (*Memmap class method*), 717
`get_requirements()` (*MFTScan class method*), 721
`get_requirements()` (*ModScan class method*), 723
`get_requirements()` (*Module class method*), 132
`get_requirements()` (*ModuleInterface class method*), 156
`get_requirements()` (*ModuleRequirement class method*), 108
`get_requirements()` (*Modules class method*), 725
`get_requirements()` (*Mount class method*), 644
`get_requirements()` (*MountInfo class method*), 604
`get_requirements()` (*MutantScan class method*), 727
`get_requirements()` (*NetScan class method*), 730
`get_requirements()` (*NetStat class method*), 733
`get_requirements()` (*Netstat class method*), 645
`get_requirements()` (*NonLinearlySegmentedLayer class method*), 244
`get_requirements()` (*Passphrase class method*), 764
`get_requirements()` (*PdbMSFStream class method*), 225
`get_requirements()` (*PdbMultiStreamFormat class method*), 228
`get_requirements()` (*PluginInterface class method*), 172
`get_requirements()` (*PoolScanner class method*), 738
`get_requirements()` (*PrintKey class method*), 668
`get_requirements()` (*Privs class method*), 741
`get_requirements()` (*PsAux class method*), 608
`get_requirements()` (*Psaux class method*), 650
`get_requirements()` (*PsList class method*), 610, 651, 744
`get_requirements()` (*PsScan class method*), 612, 747
`get_requirements()` (*PsTree class method*), 614, 655, 749
`get_requirements()` (*QemuSuspendLayer class method*), 236
`get_requirements()` (*RegistryHive class method*), 240
`get_requirements()` (*SegmentedLayer class method*), 246
`get_requirements()` (*Sessions class method*), 751
`get_requirements()` (*SizedModule class method*), 136
`get_requirements()` (*Skeleton_Key_Check class method*), 752
`get_requirements()` (*Socket_filters class method*), 656
`get_requirements()` (*Sockstat class method*), 616
`get_requirements()` (*SSDT class method*), 754
`get_requirements()` (*Strings class method*), 756
`get_requirements()` (*SvcScan class method*), 758
`get_requirements()` (*SymbolCacheMagic class method*), 90
`get_requirements()` (*SymbolFinder class method*), 92
`get_requirements()` (*SymbolTableInterface class method*), 183
`get_requirements()` (*SymlinkScan class method*), 760
`get_requirements()` (*ThrdScan class method*), 762

[get_requirements\(\)](#) (*Timeliner class method*), 786
[get_requirements\(\)](#) (*Timers class method*), 658
[get_requirements\(\)](#) (*TranslationLayerInterface class method*), 163
[get_requirements\(\)](#) (*Trustedbsd class method*), 659
[get_requirements\(\)](#) (*tty_check class method*), 618
[get_requirements\(\)](#) (*UserAssist class method*), 670
[get_requirements\(\)](#) (*VadInfo class method*), 766
[get_requirements\(\)](#) (*VadWalk class method*), 769
[get_requirements\(\)](#) (*VadYaraScan class method*), 770
[get_requirements\(\)](#) (*VerInfo class method*), 772
[get_requirements\(\)](#) (*Version1Format class method*), 538
[get_requirements\(\)](#) (*Version2Format class method*), 541
[get_requirements\(\)](#) (*Version3Format class method*), 544
[get_requirements\(\)](#) (*Version4Format class method*), 547
[get_requirements\(\)](#) (*Version5Format class method*), 550
[get_requirements\(\)](#) (*Version6Format class method*), 553
[get_requirements\(\)](#) (*Version7Format class method*), 556
[get_requirements\(\)](#) (*Version8Format class method*), 559
[get_requirements\(\)](#) (*VFSevents class method*), 661
[get_requirements\(\)](#) (*VirtMap class method*), 774
[get_requirements\(\)](#) (*VmaYaraScan class method*), 620
[get_requirements\(\)](#) (*VmwareLayer class method*), 249
[get_requirements\(\)](#) (*Volshell class method*), 54, 57, 60, 62
[get_requirements\(\)](#) (*WindowsCrashDump32Layer class method*), 190
[get_requirements\(\)](#) (*WindowsCrashDump64Layer class method*), 193
[get_requirements\(\)](#) (*WindowsIntel class method*), 208
[get_requirements\(\)](#) (*WindowsIntel32e class method*), 211
[get_requirements\(\)](#) (*WindowsIntelPAE class method*), 214
[get_requirements\(\)](#) (*WindowsKernelIntermedSymbols class method*), 438
[get_requirements\(\)](#) (*WindowsMixin class method*), 217
[get_requirements\(\)](#) (*WinSwapLayers class method*), 95
[get_requirements\(\)](#) (*XenCoreDumpLayer class method*), 252
[get_requirements\(\)](#) (*YaraScan class method*), 788
[get_resident_filecontent\(\)](#) (*MFTAttribute method*), 488
[get_resident_filename\(\)](#) (*MFTAttribute method*), 488
[get_right_child\(\)](#) (*MMVAD method*), 464
[get_right_child\(\)](#) (*MMVAD_SHORT method*), 467
[get_root_dentry\(\)](#) (*fs_struct method*), 341
[get_root_mnt\(\)](#) (*fs_struct method*), 342
[get_secret_by_name\(\)](#) (*Lsadump class method*), 712
[get_section_headers\(\)](#) (*elf method*), 398
[get_sections\(\)](#) (*IMAGE_NT_HEADERS method*), 496
[get_sections\(\)](#) (*module method*), 361
[get_session_id\(\)](#) (*EPROCESS method*), 448
[get_session_layers\(\)](#) (*ModScan class method*), 723
[get_session_layers\(\)](#) (*Modules class method*), 725
[get_sids\(\)](#) (*TOKEN method*), 473
[get_signature\(\)](#) (*MFTEntry method*), 490
[get_size\(\)](#) (*MMVAD method*), 464
[get_size\(\)](#) (*MMVAD_SHORT method*), 467
[get_size_from_index\(\)](#) (*PdbReader method*), 526
[get_size_in_sectors\(\)](#) (*PARTITION_ENTRY method*), 484
[get_slot_iter\(\)](#) (*maple_tree method*), 355
[get_special_path\(\)](#) (*vm_map_entry method*), 432
[get_src_addr\(\)](#) (*inet_sock method*), 343
[get_src_port\(\)](#) (*inet_sock method*), 343
[get_start\(\)](#) (*MMVAD method*), 464
[get_start\(\)](#) (*MMVAD_SHORT method*), 467
[get_starting_chs\(\)](#) (*PARTITION_ENTRY method*), 484
[get_starting_cylinder\(\)](#) (*PARTITION_ENTRY method*), 484
[get_starting_lba\(\)](#) (*PARTITION_ENTRY method*), 484
[get_starting_sector\(\)](#) (*PARTITION_ENTRY method*), 484
[get_state\(\)](#) (*bt_sock method*), 334
[get_state\(\)](#) (*inet_sock method*), 343
[get_state\(\)](#) (*KTHREAD method*), 460
[get_state\(\)](#) (*netlink_sock method*), 369
[get_state\(\)](#) (*packet_sock method*), 370
[get_state\(\)](#) (*sock method*), 374
[get_state\(\)](#) (*socket method*), 376, 428
[get_state\(\)](#) (*unix_sock method*), 385
[get_state\(\)](#) (*vsock_sock method*), 392
[get_state\(\)](#) (*xdp_sock method*), 394
[get_stream\(\)](#) (*PdbMultiStreamFormat method*), 228
[get_string\(\)](#) (*ABCKmsg method*), 587
[get_string\(\)](#) (*Kmsg_3_11_to_5_10 method*), 590
[get_string\(\)](#) (*Kmsg_3_5_to_3_11 method*), 592
[get_string\(\)](#) (*Kmsg_5_10_to_ method*), 594
[get_string\(\)](#) (*Kmsg_pre_3_5 method*), 595
[get_string\(\)](#) (*UNICODE_STRING method*), 475
[get_subkeys\(\)](#) (*CM_KEY_NODE method*), 513
[get_subsection\(\)](#) (*CONTROL_AREA method*), 441

`get_summary_header()` (*WindowsCrashDump32Layer method*), 190

`get_summary_header()` (*WindowsCrashDump64Layer method*), 193

`get_symbol()` (*BaseSymbolTableInterface method*), 177

`get_symbol()` (*BashIntermedSymbols method*), 406

`get_symbol()` (*ConfigurableModule method*), 128

`get_symbol()` (*IntermediateSymbolTable method*), 536

`get_symbol()` (*ISFormatTable method*), 532

`get_symbol()` (*LinuxKernelIntermedSymbols method*), 328

`get_symbol()` (*MacKernelIntermedSymbols method*), 410

`get_symbol()` (*Module method*), 133

`get_symbol()` (*module method*), 361

`get_symbol()` (*ModuleInterface method*), 156

`get_symbol()` (*NativeTable method*), 562

`get_symbol()` (*NativeTableInterface method*), 179

`get_symbol()` (*SizedModule method*), 136

`get_symbol()` (*SymbolSpace method*), 323

`get_symbol()` (*SymbolSpaceInterface method*), 181

`get_symbol()` (*SymbolTableInterface method*), 183

`get_symbol()` (*Version1Format method*), 538

`get_symbol()` (*Version2Format method*), 541

`get_symbol()` (*Version3Format method*), 544

`get_symbol()` (*Version4Format method*), 547

`get_symbol()` (*Version5Format method*), 550

`get_symbol()` (*Version6Format method*), 553

`get_symbol()` (*Version7Format method*), 556

`get_symbol()` (*Version8Format method*), 559

`get_symbol()` (*WindowsKernelIntermedSymbols method*), 438

`get_symbol_by_address()` (*module method*), 361

`get_symbol_table_name()` (*AggregateType method*), 255

`get_symbol_table_name()` (*Array method*), 257

`get_symbol_table_name()` (*BitField method*), 260

`get_symbol_table_name()` (*Boolean method*), 263

`get_symbol_table_name()` (*bpf_prog method*), 332

`get_symbol_table_name()` (*bt_sock method*), 334

`get_symbol_table_name()` (*Bytes method*), 266

`get_symbol_table_name()` (*Char method*), 271

`get_symbol_table_name()` (*ClassType method*), 274

`get_symbol_table_name()` (*CM_KEY_BODY method*), 511

`get_symbol_table_name()` (*CM_KEY_NODE method*), 513

`get_symbol_table_name()` (*CM_KEY_VALUE method*), 515

`get_symbol_table_name()` (*CMHIVE method*), 509

`get_symbol_table_name()` (*CONTROL_AREA method*), 441

`get_symbol_table_name()` (*cred method*), 336

`get_symbol_table_name()` (*dentry method*), 338

`get_symbol_table_name()` (*DEVICE_OBJECT method*), 443

`get_symbol_table_name()` (*DRIVER_OBJECT method*), 445

`get_symbol_table_name()` (*elf method*), 398

`get_symbol_table_name()` (*elf_linkmap method*), 400

`get_symbol_table_name()` (*elf_phdr method*), 402

`get_symbol_table_name()` (*elf_sym method*), 404

`get_symbol_table_name()` (*Enumeration method*), 277

`get_symbol_table_name()` (*EPROCESS method*), 448

`get_symbol_table_name()` (*ETHREAD method*), 450

`get_symbol_table_name()` (*EX_FAST_REF method*), 452

`get_symbol_table_name()` (*ExecutiveObject method*), 498

`get_symbol_table_name()` (*FILE_OBJECT method*), 454

`get_symbol_table_name()` (*fileglob method*), 413

`get_symbol_table_name()` (*files_struct method*), 340

`get_symbol_table_name()` (*Float method*), 280

`get_symbol_table_name()` (*fs_struct method*), 342

`get_symbol_table_name()` (*Function method*), 282

`get_symbol_table_name()` (*GenericIntelProcess method*), 325

`get_symbol_table_name()` (*hist_entry method*), 396

`get_symbol_table_name()` (*HMAP_ENTRY method*), 517

`get_symbol_table_name()` (*ifnet method*), 415

`get_symbol_table_name()` (*IMAGE_DOS_HEADER method*), 494

`get_symbol_table_name()` (*IMAGE_NT_HEADERS method*), 496

`get_symbol_table_name()` (*inet_sock method*), 343

`get_symbol_table_name()` (*inpcb method*), 417

`get_symbol_table_name()` (*Integer method*), 284

`get_symbol_table_name()` (*kauth_scope method*), 419

`get_symbol_table_name()` (*KDDEBUG-GER_DATA64 method*), 481

`get_symbol_table_name()` (*kernel_cap_struct method*), 346

`get_symbol_table_name()` (*kernel_cap_t method*), 349

`get_symbol_table_name()` (*KMUTANT method*), 456

`get_symbol_table_name()` (*kobject method*), 351

`get_symbol_table_name()` (*KSYSTEM_TIME method*), 458

`get_symbol_table_name()` (*KTHREAD method*), 460

`get_symbol_table_name()` (*LIST_ENTRY method*), 462

`get_symbol_table_name()` (*list_head method*), 352

`get_symbol_table_name()` (*maple_tree method*), 355

`get_symbol_table_name()` (*MFTAttribute method*), 488

`get_symbol_table_name()` (*MFTEntry method*), 490
`get_symbol_table_name()` (*MFTFileName method*), 492
`get_symbol_table_name()` (*mm_struct method*), 357
`get_symbol_table_name()` (*MMVAD method*), 464
`get_symbol_table_name()` (*MMVAD_SHORT method*), 467
`get_symbol_table_name()` (*mnt_namespace method*), 359
`get_symbol_table_name()` (*module method*), 361
`get_symbol_table_name()` (*mount method*), 364
`get_symbol_table_name()` (*net method*), 367
`get_symbol_table_name()` (*netlink_sock method*), 369
`get_symbol_table_name()` (*OBJECT_HEADER method*), 500
`get_symbol_table_name()` (*OBJECT_SYMBOLIC_LINK method*), 469
`get_symbol_table_name()` (*ObjectInterface method*), 167
`get_symbol_table_name()` (*packet_sock method*), 370
`get_symbol_table_name()` (*PARTITION_ENTRY method*), 484
`get_symbol_table_name()` (*PARTITION_TABLE method*), 486
`get_symbol_table_name()` (*Pointer method*), 288
`get_symbol_table_name()` (*POOL_HEADER method*), 503
`get_symbol_table_name()` (*POOL_HEADER_VISTA method*), 505
`get_symbol_table_name()` (*POOL_TRACKER_BIG_PAGES method*), 507
`get_symbol_table_name()` (*PrimitiveObject method*), 290
`get_symbol_table_name()` (*proc method*), 421
`get_symbol_table_name()` (*qstr method*), 372
`get_symbol_table_name()` (*queue_entry method*), 422
`get_symbol_table_name()` (*SERVICE_HEADER method*), 521
`get_symbol_table_name()` (*SERVICE_RECORD method*), 524
`get_symbol_table_name()` (*SHARED_CACHE_MAP method*), 471
`get_symbol_table_name()` (*sock method*), 374
`get_symbol_table_name()` (*sockaddr method*), 424
`get_symbol_table_name()` (*sockaddr_dl method*), 426
`get_symbol_table_name()` (*socket method*), 376, 428
`get_symbol_table_name()` (*String method*), 293
`get_symbol_table_name()` (*struct_file method*), 378
`get_symbol_table_name()` (*StructType method*), 298
`get_symbol_table_name()` (*SUMMARY_DUMP method*), 479
`get_symbol_table_name()` (*super_block method*), 380
`get_symbol_table_name()` (*sysctl_oid method*), 430
`get_symbol_table_name()` (*task_struct method*), 382
`get_symbol_table_name()` (*TOKEN method*), 474
`get_symbol_table_name()` (*UNICODE_STRING method*), 476
`get_symbol_table_name()` (*UnionType method*), 300
`get_symbol_table_name()` (*unix_sock method*), 385
`get_symbol_table_name()` (*VACB method*), 477
`get_symbol_table_name()` (*vfsmount method*), 387
`get_symbol_table_name()` (*vm_area_struct method*), 390
`get_symbol_table_name()` (*vm_map_entry method*), 432
`get_symbol_table_name()` (*vm_map_object method*), 434
`get_symbol_table_name()` (*vnode method*), 436
`get_symbol_table_name()` (*Void method*), 302
`get_symbol_table_name()` (*vsock_sock method*), 392
`get_symbol_table_name()` (*xdp_sock method*), 394
`get_symbol_type()` (*BaseSymbolTableInterface method*), 177
`get_symbol_type()` (*BashIntermedSymbols method*), 406
`get_symbol_type()` (*IntermediateSymbolTable method*), 536
`get_symbol_type()` (*ISFormatTable method*), 532
`get_symbol_type()` (*LinuxKernelIntermedSymbols method*), 328
`get_symbol_type()` (*MacKernelIntermedSymbols method*), 410
`get_symbol_type()` (*NativeTable method*), 563
`get_symbol_type()` (*NativeTableInterface method*), 179
`get_symbol_type()` (*SymbolTableInterface method*), 183
`get_symbol_type()` (*Version1Format method*), 538
`get_symbol_type()` (*Version2Format method*), 541
`get_symbol_type()` (*Version3Format method*), 544
`get_symbol_type()` (*Version4Format method*), 547
`get_symbol_type()` (*Version5Format method*), 550
`get_symbol_type()` (*Version6Format method*), 553
`get_symbol_type()` (*Version7Format method*), 556
`get_symbol_type()` (*Version8Format method*), 559
`get_symbol_type()` (*WindowsKernelIntermedSymbols method*), 438
`get_symbols()` (*elf method*), 398
`get_symbols()` (*module method*), 361
`get_symbols_by_absolute_location()` (*ConfigurableModule method*), 128
`get_symbols_by_absolute_location()` (*Module method*), 133
`get_symbols_by_absolute_location()` (*ModuleInterface method*), 156
`get_symbols_by_absolute_location()` (*SizedModule method*), 136

`get_symbols_by_location()` (*BaseSymbolTableInterface* method), 177

`get_symbols_by_location()` (*BashIntermedSymbols* method), 406

`get_symbols_by_location()` (*IntermediateSymbolTable* method), 536

`get_symbols_by_location()` (*ISFormatTable* method), 532

`get_symbols_by_location()` (*LinuxKernelIntermedSymbols* method), 328

`get_symbols_by_location()` (*MacKernelIntermedSymbols* method), 410

`get_symbols_by_location()` (*NativeTable* method), 563

`get_symbols_by_location()` (*NativeTableInterface* method), 179

`get_symbols_by_location()` (*SymbolSpace* method), 323

`get_symbols_by_location()` (*SymbolSpaceInterface* method), 181

`get_symbols_by_location()` (*SymbolTableInterface* method), 183

`get_symbols_by_location()` (*Version1Format* method), 538

`get_symbols_by_location()` (*Version2Format* method), 541

`get_symbols_by_location()` (*Version3Format* method), 544

`get_symbols_by_location()` (*Version4Format* method), 548

`get_symbols_by_location()` (*Version5Format* method), 551

`get_symbols_by_location()` (*Version6Format* method), 554

`get_symbols_by_location()` (*Version7Format* method), 557

`get_symbols_by_location()` (*Version8Format* method), 560

`get_symbols_by_location()` (*WindowsKernelIntermedSymbols* method), 439

`get_symbols_by_type()` (*BaseSymbolTableInterface* method), 177

`get_symbols_by_type()` (*BashIntermedSymbols* method), 407

`get_symbols_by_type()` (*IntermediateSymbolTable* method), 536

`get_symbols_by_type()` (*ISFormatTable* method), 532

`get_symbols_by_type()` (*LinuxKernelIntermedSymbols* method), 328

`get_symbols_by_type()` (*MacKernelIntermedSymbols* method), 410

`get_symbols_by_type()` (*NativeTable* method), 563

`get_symbols_by_type()` (*NativeTableInterface* method), 179

`get_symbols_by_type()` (*SymbolSpace* method), 323

`get_symbols_by_type()` (*SymbolSpaceInterface* method), 181

`get_symbols_by_type()` (*SymbolTableInterface* method), 183

`get_symbols_by_type()` (*Version1Format* method), 539

`get_symbols_by_type()` (*Version2Format* method), 542

`get_symbols_by_type()` (*Version3Format* method), 545

`get_symbols_by_type()` (*Version4Format* method), 548

`get_symbols_by_type()` (*Version5Format* method), 551

`get_symbols_by_type()` (*Version6Format* method), 554

`get_symbols_by_type()` (*Version7Format* method), 557

`get_symbols_by_type()` (*Version8Format* method), 560

`get_symbols_by_type()` (*WindowsKernelIntermedSymbols* method), 439

`get_symbols_names_and_addresses()` (*module* method), 361

`get_tag()` (*MMVAD* method), 465

`get_tag()` (*MMVAD_SHORT* method), 467

`get_task()` (*proc* method), 421

`get_task_capabilities()` (*Capabilities* class method), 570

`get_task_fields()` (*PsList* class method), 610

`get_tasks_capabilities()` (*Capabilities* class method), 570

`get_tcp_state()` (*inpcb* method), 417

`get_tcpip_module()` (*NetStat* class method), 733

`get_text_from_data_ring()` (*Kmsg_5_10_to_* method), 594

`get_text_from_log()` (*Kmsg_3_11_to_5_10* method), 590

`get_text_from_log()` (*Kmsg_3_5_to_3_11* method), 592

`get_threads()` (*task_struct* method), 382

`get_time()` (*KSYSTEM_TIME* method), 458

`get_time_as_integer()` (*hist_entry* method), 396

`get_time_object()` (*hist_entry* method), 396

`get_timestamp_in_sec_str()` (*ABCKmsg* method), 587

`get_timestamp_in_sec_str()` (*Kmsg_3_11_to_5_10* method), 590

`get_timestamp_in_sec_str()` (*Kmsg_3_5_to_3_11* method), 592

`get_timestamp_in_sec_str()` (*Kmsg_5_10_to_* method), 594

`get_timestamp_in_sec_str()` (*Kmsg_pre_3_5*

- method), 595
- get_type() (*BaseSymbolTableInterface* method), 177
- get_type() (*BashIntermedSymbols* method), 407
- get_type() (*bpf_prog* method), 332
- get_type() (*ConfigurableModule* method), 128
- get_type() (*IntermediateSymbolTable* method), 536
- get_type() (*ISFormatTable* method), 532
- get_type() (*LinuxKernelIntermedSymbols* method), 328
- get_type() (*MacKernelIntermedSymbols* method), 410
- get_type() (*Module* method), 133
- get_type() (*ModuleInterface* method), 156
- get_type() (*NativeTable* method), 563
- get_type() (*NativeTableInterface* method), 179
- get_type() (*SERVICE_RECORD* method), 524
- get_type() (*SizedModule* method), 136
- get_type() (*sock* method), 374
- get_type() (*super_block* method), 380
- get_type() (*SymbolSpace* method), 323
- get_type() (*SymbolSpaceInterface* method), 181
- get_type() (*SymbolTableInterface* method), 183
- get_type() (*Version1Format* method), 539
- get_type() (*Version2Format* method), 542
- get_type() (*Version3Format* method), 545
- get_type() (*Version4Format* method), 548
- get_type() (*Version5Format* method), 551
- get_type() (*Version6Format* method), 554
- get_type() (*Version7Format* method), 557
- get_type() (*Version8Format* method), 560
- get_type() (*WindowsKernelIntermedSymbols* method), 439
- get_type_class() (*BaseSymbolTableInterface* method), 177
- get_type_class() (*BashIntermedSymbols* method), 407
- get_type_class() (*IntermediateSymbolTable* method), 536
- get_type_class() (*ISFormatTable* method), 532
- get_type_class() (*LinuxKernelIntermedSymbols* method), 328
- get_type_class() (*MacKernelIntermedSymbols* method), 410
- get_type_class() (*NativeTable* method), 563
- get_type_class() (*NativeTableInterface* method), 179
- get_type_class() (*SymbolTableInterface* method), 183
- get_type_class() (*Version1Format* method), 539
- get_type_class() (*Version2Format* method), 542
- get_type_class() (*Version3Format* method), 545
- get_type_class() (*Version4Format* method), 548
- get_type_class() (*Version5Format* method), 551
- get_type_class() (*Version6Format* method), 554
- get_type_class() (*Version7Format* method), 557
- get_type_class() (*Version8Format* method), 560
- get_type_class() (*WindowsKernelIntermedSymbols* method), 439
- get_type_from_index() (*PdbReader* method), 526
- get_type_map() (*Handles* class method), 700
- get_usable_plugins() (*Timeliner* class method), 786
- get_user_hashes() (*Hashdump* class method), 702
- get_user_keys() (*Hashdump* class method), 702
- get_user_name() (*Hashdump* class method), 702
- get_vad_maps() (*VadYaraScan* static method), 770
- get_vad_root() (*EPROCESS* method), 448
- get_vaddr() (*elf_phdr* method), 402
- get_values() (*CM_KEY_NODE* method), 513
- get_version_information() (*VerInfo* class method), 772
- get_version_structure() (*Info* class method), 707
- get_vfsmnt() (*struct_file* method), 378
- get_vfsmnt_current() (*mount* method), 364
- get_vfsmnt_current() (*vfsmount* method), 387
- get_vfsmnt_parent() (*mount* method), 365
- get_vfsmnt_parent() (*vfsmount* method), 387
- get_vma_iter() (*mm_struct* method), 357
- get_vma_maps() (*VmaYaraScan* static method), 620
- get_vnode() (*vm_map_entry* method), 432
- get_volatile() (*CM_KEY_NODE* method), 514
- get_wait_reason() (*KTHREAD* method), 460
- get_wow_64_process() (*EPROCESS* method), 448
- get_yarascan_option_requirements() (*YaraScan* class method), 788
- getbuffer() (*NullFileHandler* method), 51
- GetServiceSIDs (class in *volatility3.plugins.windows.getservicesids*), 696
- GetSIDs (class in *volatility3.plugins.windows.getsids*), 697
- getter() (*classproperty* method), 47
- getvalue() (*NullFileHandler* method), 51
- group_structure (*VmwareLayer* attribute), 249
- ## H
- handler_order (*JarHandler* attribute), 242
- handler_order (*OfflineHandler* attribute), 242
- handler_order (*VolatilityHandler* attribute), 243
- Handles (class in *volatility3.plugins.windows.handles*), 699
- handles() (*Handles* method), 700
- has_capability() (*kernel_cap_struct* method), 346
- has_capability() (*kernel_cap_t* method), 349
- has_enumeration() (*ConfigurableModule* method), 128
- has_enumeration() (*Module* method), 133
- has_enumeration() (*ModuleInterface* method), 156
- has_enumeration() (*SizedModule* method), 136
- has_enumeration() (*SymbolSpace* method), 323
- has_enumeration() (*SymbolSpaceInterface* method), 181

`has_member()` (*AggregateType* method), 255
`has_member()` (*AggregateType.VolTemplateProxy* class method), 255
`has_member()` (*Array* method), 257
`has_member()` (*Array.VolTemplateProxy* class method), 256
`has_member()` (*BitField* method), 260
`has_member()` (*BitField.VolTemplateProxy* class method), 258
`has_member()` (*Boolean* method), 263
`has_member()` (*Boolean.VolTemplateProxy* class method), 261
`has_member()` (*bpf_prog* method), 332
`has_member()` (*bpf_prog.VolTemplateProxy* class method), 332
`has_member()` (*bt_sock* method), 334
`has_member()` (*bt_sock.VolTemplateProxy* class method), 333
`has_member()` (*Bytes* method), 266
`has_member()` (*Bytes.VolTemplateProxy* class method), 264
`has_member()` (*Char* method), 272
`has_member()` (*Char.VolTemplateProxy* class method), 270
`has_member()` (*ClassType* method), 274
`has_member()` (*ClassType.VolTemplateProxy* class method), 273
`has_member()` (*CM_KEY_BODY* method), 511
`has_member()` (*CM_KEY_BODY.VolTemplateProxy* class method), 511
`has_member()` (*CM_KEY_NODE* method), 514
`has_member()` (*CM_KEY_NODE.VolTemplateProxy* class method), 512
`has_member()` (*CM_KEY_VALUE* method), 516
`has_member()` (*CM_KEY_VALUE.VolTemplateProxy* class method), 515
`has_member()` (*CMHIVE* method), 509
`has_member()` (*CMHIVE.VolTemplateProxy* class method), 509
`has_member()` (*CONTROL_AREA* method), 441
`has_member()` (*CONTROL_AREA.VolTemplateProxy* class method), 440
`has_member()` (*cred* method), 336
`has_member()` (*cred.VolTemplateProxy* class method), 335
`has_member()` (*dentry* method), 338
`has_member()` (*dentry.VolTemplateProxy* class method), 337
`has_member()` (*DEVICE_OBJECT* method), 444
`has_member()` (*DEVICE_OBJECT.VolTemplateProxy* class method), 443
`has_member()` (*DRIVER_OBJECT* method), 446
`has_member()` (*DRIVER_OBJECT.VolTemplateProxy* class method), 445
`has_member()` (*elf* method), 398
`has_member()` (*elf.VolTemplateProxy* class method), 397
`has_member()` (*elf_linkmap* method), 400
`has_member()` (*elf_linkmap.VolTemplateProxy* class method), 399
`has_member()` (*elf_phdr* method), 402
`has_member()` (*elf_phdr.VolTemplateProxy* class method), 401
`has_member()` (*elf_sym* method), 404
`has_member()` (*elf_sym.VolTemplateProxy* class method), 403
`has_member()` (*Enumeration* method), 277
`has_member()` (*Enumeration.VolTemplateProxy* class method), 275
`has_member()` (*EPROCESS* method), 448
`has_member()` (*EPROCESS.VolTemplateProxy* class method), 447
`has_member()` (*ETHREAD* method), 450
`has_member()` (*ETHREAD.VolTemplateProxy* class method), 449
`has_member()` (*EX_FAST_REF* method), 452
`has_member()` (*EX_FAST_REF.VolTemplateProxy* class method), 452
`has_member()` (*ExecutiveObject* method), 499
`has_member()` (*ExecutiveObject.VolTemplateProxy* class method), 498
`has_member()` (*FILE_OBJECT* method), 454
`has_member()` (*FILE_OBJECT.VolTemplateProxy* class method), 454
`has_member()` (*fileglob* method), 413
`has_member()` (*fileglob.VolTemplateProxy* class method), 413
`has_member()` (*files_struct* method), 340
`has_member()` (*files_struct.VolTemplateProxy* class method), 339
`has_member()` (*Float* method), 280
`has_member()` (*Float.VolTemplateProxy* class method), 279
`has_member()` (*fs_struct* method), 342
`has_member()` (*fs_struct.VolTemplateProxy* class method), 341
`has_member()` (*Function* method), 282
`has_member()` (*Function.VolTemplateProxy* class method), 281
`has_member()` (*GenericIntelProcess* method), 325
`has_member()` (*GenericIntelProcess.VolTemplateProxy* class method), 325
`has_member()` (*hist_entry* method), 396
`has_member()` (*hist_entry.VolTemplateProxy* class method), 395
`has_member()` (*HMAP_ENTRY* method), 517
`has_member()` (*HMAP_ENTRY.VolTemplateProxy* class method), 517
`has_member()` (*ifnet* method), 415

- has_member() (*ifnet.VolTemplateProxy* class method), 414
- has_member() (*IMAGE_DOS_HEADER* method), 494
- has_member() (*IMAGE_DOS_HEADER.VolTemplateProxy* class method), 493
- has_member() (*IMAGE_NT_HEADERS* method), 497
- has_member() (*IMAGE_NT_HEADERS.VolTemplateProxy* class method), 496
- has_member() (*inet_sock* method), 344
- has_member() (*inet_sock.VolTemplateProxy* class method), 343
- has_member() (*inpcb* method), 417
- has_member() (*inpcb.VolTemplateProxy* class method), 416
- has_member() (*Integer* method), 285
- has_member() (*Integer.VolTemplateProxy* class method), 283
- has_member() (*kauth_scope* method), 419
- has_member() (*kauth_scope.VolTemplateProxy* class method), 418
- has_member() (*KDDEBUGGER_DATA64* method), 481
- has_member() (*KDDEBUGGER_DATA64.VolTemplateProxy* class method), 481
- has_member() (*kernel_cap_struct* method), 346
- has_member() (*kernel_cap_struct.VolTemplateProxy* class method), 345
- has_member() (*kernel_cap_t* method), 349
- has_member() (*kernel_cap_t.VolTemplateProxy* class method), 347
- has_member() (*KMUTANT* method), 456
- has_member() (*KMUTANT.VolTemplateProxy* class method), 456
- has_member() (*kobject* method), 351
- has_member() (*kobject.VolTemplateProxy* class method), 350
- has_member() (*KSYSTEM_TIME* method), 458
- has_member() (*KSYSTEM_TIME.VolTemplateProxy* class method), 458
- has_member() (*KTHREAD* method), 460
- has_member() (*KTHREAD.VolTemplateProxy* class method), 459
- has_member() (*LIST_ENTRY* method), 462
- has_member() (*LIST_ENTRY.VolTemplateProxy* class method), 461
- has_member() (*list_head* method), 353
- has_member() (*list_head.VolTemplateProxy* class method), 352
- has_member() (*maple_tree* method), 355
- has_member() (*maple_tree.VolTemplateProxy* class method), 354
- has_member() (*MFTAttribute* method), 488
- has_member() (*MFTAttribute.VolTemplateProxy* class method), 487
- has_member() (*MFTEntry* method), 490
- has_member() (*MFTEntry.VolTemplateProxy* class method), 489
- has_member() (*MFTFileName* method), 492
- has_member() (*MFTFileName.VolTemplateProxy* class method), 491
- has_member() (*mm_struct* method), 357
- has_member() (*mm_struct.VolTemplateProxy* class method), 356
- has_member() (*MMVAD* method), 465
- has_member() (*MMVAD.VolTemplateProxy* class method), 463
- has_member() (*MMVAD_SHORT* method), 467
- has_member() (*MMVAD_SHORT.VolTemplateProxy* class method), 466
- has_member() (*mnt_namespace* method), 359
- has_member() (*mnt_namespace.VolTemplateProxy* class method), 358
- has_member() (*module* method), 361
- has_member() (*module.VolTemplateProxy* class method), 360
- has_member() (*mount* method), 365
- has_member() (*mount.VolTemplateProxy* class method), 363
- has_member() (*net* method), 367
- has_member() (*net.VolTemplateProxy* class method), 366
- has_member() (*netlink_sock* method), 369
- has_member() (*netlink_sock.VolTemplateProxy* class method), 368
- has_member() (*OBJECT_HEADER* method), 500
- has_member() (*OBJECT_HEADER.VolTemplateProxy* class method), 500
- has_member() (*OBJECT_SYMBOLIC_LINK* method), 469
- has_member() (*OBJECT_SYMBOLIC_LINK.VolTemplateProxy* class method), 468
- has_member() (*ObjectInterface* method), 167
- has_member() (*ObjectInterface.VolTemplateProxy* class method), 166
- has_member() (*ObjectTemplate* method), 303
- has_member() (*packet_sock* method), 371
- has_member() (*packet_sock.VolTemplateProxy* class method), 370
- has_member() (*PARTITION_ENTRY* method), 484
- has_member() (*PARTITION_ENTRY.VolTemplateProxy* class method), 483
- has_member() (*PARTITION_TABLE* method), 486
- has_member() (*PARTITION_TABLE.VolTemplateProxy* class method), 485
- has_member() (*Pointer* method), 288
- has_member() (*Pointer.VolTemplateProxy* class method), 286
- has_member() (*POOL_HEADER* method), 503

`has_member()` (*POOL_HEADER.VolTemplateProxy class method*), 479
`has_member()` (*POOL_HEADER_VISTA method*), 505
`has_member()` (*POOL_HEADER_VISTA.VolTemplateProxy class method*), 504
`has_member()` (*POOL_TRACKER_BIG_PAGES method*), 507
`has_member()` (*POOL_TRACKER_BIG_PAGES.VolTemplateProxy class method*), 506
`has_member()` (*PrimitiveObject method*), 290
`has_member()` (*PrimitiveObject.VolTemplateProxy class method*), 289
`has_member()` (*proc method*), 421
`has_member()` (*proc.VolTemplateProxy class method*), 420
`has_member()` (*qstr method*), 372
`has_member()` (*qstr.VolTemplateProxy class method*), 372
`has_member()` (*queue_entry method*), 422
`has_member()` (*queue_entry.VolTemplateProxy class method*), 422
`has_member()` (*ReferenceTemplate method*), 304
`has_member()` (*SERVICE_HEADER method*), 521
`has_member()` (*SERVICE_HEADER.VolTemplateProxy class method*), 521
`has_member()` (*SERVICE_RECORD method*), 524
`has_member()` (*SERVICE_RECORD.VolTemplateProxy class method*), 523
`has_member()` (*SHARED_CACHE_MAP method*), 471
`has_member()` (*SHARED_CACHE_MAP.VolTemplateProxy class method*), 471
`has_member()` (*sock method*), 374
`has_member()` (*sock.VolTemplateProxy class method*), 373
`has_member()` (*sockaddr method*), 425
`has_member()` (*sockaddr.VolTemplateProxy class method*), 424
`has_member()` (*sockaddr_dl method*), 426
`has_member()` (*sockaddr_dl.VolTemplateProxy class method*), 426
`has_member()` (*socket method*), 376, 428
`has_member()` (*socket.VolTemplateProxy class method*), 375, 427
`has_member()` (*String method*), 293
`has_member()` (*String.VolTemplateProxy class method*), 291
`has_member()` (*struct_file method*), 378
`has_member()` (*struct_file.VolTemplateProxy class method*), 377
`has_member()` (*StructType method*), 298
`has_member()` (*StructType.VolTemplateProxy class method*), 298
`has_member()` (*SUMMARY_DUMP method*), 480
`has_member()` (*SUMMARY_DUMP.VolTemplateProxy class method*), 479
`has_member()` (*super_block method*), 380
`has_member()` (*super_block.VolTemplateProxy class method*), 380
`has_member()` (*SymbolSpace.UnresolvedTemplate method*), 322
`has_member()` (*sysctl_oid method*), 430
`has_member()` (*sysctl_oid.VolTemplateProxy class method*), 429
`has_member()` (*task_struct method*), 383
`has_member()` (*task_struct.VolTemplateProxy class method*), 382
`has_member()` (*Template method*), 169
`has_member()` (*TOKEN method*), 474
`has_member()` (*TOKEN.VolTemplateProxy class method*), 473
`has_member()` (*UNICODE_STRING method*), 476
`has_member()` (*UNICODE_STRING.VolTemplateProxy class method*), 475
`has_member()` (*UnionType method*), 300
`has_member()` (*UnionType.VolTemplateProxy class method*), 299
`has_member()` (*unix_sock method*), 385
`has_member()` (*unix_sock.VolTemplateProxy class method*), 384
`has_member()` (*VACB method*), 478
`has_member()` (*VACB.VolTemplateProxy class method*), 477
`has_member()` (*vfsmount method*), 388
`has_member()` (*vfsmount.VolTemplateProxy class method*), 386
`has_member()` (*vm_area_struct method*), 391
`has_member()` (*vm_area_struct.VolTemplateProxy class method*), 389
`has_member()` (*vm_map_entry method*), 432
`has_member()` (*vm_map_entry.VolTemplateProxy class method*), 432
`has_member()` (*vm_map_object method*), 434
`has_member()` (*vm_map_object.VolTemplateProxy class method*), 434
`has_member()` (*vnode method*), 436
`has_member()` (*vnode.VolTemplateProxy class method*), 435
`has_member()` (*Void method*), 302
`has_member()` (*Void.VolTemplateProxy class method*), 301
`has_member()` (*vsock_sock method*), 392
`has_member()` (*vsock_sock.VolTemplateProxy class method*), 392
`has_member()` (*xdp_sock method*), 394
`has_member()` (*xdp_sock.VolTemplateProxy class method*), 393
`has_parent()` (*mount method*), 365
`has_parent()` (*vfsmount method*), 388

- `has_symbol()` (*ConfigurableModule* method), 128
- `has_symbol()` (*Module* method), 133
- `has_symbol()` (*ModuleInterface* method), 156
- `has_symbol()` (*SizedModule* method), 137
- `has_symbol()` (*SymbolSpace* method), 323
- `has_symbol()` (*SymbolSpaceInterface* method), 181
- `has_type()` (*ConfigurableModule* method), 129
- `has_type()` (*Module* method), 133
- `has_type()` (*ModuleInterface* method), 156
- `has_type()` (*SizedModule* method), 137
- `has_type()` (*SymbolSpace* method), 323
- `has_type()` (*SymbolSpaceInterface* method), 182
- `has_valid_member()` (*AggregateType* method), 255
- `has_valid_member()` (*Array* method), 257
- `has_valid_member()` (*BitField* method), 260
- `has_valid_member()` (*Boolean* method), 263
- `has_valid_member()` (*bpf_prog* method), 333
- `has_valid_member()` (*bt_sock* method), 334
- `has_valid_member()` (*Bytes* method), 266
- `has_valid_member()` (*Char* method), 272
- `has_valid_member()` (*ClassType* method), 274
- `has_valid_member()` (*CM_KEY_BODY* method), 511
- `has_valid_member()` (*CM_KEY_NODE* method), 514
- `has_valid_member()` (*CM_KEY_VALUE* method), 516
- `has_valid_member()` (*CMHIVE* method), 509
- `has_valid_member()` (*CONTROL_AREA* method), 442
- `has_valid_member()` (*cred* method), 336
- `has_valid_member()` (*dentry* method), 338
- `has_valid_member()` (*DEVICE_OBJECT* method), 444
- `has_valid_member()` (*DRIVER_OBJECT* method), 446
- `has_valid_member()` (*elf* method), 398
- `has_valid_member()` (*elf_linkmap* method), 400
- `has_valid_member()` (*elf_phdr* method), 402
- `has_valid_member()` (*elf_sym* method), 404
- `has_valid_member()` (*Enumeration* method), 277
- `has_valid_member()` (*EPROCESS* method), 448
- `has_valid_member()` (*ETHREAD* method), 450
- `has_valid_member()` (*EX_FAST_REF* method), 453
- `has_valid_member()` (*ExecutiveObject* method), 499
- `has_valid_member()` (*FILE_OBJECT* method), 455
- `has_valid_member()` (*fileglob* method), 413
- `has_valid_member()` (*files_struct* method), 340
- `has_valid_member()` (*Float* method), 280
- `has_valid_member()` (*fs_struct* method), 342
- `has_valid_member()` (*Function* method), 282
- `has_valid_member()` (*GenericIntelProcess* method), 325
- `has_valid_member()` (*hist_entry* method), 396
- `has_valid_member()` (*HMAP_ENTRY* method), 517
- `has_valid_member()` (*ifnet* method), 415
- `has_valid_member()` (*IMAGE_DOS_HEADER* method), 494
- `has_valid_member()` (*IMAGE_NT_HEADERS* method), 497
- `has_valid_member()` (*inet_sock* method), 344
- `has_valid_member()` (*inpcb* method), 417
- `has_valid_member()` (*Integer* method), 285
- `has_valid_member()` (*kauth_scope* method), 419
- `has_valid_member()` (*KDDEBUGGER_DATA64* method), 482
- `has_valid_member()` (*kernel_cap_struct* method), 346
- `has_valid_member()` (*kernel_cap_t* method), 349
- `has_valid_member()` (*KMUTANT* method), 457
- `has_valid_member()` (*kobject* method), 351
- `has_valid_member()` (*KSYSTEM_TIME* method), 458
- `has_valid_member()` (*KTHREAD* method), 460
- `has_valid_member()` (*LIST_ENTRY* method), 462
- `has_valid_member()` (*list_head* method), 353
- `has_valid_member()` (*maple_tree* method), 355
- `has_valid_member()` (*MFTAttribute* method), 488
- `has_valid_member()` (*MFTEntry* method), 490
- `has_valid_member()` (*MFTFileName* method), 492
- `has_valid_member()` (*mm_struct* method), 357
- `has_valid_member()` (*MMVAD* method), 465
- `has_valid_member()` (*MMVAD_SHORT* method), 467
- `has_valid_member()` (*mnt_namespace* method), 359
- `has_valid_member()` (*module* method), 361
- `has_valid_member()` (*mount* method), 365
- `has_valid_member()` (*net* method), 367
- `has_valid_member()` (*netlink_sock* method), 369
- `has_valid_member()` (*OBJECT_HEADER* method), 501
- `has_valid_member()` (*OBJECT_SYMBOLIC_LINK* method), 469
- `has_valid_member()` (*ObjectInterface* method), 167
- `has_valid_member()` (*packet_sock* method), 371
- `has_valid_member()` (*PARTITION_ENTRY* method), 484
- `has_valid_member()` (*PARTITION_TABLE* method), 486
- `has_valid_member()` (*Pointer* method), 288
- `has_valid_member()` (*POOL_HEADER* method), 503
- `has_valid_member()` (*POOL_HEADER_VISTA* method), 505
- `has_valid_member()` (*POOL_TRACKER_BIG_PAGES* method), 507
- `has_valid_member()` (*PrimitiveObject* method), 290
- `has_valid_member()` (*proc* method), 421
- `has_valid_member()` (*qstr* method), 372
- `has_valid_member()` (*queue_entry* method), 423
- `has_valid_member()` (*SERVICE_HEADER* method), 522
- `has_valid_member()` (*SERVICE_RECORD* method), 524
- `has_valid_member()` (*SHARED_CACHE_MAP* method), 472

`has_valid_member()` (*sock method*), 374
`has_valid_member()` (*sockaddr method*), 425
`has_valid_member()` (*sockaddr_dl method*), 426
`has_valid_member()` (*socket method*), 376, 428
`has_valid_member()` (*String method*), 293
`has_valid_member()` (*struct_file method*), 378
`has_valid_member()` (*StructType method*), 298
`has_valid_member()` (*SUMMARY_DUMP method*), 480
`has_valid_member()` (*super_block method*), 381
`has_valid_member()` (*sysctl_oid method*), 431
`has_valid_member()` (*task_struct method*), 383
`has_valid_member()` (*TOKEN method*), 474
`has_valid_member()` (*UNICODE_STRING method*), 476
`has_valid_member()` (*UnionType method*), 300
`has_valid_member()` (*unix_sock method*), 385
`has_valid_member()` (*VACB method*), 478
`has_valid_member()` (*vfsmount method*), 388
`has_valid_member()` (*vm_area_struct method*), 391
`has_valid_member()` (*vm_map_entry method*), 433
`has_valid_member()` (*vm_map_object method*), 434
`has_valid_member()` (*vnode method*), 436
`has_valid_member()` (*Void method*), 302
`has_valid_member()` (*vsock_sock method*), 392
`has_valid_member()` (*xdp_sock method*), 394
`has_valid_members()` (*AggregateType method*), 255
`has_valid_members()` (*Array method*), 257
`has_valid_members()` (*BitField method*), 260
`has_valid_members()` (*Boolean method*), 263
`has_valid_members()` (*bpf_prog method*), 333
`has_valid_members()` (*bt_sock method*), 334
`has_valid_members()` (*Bytes method*), 266
`has_valid_members()` (*Char method*), 272
`has_valid_members()` (*ClassType method*), 274
`has_valid_members()` (*CM_KEY_BODY method*), 512
`has_valid_members()` (*CM_KEY_NODE method*), 514
`has_valid_members()` (*CM_KEY_VALUE method*), 516
`has_valid_members()` (*CMHIVE method*), 510
`has_valid_members()` (*CONTROL_AREA method*), 442
`has_valid_members()` (*cred method*), 336
`has_valid_members()` (*dentry method*), 338
`has_valid_members()` (*DEVICE_OBJECT method*), 444
`has_valid_members()` (*DRIVER_OBJECT method*), 446
`has_valid_members()` (*elf method*), 398
`has_valid_members()` (*elf_linkmap method*), 400
`has_valid_members()` (*elf_phdr method*), 402
`has_valid_members()` (*elf_sym method*), 404
`has_valid_members()` (*Enumeration method*), 277
`has_valid_members()` (*EPROCESS method*), 448
`has_valid_members()` (*ETHREAD method*), 451
`has_valid_members()` (*EX_FAST_REF method*), 453
`has_valid_members()` (*ExecutiveObject method*), 499
`has_valid_members()` (*FILE_OBJECT method*), 455
`has_valid_members()` (*fileglob method*), 414
`has_valid_members()` (*files_struct method*), 340
`has_valid_members()` (*Float method*), 280
`has_valid_members()` (*fs_struct method*), 342
`has_valid_members()` (*Function method*), 282
`has_valid_members()` (*GenericIntelProcess method*), 326
`has_valid_members()` (*hist_entry method*), 396
`has_valid_members()` (*HMAP_ENTRY method*), 518
`has_valid_members()` (*ifnet method*), 415
`has_valid_members()` (*IMAGE_DOS_HEADER method*), 494
`has_valid_members()` (*IMAGE_NT_HEADERS method*), 497
`has_valid_members()` (*inet_sock method*), 344
`has_valid_members()` (*inpcb method*), 417
`has_valid_members()` (*Integer method*), 285
`has_valid_members()` (*kauth_scope method*), 419
`has_valid_members()` (*KDDEBUGGER_DATA64 method*), 482
`has_valid_members()` (*kernel_cap_struct method*), 347
`has_valid_members()` (*kernel_cap_t method*), 349
`has_valid_members()` (*KMUTANT method*), 457
`has_valid_members()` (*kobject method*), 351
`has_valid_members()` (*KSYSTEM_TIME method*), 459
`has_valid_members()` (*KTHREAD method*), 461
`has_valid_members()` (*LIST_ENTRY method*), 462
`has_valid_members()` (*list_head method*), 353
`has_valid_members()` (*maple_tree method*), 355
`has_valid_members()` (*MFTAttribute method*), 488
`has_valid_members()` (*MFTEntry method*), 490
`has_valid_members()` (*MFTFileName method*), 492
`has_valid_members()` (*mm_struct method*), 357
`has_valid_members()` (*MMVAD method*), 465
`has_valid_members()` (*MMVAD_SHORT method*), 467
`has_valid_members()` (*mnt_namespace method*), 359
`has_valid_members()` (*module method*), 361
`has_valid_members()` (*mount method*), 365
`has_valid_members()` (*net method*), 367
`has_valid_members()` (*netlink_sock method*), 369
`has_valid_members()` (*OBJECT_HEADER method*), 501
`has_valid_members()` (*OBJECT_SYMBOLIC_LINK method*), 470
`has_valid_members()` (*ObjectInterface method*), 167
`has_valid_members()` (*packet_sock method*), 371
`has_valid_members()` (*PARTITION_ENTRY method*), 485

- `has_valid_members()` (*PARTITION_TABLE* method), 486
- `has_valid_members()` (*Pointer* method), 288
- `has_valid_members()` (*POOL_HEADER* method), 503
- `has_valid_members()` (*POOL_HEADER_VISTA* method), 505
- `has_valid_members()` (*POOL_TRACKER_BIG_PAGES* method), 507
- `has_valid_members()` (*PrimitiveObject* method), 290
- `has_valid_members()` (*proc* method), 421
- `has_valid_members()` (*qstr* method), 372
- `has_valid_members()` (*queue_entry* method), 423
- `has_valid_members()` (*SERVICE_HEADER* method), 522
- `has_valid_members()` (*SERVICE_RECORD* method), 524
- `has_valid_members()` (*SHARED_CACHE_MAP* method), 472
- `has_valid_members()` (*sock* method), 374
- `has_valid_members()` (*sockaddr* method), 425
- `has_valid_members()` (*sockaddr_dl* method), 427
- `has_valid_members()` (*socket* method), 376, 429
- `has_valid_members()` (*String* method), 293
- `has_valid_members()` (*struct_file* method), 378
- `has_valid_members()` (*StructType* method), 299
- `has_valid_members()` (*SUMMARY_DUMP* method), 480
- `has_valid_members()` (*super_block* method), 381
- `has_valid_members()` (*sysctl_oid* method), 431
- `has_valid_members()` (*task_struct* method), 383
- `has_valid_members()` (*TOKEN* method), 474
- `has_valid_members()` (*UNICODE_STRING* method), 476
- `has_valid_members()` (*UnionType* method), 300
- `has_valid_members()` (*unix_sock* method), 385
- `has_valid_members()` (*VACB* method), 478
- `has_valid_members()` (*vfsmount* method), 388
- `has_valid_members()` (*vm_area_struct* method), 391
- `has_valid_members()` (*vm_map_entry* method), 433
- `has_valid_members()` (*vm_map_object* method), 435
- `has_valid_members()` (*vnode* method), 436
- `has_valid_members()` (*Void* method), 302
- `has_valid_members()` (*vsock_sock* method), 393
- `has_valid_members()` (*xdp_sock* method), 394
- `hash` (*SizedModule* property), 137
- `HASH_PTE_SIZE_64` (*QemuSuspendLayer* attribute), 235
- `Hashdump` (class in *volatility3.plugins.windows.hashdump*), 701
- `header_structure` (*VmwareLayer* attribute), 249
- `headerpages` (*WindowsCrashDump32Layer* attribute), 190
- `headerpages` (*WindowsCrashDump64Layer* attribute), 193
- `help()` (*Volshell* method), 54, 57, 60, 62
- `HelpfulArgParser` (class in *volatility3.cli.volargparse*), 68
- `HelpfulSubparserAction` (class in *volatility3.cli.volargparse*), 69
- `Hex` (class in *volatility3.framework.renderers.format_hints*), 312
- `hex()` (*Bytes* method), 266
- `hex()` (*Float* method), 280
- `hex()` (*HexBytes* method), 314
- `hex()` (*MultiTypeData* method), 318
- `hex_bytes_as_text()` (in module *volatility3.cli.text_renderer*), 67
- `HexBytes` (class in *volatility3.framework.renderers.format_hints*), 313
- `hide_from_subclasses()` (in module *volatility3.framework*), 69
- `HierarchicalDict` (class in *volatility3.framework.interfaces.configuration*), 148
- `hist_entry` (class in *volatility3.framework.symbols.linux.extensions.bash*), 395
- `hist_entry.VolTemplateProxy` (class in *volatility3.framework.symbols.linux.extensions.bash*), 395
- `hive_offset` (*RegistryHive* property), 240
- `HiveGenerator` (class in *volatility3.plugins.windows.registry.hivelist*), 663
- `HiveList` (class in *volatility3.plugins.windows.registry.hivelist*), 663
- `HiveScan` (class in *volatility3.plugins.windows.registry.hivescan*), 665
- `HMAP_ENTRY` (class in *volatility3.framework.symbols.windows.extensions.registry*), 516
- `HMAP_ENTRY.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.registry*), 516
- I
- `IAT` (class in *volatility3.plugins.windows.iat*), 704
- `IdentifierProcessor` (class in *volatility3.framework.automagic.symbol_cache*), 87
- `IDENTIFIERS_FILENAME` (in module *volatility3.framework.constants*), 120
- `Ifconfig` (class in *volatility3.plugins.mac.ifconfig*), 630
- `ifnet` (class in *volatility3.framework.symbols.mac.extensions*), 414

`ifnet.VolTemplateProxy` (class in `volatility3.framework.symbols.mac.extensions`), 414

`imag` (Bin attribute), 311

`imag` (BitFields attribute), 260

`imag` (Boolean attribute), 263

`imag` (Char attribute), 272

`imag` (ELF_CLASS attribute), 125

`imag` (ELF_IDENT attribute), 127

`imag` (Enumeration attribute), 278

`imag` (Float attribute), 280

`imag` (Hex attribute), 313

`imag` (Integer attribute), 285

`imag` (Parallelism attribute), 123

`imag` (Pointer attribute), 288

`imag` (PoolType attribute), 740

`imag` (RegKeyFlags attribute), 519

`imag` (TimeLinerType attribute), 785

`IMAGE_DOS_HEADER` (class in `volatility3.framework.symbols.windows.extensions.pe`), 493

`IMAGE_DOS_HEADER.VolTemplateProxy` (class in `volatility3.framework.symbols.windows.extensions.pe`), 493

`IMAGE_NT_HEADERS` (class in `volatility3.framework.symbols.windows.extensions.pe`), 495

`IMAGE_NT_HEADERS.VolTemplateProxy` (class in `volatility3.framework.symbols.windows.extensions.pe`), 495

`import_file()` (in module `volatility3.framework`), 69

`import_files()` (in module `volatility3.framework`), 69

`index()` (Array method), 257

`index()` (Bytes method), 266

`index()` (Column method), 173

`index()` (DataFormatInfo method), 275

`index()` (HexBytes method), 314

`index()` (MountInfoData method), 605

`index()` (MultiTypeData method), 318

`index()` (ServiceBinaryInfo method), 758

`index()` (String method), 293

`index()` (TreeNode method), 176, 309

`inet_ntop()` (in module `volatility3.framework.symbols.windows.extensions.network`), 493

`inet_sock` (class in `volatility3.framework.symbols.linux.extensions`), 342

`inet_sock.VolTemplateProxy` (class in `volatility3.framework.symbols.linux.extensions`), 343

`Info` (class in `volatility3.plugins.windows.info`), 706

`init_order_modules()` (EPROCESS method), 448

`inpcb` (class in `volatility3.framework.symbols.mac.extensions`), 416

`inpcb.VolTemplateProxy` (class in `volatility3.framework.symbols.mac.extensions`), 416

`instance_type` (BooleanRequirement attribute), 97

`instance_type` (BytesRequirement attribute), 98

`instance_type` (IntRequirement attribute), 103

`instance_type` (SimpleTypeRequirement attribute), 152

`instance_type` (StringRequirement attribute), 113

`instance_type` (URIRequirement attribute), 117

`Integer` (class in `volatility3.framework.objects`), 283

`Integer.VolTemplateProxy` (class in `volatility3.framework.objects`), 283

`Intel` (class in `volatility3.framework.layers.intel`), 199

`Intel32e` (class in `volatility3.framework.layers.intel`), 202

`IntelPAE` (class in `volatility3.framework.layers.intel`), 205

`interface_version()` (in module `volatility3.framework`), 69

`IntermediateSymbolTable` (class in `volatility3.framework.symbols.intermed`), 534

`IntRequirement` (class in `volatility3.framework.configuration.requirements`), 102

`invalid` (HiveGenerator property), 663

`InvalidAddressException`, 564

`invalidate_caches()` (WarningFindSpec method), 47

`IOMem` (class in `volatility3.plugins.linux.iomem`), 583

`is_ancestor()` (TreeGrid method), 174, 307

`is_bootable()` (PARTITION_ENTRY method), 485

`is_dirty()` (Intel method), 200

`is_dirty()` (Intel32e method), 203

`is_dirty()` (IntelPAE method), 206

`is_dirty()` (WindowsIntel method), 208

`is_dirty()` (WindowsIntel32e method), 211

`is_dirty()` (WindowsIntelPAE method), 214

`is_dirty()` (WindowsMixin method), 217

`is_equal()` (vfsmount method), 388

`is_free()` (POOL_TRACKER_BIG_PAGES method), 508

`is_free_pool()` (POOL_HEADER method), 503

`is_free_pool()` (POOL_HEADER_VISTA method), 505

`is_integer()` (Float method), 280

`is_kernel_thread` (task_struct property), 383

`is_nonpaged_pool()` (POOL_HEADER method), 503

`is_nonpaged_pool()` (POOL_HEADER_VISTA method), 505

`is_paged_pool()` (POOL_HEADER method), 503

- is_paged_pool() (*POOL_HEADER_VISTA method*), 505
- is_path_reachable() (*mount method*), 365
- is_readable() (*Pointer method*), 288
- is_root() (*dentry method*), 338
- is_shared() (*mount method*), 365
- is_shared() (*vfsmount method*), 388
- is_slave() (*mount method*), 365
- is_slave() (*vfsmount method*), 389
- is_subdir() (*dentry method*), 338
- is_suspicious() (*vm_area_struct method*), 391
- is_suspicious() (*vm_map_entry method*), 433
- is_thread_group_leader (*task_struct property*), 383
- is_unbindable() (*mount method*), 365
- is_unbindable() (*vfsmount method*), 389
- is_url_local() (*SqliteCache method*), 89
- is_user_thread (*task_struct property*), 383
- is_vad_empty() (*Malfind class method*), 714
- is_valid() (*AVMLLayer method*), 187
- is_valid() (*BufferDataLayer method*), 231
- is_valid() (*CMHIVE method*), 510
- is_valid() (*CONTROL_AREA method*), 442
- is_valid() (*DataLayerInterface method*), 159
- is_valid() (*DRIVER_OBJECT method*), 446
- is_valid() (*elf method*), 399
- is_valid() (*Elf64Layer method*), 197
- is_valid() (*EPROCESS method*), 448
- is_valid() (*ETHREAD method*), 451
- is_valid() (*FILE_OBJECT method*), 455
- is_valid() (*FileLayer method*), 233
- is_valid() (*hist_entry method*), 396
- is_valid() (*Intel method*), 200
- is_valid() (*Intel32e method*), 203
- is_valid() (*IntelPAE method*), 206
- is_valid() (*KMUTANT method*), 457
- is_valid() (*LimeLayer method*), 220
- is_valid() (*LinearlyMappedLayer method*), 223
- is_valid() (*NonLinearlySegmentedLayer method*), 244
- is_valid() (*OBJECT_HEADER method*), 501
- is_valid() (*OBJECT_SYMBOLIC_LINK method*), 470
- is_valid() (*PdbMSFStream method*), 225
- is_valid() (*PdbMultiStreamFormat method*), 228
- is_valid() (*POOL_TRACKER_BIG_PAGES method*), 508
- is_valid() (*QemuSuspendLayer method*), 236
- is_valid() (*RegistryHive method*), 240
- is_valid() (*SegmentedLayer method*), 247
- is_valid() (*SERVICE_HEADER method*), 522
- is_valid() (*SERVICE_RECORD method*), 524
- is_valid() (*SHARED_CACHE_MAP method*), 472
- is_valid() (*TranslationLayerInterface method*), 164
- is_valid() (*vfsmount method*), 389
- is_valid() (*VmwareLayer method*), 249
- is_valid() (*WindowsCrashDump32Layer method*), 190
- is_valid() (*WindowsCrashDump64Layer method*), 193
- is_valid() (*WindowsIntel method*), 208
- is_valid() (*WindowsIntel32e method*), 211
- is_valid() (*WindowsIntelPAE method*), 214
- is_valid() (*WindowsMixin method*), 217
- is_valid() (*XenCoreDumpLayer method*), 252
- is_valid_choice (*Enumeration property*), 278
- isalnum() (*Bytes method*), 267
- isalnum() (*HexBytes method*), 314
- isalnum() (*MultiTypeData method*), 318
- isalnum() (*String method*), 293
- isalpha() (*Bytes method*), 267
- isalpha() (*HexBytes method*), 314
- isalpha() (*MultiTypeData method*), 318
- isalpha() (*String method*), 293
- isascii() (*Bytes method*), 267
- isascii() (*HexBytes method*), 314
- isascii() (*MultiTypeData method*), 318
- isascii() (*String method*), 294
- isatty() (*FileHandlerInterface method*), 170
- isatty() (*NullFileHandler method*), 51
- isdecimal() (*String method*), 294
- isdigit() (*Bytes method*), 267
- isdigit() (*HexBytes method*), 314
- isdigit() (*MultiTypeData method*), 318
- isdigit() (*String method*), 294
- ISF_EXTENSIONS (*in module volatility3.framework.constants*), 120
- ISF_MINIMUM_DEPRECATED (*in module volatility3.framework.constants*), 120
- ISF_MINIMUM_SUPPORTED (*in module volatility3.framework.constants*), 121
- IsfInfo (*class in volatility3.plugins.isfinfo*), 780
- ISFormatTable (*class in volatility3.framework.symbols.intermed*), 531
- isidentifier() (*String method*), 294
- islower() (*Bytes method*), 267
- islower() (*HexBytes method*), 314
- islower() (*MultiTypeData method*), 318
- islower() (*String method*), 294
- isnumeric() (*String method*), 294
- isprintable() (*String method*), 294
- isspace() (*Bytes method*), 267
- isspace() (*HexBytes method*), 314
- isspace() (*MultiTypeData method*), 318
- isspace() (*String method*), 294
- istitle() (*Bytes method*), 267
- istitle() (*HexBytes method*), 314
- istitle() (*MultiTypeData method*), 318
- istitle() (*String method*), 294
- isupper() (*Bytes method*), 267
- isupper() (*HexBytes method*), 315
- isupper() (*MultiTypeData method*), 319
- isupper() (*String method*), 294

items() (*HierarchicalDict* method), 149
 items() (*LayerContainer* method), 162
 items() (*ModuleCollection* method), 135
 items() (*ModuleContainer* method), 155
 items() (*ObjectInformation* method), 166
 items() (*ReadOnlyMapping* method), 168
 items() (*SymbolSpace* method), 323
 items() (*SymbolSpaceInterface* method), 182

J

JarHandler (class in volatility3.framework.layers.resources), 242
 JobLinks (class in volatility3.plugins.windows.joblinks), 708
 join() (*Bytes* method), 267
 join() (*HexBytes* method), 315
 join() (*MultiTypeData* method), 319
 join() (*String* method), 294
 JsonLinesRenderer (class in volatility3.cli.text_renderer), 65
 JsonRenderer (class in volatility3.cli.text_renderer), 65

K

Kauth_listeners (class in volatility3.plugins.mac.kauth_listeners), 631
 kauth_scope (class in volatility3.framework.symbols.mac.extensions), 418
 kauth_scope.VolTemplateProxy (class in volatility3.framework.symbols.mac.extensions), 418
 Kauth_scopes (class in volatility3.plugins.mac.kauth_scopes), 633
 KDDEBUGGER_DATA64 (class in volatility3.framework.symbols.windows.extensions.kdbg), 480
 KDDEBUGGER_DATA64.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.kdbg), 480
 kernel (Volshell property), 54, 57, 60, 63
 kernel_cap_struct (class in volatility3.framework.symbols.linux.extensions), 344
 kernel_cap_struct.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 344
 kernel_cap_t (class in volatility3.framework.symbols.linux.extensions), 347
 kernel_cap_t.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 347
 KERNEL_MODULE_NAMES (in module volatility3.framework.constants.windows), 127

KERNEL_NAME (in module volatility3.framework.constants.linux), 127
 KernelModule (class in volatility3.framework.automagic.module), 78
 KernelPDBScanner (class in volatility3.framework.automagic.pdbscan), 79
 Kevents (class in volatility3.plugins.mac.kevents), 634
 KEY_COMP_NAME (*RegKeyFlags* attribute), 518
 KEY_HIVE_ENTRY (*RegKeyFlags* attribute), 518
 KEY_HIVE_EXIT (*RegKeyFlags* attribute), 518
 KEY_IS_VOLATILE (*RegKeyFlags* attribute), 518
 key_iterator() (*PrintKey* class method), 668
 KEY_NO_DELETE (*RegKeyFlags* attribute), 518
 KEY_PREFEF_HANDLE (*RegKeyFlags* attribute), 518
 KEY_SYM_LINK (*RegKeyFlags* attribute), 518
 KEY_VIRT_MIRRORED (*RegKeyFlags* attribute), 518
 KEY_VIRT_TARGET (*RegKeyFlags* attribute), 518
 KEY_VIRTUAL_STORE (*RegKeyFlags* attribute), 518
 Keyboard_notifiers (class in volatility3.plugins.linux.keyboard_notifiers), 585
 keys() (*HierarchicalDict* method), 149
 keys() (*LayerContainer* method), 162
 keys() (*ModuleCollection* method), 135
 keys() (*ModuleContainer* method), 155
 keys() (*ObjectInformation* method), 166
 keys() (*ReadOnlyMapping* method), 168
 keys() (*SymbolSpace* method), 324
 keys() (*SymbolSpaceInterface* method), 182
 Kmsg (class in volatility3.plugins.linux.kmsg), 588
 Kmsg_3_11_to_5_10 (class in volatility3.plugins.linux.kmsg), 590
 Kmsg_3_5_to_3_11 (class in volatility3.plugins.linux.kmsg), 591
 Kmsg_5_10_to_ (class in volatility3.plugins.linux.kmsg), 593
 Kmsg_pre_3_5 (class in volatility3.plugins.linux.kmsg), 595
 KMUTANT (class in volatility3.framework.symbols.windows.extensions), 455
 KMUTANT.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions), 455
 kobject (class in volatility3.framework.symbols.linux.extensions), 350
 kobject.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 350
 KSYSTEM_TIME (class in volatility3.framework.symbols.windows.extensions), 457
 KSYSTEM_TIME.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions), 457

- 457
- KTHREAD (class in volatility3.framework.symbols.windows.extensions), 459
- KTHREAD.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions), 459
- ## L
- layer_name (BytesScanner property), 185
- layer_name (ConfigurableModule property), 129
- layer_name (Module property), 133
- layer_name (ModuleInterface property), 157
- layer_name (MultiStringScanner property), 185
- layer_name (PageMapScanner property), 94
- layer_name (PdbSignatureScanner property), 530
- layer_name (PoolHeaderScanner property), 736
- layer_name (RegExScanner property), 185
- layer_name (ScannerInterface property), 163
- layer_name (SizedModule property), 137
- layer_name (YaraScanner property), 789
- LayerContainer (class in volatility3.framework.interfaces.layers), 161
- LayerException, 564
- LayerListRequirement (class in volatility3.framework.configuration.requirements), 103
- layers (Context property), 131
- layers (ContextInterface property), 154
- LayerStacker (class in volatility3.framework.automagic.stacker), 83
- LayerWriter (class in volatility3.plugins.layerwriter), 782
- LdrModules (class in volatility3.plugins.windows.ldrmodules), 710
- length (DataFormatInfo attribute), 275
- LEVELS (ABCKmsg attribute), 587
- LEVELS (Kmsg_3_11_to_5_10 attribute), 590
- LEVELS (Kmsg_3_5_to_3_11 attribute), 591
- LEVELS (Kmsg_5_10_to_ attribute), 593
- LEVELS (Kmsg_pre_3_5 attribute), 595
- LibraryList (class in volatility3.plugins.linux.library_list), 596
- LimeFormatException, 219
- LimeLayer (class in volatility3.framework.layers.lime), 219
- LimeStacker (class in volatility3.framework.layers.lime), 221
- LinearlyMappedLayer (class in volatility3.framework.layers.linear), 222
- LinuxIdentifier (class in volatility3.framework.automagic.symbol_cache), 87
- LinuxIntelStacker (class in volatility3.framework.automagic.linux), 73
- LinuxKernelIntermedSymbols (class in volatility3.framework.symbols.linux), 326
- LinuxMetadata (class in volatility3.framework.symbols.metadata), 561
- LinuxSymbolFinder (class in volatility3.framework.automagic.linux), 73
- LinuxUtilities (class in volatility3.framework.symbols.linux), 329
- list_all_isf_files() (IsfInfo class method), 781
- list_big_pools() (BigPools class method), 671
- list_bugcheck_callbacks() (Callbacks class method), 675
- list_bugcheck_reason_callbacks() (Callbacks class method), 676
- LIST_ENTRY (class in volatility3.framework.symbols.windows.extensions), 461
- LIST_ENTRY.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions), 461
- list_fds() (Lsof class method), 600
- List_Files (class in volatility3.plugins.mac.list_files), 637
- list_files() (List_Files class method), 637
- list_handlers (ResourceAccessor attribute), 243
- list_head (class in volatility3.framework.symbols.linux.extensions), 351
- list_head.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 352
- list_hive_objects() (HiveList class method), 664
- list_hives() (HiveList class method), 664
- list_injections() (Malfind class method), 714
- list_kauth_scopes() (Kauth_scopes class method), 633
- list_kernel_events() (Kevents class method), 635
- list_modules() (Lsmmod class method), 598, 639
- list_modules() (Modules class method), 725
- list_mounts() (Mount class method), 644
- list_notify_routines() (Callbacks class method), 676
- list_plugins() (in module volatility3.framework), 70
- list_processes() (PsList class method), 744
- list_processes() (Volshell method), 63
- list_registry_callbacks() (Callbacks class method), 676
- list_sockets() (NetStat class method), 733
- list_sockets() (Netstat class method), 645
- list_sockets() (Sockstat class method), 616
- list_tasks() (PsList class method), 610
- list_tasks() (Volshell method), 57, 60

- `list_tasks_allproc()` (*PsList* class method), 652
 - `list_tasks_pid_hash_table()` (*PsList* class method), 652
 - `list_tasks_process_group()` (*PsList* class method), 652
 - `list_tasks_sessions()` (*PsList* class method), 652
 - `list_tasks_tasks()` (*PsList* class method), 653
 - `list_userassist()` (*UserAssist* method), 670
 - `list_vads()` (*VadInfo* class method), 766
 - `list_vmas()` (*Maps* class method), 606, 647
 - `ListRequirement` (class in *volatility3.framework.configuration.requirements*), 105
 - `ljust()` (*Bytes* method), 267
 - `ljust()` (*HexBytes* method), 315
 - `ljust()` (*MultiTypeData* method), 319
 - `ljust()` (*String* method), 295
 - `lmkey` (*Hashdump* attribute), 703
 - `load_cached_validations()` (in module *volatility3.schemas*), 789
 - `load_file()` (*Volshell* method), 54, 57, 60, 63
 - `load_order_modules()` (*EPROCESS* method), 449
 - `load_pdb_layer()` (*PdbReader* class method), 526
 - `load_system_defaults()` (*CommandLine* method), 48
 - `load_system_defaults()` (*VolShell* method), 49
 - `load_windows_symbol_table()` (*PDBUtility* class method), 528
 - `locate_banners()` (*Banners* class method), 776
 - `location` (*FileLayer* property), 233
 - `location_from_file()` (*CommandLine* class method), 48
 - `location_from_file()` (*URIRequirement* class method), 117
 - `location_from_file()` (*VolShell* class method), 49
 - `LOGLEVEL_DEBUG` (in module *volatility3.framework.constants*), 121
 - `LOGLEVEL_INFO` (in module *volatility3.framework.constants*), 121
 - `LOGLEVEL_V` (in module *volatility3.framework.constants*), 121
 - `LOGLEVEL_VV` (in module *volatility3.framework.constants*), 121
 - `LOGLEVEL_VVV` (in module *volatility3.framework.constants*), 121
 - `LOGLEVEL_VVVV` (in module *volatility3.framework.constants*), 121
 - `lookup()` (*Enumeration* method), 278
 - `lookup()` (*Enumeration.VolTemplateProxy* class method), 275
 - `lookup_module_address()` (*LinuxUtilities* class method), 331
 - `lookup_module_address()` (*MacUtilities* class method), 412
 - `lookup_user_sids()` (*GetSIDs* method), 698
 - `lower()` (*Bytes* method), 267
 - `lower()` (*HexBytes* method), 315
 - `lower()` (*MultiTypeData* method), 319
 - `lower()` (*String* method), 295
 - `Lsadump` (class in *volatility3.plugins.windows.lsadump*), 711
 - `Lsmode` (class in *volatility3.plugins.linux.lsmode*), 598
 - `Lsmode` (class in *volatility3.plugins.mac.lsmode*), 638
 - `Lsof` (class in *volatility3.plugins.linux.lsof*), 600
 - `Lsof` (class in *volatility3.plugins.mac.lsof*), 640
 - `lstrip()` (*Bytes* method), 267
 - `lstrip()` (*HexBytes* method), 315
 - `lstrip()` (*MultiTypeData* method), 319
 - `lstrip()` (*String* method), 295
- ## M
- `MacIdentifier` (class in *volatility3.framework.automagic.symbol_cache*), 87
 - `MacIntelStacker` (class in *volatility3.framework.automagic.mac*), 75
 - `MacKernelIntermedSymbols` (class in *volatility3.framework.symbols.mac*), 408
 - `MacSymbolFinder` (class in *volatility3.framework.automagic.mac*), 75
 - `MacUtilities` (class in *volatility3.framework.symbols.mac*), 411
 - `MAGIC` (*Elf64Layer* attribute), 196
 - `MAGIC` (*LimeLayer* attribute), 219
 - `MAGIC` (*XenCoreDumpLayer* attribute), 251
 - `main()` (in module *volatility3.cli*), 49
 - `main()` (in module *volatility3.cli.volshell*), 50
 - `major` (*super_block* property), 381
 - `make_subconfig()` (*ADS* class method), 719
 - `make_subconfig()` (*AutomagicInterface* class method), 140
 - `make_subconfig()` (*AVMLLayer* class method), 187
 - `make_subconfig()` (*Banners* class method), 776
 - `make_subconfig()` (*Bash* class method), 568, 622
 - `make_subconfig()` (*BashIntermedSymbols* class method), 407
 - `make_subconfig()` (*BigPools* class method), 672
 - `make_subconfig()` (*BufferDataLayer* class method), 231
 - `make_subconfig()` (*Cachedump* class method), 673
 - `make_subconfig()` (*Callbacks* class method), 677
 - `make_subconfig()` (*Capabilities* class method), 570
 - `make_subconfig()` (*Check_afinfo* class method), 572
 - `make_subconfig()` (*Check_creds* class method), 574
 - `make_subconfig()` (*Check_idt* class method), 575
 - `make_subconfig()` (*Check_modules* class method), 577
 - `make_subconfig()` (*Check_syscall* class method), 579, 624
 - `make_subconfig()` (*Check_sysctl* class method), 625

`make_subconfig()` (*Check_trap_table* class method), 627
`make_subconfig()` (*CmdLine* class method), 678
`make_subconfig()` (*ConfigurableInterface* class method), 144
`make_subconfig()` (*ConfigurableModule* class method), 129
`make_subconfig()` (*ConfigWriter* class method), 778
`make_subconfig()` (*ConstructionMagic* class method), 72
`make_subconfig()` (*Crashinfo* class method), 680
`make_subconfig()` (*DataLayerInterface* class method), 159
`make_subconfig()` (*DeviceTree* class method), 682
`make_subconfig()` (*DllList* class method), 684
`make_subconfig()` (*Dmesg* class method), 629
`make_subconfig()` (*DriverIrp* class method), 685
`make_subconfig()` (*DriverModule* class method), 687
`make_subconfig()` (*DriverScan* class method), 689
`make_subconfig()` (*DumpFiles* class method), 691
`make_subconfig()` (*Elf64Layer* class method), 197
`make_subconfig()` (*Elfs* class method), 580
`make_subconfig()` (*Envvars* class method), 582, 693
`make_subconfig()` (*FileLayer* class method), 233
`make_subconfig()` (*FileScan* class method), 694
`make_subconfig()` (*FrameworkInfo* class method), 779
`make_subconfig()` (*GetServiceSIDs* class method), 696
`make_subconfig()` (*GetSIDs* class method), 698
`make_subconfig()` (*Handles* class method), 700
`make_subconfig()` (*Hashdump* class method), 703
`make_subconfig()` (*HiveList* class method), 664
`make_subconfig()` (*HiveScan* class method), 666
`make_subconfig()` (*IAT* class method), 705
`make_subconfig()` (*Ifconfig* class method), 630
`make_subconfig()` (*Info* class method), 707
`make_subconfig()` (*Intel* class method), 200
`make_subconfig()` (*Intel32e* class method), 203
`make_subconfig()` (*IntelPAE* class method), 206
`make_subconfig()` (*IntermediateSymbolTable* class method), 536
`make_subconfig()` (*IOMem* class method), 584
`make_subconfig()` (*IsfInfo* class method), 781
`make_subconfig()` (*ISFormatTable* class method), 532
`make_subconfig()` (*JobLinks* class method), 709
`make_subconfig()` (*Kauth_listeners* class method), 632
`make_subconfig()` (*Kauth_scopes* class method), 633
`make_subconfig()` (*KernelModule* class method), 78
`make_subconfig()` (*KernelPDBScanner* class method), 81
`make_subconfig()` (*Kevents* class method), 635
`make_subconfig()` (*Keyboard_notifiers* class method), 586
`make_subconfig()` (*Kmsg* class method), 589
`make_subconfig()` (*LayerStacker* class method), 84
`make_subconfig()` (*LayerWriter* class method), 782
`make_subconfig()` (*LdrModules* class method), 710
`make_subconfig()` (*LibraryList* class method), 597
`make_subconfig()` (*LimeLayer* class method), 220
`make_subconfig()` (*LinearlyMappedLayer* class method), 223
`make_subconfig()` (*LinuxKernelIntermedSymbols* class method), 328
`make_subconfig()` (*LinuxSymbolFinder* class method), 74
`make_subconfig()` (*List_Files* class method), 637
`make_subconfig()` (*Lsadump* class method), 712
`make_subconfig()` (*Lsmode* class method), 599, 639
`make_subconfig()` (*Lsof* class method), 600, 640
`make_subconfig()` (*MacKernelIntermedSymbols* class method), 410
`make_subconfig()` (*MacSymbolFinder* class method), 77
`make_subconfig()` (*Malfind* class method), 602, 642, 714
`make_subconfig()` (*Maps* class method), 606, 648
`make_subconfig()` (*MBRScan* class method), 716
`make_subconfig()` (*Memmap* class method), 717
`make_subconfig()` (*MFTScan* class method), 721
`make_subconfig()` (*ModScan* class method), 723
`make_subconfig()` (*Module* class method), 133
`make_subconfig()` (*ModuleInterface* class method), 157
`make_subconfig()` (*Modules* class method), 726
`make_subconfig()` (*Mount* class method), 644
`make_subconfig()` (*MountInfo* class method), 604
`make_subconfig()` (*MutantScan* class method), 727
`make_subconfig()` (*NetScan* class method), 730
`make_subconfig()` (*NetStat* class method), 734
`make_subconfig()` (*Netstat* class method), 646
`make_subconfig()` (*NonLinearlySegmentedLayer* class method), 244
`make_subconfig()` (*Passphrase* class method), 764
`make_subconfig()` (*PdbMSFStream* class method), 226
`make_subconfig()` (*PdbMultiStreamFormat* class method), 228
`make_subconfig()` (*PluginInterface* class method), 172
`make_subconfig()` (*PoolScanner* class method), 738
`make_subconfig()` (*PrintKey* class method), 668
`make_subconfig()` (*Privs* class method), 742
`make_subconfig()` (*PsAux* class method), 608
`make_subconfig()` (*Psaux* class method), 650
`make_subconfig()` (*PsList* class method), 611, 653, 744
`make_subconfig()` (*PsScan* class method), 612, 747
`make_subconfig()` (*PsTree* class method), 614, 655, 749
`make_subconfig()` (*QemuSuspendLayer* class method), 237
`make_subconfig()` (*RegistryHive* class method), 240

`make_subconfig()` (*SegmentedLayer* class method), 247

`make_subconfig()` (*Sessions* class method), 751

`make_subconfig()` (*SizedModule* class method), 137

`make_subconfig()` (*Skeleton_Key_Check* class method), 752

`make_subconfig()` (*Socket_filters* class method), 656

`make_subconfig()` (*Sockstat* class method), 617

`make_subconfig()` (*SSDT* class method), 754

`make_subconfig()` (*Strings* class method), 756

`make_subconfig()` (*SvcScan* class method), 759

`make_subconfig()` (*SymbolCacheMagic* class method), 90

`make_subconfig()` (*SymbolFinder* class method), 92

`make_subconfig()` (*SymbolTableInterface* class method), 184

`make_subconfig()` (*SymlinkScan* class method), 760

`make_subconfig()` (*ThrdScan* class method), 762

`make_subconfig()` (*Timeliner* class method), 786

`make_subconfig()` (*Timers* class method), 658

`make_subconfig()` (*TranslationLayerInterface* class method), 164

`make_subconfig()` (*Trustedbsd* class method), 660

`make_subconfig()` (*tty_check* class method), 618

`make_subconfig()` (*UserAssist* class method), 670

`make_subconfig()` (*VadInfo* class method), 766

`make_subconfig()` (*VadWalk* class method), 769

`make_subconfig()` (*VadYaraScan* class method), 770

`make_subconfig()` (*VerInfo* class method), 772

`make_subconfig()` (*Version1Format* class method), 539

`make_subconfig()` (*Version2Format* class method), 542

`make_subconfig()` (*Version3Format* class method), 545

`make_subconfig()` (*Version4Format* class method), 548

`make_subconfig()` (*Version5Format* class method), 551

`make_subconfig()` (*Version6Format* class method), 554

`make_subconfig()` (*Version7Format* class method), 557

`make_subconfig()` (*Version8Format* class method), 560

`make_subconfig()` (*VFSevents* class method), 661

`make_subconfig()` (*VirtMap* class method), 774

`make_subconfig()` (*VmaYaraScan* class method), 620

`make_subconfig()` (*VmwareLayer* class method), 249

`make_subconfig()` (*Volshell* class method), 54, 57, 60, 63

`make_subconfig()` (*WindowsCrashDump32Layer* class method), 191

`make_subconfig()` (*WindowsCrashDump64Layer* class method), 193

`make_subconfig()` (*WindowsIntel* class method), 209

`make_subconfig()` (*WindowsIntel32e* class method), 211

`make_subconfig()` (*WindowsIntelPAE* class method), 214

`make_subconfig()` (*WindowsKernelIntermedSymbols* class method), 439

`make_subconfig()` (*WindowsMixin* class method), 217

`make_subconfig()` (*WinSwapLayers* class method), 95

`make_subconfig()` (*XenCoreDumpLayer* class method), 252

`make_subconfig()` (*YaraScan* class method), 788

`maketrans()` (*Bytes* static method), 267

`maketrans()` (*HexBytes* static method), 315

`maketrans()` (*MultiTypeData* static method), 319

`maketrans()` (*String* static method), 295

Malfind (class in *volatility3.plugins.linux.malfind*), 601

Malfind (class in *volatility3.plugins.mac.malfind*), 642

Malfind (class in *volatility3.plugins.windows.malfind*), 713

MAPLE_ARANGE_64 (*maple_tree* attribute), 354

MAPLE_DENSE (*maple_tree* attribute), 354

MAPLE_LEAF_64 (*maple_tree* attribute), 354

MAPLE_NODE_POINTER_MASK (*maple_tree* attribute), 354

MAPLE_NODE_TYPE_MASK (*maple_tree* attribute), 354

MAPLE_NODE_TYPE_SHIFT (*maple_tree* attribute), 354

MAPLE_RANGE_64 (*maple_tree* attribute), 354

maple_tree (class in *volatility3.framework.symbols.linux.extensions*), 354

maple_tree.VolTemplateProxy (class in *volatility3.framework.symbols.linux.extensions*), 354

`mapping()` (*AVMLLayer* method), 187

`mapping()` (*Elf64Layer* method), 197

`mapping()` (*Intel* method), 200

`mapping()` (*Intel32e* method), 203

`mapping()` (*IntelPAE* method), 206

`mapping()` (*LimeLayer* method), 220

`mapping()` (*LinearlyMappedLayer* method), 223

`mapping()` (*NonLinearlySegmentedLayer* method), 245

`mapping()` (*PdbMSFStream* method), 226

`mapping()` (*PdbMultiStreamFormat* method), 229

`mapping()` (*QemuSuspendLayer* method), 237

`mapping()` (*RegistryHive* method), 240

`mapping()` (*SegmentedLayer* method), 247

`mapping()` (*TranslationLayerInterface* method), 164

`mapping()` (*VmwareLayer* method), 250

`mapping()` (*WindowsCrashDump32Layer* method), 191

`mapping()` (*WindowsCrashDump64Layer* method), 194

`mapping()` (*WindowsIntel* method), 209

`mapping()` (*WindowsIntel32e* method), 212

`mapping()` (*WindowsIntelPAE* method), 214

`mapping()` (*WindowsMixin* method), 217

`mapping()` (*XenCoreDumpLayer* method), 252

Maps (class in *volatility3.plugins.linux.proc*), 606

Maps (class in *volatility3.plugins.mac.proc_maps*), 647

`mask_mods_list()` (*LinuxUtilities* class method), 331

`mask_mods_list()` (*MacUtilities* class method), 412

`matches_required()` (*PluginRequirement* class method), 111

`matches_required()` (*VersionRequirement* class method), 119
`max_depth()` (*TreeGrid* method), 175, 307
`max_pdb_size` (*KernelPDBScanner* attribute), 81
`maximum_address` (*AVMLLayer* property), 187
`maximum_address` (*BufferDataLayer* property), 231
`maximum_address` (*DataLayerInterface* property), 160
`maximum_address` (*Elf64Layer* property), 197
`maximum_address` (*FileLayer* property), 234
`maximum_address` (*Intel* attribute), 201
`maximum_address` (*Intel32e* attribute), 203
`maximum_address` (*IntelPAE* attribute), 206
`maximum_address` (*LimeLayer* property), 220
`maximum_address` (*LinearlyMappedLayer* property), 223
`maximum_address` (*NonLinearlySegmentedLayer* property), 245
`maximum_address` (*PdbMSFStream* property), 226
`maximum_address` (*PdbMultiStreamFormat* property), 229
`maximum_address` (*QemuSuspendLayer* property), 237
`maximum_address` (*RegistryHive* property), 240
`maximum_address` (*SegmentedLayer* property), 247
`maximum_address` (*TranslationLayerInterface* property), 164
`maximum_address` (*VmwareLayer* property), 250
`maximum_address` (*WindowsCrashDump32Layer* property), 191
`maximum_address` (*WindowsCrashDump64Layer* property), 194
`maximum_address` (*WindowsIntel* attribute), 209
`maximum_address` (*WindowsIntel32e* attribute), 212
`maximum_address` (*WindowsIntelPAE* attribute), 215
`maximum_address` (*WindowsMixin* attribute), 217
`maximum_address` (*XenCoreDumpLayer* property), 252
`MAXSIZE_DEFAULT` (*Maps* attribute), 606, 647
`MAXSIZE_DEFAULT` (*VadInfo* attribute), 766
`MBRScan` (class in *volatility3.plugins.windows.mbrscan*), 715
`mem_order_modules()` (*EPROCESS* method), 449
`member()` (*AggregateType* method), 256
`member()` (*bpf_prog* method), 333
`member()` (*bt_sock* method), 335
`member()` (*ClassType* method), 274
`member()` (*CM_KEY_BODY* method), 512
`member()` (*CM_KEY_NODE* method), 514
`member()` (*CM_KEY_VALUE* method), 516
`member()` (*CMHIVE* method), 510
`member()` (*CONTROL_AREA* method), 442
`member()` (*cred* method), 336
`member()` (*dentry* method), 338
`member()` (*DEVICE_OBJECT* method), 444
`member()` (*DRIVER_OBJECT* method), 446
`member()` (*elf* method), 399
`member()` (*elf_linkmap* method), 400
`member()` (*elf_phdr* method), 402
`member()` (*elf_sym* method), 404
`member()` (*EPROCESS* method), 449
`member()` (*ETHREAD* method), 451
`member()` (*EX_FAST_REF* method), 453
`member()` (*FILE_OBJECT* method), 455
`member()` (*fileglob* method), 414
`member()` (*files_struct* method), 340
`member()` (*fs_struct* method), 342
`member()` (*GenericIntelProcess* method), 326
`member()` (*hist_entry* method), 397
`member()` (*HMAP_ENTRY* method), 518
`member()` (*ifnet* method), 416
`member()` (*IMAGE_DOS_HEADER* method), 495
`member()` (*IMAGE_NT_HEADERS* method), 497
`member()` (*inet_sock* method), 344
`member()` (*inpcb* method), 417
`member()` (*kauth_scope* method), 419
`member()` (*KDDEBUGGER_DATA64* method), 482
`member()` (*kernel_cap_struct* method), 347
`member()` (*kernel_cap_t* method), 349
`member()` (*KMUTANT* method), 457
`member()` (*kobject* method), 351
`member()` (*KSYSTEM_TIME* method), 459
`member()` (*KTHREAD* method), 461
`member()` (*LIST_ENTRY* method), 462
`member()` (*list_head* method), 353
`member()` (*maple_tree* method), 355
`member()` (*MFTAttribute* method), 489
`member()` (*MFTEntry* method), 490
`member()` (*MFTFileName* method), 492
`member()` (*mm_struct* method), 357
`member()` (*MMVAD* method), 465
`member()` (*MMVAD_SHORT* method), 468
`member()` (*mnt_namespace* method), 359
`member()` (*module* method), 362
`member()` (*mount* method), 366
`member()` (*net* method), 367
`member()` (*netlink_sock* method), 369
`member()` (*OBJECT_HEADER* method), 501
`member()` (*OBJECT_SYMBOLIC_LINK* method), 470
`member()` (*packet_sock* method), 371
`member()` (*PARTITION_ENTRY* method), 485
`member()` (*PARTITION_TABLE* method), 487
`member()` (*POOL_HEADER* method), 503
`member()` (*POOL_HEADER_VISTA* method), 506
`member()` (*POOL_TRACKER_BIG_PAGES* method), 508
`member()` (*proc* method), 421
`member()` (*qstr* method), 373
`member()` (*queue_entry* method), 423
`member()` (*SERVICE_HEADER* method), 522
`member()` (*SERVICE_RECORD* method), 524

`member()` (*SHARED_CACHE_MAP* method), 472
`member()` (*sock* method), 375
`member()` (*sockaddr* method), 425
`member()` (*sockaddr_dl* method), 427
`member()` (*socket* method), 376, 429
`member()` (*struct_file* method), 378
`member()` (*StructType* method), 299
`member()` (*SUMMARY_DUMP* method), 480
`member()` (*super_block* method), 381
`member()` (*sysctl_oid* method), 431
`member()` (*task_struct* method), 383
`member()` (*TOKEN* method), 474
`member()` (*UNICODE_STRING* method), 476
`member()` (*UnionType* method), 301
`member()` (*unix_sock* method), 385
`member()` (*VACB* method), 478
`member()` (*vfsmount* method), 389
`member()` (*vm_area_struct* method), 391
`member()` (*vm_map_entry* method), 433
`member()` (*vm_map_object* method), 435
`member()` (*vnode* method), 436
`member()` (*vsock_sock* method), 393
`member()` (*xdp_sock* method), 395
`Memmap` (class in *volatility3.plugins.windows.memmap*), 717
`merge()` (*HierarchicalDict* method), 149
`metadata` (*AVMLLayer* property), 187
`metadata` (*BashIntermedSymbols* property), 407
`metadata` (*BufferDataLayer* property), 231
`metadata` (*DataLayerInterface* property), 160
`metadata` (*Elf64Layer* property), 197
`metadata` (*FileLayer* property), 234
`metadata` (*Intel* property), 201
`metadata` (*Intel32e* property), 203
`metadata` (*IntelPAE* property), 206
`metadata` (*IntermediateSymbolTable* property), 536
`metadata` (*ISFormatTable* property), 533
`metadata` (*LimeLayer* property), 220
`metadata` (*LinearlyMappedLayer* property), 223
`metadata` (*LinuxKernelIntermedSymbols* property), 329
`metadata` (*MacKernelIntermedSymbols* property), 410
`metadata` (*NonLinearlySegmentedLayer* property), 245
`metadata` (*PdbMSFStream* property), 226
`metadata` (*PdbMultiStreamFormat* property), 229
`metadata` (*QemuSuspendLayer* property), 237
`metadata` (*RegistryHive* property), 240
`metadata` (*SegmentedLayer* property), 247
`metadata` (*TranslationLayerInterface* property), 164
`metadata` (*Version1Format* property), 539
`metadata` (*Version2Format* property), 542
`metadata` (*Version3Format* property), 545
`metadata` (*Version4Format* property), 548
`metadata` (*Version5Format* property), 551
`metadata` (*Version6Format* property), 554
`metadata` (*Version7Format* property), 557
`metadata` (*Version8Format* property), 560
`metadata` (*VmwareLayer* property), 250
`metadata` (*WindowsCrashDump32Layer* property), 191
`metadata` (*WindowsCrashDump64Layer* property), 194
`metadata` (*WindowsIntel* property), 209
`metadata` (*WindowsIntel32e* property), 212
`metadata` (*WindowsIntelPAE* property), 215
`metadata` (*WindowsKernelIntermedSymbols* property), 439
`metadata` (*WindowsMixin* property), 217
`metadata` (*XenCoreDumpLayer* property), 252
`MetadataInterface` (class in *volatility3.framework.interfaces.symbols*), 178
`method_fixed_mapping()` (*KernelPDBScanner* method), 82
`method_kdbg_offset()` (*KernelPDBScanner* method), 82
`method_module_offset()` (*KernelPDBScanner* method), 82
`method_slow_scan()` (*KernelPDBScanner* method), 82
`methods` (*KernelPDBScanner* attribute), 82
`MFTAttribute` (class in *volatility3.framework.symbols.windows.extensions.mft*), 487
`MFTAttribute.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.mft*), 487
`MFTEntry` (class in *volatility3.framework.symbols.windows.extensions.mft*), 489
`MFTEntry.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.mft*), 489
`MFTFileName` (class in *volatility3.framework.symbols.windows.extensions.mft*), 491
`MFTFileName.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.mft*), 491
`MFTScan` (class in *volatility3.plugins.windows.mftscan*), 720
`minimum_address` (*AVMLLayer* property), 187
`minimum_address` (*BufferDataLayer* property), 231
`minimum_address` (*DataLayerInterface* property), 160
`minimum_address` (*Elf64Layer* property), 197
`minimum_address` (*FileLayer* property), 234
`minimum_address` (*Intel* attribute), 201
`minimum_address` (*Intel32e* attribute), 203
`minimum_address` (*IntelPAE* attribute), 206
`minimum_address` (*LimeLayer* property), 220
`minimum_address` (*LinearlyMappedLayer* property), 223
`minimum_address` (*NonLinearlySegmentedLayer* prop-

- erty), 245
- minimum_address (*PdbMSFStream* property), 226
- minimum_address (*PdbMultiStreamFormat* property), 229
- minimum_address (*QemuSuspendLayer* property), 237
- minimum_address (*RegistryHive* property), 240
- minimum_address (*SegmentedLayer* property), 247
- minimum_address (*TranslationLayerInterface* property), 164
- minimum_address (*VmwareLayer* property), 250
- minimum_address (*WindowsCrashDump32Layer* property), 191
- minimum_address (*WindowsCrashDump64Layer* property), 194
- minimum_address (*WindowsIntel* attribute), 209
- minimum_address (*WindowsIntel32e* attribute), 212
- minimum_address (*WindowsIntelPAE* attribute), 215
- minimum_address (*WindowsMixin* attribute), 217
- minimum_address (*XenCoreDumpLayer* property), 253
- minor (*super_block* property), 381
- MINORBITS (*super_block* attribute), 379
- MissingModuleException, 564
- mm_struct (class in *volatility3.framework.symbols.linux.extensions*), 356
- mm_struct.VolTemplateProxy (class in *volatility3.framework.symbols.linux.extensions*), 356
- MMVAD (class in *volatility3.framework.symbols.windows.extensions*), 463
- MMVAD.VolTemplateProxy (class in *volatility3.framework.symbols.windows.extensions*), 463
- MMVAD_SHORT (class in *volatility3.framework.symbols.windows.extensions*), 465
- MMVAD_SHORT.VolTemplateProxy (class in *volatility3.framework.symbols.windows.extensions*), 466
- MNT_FLAGS (*mount* attribute), 362
- mnt_id (*MountInfoData* attribute), 605
- mnt_namespace (class in *volatility3.framework.symbols.linux.extensions*), 358
- mnt_namespace.VolTemplateProxy (class in *volatility3.framework.symbols.linux.extensions*), 358
- MNT_NOATIME (*mount* attribute), 362
- MNT_NODEV (*mount* attribute), 362
- MNT_NODIRATIME (*mount* attribute), 362
- MNT_NOEXEC (*mount* attribute), 362
- MNT_NOSUID (*mount* attribute), 362
- mnt_opts (*MountInfoData* attribute), 605
- MNT_READONLY (*mount* attribute), 362
- MNT_RELATIME (*mount* attribute), 362
- mnt_root_path (*MountInfoData* attribute), 605
- MNT_SHARED (*mount* attribute), 362
- MNT_SHRINKABLE (*mount* attribute), 363
- mnt_type (*MountInfoData* attribute), 605
- MNT_UNBINDABLE (*mount* attribute), 363
- MNT_WRITE_HOLD (*mount* attribute), 363
- mod_mem_type (*module* property), 362
- MODIFIED (*TimeLinerType* attribute), 784
- ModScan (class in *volatility3.plugins.windows.modscan*), 722
- module
 - volatility3, 47
 - volatility3.cli, 48
 - volatility3.cli.text_filter, 64
 - volatility3.cli.text_renderer, 64
 - volatility3.cli.volargparse, 68
 - volatility3.cli.volshell, 49
 - volatility3.cli.volshell.generic, 51
 - volatility3.cli.volshell.linux, 55
 - volatility3.cli.volshell.mac, 58
 - volatility3.cli.volshell.windows, 61
 - volatility3.framework, 69
 - volatility3.framework.automagic, 70
 - volatility3.framework.automagic.construct_layers, 71
 - volatility3.framework.automagic.linux, 73
 - volatility3.framework.automagic.mac, 75
 - volatility3.framework.automagic.module, 78
 - volatility3.framework.automagic.pdbscan, 79
 - volatility3.framework.automagic.stacker, 83
 - volatility3.framework.automagic.symbol_cache, 86
 - volatility3.framework.automagic.symbol_finder, 91
 - volatility3.framework.automagic.windows, 93
 - volatility3.framework.configuration, 96
 - volatility3.framework.configuration.requirements, 96
 - volatility3.framework.constants, 120
 - volatility3.framework.constants.linux, 124
 - volatility3.framework.constants.windows, 127
 - volatility3.framework.contexts, 127
 - volatility3.framework.exceptions, 564
 - volatility3.framework.interfaces, 139
 - volatility3.framework.interfaces.automagic, 139

volatility3.framework.interfaces.configuration, 141

volatility3.framework.interfaces.context, 153

volatility3.framework.interfaces.layers, 158

volatility3.framework.interfaces.objects, 165

volatility3.framework.interfaces.plugins, 169

volatility3.framework.interfaces.renderers, 173

volatility3.framework.interfaces.symbols, 176

volatility3.framework.layers, 185

volatility3.framework.layers.avml, 186

volatility3.framework.layers.cloudstorage, 189

volatility3.framework.layers.codecs, 185

volatility3.framework.layers.crash, 189

volatility3.framework.layers.elf, 196

volatility3.framework.layers.intel, 199

volatility3.framework.layers.leechcore, 219

volatility3.framework.layers.lime, 219

volatility3.framework.layers.linear, 222

volatility3.framework.layers.msf, 225

volatility3.framework.layers.physical, 230

volatility3.framework.layers.qemu, 235

volatility3.framework.layers.registry, 238

volatility3.framework.layers.resources, 242

volatility3.framework.layers.scanners, 185

volatility3.framework.layers.scanners.multiregexp, 186

volatility3.framework.layers.segmented, 244

volatility3.framework.layers.vmware, 248

volatility3.framework.layers.xen, 251

volatility3.framework.objects, 254

volatility3.framework.objects.templates, 303

volatility3.framework.objects.utility, 305

volatility3.framework.plugins, 306

volatility3.framework.renderers, 306

volatility3.framework.renderers.conversion, 309

volatility3.framework.renderers.format_hints, 310

volatility3.framework.symbols, 321

volatility3.framework.symbols.generic, 324

volatility3.framework.symbols.intermed, 531

volatility3.framework.symbols.linux, 326

volatility3.framework.symbols.linux.bash, 405

volatility3.framework.symbols.linux.extensions, 331

volatility3.framework.symbols.linux.extensions.bash, 395

volatility3.framework.symbols.linux.extensions.elf, 397

volatility3.framework.symbols.mac, 408

volatility3.framework.symbols.mac.extensions, 412

volatility3.framework.symbols.metadata, 561

volatility3.framework.symbols.native, 562

volatility3.framework.symbols.windows, 437

volatility3.framework.symbols.windows.extensions, 440

volatility3.framework.symbols.windows.extensions.crash, 478

volatility3.framework.symbols.windows.extensions.kdbg, 480

volatility3.framework.symbols.windows.extensions.mbr, 482

volatility3.framework.symbols.windows.extensions.mft, 487

volatility3.framework.symbols.windows.extensions.network, 493

volatility3.framework.symbols.windows.extensions.pe, 493

volatility3.framework.symbols.windows.extensions.pool, 497

volatility3.framework.symbols.windows.extensions.regis, 508

volatility3.framework.symbols.windows.extensions.servi, 520

volatility3.framework.symbols.windows.pdbconv, 525

volatility3.framework.symbols.windows.pdbutil, 527

volatility3.framework.symbols.windows.versions, 530

volatility3.framework.symbols.wrappers, 564

volatility3.plugins, 567

volatility3.plugins.banners, 775

volatility3.plugins.configwriter, 777

volatility3.plugins.frameworkinfo, 779

volatility3.plugins.isfinfo, 780

volatility3.plugins.layerwriter, 782
volatility3.plugins.linux, 567
volatility3.plugins.linux.bash, 567
volatility3.plugins.linux.capabilities, 569
volatility3.plugins.linux.check_afinfo, 572
volatility3.plugins.linux.check_creds, 573
volatility3.plugins.linux.check_idt, 575
volatility3.plugins.linux.check_modules, 576
volatility3.plugins.linux.check_syscall, 578
volatility3.plugins.linux.elfs, 580
volatility3.plugins.linux.envvars, 582
volatility3.plugins.linux.iomem, 583
volatility3.plugins.linux.keyboard_notifiers, 585
volatility3.plugins.linux.kmsg, 587
volatility3.plugins.linux.library_list, 596
volatility3.plugins.linux.lsmod, 598
volatility3.plugins.linux.lsof, 600
volatility3.plugins.linux.malfind, 601
volatility3.plugins.linux.mountinfo, 603
volatility3.plugins.linux.proc, 606
volatility3.plugins.linux.psaux, 608
volatility3.plugins.linux.pslist, 609
volatility3.plugins.linux.psscan, 612
volatility3.plugins.linux.pstree, 614
volatility3.plugins.linux.sockstat, 616
volatility3.plugins.linux.tty_check, 618
volatility3.plugins.linux.vmayarascan, 619
volatility3.plugins.mac, 621
volatility3.plugins.mac.bash, 621
volatility3.plugins.mac.check_syscall, 623
volatility3.plugins.mac.check_sysctl, 625
volatility3.plugins.mac.check_trap_table, 626
volatility3.plugins.mac.dmesg, 628
volatility3.plugins.mac.ifconfig, 630
volatility3.plugins.mac.kauth_listeners, 631
volatility3.plugins.mac.kauth_scopes, 633
volatility3.plugins.mac.kevents, 634
volatility3.plugins.mac.list_files, 637
volatility3.plugins.mac.lsmod, 638
volatility3.plugins.mac.lsof, 640
volatility3.plugins.mac.malfind, 642
volatility3.plugins.mac.mount, 643
volatility3.plugins.mac.netstat, 645
volatility3.plugins.mac.proc_maps, 647
volatility3.plugins.mac.psaux, 649
volatility3.plugins.mac.pslist, 651
volatility3.plugins.mac.pstree, 654
volatility3.plugins.mac.socket_filters, 656
volatility3.plugins.mac.timers, 657
volatility3.plugins.mac.trustedbsd, 659
volatility3.plugins.mac.vfsevents, 661
volatility3.plugins.timeliner, 784
volatility3.plugins.windows, 662
volatility3.plugins.windows.bigpools, 671
volatility3.plugins.windows.cachedump, 673
volatility3.plugins.windows.callbacks, 675
volatility3.plugins.windows.cmdline, 678
volatility3.plugins.windows.crashinfo, 680
volatility3.plugins.windows.devicetree, 681
volatility3.plugins.windows.dlllist, 683
volatility3.plugins.windows.driverirp, 685
volatility3.plugins.windows.drivermodule, 686
volatility3.plugins.windows.driverscan, 688
volatility3.plugins.windows.dumpfiles, 690
volatility3.plugins.windows.envvars, 692
volatility3.plugins.windows.filescan, 694
volatility3.plugins.windows.getservicesids, 696
volatility3.plugins.windows.getsids, 697
volatility3.plugins.windows.handles, 699
volatility3.plugins.windows.hashdump, 701
volatility3.plugins.windows.iat, 704
volatility3.plugins.windows.info, 706
volatility3.plugins.windows.joblinks, 708
volatility3.plugins.windows.ldrmodules, 710
volatility3.plugins.windows.lsadump, 711
volatility3.plugins.windows.malfind, 713
volatility3.plugins.windows.mbrscan, 715
volatility3.plugins.windows.memmap, 717
volatility3.plugins.windows.mftscan, 719
volatility3.plugins.windows.modscan, 722
volatility3.plugins.windows.modules, 724
volatility3.plugins.windows.mutantscan, 727
volatility3.plugins.windows.netscan, 729
volatility3.plugins.windows.netstat, 731

- volatility3.plugins.windows.poolscanner, 736
 - volatility3.plugins.windows.privileges, 741
 - volatility3.plugins.windows.plist, 743
 - volatility3.plugins.windows.psscan, 746
 - volatility3.plugins.windows.pstree, 749
 - volatility3.plugins.windows.registry, 663
 - volatility3.plugins.windows.registry.hivelist, 663
 - volatility3.plugins.windows.registry.hivesman, 665
 - volatility3.plugins.windows.registry.printkey, 667
 - volatility3.plugins.windows.registry.userassist, 669
 - volatility3.plugins.windows.sessions, 750
 - volatility3.plugins.windows.skeleton_key_checker, 752
 - volatility3.plugins.windows.ssdt, 753
 - volatility3.plugins.windows.strings, 755
 - volatility3.plugins.windows.svcscan, 757
 - volatility3.plugins.windows.symlinkscan, 760
 - volatility3.plugins.windows.thrdsan, 762
 - volatility3.plugins.windows.truecrypt, 764
 - volatility3.plugins.windows.vadinfo, 766
 - volatility3.plugins.windows.vadwalk, 768
 - volatility3.plugins.windows.vadyarasan, 770
 - volatility3.plugins.windows.verinfo, 772
 - volatility3.plugins.windows.virtmap, 774
 - volatility3.plugins.yarascan, 787
 - volatility3.schemas, 789
 - volatility3.symbols, 790
 - Module (class in volatility3.framework.contexts), 132
 - module (class in volatility3.framework.symbols.linux.extensions), 359
 - module() (Context method), 131
 - module() (ContextInterface method), 154
 - module.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 360
 - module_from_pdb() (PDBUtility class method), 528
 - ModuleCollection (class in volatility3.framework.contexts), 135
 - ModuleContainer (class in volatility3.framework.interfaces.context), 155
 - ModuleInterface (class in volatility3.framework.interfaces.context), 155
 - ModuleRequirement (class in volatility3.framework.configuration.requirements), 107
 - Modules (class in volatility3.plugins.windows.modules), 724
 - modules (Context property), 131
 - modules (ContextInterface property), 154
 - modules (ModuleCollection property), 135
 - mount (class in volatility3.framework.symbols.linux.extensions), 362
 - Mount (class in volatility3.plugins.mac.mount), 643
 - Mount.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 363
 - MountInfo (class in volatility3.plugins.linux.mountinfo), 603
 - MountInfoData (class in volatility3.plugins.linux.mountinfo), 605
 - MT_FLAGS_HEIGHT_MASK (maple_tree attribute), 354
 - MT_FLAGS_HEIGHT_OFFSET (maple_tree attribute), 354
 - Multiprocessing (Parallelism attribute), 122
 - MultiRegex (class in volatility3.framework.layers.scanners.multiregexp), 186
 - MultiRequirement (class in volatility3.framework.configuration.requirements), 109
 - MultiStringScanner (class in volatility3.framework.layers.scanners), 185
 - MultiTypeData (class in volatility3.framework.renderers.format_hints), 317
 - multitypedata_as_text() (in module volatility3.cli.text_renderer), 67
 - MutantScan (class in volatility3.plugins.windows.mutantscan), 727
 - MuteProgress (class in volatility3.cli), 49
- ## N
- name (AVMLLayer property), 188
 - name (BooleanRequirement property), 97
 - name (BufferDataLayer property), 231
 - name (BytesRequirement property), 98
 - name (ChoiceRequirement property), 100
 - name (ClassRequirement property), 142
 - name (CLIRenderer attribute), 65
 - name (CMHIVE property), 510
 - name (Column attribute), 173
 - name (ComplexListRequirement property), 101
 - name (ConfigurableModule property), 129
 - name (ConfigurableRequirementInterface property), 145
 - name (ConstructableRequirementInterface property), 147
 - name (CSVRenderer attribute), 65
 - name (DataLayerInterface property), 160
 - name (Elf64Layer property), 197

- name (*FileLayer* property), 234
- name (*Intel* property), 201
- name (*Intel32e* property), 203
- name (*IntelPAE* property), 206
- name (*IntRequirement* property), 103
- name (*JsonLinesRenderer* attribute), 65
- name (*JsonRenderer* attribute), 66
- name (*LayerListRequirement* property), 104
- name (*LimeLayer* property), 220
- name (*LinearlyMappedLayer* property), 224
- name (*ListRequirement* property), 106
- name (*Module* property), 133
- name (*ModuleInterface* property), 157
- name (*ModuleRequirement* property), 108
- name (*MultiRequirement* property), 109
- name (*NoneRenderer* attribute), 66
- name (*NonLinearlySegmentedLayer* property), 245
- name (*PdbMSFStream* property), 226
- name (*PdbMultiStreamFormat* property), 229
- name (*PluginRequirement* property), 111
- name (*PrettyTextRenderer* attribute), 66
- name (*ProducerMetadata* property), 561
- name (*QemuSuspendLayer* property), 237
- name (*QuickTextRenderer* attribute), 67
- name (*RegistryHive* property), 240
- name (*RequirementInterface* property), 150
- name (*SegmentedLayer* property), 247
- name (*SimpleTypeRequirement* property), 152
- name (*SizedModule* property), 137
- name (*StringRequirement* property), 113
- name (*SymbolInterface* property), 180
- name (*SymbolTableRequirement* property), 114
- name (*TranslationLayerInterface* property), 164
- name (*TranslationLayerRequirement* property), 116
- name (*URIRequirement* property), 118
- name (*VersionRequirement* property), 119
- name (*VmwareLayer* property), 250
- name (*WindowsCrashDump32Layer* property), 191
- name (*WindowsCrashDump64Layer* property), 194
- name (*WindowsIntel* property), 209
- name (*WindowsIntel32e* property), 212
- name (*WindowsIntelPAE* property), 215
- name (*WindowsMixin* property), 218
- name (*XenCoreDumpLayer* property), 253
- name_as_str() (*qstr* method), 373
- name_strip() (*PdbReader* method), 526
- NameInfo (*OBJECT_HEADER* property), 499
- natives (*BaseSymbolTableInterface* property), 178
- natives (*BashIntermedSymbols* property), 407
- natives (*IntermediateSymbolTable* property), 536
- natives (*ISFormatTable* property), 533
- natives (*LinuxKernelIntermedSymbols* property), 329
- natives (*MacKernelIntermedSymbols* property), 410
- natives (*NativeTable* property), 563
- natives (*NativeTableInterface* property), 179
- natives (*SymbolTableInterface* property), 184
- natives (*Version1Format* property), 539
- natives (*Version2Format* property), 542
- natives (*Version3Format* property), 545
- natives (*Version4Format* property), 548
- natives (*Version5Format* property), 551
- natives (*Version6Format* property), 554
- natives (*Version7Format* property), 557
- natives (*Version8Format* property), 560
- natives (*WindowsKernelIntermedSymbols* property), 439
- NativeTable (class in *volatility3.framework.symbols.native*), 562
- NativeTableInterface (class in *volatility3.framework.interfaces.symbols*), 178
- net (class in *volatility3.framework.symbols.linux.extensions*), 366
- net.VolTemplateProxy (class in *volatility3.framework.symbols.linux.extensions*), 366
- netlink_sock (class in *volatility3.framework.symbols.linux.extensions*), 368
- netlink_sock.VolTemplateProxy (class in *volatility3.framework.symbols.linux.extensions*), 368
- NetScan (class in *volatility3.plugins.windows.netscan*), 729
- Netstat (class in *volatility3.plugins.mac.netstat*), 645
- NetStat (class in *volatility3.plugins.windows.netstat*), 731
- new_requirement() (*ComplexListRequirement* method), 101
- new_requirement() (*LayerListRequirement* method), 104
- next_peer() (*mount* method), 366
- non_cached_schemes() (*JarHandler* class method), 242
- non_cached_schemes() (*OfflineHandler* class method), 242
- non_cached_schemes() (*VolatilityHandler* class method), 243
- NoneRenderer (class in *volatility3.cli.text_renderer*), 66
- NonInheritable (class in *volatility3.framework*), 69
- NonLinearlySegmentedLayer (class in *volatility3.framework.layers.segmented*), 244
- NONPAGED (*PoolType* attribute), 739
- NotApplicableValue (class in *volatility3.framework.renderers*), 306
- NotAvailableValue (class in *volatility3.framework.renderers*), 306
- nsec_to_sec_str() (*ABCKmsg* method), 587
- nsec_to_sec_str() (*Kmsg_3_11_to_5_10* method), 590

- `nsec_to_sec_str()` (*Kmsg_3_5_to_3_11 method*), 592
- `nsec_to_sec_str()` (*Kmsg_5_10_to_ method*), 594
- `nsec_to_sec_str()` (*Kmsg_pre_3_5 method*), 595
- `NullFileHandler` (class in *volatility3.cli.volshell.generic*), 51
- `num_symtab` (module property), 362
- `numerator` (*Bin attribute*), 311
- `numerator` (*BitField attribute*), 260
- `numerator` (*Boolean attribute*), 263
- `numerator` (*Char attribute*), 272
- `numerator` (*ELF_CLASS attribute*), 125
- `numerator` (*ELF_IDENT attribute*), 127
- `numerator` (*Enumeration attribute*), 278
- `numerator` (*Hex attribute*), 313
- `numerator` (*Integer attribute*), 285
- `numerator` (*Parallelism attribute*), 123
- `numerator` (*Pointer attribute*), 288
- `numerator` (*PoolType attribute*), 740
- `numerator` (*RegKeyFlags attribute*), 519
- `numerator` (*TimeLinerType attribute*), 785
- ## O
- `object()` (*ConfigurableModule method*), 129
- `object()` (*Context method*), 131
- `object()` (*ContextInterface method*), 154
- `object()` (*Module method*), 134
- `object()` (*ModuleInterface method*), 157
- `object()` (*SizedModule method*), 137
- `object_from_symbol()` (*ConfigurableModule method*), 129
- `object_from_symbol()` (*Module method*), 134
- `object_from_symbol()` (*ModuleInterface method*), 157
- `object_from_symbol()` (*SizedModule method*), 138
- `OBJECT_HEADER` (class in *volatility3.framework.symbols.windows.extensions.pool*), 499
- `OBJECT_HEADER.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions.pool*), 499
- `OBJECT_SYMBOLIC_LINK` (class in *volatility3.framework.symbols.windows.extensions*), 468
- `OBJECT_SYMBOLIC_LINK.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions*), 468
- `ObjectInformation` (class in *volatility3.framework.interfaces.objects*), 165
- `ObjectInterface` (class in *volatility3.framework.interfaces.objects*), 166
- `ObjectInterface.VolTemplateProxy` (class in *volatility3.framework.interfaces.objects*), 166
- `ObjectTemplate` (class in *volatility3.framework.objects.templates*), 303
- `odd_parity` (*Hashdump attribute*), 703
- `Off` (*Parallelism attribute*), 122
- `OFFLINE` (in module *volatility3.framework.constants*), 121
- `OfflineException`, 565
- `OfflineHandler` (class in *volatility3.framework.layers.resources*), 242
- `offset` (*ConfigurableModule property*), 130
- `offset` (*Module property*), 134
- `offset` (*ModuleInterface property*), 158
- `offset` (*SizedModule property*), 138
- `omap_lookup()` (*PdbReader method*), 526
- `open` (*ADS property*), 719
- `open` (*Banners property*), 776
- `open` (*Bash property*), 568, 622
- `open` (*BigPools property*), 672
- `open` (*Cachedump property*), 674
- `open` (*Callbacks property*), 677
- `open` (*Capabilities property*), 570
- `open` (*Check_afinfo property*), 572
- `open` (*Check_creds property*), 574
- `open` (*Check_idt property*), 576
- `open` (*Check_modules property*), 577
- `open` (*Check_syscall property*), 579, 624
- `open` (*Check_sysctl property*), 625
- `open` (*Check_trap_table property*), 627
- `open` (*CmdLine property*), 679
- `open` (*ConfigWriter property*), 778
- `open` (*Crashinfo property*), 680
- `open` (*DeviceTree property*), 682
- `open` (*DllList property*), 684
- `open` (*Dmesg property*), 629
- `open` (*DriverIrp property*), 686
- `open` (*DriverModule property*), 687
- `open` (*DriverScan property*), 689
- `open` (*DumpFiles property*), 691
- `open` (*Elfs property*), 581
- `open` (*Envars property*), 582, 693
- `open` (*FileScan property*), 695
- `open` (*FrameworkInfo property*), 779
- `open` (*GetServiceSIDs property*), 696
- `open` (*GetSIDs property*), 698
- `open` (*Handles property*), 701
- `open` (*Hashdump property*), 703
- `open` (*HiveList property*), 665
- `open` (*HiveScan property*), 666
- `open` (*IAT property*), 705
- `open` (*Ifconfig property*), 630
- `open` (*Info property*), 707
- `open` (*IOMem property*), 584
- `open` (*IsfInfo property*), 781
- `open` (*JobLinks property*), 709

- open (*Kauth_listeners property*), 632
- open (*Kauth_scopes property*), 634
- open (*Kevents property*), 636
- open (*Keyboard_notifiers property*), 586
- open (*Kmsg property*), 589
- open (*LayerWriter property*), 783
- open (*LdrModules property*), 710
- open (*LibraryList property*), 597
- open (*List_Files property*), 637
- open (*Lsadbump property*), 712
- open (*Lsmdb property*), 599, 639
- open (*Lsof property*), 601, 641
- open (*Malfind property*), 602, 642, 714
- open (*Maps property*), 607, 648
- open (*MBRScan property*), 716
- open (*Memmap property*), 718
- open (*MFTScan property*), 721
- open (*ModScan property*), 723
- open (*Modules property*), 726
- open (*Mount property*), 644
- open (*MountInfo property*), 604
- open (*MutantScan property*), 727
- open (*NetScan property*), 730
- open (*NetStat property*), 734
- open (*Netstat property*), 646
- open (*Passphrase property*), 764
- open (*PluginInterface property*), 172
- open (*PoolScanner property*), 738
- open (*PrintKey property*), 668
- open (*Privs property*), 742
- open (*PsAux property*), 609
- open (*Psaux property*), 650
- open (*PsList property*), 611, 653, 744
- open (*PsScan property*), 613, 747
- open (*PsTree property*), 615, 655, 749
- open (*Sessions property*), 751
- open (*Skeleton_Key_Check property*), 753
- open (*Socket_filters property*), 657
- open (*Sockstat property*), 617
- open (*SSDT property*), 755
- open (*Strings property*), 757
- open (*SvcScan property*), 759
- open (*SymlinkScan property*), 760
- open (*ThrdScan property*), 762
- open (*Timeliner property*), 787
- open (*Timers property*), 658
- open (*Trustedbsd property*), 660
- open (*tty_check property*), 619
- open (*UserAssist property*), 670
- open (*VadInfo property*), 767
- open (*VadWalk property*), 769
- open (*VadYaraScan property*), 771
- open (*VerInfo property*), 773
- open (*VFSevents property*), 661
- open (*VirtMap property*), 775
- open (*VmaYaraScan property*), 620
- open (*Volshell property*), 54, 57, 60, 63
- open (*YaraScan property*), 788
- open() (*ResourceAccessor method*), 243
- operating_system (*IdentifierProcessor attribute*), 87
- operating_system (*LinuxIdentifier attribute*), 87
- operating_system (*LinuxSymbolFinder attribute*), 75
- operating_system (*MacIdentifier attribute*), 88
- operating_system (*MacSymbolFinder attribute*), 77
- operating_system (*SymbolFinder attribute*), 93
- operating_system (*WindowsIdentifier attribute*), 91
- optional (*BooleanRequirement property*), 97
- optional (*BytesRequirement property*), 98
- optional (*ChoiceRequirement property*), 100
- optional (*ClassRequirement property*), 142
- optional (*ComplexListRequirement property*), 101
- optional (*ConfigurableRequirementInterface property*), 145
- optional (*ConstructableRequirementInterface property*), 147
- optional (*IntRequirement property*), 103
- optional (*LayerListRequirement property*), 105
- optional (*ListRequirement property*), 106
- optional (*ModuleRequirement property*), 108
- optional (*MultiRequirement property*), 109
- optional (*PluginRequirement property*), 111
- optional (*RequirementInterface property*), 150
- optional (*SimpleTypeRequirement property*), 152
- optional (*StringRequirement property*), 113
- optional (*SymbolTableRequirement property*), 114
- optional (*TranslationLayerRequirement property*), 116
- optional (*URIRequirement property*), 118
- optional (*VersionRequirement property*), 119
- optional() (*in module volatility3.cli.text_renderer*), 68
- optional_set_type_class() (*BaseSymbolTableInterface method*), 178
- optional_set_type_class() (*BashIntermedSymbols method*), 407
- optional_set_type_class() (*IntermediateSymbolTable method*), 536
- optional_set_type_class() (*ISFormatTable method*), 533
- optional_set_type_class() (*LinuxKernelIntermedSymbols method*), 329
- optional_set_type_class() (*MacKernelIntermedSymbols method*), 410
- optional_set_type_class() (*NativeTable method*), 563
- optional_set_type_class() (*NativeTableInterface method*), 180
- optional_set_type_class() (*SymbolTableInterface method*), 184

- optional_set_type_class() (Version1Format method), 539
- optional_set_type_class() (Version2Format method), 542
- optional_set_type_class() (Version3Format method), 545
- optional_set_type_class() (Version4Format method), 548
- optional_set_type_class() (Version5Format method), 551
- optional_set_type_class() (Version6Format method), 554
- optional_set_type_class() (Version7Format method), 557
- optional_set_type_class() (Version8Format method), 560
- optional_set_type_class() (WindowsKernelIntermedSymbols method), 439
- order_extra_verbose_levels() (CommandLine method), 48
- order_extra_verbose_levels() (VolShell method), 50
- OsDistinguisher (class in volatility3.framework.symbols.windows.versions), 530
- output_result() (JsonLinesRenderer method), 65
- output_result() (JsonRenderer method), 66
- overlap (PageMapScanner attribute), 94
- overlap (PdbSignatureScanner attribute), 530
- owning_process() (ETHREAD method), 451
- ## P
- PACKAGE_VERSION (in module volatility3.framework.constants), 121
- packet_sock (class in volatility3.framework.symbols.linux.extensions), 369
- packet_sock.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 370
- PAGE_MASK (CONTROL_AREA attribute), 440
- page_mask (Intel attribute), 201
- page_mask (Intel32e attribute), 204
- page_mask (IntelPAE attribute), 206
- page_mask (WindowsIntel attribute), 209
- page_mask (WindowsIntel32e attribute), 212
- page_mask (WindowsIntelPAE attribute), 215
- page_mask (WindowsMixin attribute), 218
- page_shift (Intel attribute), 201
- page_shift (Intel32e attribute), 204
- page_shift (IntelPAE attribute), 206
- page_shift (WindowsIntel attribute), 209
- page_shift (WindowsIntel32e attribute), 212
- page_shift (WindowsIntelPAE attribute), 215
- page_shift (WindowsMixin attribute), 218
- PAGE_SIZE (CONTROL_AREA attribute), 440
- page_size (Intel attribute), 201
- page_size (Intel32e attribute), 204
- page_size (IntelPAE attribute), 206
- page_size (PdbMultiStreamFormat property), 229
- page_size (WindowsIntel attribute), 209
- page_size (WindowsIntel32e attribute), 212
- page_size (WindowsIntelPAE attribute), 215
- page_size (WindowsMixin attribute), 218
- PAGED (PoolType attribute), 739
- PagedInvalidAddressException, 565
- PageMapScanner (class in volatility3.framework.automagic.windows), 94
- Parallelism (class in volatility3.framework.constants), 121
- PARALLELISM (in module volatility3.framework.constants), 121
- parent (TreeNode property), 176, 309
- parent_e_type (elf_phdr property), 402
- parent_id (MountInfoData attribute), 605
- parent_offset (elf_phdr property), 402
- parent_path() (in module volatility3.framework.interfaces.configuration), 152
- parse_args() (HelpfulArgParser method), 68
- parse_bitmap() (NetStat class method), 734
- parse_cache_entry() (Cachedump static method), 674
- parse_decrypted_cache() (Cachedump static method), 674
- parse_hashtable() (NetStat class method), 734
- parse_intermixed_args() (HelpfulArgParser method), 68
- parse_known_args() (HelpfulArgParser method), 68
- parse_known_intermixed_args() (HelpfulArgParser method), 68
- parse_partitions() (NetStat class method), 735
- parse_resource() (IOMem class method), 584
- parse_string() (PdbReader static method), 526
- parse_userassist_data() (UserAssist method), 670
- partition() (Bytes method), 267
- partition() (HexBytes method), 315
- partition() (MultiTypeData method), 319
- partition() (String method), 295
- PARTITION_ENTRY (class in volatility3.framework.symbols.windows.extensions.mbr), 482
- PARTITION_ENTRY.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.mbr), 482
- PARTITION_TABLE (class in volatility3.framework.symbols.windows.extensions.mbr), 485
- PARTITION_TABLE.VolTemplateProxy

- (class in volatility3.framework.symbols.windows.extensions.mbr), 485
- Passphrase (class in volatility3.plugins.windows.truecrypt), 764
- path (*TreeNode* property), 176, 309
- path() (*dentry* method), 338
- path_changed() (*TreeNode* method), 176, 309
- path_depth (*TreeNode* property), 176, 309
- path_depth() (in module volatility3.framework.interfaces.configuration), 152
- path_depth() (*TreeGrid* static method), 175, 307
- path_for_file() (*LinuxUtilities* class method), 331
- path_head() (in module volatility3.framework.interfaces.configuration), 153
- path_join() (in module volatility3.framework.interfaces.configuration), 153
- path_root (*MountInfoData* attribute), 605
- path_sep (*TreeGrid* attribute), 307
- pci_hole_table (*QemuSuspendLayer* attribute), 237
- pdb_age (*WindowsMetadata* property), 562
- pdb_guid (*WindowsMetadata* property), 562
- pdb_layer_name (*PdbReader* property), 526
- pdb_symbol_table (*PdbMSFStream* property), 226
- pdb_symbol_table (*PdbMultiStreamFormat* property), 229
- PDBFormatException, 225
- PdbMSFStream (class in volatility3.framework.layers.msf), 225
- PdbMultiStreamFormat (class in volatility3.framework.layers.msf), 227
- pdbname_scan() (*PDBUtility* class method), 528
- PdbReader (class in volatility3.framework.symbols.windows.pdbconv), 525
- PdbRetreiver (class in volatility3.framework.symbols.windows.pdbconv), 527
- PdbSignatureScanner (class in volatility3.framework.symbols.windows.pdbutil), 529
- PDBUtility (class in volatility3.framework.symbols.windows.pdbutil), 527
- pe_version (*WindowsMetadata* property), 562
- pe_version_string (*WindowsMetadata* property), 562
- perm_flags (*vm_area_struct* attribute), 391
- PHYSICAL_DEFAULT (*PsList* attribute), 743
- physical_offset_from_virtual() (*PsScan* class method), 747
- pid (*TaskData* attribute), 571
- PluginInterface (class in volatility3.framework.interfaces.plugins), 171
- PluginRequirement (class in volatility3.framework.configuration.requirements), 110
- PluginRequirementException, 565
- PLUGINS_PATH (in module volatility3.framework.constants), 121
- PluginVersionException, 565
- Pointer (class in volatility3.framework.objects), 286
- Pointer.VolTemplateProxy (class in volatility3.framework.objects), 286
- pointer_to_string() (in module volatility3.framework.objects.utility), 305
- POOL_HEADER (class in volatility3.framework.symbols.windows.extensions.pool), 501
- POOL_HEADER.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.pool), 501
- POOL_HEADER_VISTA (class in volatility3.framework.symbols.windows.extensions.pool), 503
- POOL_HEADER_VISTA.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.pool), 504
- pool_scan() (*PoolScanner* class method), 738
- POOL_TRACKER_BIG_PAGES (class in volatility3.framework.symbols.windows.extensions.pool), 506
- POOL_TRACKER_BIG_PAGES.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.pool), 506
- pool_type_lookup (*POOL_TRACKER_BIG_PAGES* attribute), 508
- PoolConstraint (class in volatility3.plugins.windows.poolscanner), 736
- PoolHeaderScanner (class in volatility3.plugins.windows.poolscanner), 736
- PoolScanner (class in volatility3.plugins.windows.poolscanner), 736
- PoolType (class in volatility3.plugins.windows.poolscanner), 739
- populate() (*TreeGrid* method), 175, 307
- populate_config() (*CommandLine* method), 48
- populate_config() (*VolShell* method), 50
- populate_requirements_argparse() (*CommandLine* method), 49
- populate_requirements_argparse() (*VolShell* method), 50
- populated (*TreeGrid* property), 175, 308
- possible_architectures (*Disassembly* attribute), 173

`ppid` (*TaskData* attribute), 571
`preferred_filename` (*FileHandlerInterface* property), 170
`preferred_filename` (*NullFileHandler* property), 51
`preprocess()` (*MultiRegex* method), 186
`PrettyTextRenderer` (class in *volatility3.cli.text_renderer*), 66
`PrimitiveObject` (class in *volatility3.framework.objects*), 289
`PrimitiveObject.VolTemplateProxy` (class in *volatility3.framework.objects*), 289
`print_help()` (*HelpfulArgParser* method), 68
`print_usage()` (*HelpfulArgParser* method), 69
`PrintedProgress` (class in *volatility3.cli*), 49
`PrintKey` (class in *volatility3.plugins.windows.registry.printkey*), 667
`priority` (*AutomagicInterface* attribute), 140
`priority` (*ConstructionMagic* attribute), 72
`priority` (*KernelModule* attribute), 79
`priority` (*KernelPDBScanner* attribute), 82
`priority` (*LayerStacker* attribute), 85
`priority` (*LinuxSymbolFinder* attribute), 75
`priority` (*MacSymbolFinder* attribute), 77
`priority` (*SymbolCacheMagic* attribute), 91
`priority` (*SymbolFinder* attribute), 93
`priority` (*WinSwapLayers* attribute), 95
`privileges()` (*TOKEN* method), 474
`Privs` (class in *volatility3.plugins.windows.privileges*), 741
`proc` (class in *volatility3.framework.symbols.mac.extensions*), 419
`proc.VolTemplateProxy` (class in *volatility3.framework.symbols.mac.extensions*), 420
`proc_filters` (*Kevents* attribute), 636
`process()` (*RemoteIdentifierFormat* method), 88
`process_dump()` (*PsList* class method), 744
`process_exceptions()` (*CommandLine* method), 49
`process_exceptions()` (*VolShell* method), 50
`process_file_object()` (*DumpFiles* class method), 691
`process_index_array()` (*SHARED_CACHE_MAP* method), 472
`process_sock()` (*SockHandlers* method), 616
`process_types()` (*PdbReader* method), 526
`process_unsatisfied_exceptions()` (*CommandLine* method), 49
`process_unsatisfied_exceptions()` (*VolShell* method), 50
`process_v1()` (*RemoteIdentifierFormat* method), 88
`process_yara_options()` (*YaraScan* class method), 788
`producer` (*BashIntermedSymbols* property), 407
`producer` (*IntermediateSymbolTable* property), 537
`producer` (*ISFormatTable* property), 533
`producer` (*LinuxKernelIntermedSymbols* property), 329
`producer` (*MacKernelIntermedSymbols* property), 411
`producer` (*Version1Format* property), 539
`producer` (*Version2Format* property), 542
`producer` (*Version3Format* property), 545
`producer` (*Version4Format* property), 548
`producer` (*Version5Format* property), 551
`producer` (*Version6Format* property), 554
`producer` (*Version7Format* property), 557
`producer` (*Version8Format* property), 560
`producer` (*WindowsKernelIntermedSymbols* property), 439
`ProducerMetadata` (class in *volatility3.framework.symbols.metadata*), 561
`ProgressCallback` (in module *volatility3.framework.constants*), 123
`protect_values()` (*VadInfo* class method), 767
`provides` (*LinuxKernelIntermedSymbols* attribute), 329
`provides` (*MacKernelIntermedSymbols* attribute), 411
`provides` (*WindowsCrashDump32Layer* attribute), 191
`provides` (*WindowsCrashDump64Layer* attribute), 194
`PsAux` (class in *volatility3.plugins.linux.psaux*), 608
`Psaux` (class in *volatility3.plugins.mac.psaux*), 649
`PsList` (class in *volatility3.plugins.linux.pslist*), 609
`PsList` (class in *volatility3.plugins.mac.pslist*), 651
`PsList` (class in *volatility3.plugins.windows.pslist*), 743
`pslist_methods` (*PsList* attribute), 653
`PsScan` (class in *volatility3.plugins.linux.psscan*), 612
`PsScan` (class in *volatility3.plugins.windows.psscan*), 746
`PsTree` (class in *volatility3.plugins.linux.pstree*), 614
`PsTree` (class in *volatility3.plugins.mac.pstree*), 654
`PsTree` (class in *volatility3.plugins.windows.pstree*), 749
`PYTHONPATH`, 23

Q

`QemuStacker` (class in *volatility3.framework.layers.qemu*), 235
`QemuSuspendLayer` (class in *volatility3.framework.layers.qemu*), 235
`QEVm_CONFIGURATION` (*QemuSuspendLayer* attribute), 235
`QEVm_EOF` (*QemuSuspendLayer* attribute), 235
`QEVm_SECTION_END` (*QemuSuspendLayer* attribute), 235
`QEVm_SECTION_FOOTER` (*QemuSuspendLayer* attribute), 235
`QEVm_SECTION_FULL` (*QemuSuspendLayer* attribute), 235
`QEVm_SECTION_PART` (*QemuSuspendLayer* attribute), 235
`QEVm_SECTION_START` (*QemuSuspendLayer* attribute), 235
`QEVm_SUBSECTION` (*QemuSuspendLayer* attribute), 235

- QEMU_VMDESCRIPTION (*QemuSuspendLayer* attribute), 236
- qstr (class in *volatility3.framework.symbols.linux.extensions*), 371
- qstr.VolTemplateProxy (class in *volatility3.framework.symbols.linux.extensions*), 371
- queue_entry (class in *volatility3.framework.symbols.mac.extensions*), 421
- queue_entry.VolTemplateProxy (class in *volatility3.framework.symbols.mac.extensions*), 422
- QuickTextRenderer (class in *volatility3.cli.text_renderer*), 67
- quoted_optional() (in module *volatility3.cli.text_renderer*), 68
- R**
- random_string() (*Volshell* method), 54, 57, 60, 63
- read() (*AVMLLayer* method), 188
- read() (*BufferDataLayer* method), 231
- read() (*DataLayerInterface* method), 160
- read() (*Elf64Layer* method), 197
- read() (*FileHandlerInterface* method), 170
- read() (*FileLayer* method), 234
- read() (*Intel* method), 201
- read() (*Intel32e* method), 204
- read() (*IntelPAE* method), 206
- read() (*LayerContainer* method), 162
- read() (*LimeLayer* method), 220
- read() (*LinearlyMappedLayer* method), 224
- read() (*NonLinearlySegmentedLayer* method), 245
- read() (*NullFileHandler* method), 51
- read() (*PdbMSFStream* method), 226
- read() (*PdbMultiStreamFormat* method), 229
- read() (*QemuSuspendLayer* method), 237
- read() (*RegistryHive* method), 240
- read() (*SegmentedLayer* method), 247
- read() (*TranslationLayerInterface* method), 164
- read() (*VmwareLayer* method), 250
- read() (*WindowsCrashDump32Layer* method), 191
- read() (*WindowsCrashDump64Layer* method), 194
- read() (*WindowsIntel* method), 209
- read() (*WindowsIntel32e* method), 212
- read() (*WindowsIntelPAE* method), 215
- read() (*WindowsMixin* method), 218
- read() (*XenCoreDumpLayer* method), 253
- read1() (*NullFileHandler* method), 51
- read_dbi_stream() (*PdbReader* method), 526
- read_ipi_stream() (*PdbReader* method), 526
- read_necessary_streams() (*PdbReader* method), 526
- read_pdb_info_stream() (*PdbReader* method), 526
- read_pointer() (*NetStat* class method), 735
- read_streams() (*PdbMultiStreamFormat* method), 229
- read_symbol_stream() (*PdbReader* method), 527
- read_tpi_stream() (*PdbReader* method), 527
- readable() (*FileHandlerInterface* method), 170
- readable() (*NullFileHandler* method), 51
- readall() (*FileHandlerInterface* method), 170
- readall() (*NullFileHandler* method), 51
- readinto() (*FileHandlerInterface* method), 170
- readinto() (*NullFileHandler* method), 51
- readinto1() (*NullFileHandler* method), 52
- readline() (*FileHandlerInterface* method), 170
- readline() (*NullFileHandler* method), 52
- readlines() (*FileHandlerInterface* method), 170
- readlines() (*NullFileHandler* method), 52
- ReadOnlyMapping (class in *volatility3.framework.interfaces.objects*), 168
- real (*Bin* attribute), 311
- real (*BitField* attribute), 260
- real (*Boolean* attribute), 263
- real (*Char* attribute), 272
- real (*ELF_CLASS* attribute), 125
- real (*ELF_IDENT* attribute), 127
- real (*Enumeration* attribute), 278
- real (*Float* attribute), 281
- real (*Hex* attribute), 313
- real (*Integer* attribute), 285
- real (*Parallelism* attribute), 123
- real (*Pointer* attribute), 289
- real (*PoolType* attribute), 741
- real (*RegKeyFlags* attribute), 519
- real (*TimeLinerType* attribute), 785
- reconstruct() (*IMAGE_DOS_HEADER* method), 495
- record_cached_validations() (in module *volatility3.schemas*), 789
- recurse_symbol_fulfiller() (*KernelPDBScanner* method), 82
- reference_count() (*kobject* method), 351
- ReferenceTemplate (class in *volatility3.framework.objects.templates*), 304
- REG_BINARY (*RegValueTypes* attribute), 520
- REG_DWORD (*RegValueTypes* attribute), 520
- REG_DWORD_BIG_ENDIAN (*RegValueTypes* attribute), 520
- REG_EXPAND_SZ (*RegValueTypes* attribute), 520
- REG_FULL_RESOURCE_DESCRIPTOR (*RegValueTypes* attribute), 520
- REG_LINK (*RegValueTypes* attribute), 520
- REG_MULTI_SZ (*RegValueTypes* attribute), 520
- REG_NONE (*RegValueTypes* attribute), 520
- REG_QWORD (*RegValueTypes* attribute), 520
- REG_RESOURCE_LIST (*RegValueTypes* attribute), 520
- REG_RESOURCE_REQUIREMENTS_LIST (*RegValueTypes* attribute), 520
- REG_SZ (*RegValueTypes* attribute), 520

REG_UNKNOWN (*RegValueTypes* attribute), 520
 RegExScanner (class in *volatility3.framework.layers.scanners*), 185
 register() (*HelpfulArgParser* method), 69
 RegistryFormatException, 238
 RegistryHive (class in *volatility3.framework.layers.registry*), 238
 RegistryInvalidIndex, 241
 RegKeyFlags (class in *volatility3.framework.symbols.windows.extensions.registry*), 518
 RegValueTypes (class in *volatility3.framework.symbols.windows.extensions.registry*), 520
 relative_child_offset() (Aggregate-*Type.VolTemplateProxy* class method), 255
 relative_child_offset() (*Array.VolTemplateProxy* class method), 256
 relative_child_offset() (*BitField.VolTemplateProxy* class method), 258
 relative_child_offset() (*Boolean.VolTemplateProxy* class method), 261
 relative_child_offset() (*bpf_prog.VolTemplateProxy* class method), 332
 relative_child_offset() (*bt_sock.VolTemplateProxy* class method), 334
 relative_child_offset() (*Bytes.VolTemplateProxy* class method), 265
 relative_child_offset() (*Char.VolTemplateProxy* class method), 270
 relative_child_offset() (*ClassType.VolTemplateProxy* class method), 273
 relative_child_offset() (*CM_KEY_BODY.VolTemplateProxy* class method), 511
 relative_child_offset() (*CM_KEY_NODE.VolTemplateProxy* class method), 513
 relative_child_offset() (*CM_KEY_VALUE.VolTemplateProxy* class method), 515
 relative_child_offset() (*CMHIVE.VolTemplateProxy* class method), 509
 relative_child_offset() (*CONTROL_AREA.VolTemplateProxy* class method), 441
 relative_child_offset() (*cred.VolTemplateProxy* class method), 335
 relative_child_offset() (*dentry.VolTemplateProxy* class method), 337
 relative_child_offset() (*DEVICE_OBJECT.VolTemplateProxy* class method), 443
 relative_child_offset() (*DRIVER_OBJECT.VolTemplateProxy* class method), 445
 relative_child_offset() (*elf.VolTemplateProxy* class method), 397
 relative_child_offset() (*elf_linkmap.VolTemplateProxy* class method), 399
 relative_child_offset() (*elf_phdr.VolTemplateProxy* class method), 401
 relative_child_offset() (*elf_sym.VolTemplateProxy* class method), 403
 relative_child_offset() (*Enumeration.VolTemplateProxy* class method), 275
 relative_child_offset() (*EPROCESS.VolTemplateProxy* class method), 447
 relative_child_offset() (*ETHREAD.VolTemplateProxy* class method), 450
 relative_child_offset() (*EX_FAST_REF.VolTemplateProxy* class method), 452
 relative_child_offset() (*ExecutiveObject.VolTemplateProxy* class method), 498
 relative_child_offset() (*FILE_OBJECT.VolTemplateProxy* class method), 454
 relative_child_offset() (*fileglob.VolTemplateProxy* class method), 413
 relative_child_offset() (*files_struct.VolTemplateProxy* class method), 339
 relative_child_offset() (*Float.VolTemplateProxy* class method), 279
 relative_child_offset() (*fs_struct.VolTemplateProxy* class method), 341
 relative_child_offset() (*Function.VolTemplateProxy* class method), 281
 relative_child_offset() (*GenericIntelProcess.VolTemplateProxy* class method), 325
 relative_child_offset() (*hist_entry.VolTemplateProxy* class method), 395
 relative_child_offset() (*HMAP_ENTRY.VolTemplateProxy* class method), 517

`relative_child_offset()` (*ifnet.VolTemplateProxy* class method), 415
`relative_child_offset()` (*IM-AGE_DOS_HEADER.VolTemplateProxy* class method), 493
`relative_child_offset()` (*IM-AGE_NT_HEADERS.VolTemplateProxy* class method), 496
`relative_child_offset()` (*inet_sock.VolTemplateProxy* class method), 343
`relative_child_offset()` (*inpcb.VolTemplateProxy* class method), 416
`relative_child_offset()` (*Integer.VolTemplateProxy* class method), 283
`relative_child_offset()` (*kauth_scope.VolTemplateProxy* class method), 418
`relative_child_offset()` (*KDDEBUG-GER_DATA64.VolTemplateProxy* class method), 481
`relative_child_offset()` (*kernel_cap_struct.VolTemplateProxy* class method), 345
`relative_child_offset()` (*kernel_cap_t.VolTemplateProxy* class method), 348
`relative_child_offset()` (*KMUTANT.VolTemplateProxy* class method), 456
`relative_child_offset()` (*kobject.VolTemplateProxy* class method), 350
`relative_child_offset()` (*KSYSTEM_TIME.VolTemplateProxy* class method), 458
`relative_child_offset()` (*KTHREAD.VolTemplateProxy* class method), 460
`relative_child_offset()` (*LIST_ENTRY.VolTemplateProxy* class method), 461
`relative_child_offset()` (*list_head.VolTemplateProxy* class method), 352
`relative_child_offset()` (*maple_tree.VolTemplateProxy* class method), 354
`relative_child_offset()` (*MFTAttribute.VolTemplateProxy* class method), 487
`relative_child_offset()` (*MFTEntry.VolTemplateProxy* class method), 489
`relative_child_offset()` (*MFTFileName.VolTemplateProxy* class method), 491
`relative_child_offset()` (*mm_struct.VolTemplateProxy* class method), 356
`relative_child_offset()` (*MM-VAD.VolTemplateProxy* class method), 463
`relative_child_offset()` (*MM-VAD_SHORT.VolTemplateProxy* class method), 466
`relative_child_offset()` (*mnt_namespace.VolTemplateProxy* class method), 358
`relative_child_offset()` (*module.VolTemplateProxy* class method), 360
`relative_child_offset()` (*mount.VolTemplateProxy* class method), 363
`relative_child_offset()` (*net.VolTemplateProxy* class method), 366
`relative_child_offset()` (*netlink_sock.VolTemplateProxy* class method), 368
`relative_child_offset()` (*OBJECT_HEADER.VolTemplateProxy* class method), 500
`relative_child_offset()` (*OBJECT_SYMBOLIC_LINK.VolTemplateProxy* class method), 468
`relative_child_offset()` (*ObjectInterface.VolTemplateProxy* class method), 167
`relative_child_offset()` (*ObjectTemplate* method), 304
`relative_child_offset()` (*packet_sock.VolTemplateProxy* class method), 370
`relative_child_offset()` (*PARTITION_ENTRY.VolTemplateProxy* class method), 483
`relative_child_offset()` (*PARTITION_TABLE.VolTemplateProxy* class method), 485
`relative_child_offset()` (*Pointer.VolTemplateProxy* class method), 286
`relative_child_offset()` (*POOL_HEADER.VolTemplateProxy* class method), 502
`relative_child_offset()` (*POOL_HEADER_VISTA.VolTemplateProxy* class method), 504
`relative_child_offset()` (*POOL_TRACKER_BIG_PAGES.VolTemplateProxy* class method), 506
`relative_child_offset()` (*PrimitiveObject.VolTemplateProxy* class method), 290
`relative_child_offset()` (*proc.VolTemplateProxy*

class method), 420
`relative_child_offset()` (*qstr.VolTemplateProxy class method*), 372
`relative_child_offset()` (*queue_entry.VolTemplateProxy class method*), 422
`relative_child_offset()` (*ReferenceTemplate method*), 305
`relative_child_offset()` (*SER-VICE_HEADER.VolTemplateProxy class method*), 521
`relative_child_offset()` (*SER-VICE_RECORD.VolTemplateProxy class method*), 523
`relative_child_offset()` (*SHARED_CACHE_MAP.VolTemplateProxy class method*), 471
`relative_child_offset()` (*sock.VolTemplateProxy class method*), 373
`relative_child_offset()` (*sock-addr.VolTemplateProxy class method*), 424
`relative_child_offset()` (*sock-addr_dl.VolTemplateProxy class method*), 426
`relative_child_offset()` (*socket.VolTemplateProxy class method*), 375, 428
`relative_child_offset()` (*String.VolTemplateProxy class method*), 291
`relative_child_offset()` (*struct_file.VolTemplateProxy class method*), 377
`relative_child_offset()` (*Struct-Type.VolTemplateProxy class method*), 298
`relative_child_offset()` (*SUM-MARY_DUMP.VolTemplateProxy class method*), 479
`relative_child_offset()` (*super_block.VolTemplateProxy class method*), 380
`relative_child_offset()` (*Symbol-Space.UnresolvedTemplate method*), 322
`relative_child_offset()` (*sysctl_oid.VolTemplateProxy class method*), 429
`relative_child_offset()` (*task_struct.VolTemplateProxy class method*), 382
`relative_child_offset()` (*Template method*), 169
`relative_child_offset()` (*TO-KEN.VolTemplateProxy class method*), 473
`relative_child_offset()` (*UNI-CODE_STRING.VolTemplateProxy class method*), 475
`relative_child_offset()` (*Union-Type.VolTemplateProxy class method*), 300
`relative_child_offset()` (*unix_sock.VolTemplateProxy class method*), 384
`relative_child_offset()` (*VACB.VolTemplateProxy class method*), 477
`relative_child_offset()` (*vfs-mount.VolTemplateProxy class method*), 386
`relative_child_offset()` (*vm_area_struct.VolTemplateProxy class method*), 389
`relative_child_offset()` (*vm_map_entry.VolTemplateProxy class method*), 432
`relative_child_offset()` (*vm_map_object.VolTemplateProxy class method*), 434
`relative_child_offset()` (*vnnode.VolTemplateProxy class method*), 435
`relative_child_offset()` (*Void.VolTemplateProxy class method*), 301
`relative_child_offset()` (*vsock_sock.VolTemplateProxy class method*), 392
`relative_child_offset()` (*xdp_sock.VolTemplateProxy class method*), 394
`REMOTE_ISF_URL` (*in module volatility3.framework.constants*), 123
`RemoteIdentifierFormat` (*class in volatility3.framework.automagic.symbol_cache*), 88
`remove()` (*SymbolSpace method*), 324
`remove_requirement()` (*BooleanRequirement method*), 97
`remove_requirement()` (*BytesRequirement method*), 98
`remove_requirement()` (*ChoiceRequirement method*), 100
`remove_requirement()` (*ClassRequirement method*), 142
`remove_requirement()` (*ComplexListRequirement method*), 102
`remove_requirement()` (*ConfigurableRequirementInterface method*), 145
`remove_requirement()` (*ConstructableRequirementInterface method*), 147
`remove_requirement()` (*IntRequirement method*), 103
`remove_requirement()` (*LayerListRequirement method*), 105
`remove_requirement()` (*ListRequirement method*), 106
`remove_requirement()` (*ModuleRequirement method*), 108

`remove_requirement()` (*MultiRequirement* method), 109
`remove_requirement()` (*PluginRequirement* method), 111
`remove_requirement()` (*RequirementInterface* method), 150
`remove_requirement()` (*SimpleTypeRequirement* method), 152
`remove_requirement()` (*StringRequirement* method), 113
`remove_requirement()` (*SymbolTableRequirement* method), 114
`remove_requirement()` (*TranslationLayerRequirement* method), 116
`remove_requirement()` (*URIRequirement* method), 118
`remove_requirement()` (*VersionRequirement* method), 119
`removeprefix()` (*Bytes* method), 268
`removeprefix()` (*HexBytes* method), 315
`removeprefix()` (*MultiTypeData* method), 319
`removeprefix()` (*String* method), 295
`removesuffix()` (*Bytes* method), 268
`removesuffix()` (*HexBytes* method), 315
`removesuffix()` (*MultiTypeData* method), 319
`removesuffix()` (*String* method), 295
`render()` (*CLIRenderer* method), 65
`render()` (*CSVRenderer* method), 65
`render()` (*JsonLinesRenderer* method), 65
`render()` (*JsonRenderer* method), 66
`render()` (*NoneRenderer* method), 66
`render()` (*PrettyTextRenderer* method), 66
`render()` (*QuickTextRenderer* method), 67
`render()` (*Renderer* method), 174
`render_treegrid()` (*Volshell* method), 54, 57, 60, 63
`Renderer` (class in *volatility3.framework.interfaces.renderers*), 173
`replace()` (*Bytes* method), 268
`replace()` (*HexBytes* method), 315
`replace()` (*MultiTypeData* method), 319
`replace()` (*String* method), 295
`replace_child()` (*AggregateType.VolTemplateProxy* class method), 255
`replace_child()` (*Array.VolTemplateProxy* class method), 256
`replace_child()` (*BitField.VolTemplateProxy* class method), 258
`replace_child()` (*Boolean.VolTemplateProxy* class method), 261
`replace_child()` (*bpf_prog.VolTemplateProxy* class method), 332
`replace_child()` (*bt_sock.VolTemplateProxy* class method), 334
`replace_child()` (*Bytes.VolTemplateProxy* class method), 265
`replace_child()` (*Char.VolTemplateProxy* class method), 270
`replace_child()` (*ClassType.VolTemplateProxy* class method), 273
`replace_child()` (*CM_KEY_BODY.VolTemplateProxy* class method), 511
`replace_child()` (*CM_KEY_NODE.VolTemplateProxy* class method), 513
`replace_child()` (*CM_KEY_VALUE.VolTemplateProxy* class method), 515
`replace_child()` (*CMHIVE.VolTemplateProxy* class method), 509
`replace_child()` (*CONTROL_AREA.VolTemplateProxy* class method), 441
`replace_child()` (*cred.VolTemplateProxy* class method), 335
`replace_child()` (*dentry.VolTemplateProxy* class method), 337
`replace_child()` (*DEVICE_OBJECT.VolTemplateProxy* class method), 443
`replace_child()` (*DRIVER_OBJECT.VolTemplateProxy* class method), 445
`replace_child()` (*elf.VolTemplateProxy* class method), 397
`replace_child()` (*elf_linkmap.VolTemplateProxy* class method), 399
`replace_child()` (*elf_phdr.VolTemplateProxy* class method), 401
`replace_child()` (*elf_sym.VolTemplateProxy* class method), 403
`replace_child()` (*Enumeration.VolTemplateProxy* class method), 276
`replace_child()` (*EPROCESS.VolTemplateProxy* class method), 447
`replace_child()` (*ETHREAD.VolTemplateProxy* class method), 450
`replace_child()` (*EX_FAST_REF.VolTemplateProxy* class method), 452
`replace_child()` (*ExecutiveObject.VolTemplateProxy* class method), 498
`replace_child()` (*FILE_OBJECT.VolTemplateProxy* class method), 454
`replace_child()` (*fileglob.VolTemplateProxy* class method), 413
`replace_child()` (*files_struct.VolTemplateProxy* class method), 339
`replace_child()` (*Float.VolTemplateProxy* class method), 279
`replace_child()` (*fs_struct.VolTemplateProxy* class method), 341
`replace_child()` (*Function.VolTemplateProxy* class method), 265

method), 281

replace_child() (*GenericIntelProcess.VolTemplateProxy* class method), 325

replace_child() (*hist_entry.VolTemplateProxy* class method), 395

replace_child() (*HMAP_ENTRY.VolTemplateProxy* class method), 517

replace_child() (*ifnet.VolTemplateProxy* class method), 415

replace_child() (*IM-AGE_DOS_HEADER.VolTemplateProxy* class method), 493

replace_child() (*IM-AGE_NT_HEADERS.VolTemplateProxy* class method), 496

replace_child() (*inet_sock.VolTemplateProxy* class method), 343

replace_child() (*inpcb.VolTemplateProxy* class method), 416

replace_child() (*Integer.VolTemplateProxy* class method), 283

replace_child() (*kauth_scope.VolTemplateProxy* class method), 418

replace_child() (*KDDEBUG-GER_DATA64.VolTemplateProxy* class method), 481

replace_child() (*kernel_cap_struct.VolTemplateProxy* class method), 345

replace_child() (*kernel_cap_t.VolTemplateProxy* class method), 348

replace_child() (*KMUTANT.VolTemplateProxy* class method), 456

replace_child() (*kobject.VolTemplateProxy* class method), 350

replace_child() (*KSYSTEM_TIME.VolTemplateProxy* class method), 458

replace_child() (*KTHREAD.VolTemplateProxy* class method), 460

replace_child() (*LIST_ENTRY.VolTemplateProxy* class method), 462

replace_child() (*list_head.VolTemplateProxy* class method), 352

replace_child() (*maple_tree.VolTemplateProxy* class method), 354

replace_child() (*MFTAttribute.VolTemplateProxy* class method), 487

replace_child() (*MFTEntry.VolTemplateProxy* class method), 489

replace_child() (*MFTFileName.VolTemplateProxy* class method), 491

replace_child() (*mm_struct.VolTemplateProxy* class method), 356

replace_child() (*MMVAD.VolTemplateProxy* class method), 463

replace_child() (*MMVAD_SHORT.VolTemplateProxy* class method), 466

replace_child() (*mnt_namespace.VolTemplateProxy* class method), 358

replace_child() (*module.VolTemplateProxy* class method), 360

replace_child() (*mount.VolTemplateProxy* class method), 363

replace_child() (*net.VolTemplateProxy* class method), 366

replace_child() (*netlink_sock.VolTemplateProxy* class method), 368

replace_child() (*OBJECT_HEADER.VolTemplateProxy* class method), 500

replace_child() (*OBJECT_SYMBOLIC_LINK.VolTemplateProxy* class method), 469

replace_child() (*ObjectInterface.VolTemplateProxy* class method), 167

replace_child() (*ObjectTemplate* method), 304

replace_child() (*packet_sock.VolTemplateProxy* class method), 370

replace_child() (*PARTITION_ENTRY.VolTemplateProxy* class method), 483

replace_child() (*PARTITION_TABLE.VolTemplateProxy* class method), 486

replace_child() (*Pointer.VolTemplateProxy* class method), 286

replace_child() (*POOL_HEADER.VolTemplateProxy* class method), 502

replace_child() (*POOL_HEADER_VISTA.VolTemplateProxy* class method), 504

replace_child() (*POOL_TRACKER_BIG_PAGES.VolTemplateProxy* class method), 506

replace_child() (*PrimitiveObject.VolTemplateProxy* class method), 290

replace_child() (*proc.VolTemplateProxy* class method), 420

replace_child() (*qstr.VolTemplateProxy* class method), 372

replace_child() (*queue_entry.VolTemplateProxy* class method), 422

replace_child() (*ReferenceTemplate* method), 305

replace_child() (*SERVICE_HEADER.VolTemplateProxy* class method), 521

replace_child() (*SERVICE_RECORD.VolTemplateProxy* class method), 523

replace_child() (*SHARED_CACHE_MAP.VolTemplateProxy*

- class method*), 471
- `replace_child()` (*sock.VolTemplateProxy class method*), 374
- `replace_child()` (*sockaddr.VolTemplateProxy class method*), 424
- `replace_child()` (*sockaddr_dl.VolTemplateProxy class method*), 426
- `replace_child()` (*socket.VolTemplateProxy class method*), 375, 428
- `replace_child()` (*String.VolTemplateProxy class method*), 291
- `replace_child()` (*struct_file.VolTemplateProxy class method*), 377
- `replace_child()` (*StructType.VolTemplateProxy class method*), 298
- `replace_child()` (*SUMMARY_DUMP.VolTemplateProxy class method*), 479
- `replace_child()` (*super_block.VolTemplateProxy class method*), 380
- `replace_child()` (*SymbolSpace.UnresolvedTemplate method*), 322
- `replace_child()` (*sysctl_oid.VolTemplateProxy class method*), 430
- `replace_child()` (*task_struct.VolTemplateProxy class method*), 382
- `replace_child()` (*Template method*), 169
- `replace_child()` (*TOKEN.VolTemplateProxy class method*), 473
- `replace_child()` (*UNICODE_STRING.VolTemplateProxy class method*), 475
- `replace_child()` (*UnionType.VolTemplateProxy class method*), 300
- `replace_child()` (*unix_sock.VolTemplateProxy class method*), 384
- `replace_child()` (*VACB.VolTemplateProxy class method*), 477
- `replace_child()` (*vfsmount.VolTemplateProxy class method*), 386
- `replace_child()` (*vm_area_struct.VolTemplateProxy class method*), 390
- `replace_child()` (*vm_map_entry.VolTemplateProxy class method*), 432
- `replace_child()` (*vm_map_object.VolTemplateProxy class method*), 434
- `replace_child()` (*vnnode.VolTemplateProxy class method*), 435
- `replace_child()` (*Void.VolTemplateProxy class method*), 301
- `replace_child()` (*vssock_sock.VolTemplateProxy class method*), 392
- `replace_child()` (*xdp_sock.VolTemplateProxy class method*), 394
- `replace_forward_references()` (*PdbReader method*), 527
- `replace_header_field()` (*IMAGE_DOS_HEADER method*), 495
- `require_interface_version()` (*in module volatility3.framework*), 70
- `RequirementInterface` (*class in volatility3.framework.interfaces.configuration*), 149
- `requirements` (*BooleanRequirement property*), 97
- `requirements` (*BytesRequirement property*), 98
- `requirements` (*ChoiceRequirement property*), 100
- `requirements` (*ClassRequirement property*), 143
- `requirements` (*ComplexListRequirement property*), 102
- `requirements` (*ConfigurableRequirementInterface property*), 145
- `requirements` (*ConstructableRequirementInterface property*), 147
- `requirements` (*IntRequirement property*), 103
- `requirements` (*LayerListRequirement property*), 105
- `requirements` (*ListRequirement property*), 106
- `requirements` (*ModuleRequirement property*), 108
- `requirements` (*MultiRequirement property*), 110
- `requirements` (*PluginRequirement property*), 111
- `requirements` (*RequirementInterface property*), 150
- `requirements` (*SimpleTypeRequirement property*), 152
- `requirements` (*StringRequirement property*), 113
- `requirements` (*SymbolTableRequirement property*), 115
- `requirements` (*TranslationLayerRequirement property*), 116
- `requirements` (*URIRequirement property*), 118
- `requirements` (*VersionRequirement property*), 119
- `reset()` (*PdbReader method*), 527
- `ResourceAccessor` (*class in volatility3.framework.layers.resources*), 243
- `retrieve_pdb()` (*PdbRetriever method*), 527
- `rfind()` (*Bytes method*), 268
- `rfind()` (*HexBytes method*), 316
- `rfind()` (*MultiTypeData method*), 320
- `rfind()` (*String method*), 295
- `rindex()` (*Bytes method*), 268
- `rindex()` (*HexBytes method*), 316
- `rindex()` (*MultiTypeData method*), 320
- `rindex()` (*String method*), 296
- `rjust()` (*Bytes method*), 268
- `rjust()` (*HexBytes method*), 316
- `rjust()` (*MultiTypeData method*), 320
- `rjust()` (*String method*), 296
- `root_cell_offset` (*RegistryHive property*), 241
- `round()` (*in module volatility3.framework.renderers.conversion*), 309
- `row_count` (*TreeGrid property*), 308
- `RowStructureConstructor()` (*in module volatility3.framework.renderers*), 307

`rpartition()` (*Bytes method*), 268
`rpartition()` (*HexBytes method*), 316
`rpartition()` (*MultiTypeData method*), 320
`rpartition()` (*String method*), 296
`rsplit()` (*Bytes method*), 268
`rsplit()` (*HexBytes method*), 316
`rsplit()` (*MultiTypeData method*), 320
`rsplit()` (*String method*), 296
`rstrip()` (*Bytes method*), 269
`rstrip()` (*HexBytes method*), 316
`rstrip()` (*MultiTypeData method*), 320
`rstrip()` (*String method*), 296
`run()` (*ABCKmsg method*), 587
`run()` (*ADS method*), 719
`run()` (*Banners method*), 776
`run()` (*Bash method*), 568, 622
`run()` (*BigPools method*), 672
`run()` (*Cachedump method*), 674
`run()` (*Callbacks method*), 677
`run()` (*Capabilities method*), 570
`run()` (*Check_afinfo method*), 573
`run()` (*Check_creds method*), 574
`run()` (*Check_idt method*), 576
`run()` (*Check_modules method*), 577
`run()` (*Check_syscall method*), 579, 624
`run()` (*Check_sysctl method*), 625
`run()` (*Check_trap_table method*), 627
`run()` (*CmdLine method*), 679
`run()` (*CommandLine method*), 49
`run()` (*ConfigWriter method*), 778
`run()` (*Crashinfo method*), 680
`run()` (*DeviceTree method*), 682
`run()` (*DllList method*), 684
`run()` (*Dmesg method*), 629
`run()` (*DriverIrp method*), 686
`run()` (*DriverModule method*), 687
`run()` (*DriverScan method*), 689
`run()` (*DumpFiles method*), 691
`run()` (*Elfs method*), 581
`run()` (*Envvars method*), 582, 693
`run()` (*FileScan method*), 695
`run()` (*FrameworkInfo method*), 779
`run()` (*GetServiceSIDs method*), 696
`run()` (*GetSIDs method*), 698
`run()` (*Handles method*), 701
`run()` (*Hashdump method*), 703
`run()` (*HiveList method*), 665
`run()` (*HiveScan method*), 666
`run()` (*IAT method*), 705
`run()` (*Ifconfig method*), 630
`run()` (*in module volatility3.framework.automagic*), 70
`run()` (*Info method*), 707
`run()` (*IOMem method*), 584
`run()` (*IsfInfo method*), 781
`run()` (*JobLinks method*), 709
`run()` (*Kauth_listeners method*), 632
`run()` (*Kauth_scopes method*), 634
`run()` (*Kevents method*), 636
`run()` (*Keyboard_notifiers method*), 586
`run()` (*Kmsg method*), 589
`run()` (*Kmsg_3_11_to_5_10 method*), 591
`run()` (*Kmsg_3_5_to_3_11 method*), 592
`run()` (*Kmsg_5_10_to_ method*), 594
`run()` (*Kmsg_pre_3_5 method*), 595
`run()` (*LayerWriter method*), 783
`run()` (*LdrModules method*), 711
`run()` (*LibraryList method*), 597
`run()` (*List_Files method*), 638
`run()` (*Lsadump method*), 712
`run()` (*Lsmmod method*), 599, 639
`run()` (*Lsof method*), 601, 641
`run()` (*Malfind method*), 602, 642, 714
`run()` (*Maps method*), 607, 648
`run()` (*MBRScan method*), 716
`run()` (*Memmap method*), 718
`run()` (*MFTScan method*), 721
`run()` (*ModScan method*), 723
`run()` (*Modules method*), 726
`run()` (*Mount method*), 644
`run()` (*MountInfo method*), 604
`run()` (*MutantScan method*), 728
`run()` (*NetScan method*), 730
`run()` (*NetStat method*), 735
`run()` (*Netstat method*), 646
`run()` (*Passphrase method*), 764
`run()` (*PluginInterface method*), 172
`run()` (*PoolScanner method*), 739
`run()` (*PrintKey method*), 668
`run()` (*Privs method*), 742
`run()` (*PsAux method*), 609
`run()` (*Psaux method*), 650
`run()` (*PsList method*), 611, 653, 745
`run()` (*PsScan method*), 613, 747
`run()` (*PsTree method*), 615, 655, 750
`run()` (*Sessions method*), 751
`run()` (*Skeleton_Key_Check method*), 753
`run()` (*Socket_filters method*), 657
`run()` (*Sockstat method*), 617
`run()` (*SSDT method*), 755
`run()` (*Strings method*), 757
`run()` (*SvcScan method*), 759
`run()` (*SymlinkScan method*), 761
`run()` (*ThrdScan method*), 763
`run()` (*Timeliner method*), 787
`run()` (*Timers method*), 658
`run()` (*Trustedbsd method*), 660
`run()` (*tty_check method*), 619
`run()` (*UserAssist method*), 670

run() (*VadInfo* method), 767
 run() (*VadWalk* method), 769
 run() (*VadYaraScan* method), 771
 run() (*VerInfo* method), 773
 run() (*VFSevents* method), 662
 run() (*VirtMap* method), 775
 run() (*VmaYaraScan* method), 620
 run() (*VolShell* method), 50
 run() (*Volshell* method), 55, 57, 60, 63
 run() (*YaraScan* method), 788
 run_all() (*ABCKmsg* class method), 587
 run_all() (*Kmsg_3_11_to_5_10* class method), 591
 run_all() (*Kmsg_3_5_to_3_11* class method), 592
 run_all() (*Kmsg_5_10_to_* class method), 594
 run_all() (*Kmsg_pre_3_5* class method), 596
 run_script() (*Volshell* method), 55, 58, 60, 63

S

sanitize_filename() (*FileHandlerInterface* static method), 170
 sanitize_filename() (*NullFileHandler* static method), 52
 sanitize_name() (*TreeGrid* static method), 175, 308
 save_vacb() (*SHARED_CACHE_MAP* method), 472
 SB_DIRSYNC (*super_block* attribute), 379
 SB_I_VERSION (*super_block* attribute), 379
 SB_KERNMOUNT (*super_block* attribute), 379
 SB_LAZYTIME (*super_block* attribute), 379
 SB_MANDLOCK (*super_block* attribute), 379
 SB_NOATIME (*super_block* attribute), 379
 SB_NODEV (*super_block* attribute), 379
 SB_NODIRATIME (*super_block* attribute), 379
 SB_NOEXEC (*super_block* attribute), 379
 SB_NOSUID (*super_block* attribute), 379
 sb_opts (*MountInfoData* attribute), 605
 SB_OPTS (*super_block* attribute), 379
 SB_POSIXACL (*super_block* attribute), 379
 SB_RDONLY (*super_block* attribute), 379
 SB_SILENT (*super_block* attribute), 379
 SB_SYNCHRONOUS (*super_block* attribute), 379
 scan() (*AVMLLayer* method), 188
 scan() (*BufferDataLayer* method), 232
 scan() (*DataLayerInterface* method), 160
 scan() (*Elf64Layer* method), 197
 scan() (*FileLayer* method), 234
 scan() (*Intel* method), 201
 scan() (*Intel32e* method), 204
 scan() (*IntelPAE* method), 207
 scan() (*LimeLayer* method), 221
 scan() (*LinearlyMappedLayer* method), 224
 scan() (*NetScan* class method), 731
 scan() (*NonLinearlySegmentedLayer* method), 245
 scan() (*PdbMSFStream* method), 226
 scan() (*PdbMultiStreamFormat* method), 229
 scan() (*QemuSuspendLayer* method), 237
 scan() (*RegistryHive* method), 241
 scan() (*SegmentedLayer* method), 247
 scan() (*TranslationLayerInterface* method), 164
 scan() (*VmwareLayer* method), 250
 scan() (*WindowsCrashDump32Layer* method), 191
 scan() (*WindowsCrashDump64Layer* method), 194
 scan() (*WindowsIntel* method), 209
 scan() (*WindowsIntel32e* method), 212
 scan() (*WindowsIntelPAE* method), 215
 scan() (*WindowsMixin* method), 218
 scan() (*XenCoreDumpLayer* method), 253
 scan_drivers() (*DriverScan* class method), 689
 scan_files() (*FileScan* class method), 695
 scan_hives() (*HiveScan* class method), 666
 scan_module() (*Passphrase* method), 765
 scan_modules() (*ModScan* class method), 723
 scan_mutants() (*MutantScan* class method), 728
 scan_processes() (*PsScan* class method), 748
 scan_symlinks() (*SymlinkScan* class method), 761
 scan_tasks() (*PsScan* class method), 613
 scan_threads() (*ThrdScan* class method), 763
 scannable_sections() (*VirtMap* class method), 775
 ScannerInterface (class in *volatility3.framework.interfaces.layers*), 162
 search() (*MultiRegexp* method), 186
 search() (*MultiStringScanner* method), 185
 section_strtab (*module* property), 362
 section_symtab (*module* property), 362
 seek() (*FileHandlerInterface* method), 170
 seek() (*NullFileHandler* method), 52
 seekable() (*FileHandlerInterface* method), 171
 seekable() (*NullFileHandler* method), 52
 SEGMENT_FLAG_COMPRESS (*QemuSuspendLayer* attribute), 236
 SEGMENT_FLAG_CONTINUE (*QemuSuspendLayer* attribute), 236
 SEGMENT_FLAG_EOS (*QemuSuspendLayer* attribute), 236
 SEGMENT_FLAG_HOOK (*QemuSuspendLayer* attribute), 236
 SEGMENT_FLAG_MEM_SIZE (*QemuSuspendLayer* attribute), 236
 SEGMENT_FLAG_PAGE (*QemuSuspendLayer* attribute), 236
 SEGMENT_FLAG_XBZRLE (*QemuSuspendLayer* attribute), 236
 SegmentedLayer (class in *volatility3.framework.layers.segmented*), 246
 separator (*HierarchicalDict* property), 149
 separator (*WindowsIdentifier* attribute), 91
 SERVICE_HEADER (class in *volatility3.framework.symbols.windows.extensions.services*), 520

SERVICE_HEADER.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.service_header), 521

SERVICE_RECORD (class in volatility3.framework.symbols.windows.extensions.service_header), 522

SERVICE_RECORD.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.service_header), 522

ServiceBinaryInfo (class in volatility3.plugins.windows.svcscan), 757

Sessions (class in volatility3.plugins.windows.sessions), 750

set_defaults() (HelpfulArgParser method), 69

set_kernel_virtual_offset() (KernelPDBScanner method), 82

set_open_method() (ADS method), 720

set_open_method() (Banners method), 777

set_open_method() (Bash method), 569, 623

set_open_method() (BigPools method), 672

set_open_method() (Cachedump method), 674

set_open_method() (Callbacks method), 677

set_open_method() (Capabilities method), 571

set_open_method() (Check_afinfo method), 573

set_open_method() (Check_creds method), 574

set_open_method() (Check_idt method), 576

set_open_method() (Check_modules method), 578

set_open_method() (Check_syscall method), 579, 624

set_open_method() (Check_sysctl method), 626

set_open_method() (Check_trap_table method), 627

set_open_method() (CmdLine method), 679

set_open_method() (ConfigWriter method), 778

set_open_method() (Crashinfo method), 681

set_open_method() (DeviceTree method), 682

set_open_method() (DllList method), 684

set_open_method() (Dmesg method), 629

set_open_method() (DriverIrp method), 686

set_open_method() (DriverModule method), 687

set_open_method() (DriverScan method), 689

set_open_method() (DumpFiles method), 692

set_open_method() (Elfs method), 581

set_open_method() (Envars method), 583, 693

set_open_method() (FileScan method), 695

set_open_method() (FrameworkInfo method), 780

set_open_method() (GetServiceSIDs method), 697

set_open_method() (GetSIDs method), 698

set_open_method() (Handles method), 701

set_open_method() (Hashdump method), 703

set_open_method() (HiveList method), 665

set_open_method() (HiveScan method), 667

set_open_method() (IAT method), 705

set_open_method() (Ifconfig method), 631

set_open_method() (Info method), 707

set_open_method() (IOMem method), 585

set_open_method() (IsfInfo method), 781

set_open_method() (JobLinks method), 709

set_open_method() (Kauth_listeners method), 632

set_open_method() (Kauth_scopes method), 634

set_open_method() (Kevents method), 636

set_open_method() (Keyboard_notifiers method), 586

set_open_method() (Kmsg method), 589

set_open_method() (LayerWriter method), 783

set_open_method() (LdrModules method), 711

set_open_method() (LibraryList method), 597

set_open_method() (List_Files method), 638

set_open_method() (Lsadump method), 713

set_open_method() (Lsmode method), 599, 640

set_open_method() (Lsof method), 601, 641

set_open_method() (Malfind method), 602, 643, 715

set_open_method() (Maps method), 607, 648

set_open_method() (MBRScan method), 716

set_open_method() (Memmap method), 718

set_open_method() (MFTScan method), 721

set_open_method() (ModScan method), 724

set_open_method() (Modules method), 726

set_open_method() (Mount method), 644

set_open_method() (MountInfo method), 604

set_open_method() (MutantScan method), 728

set_open_method() (NetScan method), 731

set_open_method() (NetStat method), 736

set_open_method() (Netstat method), 646

set_open_method() (Passphrase method), 765

set_open_method() (PluginInterface method), 172

set_open_method() (PoolScanner method), 739

set_open_method() (PrintKey method), 669

set_open_method() (Privs method), 742

set_open_method() (PsAux method), 609

set_open_method() (Psaux method), 650

set_open_method() (PsList method), 611, 654, 745

set_open_method() (PsScan method), 613, 748

set_open_method() (PsTree method), 615, 655, 750

set_open_method() (Sessions method), 751

set_open_method() (Skeleton_Key_Check method), 753

set_open_method() (Socket_filters method), 657

set_open_method() (Sockstat method), 617

set_open_method() (SSDT method), 755

set_open_method() (Strings method), 757

set_open_method() (SvcScan method), 759

set_open_method() (SymlinkScan method), 761

set_open_method() (ThrdScan method), 763

set_open_method() (Timeliner method), 787

set_open_method() (Timers method), 658

set_open_method() (Trustedbsd method), 660

set_open_method() (tty_check method), 619

set_open_method() (UserAssist method), 670

set_open_method() (VadInfo method), 767

set_open_method() (VadWalk method), 769

set_open_method() (*VadYaraScan method*), 771
 set_open_method() (*VerInfo method*), 773
 set_open_method() (*VFSevents method*), 662
 set_open_method() (*VirtMap method*), 775
 set_open_method() (*VmaYaraScan method*), 621
 set_open_method() (*Volshell method*), 55, 58, 61, 63
 set_open_method() (*YaraScan method*), 788
 set_type_class() (*BaseSymbolTableInterface method*), 178
 set_type_class() (*BashIntermedSymbols method*), 407
 set_type_class() (*IntermediateSymbolTable method*), 537
 set_type_class() (*ISFormatTable method*), 533
 set_type_class() (*LinuxKernelIntermedSymbols method*), 329
 set_type_class() (*MacKernelIntermedSymbols method*), 411
 set_type_class() (*NativeTable method*), 563
 set_type_class() (*NativeTableInterface method*), 180
 set_type_class() (*SymbolTableInterface method*), 184
 set_type_class() (*Version1Format method*), 539
 set_type_class() (*Version2Format method*), 542
 set_type_class() (*Version3Format method*), 545
 set_type_class() (*Version4Format method*), 549
 set_type_class() (*Version5Format method*), 552
 set_type_class() (*Version6Format method*), 555
 set_type_class() (*Version7Format method*), 558
 set_type_class() (*Version8Format method*), 561
 set_type_class() (*WindowsKernelIntermedSymbols method*), 439
 setter() (*classproperty method*), 47
 setup_logging() (*CommandLine class method*), 49
 setup_logging() (*VolShell class method*), 50
 SHARED_CACHE_MAP (*class in volatility3.framework.symbols.windows.extensions*), 470
 SHARED_CACHE_MAP.VolTemplateProxy (*class in volatility3.framework.symbols.windows.extensions*), 470
 sid_to_key() (*Hashdump class method*), 704
 sidbytes_to_key() (*Hashdump class method*), 704
 SIGNATURE (*WindowsCrashDump32Layer attribute*), 189
 SIGNATURE (*WindowsCrashDump64Layer attribute*), 192
 signed (*DataFormatInfo attribute*), 275
 SimpleTypeRequirement (*class in volatility3.framework.interfaces.configuration*), 151
 size (*ObjectTemplate property*), 304
 size (*ReferenceTemplate property*), 305
 size (*SizedModule property*), 138
 size (*SymbolSpace.UnresolvedTemplate property*), 322
 size (*Template property*), 169
 size() (*AggregateType.VolTemplateProxy class method*), 255
 size() (*Array.VolTemplateProxy class method*), 257
 size() (*BitField.VolTemplateProxy class method*), 258
 size() (*Boolean.VolTemplateProxy class method*), 262
 size() (*bpf_prog.VolTemplateProxy class method*), 332
 size() (*bt_sock.VolTemplateProxy class method*), 334
 size() (*Bytes.VolTemplateProxy class method*), 265
 size() (*Char.VolTemplateProxy class method*), 270
 size() (*ClassType.VolTemplateProxy class method*), 273
 size() (*CM_KEY_BODY.VolTemplateProxy class method*), 511
 size() (*CM_KEY_NODE.VolTemplateProxy class method*), 513
 size() (*CM_KEY_VALUE.VolTemplateProxy class method*), 515
 size() (*CMHIVE.VolTemplateProxy class method*), 509
 size() (*CONTROL_AREA.VolTemplateProxy class method*), 441
 size() (*cred.VolTemplateProxy class method*), 335
 size() (*dentry.VolTemplateProxy class method*), 337
 size() (*DEVICE_OBJECT.VolTemplateProxy class method*), 443
 size() (*DRIVER_OBJECT.VolTemplateProxy class method*), 445
 size() (*elf.VolTemplateProxy class method*), 398
 size() (*elf_linkmap.VolTemplateProxy class method*), 400
 size() (*elf_phdr.VolTemplateProxy class method*), 401
 size() (*elf_sym.VolTemplateProxy class method*), 403
 size() (*Enumeration.VolTemplateProxy class method*), 276
 size() (*EPROCESS.VolTemplateProxy class method*), 447
 size() (*ETHREAD.VolTemplateProxy class method*), 450
 size() (*EX_FAST_REF.VolTemplateProxy class method*), 452
 size() (*ExecutiveObject.VolTemplateProxy class method*), 498
 size() (*FILE_OBJECT.VolTemplateProxy class method*), 454
 size() (*fileglob.VolTemplateProxy class method*), 413
 size() (*files_struct.VolTemplateProxy class method*), 339
 size() (*Float.VolTemplateProxy class method*), 279
 size() (*fs_struct.VolTemplateProxy class method*), 341
 size() (*Function.VolTemplateProxy class method*), 282
 size() (*GenericIntelProcess.VolTemplateProxy class method*), 325
 size() (*hist_entry.VolTemplateProxy class method*), 396
 size() (*HMAP_ENTRY.VolTemplateProxy class method*), 517

`size()` (*ifnet.VolTemplateProxy* class method), 415
`size()` (*IMAGE_DOS_HEADER.VolTemplateProxy* class method), 493
`size()` (*IMAGE_NT_HEADERS.VolTemplateProxy* class method), 496
`size()` (*inet_sock.VolTemplateProxy* class method), 343
`size()` (*inpcb.VolTemplateProxy* class method), 416
`size()` (*Integer.VolTemplateProxy* class method), 283
`size()` (*kauth_scope.VolTemplateProxy* class method), 418
`size()` (*KDDEBUGGER_DATA64.VolTemplateProxy* class method), 481
`size()` (*kernel_cap_struct.VolTemplateProxy* class method), 345
`size()` (*kernel_cap_t.VolTemplateProxy* class method), 348
`size()` (*KMUTANT.VolTemplateProxy* class method), 456
`size()` (*kobject.VolTemplateProxy* class method), 350
`size()` (*KSYSTEM_TIME.VolTemplateProxy* class method), 458
`size()` (*KTHREAD.VolTemplateProxy* class method), 460
`size()` (*LIST_ENTRY.VolTemplateProxy* class method), 462
`size()` (*list_head.VolTemplateProxy* class method), 352
`size()` (*maple_tree.VolTemplateProxy* class method), 355
`size()` (*MFTAttribute.VolTemplateProxy* class method), 488
`size()` (*MFTEntry.VolTemplateProxy* class method), 489
`size()` (*MFTFileName.VolTemplateProxy* class method), 491
`size()` (*mm_struct.VolTemplateProxy* class method), 356
`size()` (*MMVAD.VolTemplateProxy* class method), 464
`size()` (*MMVAD_SHORT.VolTemplateProxy* class method), 466
`size()` (*mnt_namespace.VolTemplateProxy* class method), 358
`size()` (*module.VolTemplateProxy* class method), 360
`size()` (*mount.VolTemplateProxy* class method), 363
`size()` (*net.VolTemplateProxy* class method), 366
`size()` (*netlink_sock.VolTemplateProxy* class method), 368
`size()` (*OBJECT_HEADER.VolTemplateProxy* class method), 500
`size()` (*OBJECT_SYMBOLIC_LINK.VolTemplateProxy* class method), 469
`size()` (*ObjectInterface.VolTemplateProxy* class method), 167
`size()` (*packet_sock.VolTemplateProxy* class method), 370
`size()` (*PARTITION_ENTRY.VolTemplateProxy* class method), 483
`size()` (*PARTITION_TABLE.VolTemplateProxy* class method), 486
`size()` (*Pointer.VolTemplateProxy* class method), 286
`size()` (*POOL_HEADER.VolTemplateProxy* class method), 502
`size()` (*POOL_HEADER_VISTA.VolTemplateProxy* class method), 504
`size()` (*POOL_TRACKER_BIG_PAGES.VolTemplateProxy* class method), 506
`size()` (*PrimitiveObject.VolTemplateProxy* class method), 290
`size()` (*proc.VolTemplateProxy* class method), 420
`size()` (*qstr.VolTemplateProxy* class method), 372
`size()` (*queue_entry.VolTemplateProxy* class method), 422
`size()` (*SERVICE_HEADER.VolTemplateProxy* class method), 521
`size()` (*SERVICE_RECORD.VolTemplateProxy* class method), 523
`size()` (*SHARED_CACHE_MAP.VolTemplateProxy* class method), 471
`size()` (*sock.VolTemplateProxy* class method), 374
`size()` (*sockaddr.VolTemplateProxy* class method), 424
`size()` (*sockaddr_dl.VolTemplateProxy* class method), 426
`size()` (*socket.VolTemplateProxy* class method), 376, 428
`size()` (*String.VolTemplateProxy* class method), 292
`size()` (*struct_file.VolTemplateProxy* class method), 377
`size()` (*StructType.VolTemplateProxy* class method), 298
`size()` (*SUMMARY_DUMP.VolTemplateProxy* class method), 479
`size()` (*super_block.VolTemplateProxy* class method), 380
`size()` (*sysctl_oid.VolTemplateProxy* class method), 430
`size()` (*task_struct.VolTemplateProxy* class method), 382
`size()` (*TOKEN.VolTemplateProxy* class method), 473
`size()` (*UNICODE_STRING.VolTemplateProxy* class method), 475
`size()` (*UnionType.VolTemplateProxy* class method), 300
`size()` (*unix_sock.VolTemplateProxy* class method), 384
`size()` (*VACB.VolTemplateProxy* class method), 477
`size()` (*vfsmount.VolTemplateProxy* class method), 386
`size()` (*vm_area_struct.VolTemplateProxy* class method), 390
`size()` (*vm_map_entry.VolTemplateProxy* class method), 432
`size()` (*vm_map_object.VolTemplateProxy* class method), 434
`size()` (*vnnode.VolTemplateProxy* class method), 436
`size()` (*Void.VolTemplateProxy* class method), 301

[size\(\)](#) (*vssock_sock.VolTemplateProxy* class method), 392
[size\(\)](#) (*xdp_sock.VolTemplateProxy* class method), 394
[SizedModule](#) (class in *volatility3.framework.contexts*), 135
[Skeleton_Key_Check](#) (class in *volatility3.plugins.windows.skeleton_key_check*), 752
[SnappyException](#), 189
[sock](#) (class in *volatility3.framework.symbols.linux.extensions*), 373
[sock.VolTemplateProxy](#) (class in *volatility3.framework.symbols.linux.extensions*), 373
[sockaddr](#) (class in *volatility3.framework.symbols.mac.extensions*), 424
[sockaddr.VolTemplateProxy](#) (class in *volatility3.framework.symbols.mac.extensions*), 424
[sockaddr_dl](#) (class in *volatility3.framework.symbols.mac.extensions*), 425
[sockaddr_dl\(\)](#) (*ifnet* method), 416
[sockaddr_dl.VolTemplateProxy](#) (class in *volatility3.framework.symbols.mac.extensions*), 425
[socket](#) (class in *volatility3.framework.symbols.linux.extensions*), 375
[socket](#) (class in *volatility3.framework.symbols.mac.extensions*), 427
[socket.VolTemplateProxy](#) (class in *volatility3.framework.symbols.linux.extensions*), 375
[socket.VolTemplateProxy](#) (class in *volatility3.framework.symbols.mac.extensions*), 427
[Socket_filters](#) (class in *volatility3.plugins.mac.socket_filters*), 656
[SockHandlers](#) (class in *volatility3.plugins.linux.sockstat*), 616
[Sockstat](#) (class in *volatility3.plugins.linux.sockstat*), 616
[splice\(\)](#) (*HierarchicalDict* method), 149
[split\(\)](#) (*Bytes* method), 269
[split\(\)](#) (*HexBytes* method), 316
[split\(\)](#) (*MultiTypeData* method), 320
[split\(\)](#) (*String* method), 296
[splitlines\(\)](#) (*Bytes* method), 269
[splitlines\(\)](#) (*HexBytes* method), 316
[splitlines\(\)](#) (*MultiTypeData* method), 320
[splitlines\(\)](#) (*String* method), 296
[SQLITE_CACHE_PERIOD](#) (in module *volatility3.framework.constants*), 123
[SqliteCache](#) (class in *volatility3.framework.automagic.symbol_cache*), 88
[SSDT](#) (class in *volatility3.plugins.windows.ssdt*), 753
[st_dev](#) (*MountInfoData* attribute), 605
[stack\(\)](#) (*AVMLStacker* class method), 188
[stack\(\)](#) (*Elf64Stacker* class method), 198
[stack\(\)](#) (*LayerStacker* method), 85
[stack\(\)](#) (*LimeStacker* class method), 221
[stack\(\)](#) (*LinuxIntelStacker* class method), 73
[stack\(\)](#) (*MacIntelStacker* class method), 75
[stack\(\)](#) (*QemuStacker* class method), 235
[stack\(\)](#) (*StackerLayerInterface* class method), 141
[stack\(\)](#) (*VmwareStacker* class method), 251
[stack\(\)](#) (*WindowsCrashDumpStacker* class method), 195
[stack\(\)](#) (*WindowsIntelStacker* class method), 96
[stack\(\)](#) (*XenCoreDumpStacker* class method), 254
[stack_layer\(\)](#) (*LayerStacker* class method), 85
[stack_order](#) (*AVMLStacker* attribute), 189
[stack_order](#) (*Elf64Stacker* attribute), 198
[stack_order](#) (*LimeStacker* attribute), 222
[stack_order](#) (*LinuxIntelStacker* attribute), 73
[stack_order](#) (*MacIntelStacker* attribute), 75
[stack_order](#) (*QemuStacker* attribute), 235
[stack_order](#) (*StackerLayerInterface* attribute), 141
[stack_order](#) (*VmwareStacker* attribute), 251
[stack_order](#) (*WindowsCrashDumpStacker* attribute), 196
[stack_order](#) (*WindowsIntelStacker* attribute), 96
[stack_order](#) (*XenCoreDumpStacker* attribute), 254
[stacker_slow_warning\(\)](#) (*AVMLStacker* class method), 189
[stacker_slow_warning\(\)](#) (*Elf64Stacker* class method), 199
[stacker_slow_warning\(\)](#) (*LimeStacker* class method), 222
[stacker_slow_warning\(\)](#) (*LinuxIntelStacker* class method), 73
[stacker_slow_warning\(\)](#) (*MacIntelStacker* class method), 75
[stacker_slow_warning\(\)](#) (*QemuStacker* class method), 235
[stacker_slow_warning\(\)](#) (*StackerLayerInterface* class method), 141
[stacker_slow_warning\(\)](#) (*VmwareStacker* class method), 251
[stacker_slow_warning\(\)](#) (*WindowsCrashDumpStacker* class method), 196
[stacker_slow_warning\(\)](#) (*WindowsIntelStacker* class method), 96
[stacker_slow_warning\(\)](#) (*XenCoreDumpStacker* class method), 254

StackerLayerInterface (class in volatility3.framework.interfaces.automagic), 141

startswith() (Bytes method), 269

startswith() (HexBytes method), 317

startswith() (MultiTypeData method), 321

startswith() (String method), 296

String (class in volatility3.framework.objects), 291

String (UNICODE_STRING property), 475

String.VolTemplateProxy (class in volatility3.framework.objects), 291

StringRequirement (class in volatility3.framework.configuration.requirements), 112

Strings (class in volatility3.plugins.windows.strings), 755

strings_pattern (Strings attribute), 757

strip() (Bytes method), 269

strip() (HexBytes method), 317

strip() (MultiTypeData method), 321

strip() (String method), 297

struct_file (class in volatility3.framework.symbols.linux.extensions), 377

struct_file.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 377

StructType (class in volatility3.framework.objects), 297

StructType.VolTemplateProxy (class in volatility3.framework.objects), 297

structure (Intel attribute), 201

structure (Intel32e attribute), 204

structure (IntelPAE attribute), 207

structure (WindowsIntel attribute), 210

structure (WindowsIntel32e attribute), 212

structure (WindowsIntelPAE attribute), 215

structure (WindowsMixin attribute), 218

structured_output (CLIRenderer attribute), 65

structured_output (CSVRenderer attribute), 65

structured_output (JsonLinesRenderer attribute), 65

structured_output (JsonRenderer attribute), 66

structured_output (NoneRenderer attribute), 66

structured_output (PrettyTextRenderer attribute), 67

structured_output (QuickTextRenderer attribute), 67

SUMMARY_DUMP (class in volatility3.framework.symbols.windows.extensions.crashdump), 478

SUMMARY_DUMP.VolTemplateProxy (class in volatility3.framework.symbols.windows.extensions.crashdump), 479

super_block (class in volatility3.framework.symbols.linux.extensions), 379

super_block.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 379

supported_dumptypes (WindowsCrashDump32Layer attribute), 192

supported_dumptypes (WindowsCrashDump64Layer attribute), 194

SvcScan (class in volatility3.plugins.windows.svcscan), 758

swapcase() (Bytes method), 269

swapcase() (HexBytes method), 317

swapcase() (MultiTypeData method), 321

swapcase() (String method), 297

SwappedInvalidAddressException, 566

SYMBOL (SymbolType attribute), 324

SYMBOL_BASEPATHS (in module volatility3.framework.constants), 123

symbol_class (LinuxSymbolFinder attribute), 75

symbol_class (MacSymbolFinder attribute), 77

symbol_class (SymbolFinder attribute), 93

symbol_space (Context property), 132

symbol_space (ContextInterface property), 154

symbol_table_from_offset() (PDBUtility class method), 529

symbol_table_from_pdb() (PDBUtility class method), 529

symbol_table_is_64bit() (in module volatility3.framework.symbols), 324

symbol_table_name (ConfigurableModule property), 130

symbol_table_name (Module property), 134

symbol_table_name (ModuleInterface property), 158

symbol_table_name (SizedModule property), 138

SymbolCacheMagic (class in volatility3.framework.automagic.symbol_cache), 89

SymbolError, 566

SymbolFinder (class in volatility3.framework.automagic.symbol_finder), 91

SymbolInterface (class in volatility3.framework.interfaces.symbols), 180

symbols (BaseSymbolTableInterface property), 178

symbols (BashIntermedSymbols property), 407

symbols (ConfigurableModule property), 130

symbols (IntermediateSymbolTable property), 537

symbols (ISFormatTable property), 533

symbols (LinuxKernelIntermedSymbols property), 329

symbols (MacKernelIntermedSymbols property), 411

symbols (Module property), 134

symbols (NativeTable property), 564

symbols (NativeTableInterface property), 180

symbols (SizedModule property), 138

symbols (SymbolTableInterface property), 184

symbols (Version1Format property), 540

symbols (Version2Format property), 543

symbols (Version3Format property), 546

symbols (Version4Format property), 549

- symbols (*Version5Format* property), 552
 - symbols (*Version6Format* property), 555
 - symbols (*Version7Format* property), 558
 - symbols (*Version8Format* property), 561
 - symbols (*WindowsKernelIntermedSymbols* property), 440
 - symbols() (*ModuleInterface* method), 158
 - SymbolSpace (class in *volatility3.framework.symbols*), 321
 - SymbolSpace.UnresolvedTemplate (class in *volatility3.framework.symbols*), 321
 - SymbolSpaceError, 566
 - SymbolSpaceInterface (class in *volatility3.framework.interfaces.symbols*), 180
 - SymbolTableInterface (class in *volatility3.framework.interfaces.symbols*), 182
 - SymbolTableRequirement (class in *volatility3.framework.configuration.requirements*), 113
 - SymbolType (class in *volatility3.framework.symbols*), 324
 - SymlinkScan (class in *volatility3.plugins.windows.symlinkscan*), 760
 - syntab_checks() (*ABCKmsg* class method), 588
 - syntab_checks() (*Kmsg_3_11_to_5_10* class method), 591
 - syntab_checks() (*Kmsg_3_5_to_3_11* class method), 593
 - syntab_checks() (*Kmsg_5_10_to_* class method), 595
 - syntab_checks() (*Kmsg_pre_3_5* class method), 596
 - sysctl_oid (class in *volatility3.framework.symbols.mac.extensions*), 429
 - sysctl_oid.VolTemplateProxy (class in *volatility3.framework.symbols.mac.extensions*), 429
- ## T
- tab_stop() (*PrettyTextRenderer* method), 67
 - TASK_RUNNING (*DescExitStateEnum* attribute), 612
 - task_struct (class in *volatility3.framework.symbols.linux.extensions*), 381
 - task_struct.VolTemplateProxy (class in *volatility3.framework.symbols.linux.extensions*), 381
 - TaskData (class in *volatility3.plugins.linux.capabilities*), 571
 - tell() (*FileHandlerInterface* method), 171
 - tell() (*NullFileHandler* method), 52
 - Template (class in *volatility3.framework.interfaces.objects*), 168
 - test_sets (*WindowsIntelStacker* attribute), 96
 - tests (*PageMapScanner* attribute), 94
 - tgid (*TaskData* attribute), 571
 - ThrdScan (class in *volatility3.plugins.windows.thrdscan*), 762
 - thread_safe (*BytesScanner* attribute), 185
 - thread_safe (*MultiStringScanner* attribute), 185
 - thread_safe (*PageMapScanner* attribute), 94
 - thread_safe (*PdbSignatureScanner* attribute), 530
 - thread_safe (*PoolHeaderScanner* attribute), 736
 - thread_safe (*RegExScanner* attribute), 185
 - thread_safe (*ScannerInterface* attribute), 163
 - thread_safe (*YaraScanner* attribute), 789
 - Threading (*Parallelism* attribute), 122
 - Timeliner (class in *volatility3.plugins.timeliner*), 786
 - TimeLinerInterface (class in *volatility3.plugins.timeliner*), 784
 - TimeLinerType (class in *volatility3.plugins.timeliner*), 784
 - timer_filters (*Kevents* attribute), 636
 - Timers (class in *volatility3.plugins.mac.timers*), 657
 - title() (*Bytes* method), 269
 - title() (*HexBytes* method), 317
 - title() (*MultiTypeData* method), 321
 - title() (*String* method), 297
 - to_bytes() (*Bin* method), 311
 - to_bytes() (*BitField* method), 260
 - to_bytes() (*Boolean* method), 264
 - to_bytes() (*Char* method), 272
 - to_bytes() (*ELF_CLASS* method), 125
 - to_bytes() (*ELF_IDENT* method), 127
 - to_bytes() (*Enumeration* method), 278
 - to_bytes() (*Hex* method), 313
 - to_bytes() (*Integer* method), 285
 - to_bytes() (*Parallelism* method), 123
 - to_bytes() (*Pointer* method), 289
 - to_bytes() (*PoolType* method), 741
 - to_bytes() (*RegKeyFlags* method), 519
 - to_bytes() (*TimeLinerType* method), 785
 - to_list() (*LIST_ENTRY* method), 463
 - to_list() (*list_head* method), 353
 - TOKEN (class in *volatility3.framework.symbols.windows.extensions*), 473
 - TOKEN.VolTemplateProxy (class in *volatility3.framework.symbols.windows.extensions*), 473
 - translate() (*Bytes* method), 269
 - translate() (*Elf64Layer* method), 198
 - translate() (*HexBytes* method), 317
 - translate() (*Intel* method), 201
 - translate() (*Intel32e* method), 204
 - translate() (*IntelPAE* method), 207
 - translate() (*LimeLayer* method), 221
 - translate() (*LinearlyMappedLayer* method), 224
 - translate() (*MultiTypeData* method), 321
 - translate() (*PdbMSFStream* method), 227

`translate()` (*PdbMultiStreamFormat* method), 230
`translate()` (*RegistryHive* method), 241
`translate()` (*SegmentedLayer* method), 248
`translate()` (*String* method), 297
`translate()` (*VmwareLayer* method), 250
`translate()` (*WindowsCrashDump32Layer* method), 192
`translate()` (*WindowsCrashDump64Layer* method), 194
`translate()` (*WindowsIntel* method), 210
`translate()` (*WindowsIntel32e* method), 213
`translate()` (*WindowsIntelPAE* method), 215
`translate()` (*WindowsMixin* method), 218
`translate()` (*XenCoreDumpLayer* method), 253
`TranslationLayerInterface` (class in *volatility3.framework.interfaces.layers*), 163
`TranslationLayerRequirement` (class in *volatility3.framework.configuration.requirements*), 115
`traverse()` (*MMVAD* method), 465
`traverse()` (*MMVAD_SHORT* method), 468
`traverse()` (*SERVICE_RECORD* method), 524
`TreeGrid` (class in *volatility3.framework.interfaces.renderers*), 174
`TreeGrid` (class in *volatility3.framework.renderers*), 307
`TreeNode` (class in *volatility3.framework.interfaces.renderers*), 176
`TreeNode` (class in *volatility3.framework.renderers*), 308
`truncate()` (*FileHandlerInterface* method), 171
`truncate()` (*NullFileHandler* method), 52
`Trustedbsd` (class in *volatility3.plugins.mac.trustedbsd*), 659
`tty_check` (class in *volatility3.plugins.linux.tty_check*), 618
`type` (*Column* attribute), 173
`type` (*SymbolInterface* property), 180
`TYPE` (*SymbolType* attribute), 324
`type_handlers` (*PdbReader* attribute), 527
`type_name` (*SymbolInterface* property), 180
`type_prefix` (*elf_phdr* property), 402
`types` (*BaseSymbolTableInterface* property), 178
`types` (*BashIntermedSymbols* property), 408
`types` (*IntermediateSymbolTable* property), 537
`types` (*ISFormatTable* property), 533
`types` (*LinuxKernelIntermedSymbols* property), 329
`types` (*MacKernelIntermedSymbols* property), 411
`types` (*NativeTable* property), 564
`types` (*NativeTableInterface* property), 180
`types` (*SymbolTableInterface* property), 184
`types` (*Version1Format* property), 540
`types` (*Version2Format* property), 543
`types` (*Version3Format* property), 546
`types` (*Version4Format* property), 549
`types` (*Version5Format* property), 552

`types` (*Version6Format* property), 555
`types` (*Version7Format* property), 558
`types` (*Version8Format* property), 561
`types` (*WindowsKernelIntermedSymbols* property), 440

U

`uncompress()` (in module *volatility3.framework.layers.avml*), 189
`UNICODE_STRING` (class in *volatility3.framework.symbols.windows.extensions*), 474
`UNICODE_STRING.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions*), 475
`UnionType` (class in *volatility3.framework.objects*), 299
`UnionType.VolTemplateProxy` (class in *volatility3.framework.objects*), 299
`unix_sock` (class in *volatility3.framework.symbols.linux.extensions*), 384
`unix_sock.VolTemplateProxy` (class in *volatility3.framework.symbols.linux.extensions*), 384
`unixtime_to_datetime()` (in module *volatility3.framework.renderers.conversion*), 310
`UnparsableValue` (class in *volatility3.framework.renderers*), 309
`UnreadableValue` (class in *volatility3.framework.renderers*), 309
`unsatisfied()` (*ADS* class method), 720
`unsatisfied()` (*AutomagicInterface* class method), 140
`unsatisfied()` (*AVMLLayer* class method), 188
`unsatisfied()` (*Banners* class method), 777
`unsatisfied()` (*Bash* class method), 569, 623
`unsatisfied()` (*BashIntermedSymbols* class method), 408
`unsatisfied()` (*BigPools* class method), 672
`unsatisfied()` (*BooleanRequirement* method), 97
`unsatisfied()` (*BufferDataLayer* class method), 232
`unsatisfied()` (*BytesRequirement* method), 99
`unsatisfied()` (*Cachedump* class method), 674
`unsatisfied()` (*Callbacks* class method), 677
`unsatisfied()` (*Capabilities* class method), 571
`unsatisfied()` (*Check_afinfo* class method), 573
`unsatisfied()` (*Check_creds* class method), 574
`unsatisfied()` (*Check_idt* class method), 576
`unsatisfied()` (*Check_modules* class method), 578
`unsatisfied()` (*Check_syscall* class method), 579, 624
`unsatisfied()` (*Check_sysctl* class method), 626
`unsatisfied()` (*Check_trap_table* class method), 627
`unsatisfied()` (*ChoiceRequirement* method), 100
`unsatisfied()` (*ClassRequirement* method), 143
`unsatisfied()` (*CmdLine* class method), 679
`unsatisfied()` (*ComplexListRequirement* method), 102

- `unsatisfied()` (*ConfigurableInterface* class method), 144
- `unsatisfied()` (*ConfigurableModule* class method), 130
- `unsatisfied()` (*ConfigurableRequirementInterface* method), 145
- `unsatisfied()` (*ConfigWriter* class method), 778
- `unsatisfied()` (*ConstructableRequirementInterface* method), 147
- `unsatisfied()` (*ConstructionMagic* class method), 72
- `unsatisfied()` (*Crashinfo* class method), 681
- `unsatisfied()` (*DataLayerInterface* class method), 161
- `unsatisfied()` (*DeviceTree* class method), 682
- `unsatisfied()` (*DllList* class method), 684
- `unsatisfied()` (*Dmesg* class method), 629
- `unsatisfied()` (*DriverIrp* class method), 686
- `unsatisfied()` (*DriverModule* class method), 688
- `unsatisfied()` (*DriverScan* class method), 690
- `unsatisfied()` (*DumpFiles* class method), 692
- `unsatisfied()` (*Elf64Layer* class method), 198
- `unsatisfied()` (*Elfs* class method), 581
- `unsatisfied()` (*Envvars* class method), 583, 693
- `unsatisfied()` (*FileLayer* class method), 234
- `unsatisfied()` (*FileScan* class method), 695
- `unsatisfied()` (*FrameworkInfo* class method), 780
- `unsatisfied()` (*GetServiceSIDs* class method), 697
- `unsatisfied()` (*GetSIDs* class method), 699
- `unsatisfied()` (*Handles* class method), 701
- `unsatisfied()` (*Hashdump* class method), 704
- `unsatisfied()` (*HiveList* class method), 665
- `unsatisfied()` (*HiveScan* class method), 667
- `unsatisfied()` (*IAT* class method), 705
- `unsatisfied()` (*Ifconfig* class method), 631
- `unsatisfied()` (*Info* class method), 708
- `unsatisfied()` (*Intel* class method), 201
- `unsatisfied()` (*Intel32e* class method), 204
- `unsatisfied()` (*IntelPAE* class method), 207
- `unsatisfied()` (*IntermediateSymbolTable* class method), 537
- `unsatisfied()` (*IntRequirement* method), 103
- `unsatisfied()` (*IOMem* class method), 585
- `unsatisfied()` (*IsfInfo* class method), 781
- `unsatisfied()` (*ISFormatTable* class method), 533
- `unsatisfied()` (*JobLinks* class method), 709
- `unsatisfied()` (*Kauth_listeners* class method), 632
- `unsatisfied()` (*Kauth_scopes* class method), 634
- `unsatisfied()` (*KernelModule* class method), 79
- `unsatisfied()` (*KernelPDBScanner* class method), 82
- `unsatisfied()` (*Kevents* class method), 636
- `unsatisfied()` (*Keyboard_notifiers* class method), 586
- `unsatisfied()` (*Kmsg* class method), 589
- `unsatisfied()` (*LayerListRequirement* method), 105
- `unsatisfied()` (*LayerStacker* class method), 85
- `unsatisfied()` (*LayerWriter* class method), 783
- `unsatisfied()` (*LdrModules* class method), 711
- `unsatisfied()` (*LibraryList* class method), 597
- `unsatisfied()` (*LimeLayer* class method), 221
- `unsatisfied()` (*LinearlyMappedLayer* class method), 224
- `unsatisfied()` (*LinuxKernelIntermedSymbols* class method), 329
- `unsatisfied()` (*LinuxSymbolFinder* class method), 75
- `unsatisfied()` (*List_Files* class method), 638
- `unsatisfied()` (*ListRequirement* method), 106
- `unsatisfied()` (*Lsadbump* class method), 713
- `unsatisfied()` (*Lsmmod* class method), 599, 640
- `unsatisfied()` (*Lsof* class method), 601, 641
- `unsatisfied()` (*MacKernelIntermedSymbols* class method), 411
- `unsatisfied()` (*MacSymbolFinder* class method), 77
- `unsatisfied()` (*Malfind* class method), 603, 643, 715
- `unsatisfied()` (*Maps* class method), 607, 648
- `unsatisfied()` (*MBRScan* class method), 716
- `unsatisfied()` (*Memmap* class method), 718
- `unsatisfied()` (*MFTScan* class method), 721
- `unsatisfied()` (*ModScan* class method), 724
- `unsatisfied()` (*Module* class method), 134
- `unsatisfied()` (*ModuleInterface* class method), 158
- `unsatisfied()` (*ModuleRequirement* method), 108
- `unsatisfied()` (*Modules* class method), 726
- `unsatisfied()` (*Mount* class method), 645
- `unsatisfied()` (*MountInfo* class method), 604
- `unsatisfied()` (*MultiRequirement* method), 110
- `unsatisfied()` (*MutantScan* class method), 728
- `unsatisfied()` (*NetScan* class method), 731
- `unsatisfied()` (*NetStat* class method), 736
- `unsatisfied()` (*Netstat* class method), 646
- `unsatisfied()` (*NonLinearlySegmentedLayer* class method), 246
- `unsatisfied()` (*Passphrase* class method), 765
- `unsatisfied()` (*PdbMSFStream* class method), 227
- `unsatisfied()` (*PdbMultiStreamFormat* class method), 230
- `unsatisfied()` (*PluginInterface* class method), 172
- `unsatisfied()` (*PluginRequirement* method), 111
- `unsatisfied()` (*PoolScanner* class method), 739
- `unsatisfied()` (*PrintKey* class method), 669
- `unsatisfied()` (*Privs* class method), 742
- `unsatisfied()` (*PsAux* class method), 609
- `unsatisfied()` (*Psaux* class method), 650
- `unsatisfied()` (*PsList* class method), 611, 654, 745
- `unsatisfied()` (*PsScan* class method), 613, 748
- `unsatisfied()` (*PsTree* class method), 615, 655, 750
- `unsatisfied()` (*QemuSuspendLayer* class method), 238
- `unsatisfied()` (*RegistryHive* class method), 241
- `unsatisfied()` (*RequirementInterface* method), 150
- `unsatisfied()` (*SegmentedLayer* class method), 248
- `unsatisfied()` (*Sessions* class method), 751

`unsatisfied()` (*SimpleTypeRequirement* method), 152
`unsatisfied()` (*SizedModule* class method), 138
`unsatisfied()` (*Skeleton_Key_Check* class method), 753
`unsatisfied()` (*Socket_filters* class method), 657
`unsatisfied()` (*Sockstat* class method), 617
`unsatisfied()` (*SSDT* class method), 755
`unsatisfied()` (*StringRequirement* method), 113
`unsatisfied()` (*Strings* class method), 757
`unsatisfied()` (*SvcScan* class method), 759
`unsatisfied()` (*SymbolCacheMagic* class method), 91
`unsatisfied()` (*SymbolFinder* class method), 93
`unsatisfied()` (*SymbolTableInterface* class method), 184
`unsatisfied()` (*SymbolTableRequirement* method), 115
`unsatisfied()` (*SymlinkScan* class method), 761
`unsatisfied()` (*ThrdScan* class method), 763
`unsatisfied()` (*Timeliner* class method), 787
`unsatisfied()` (*Timers* class method), 659
`unsatisfied()` (*TranslationLayerInterface* class method), 165
`unsatisfied()` (*TranslationLayerRequirement* method), 116
`unsatisfied()` (*Trustedbsd* class method), 660
`unsatisfied()` (*tty_check* class method), 619
`unsatisfied()` (*URIRequirement* method), 118
`unsatisfied()` (*UserAssist* class method), 670
`unsatisfied()` (*VadInfo* class method), 767
`unsatisfied()` (*VadWalk* class method), 769
`unsatisfied()` (*VadYaraScan* class method), 771
`unsatisfied()` (*VerInfo* class method), 773
`unsatisfied()` (*Version1Format* class method), 540
`unsatisfied()` (*Version2Format* class method), 543
`unsatisfied()` (*Version3Format* class method), 546
`unsatisfied()` (*Version4Format* class method), 549
`unsatisfied()` (*Version5Format* class method), 552
`unsatisfied()` (*Version6Format* class method), 555
`unsatisfied()` (*Version7Format* class method), 558
`unsatisfied()` (*Version8Format* class method), 561
`unsatisfied()` (*VersionRequirement* method), 119
`unsatisfied()` (*VFSevents* class method), 662
`unsatisfied()` (*VirtMap* class method), 775
`unsatisfied()` (*VmaYaraScan* class method), 621
`unsatisfied()` (*VmwareLayer* class method), 250
`unsatisfied()` (*Volshell* class method), 55, 58, 61, 63
`unsatisfied()` (*WindowsCrashDump32Layer* class method), 192
`unsatisfied()` (*WindowsCrashDump64Layer* class method), 195
`unsatisfied()` (*WindowsIntel* class method), 210
`unsatisfied()` (*WindowsIntel32e* class method), 213
`unsatisfied()` (*WindowsIntelPAE* class method), 215
`unsatisfied()` (*WindowsKernelIntermedSymbols* class method), 440
`unsatisfied()` (*WindowsMixin* class method), 218
`unsatisfied()` (*WinSwapLayers* class method), 95
`unsatisfied()` (*XenCoreDumpLayer* class method), 253
`unsatisfied()` (*YaraScan* class method), 789
`unsatisfied_children()` (*BooleanRequirement* method), 97
`unsatisfied_children()` (*BytesRequirement* method), 99
`unsatisfied_children()` (*ChoiceRequirement* method), 100
`unsatisfied_children()` (*ClassRequirement* method), 143
`unsatisfied_children()` (*ComplexListRequirement* method), 102
`unsatisfied_children()` (*ConfigurableRequirementInterface* method), 146
`unsatisfied_children()` (*ConstructableRequirementInterface* method), 147
`unsatisfied_children()` (*IntRequirement* method), 103
`unsatisfied_children()` (*LayerListRequirement* method), 105
`unsatisfied_children()` (*ListRequirement* method), 107
`unsatisfied_children()` (*ModuleRequirement* method), 108
`unsatisfied_children()` (*MultiRequirement* method), 110
`unsatisfied_children()` (*PluginRequirement* method), 112
`unsatisfied_children()` (*RequirementInterface* method), 151
`unsatisfied_children()` (*SimpleTypeRequirement* method), 152
`unsatisfied_children()` (*StringRequirement* method), 113
`unsatisfied_children()` (*SymbolTableRequirement* method), 115
`unsatisfied_children()` (*TranslationLayerRequirement* method), 117
`unsatisfied_children()` (*URIRequirement* method), 118
`unsatisfied_children()` (*VersionRequirement* method), 120
`UnsatisfiedException`, 566
`update()` (*CacheManagerInterface* method), 87
`update()` (*SqliteCache* method), 89
`update_vol()` (*ObjectTemplate* method), 304
`update_vol()` (*ReferenceTemplate* method), 305
`update_vol()` (*SymbolSpace.UnresolvedTemplate* method), 322
`update_vol()` (*Template* method), 169
`upper()` (*Bytes* method), 269

- `upper()` (*HexBytes* method), 317
- `upper()` (*MultiTypeData* method), 321
- `upper()` (*String* method), 297
- `URIRequirement` (class in *volatility3.framework.configuration.requirements*), 117
- `UserAssist` (class in *volatility3.plugins.windows.registry.userassist*), 669
- `uses_cache()` (*ResourceAccessor* method), 243
- V**
- `VACB` (class in *volatility3.framework.symbols.windows.extensions*), 476
- `VACB.VolTemplateProxy` (class in *volatility3.framework.symbols.windows.extensions*), 477
- `VACB_ARRAY` (*SHARED_CACHE_MAP* attribute), 470
- `VACB_BLOCK` (*SHARED_CACHE_MAP* attribute), 470
- `VACB_LEVEL_SHIFT` (*SHARED_CACHE_MAP* attribute), 470
- `VACB_OFFSET_SHIFT` (*SHARED_CACHE_MAP* attribute), 470
- `VACB_SIZE_OF_FIRST_LEVEL` (*SHARED_CACHE_MAP* attribute), 470
- `vad_dump()` (*VadInfo* class method), 768
- `VadInfo` (class in *volatility3.plugins.windows.vadinfo*), 766
- `VadWalk` (class in *volatility3.plugins.windows.vadwalk*), 768
- `VadYaraScan` (class in *volatility3.plugins.windows.vadyarascan*), 770
- `valid()` (in module *volatility3.schemas*), 789
- `validate()` (in module *volatility3.schemas*), 789
- `VALIDDUMP` (*WindowsCrashDump32Layer* attribute), 189
- `VALIDDUMP` (*WindowsCrashDump64Layer* attribute), 192
- `values` (*TreeNode* property), 176, 309
- `values()` (*HierarchicalDict* method), 149
- `values()` (*LayerContainer* method), 162
- `values()` (*ModuleCollection* method), 135
- `values()` (*ModuleContainer* method), 155
- `values()` (*ObjectInformation* method), 166
- `values()` (*ReadOnlyMapping* method), 168
- `values()` (*SymbolSpace* method), 324
- `values()` (*SymbolSpaceInterface* method), 182
- `values()` (*TreeGrid* method), 175, 308
- `verify_table_versions()` (*SymbolSpace* method), 324
- `VerInfo` (class in *volatility3.plugins.windows.verinfo*), 772
- `version` (*ADS* attribute), 720
- `version` (*Banners* attribute), 777
- `version` (*Bash* attribute), 569, 623
- `version` (*BigPools* attribute), 673
- `version` (*BytesScanner* attribute), 185
- `version` (*Cachedump* attribute), 674
- `version` (*CacheManagerInterface* attribute), 87
- `version` (*Callbacks* attribute), 678
- `version` (*Capabilities* attribute), 571
- `version` (*Check_afinfo* attribute), 573
- `version` (*Check_creds* attribute), 575
- `version` (*Check_idt* attribute), 576
- `version` (*Check_modules* attribute), 578
- `version` (*Check_syscall* attribute), 579, 624
- `version` (*Check_sysctl* attribute), 626
- `version` (*Check_trap_table* attribute), 628
- `version` (*CmdLine* attribute), 679
- `version` (*ConfigWriter* attribute), 778
- `version` (*Crashinfo* attribute), 681
- `version` (*DeviceTree* attribute), 683
- `version` (*DllList* attribute), 685
- `version` (*Dmesg* attribute), 629
- `version` (*DriverIrp* attribute), 686
- `version` (*DriverModule* attribute), 688
- `version` (*DriverScan* attribute), 690
- `version` (*DumpFiles* attribute), 692
- `version` (*Elfs* attribute), 581
- `version` (*Envvars* attribute), 583, 694
- `version` (*FileScan* attribute), 695
- `version` (*FrameworkInfo* attribute), 780
- `version` (*GetServiceSIDs* attribute), 697
- `version` (*GetSIDs* attribute), 699
- `version` (*Handles* attribute), 701
- `version` (*Hashdump* attribute), 704
- `version` (*HiveList* attribute), 665
- `version` (*HiveScan* attribute), 667
- `version` (*IAT* attribute), 705
- `version` (*Ifconfig* attribute), 631
- `version` (*Info* attribute), 708
- `version` (*IOMem* attribute), 585
- `version` (*IsfInfo* attribute), 782
- `version` (*ISFormatTable* attribute), 533
- `version` (*JobLinks* attribute), 709
- `version` (*Kauth_listeners* attribute), 633
- `version` (*Kauth_scopes* attribute), 634
- `version` (*Kevents* attribute), 636
- `version` (*Keyboard_notifiers* attribute), 586
- `version` (*Kmsg* attribute), 590
- `version` (*LayerWriter* attribute), 783
- `version` (*LdrModules* attribute), 711
- `version` (*LibraryList* attribute), 598
- `VERSION` (*LimeLayer* attribute), 219
- `version` (*LinuxUtilities* attribute), 331
- `version` (*List_Files* attribute), 638
- `version` (*Lsadbump* attribute), 713
- `version` (*Lsmod* attribute), 600, 640
- `version` (*Lsof* attribute), 601, 641

`version` (*MacUtilities* attribute), 412
`version` (*Malfind* attribute), 603, 643, 715
`version` (*Maps* attribute), 607, 648
`version` (*MBRScan* attribute), 717
`version` (*Memmap* attribute), 718
`version` (*MFTScan* attribute), 722
`version` (*ModScan* attribute), 724
`version` (*Modules* attribute), 727
`version` (*Mount* attribute), 645
`version` (*MountInfo* attribute), 605
`version` (*MultiStringScanner* attribute), 185
`version` (*MutantScan* attribute), 728
`version` (*NetScan* attribute), 731
`version` (*NetStat* attribute), 736
`version` (*Netstat* attribute), 647
`version` (*PageMapScanner* attribute), 94
`version` (*Passphrase* attribute), 765
`version` (*PdbSignatureScanner* attribute), 530
`version` (*PDBUtility* attribute), 529
`version` (*PluginInterface* attribute), 173
`version` (*PoolHeaderScanner* attribute), 736
`version` (*PoolScanner* attribute), 739
`version` (*PrintKey* attribute), 669
`version` (*Privs* attribute), 742
`version` (*ProducerMetadata* property), 561
`version` (*PsAux* attribute), 609
`version` (*Psaux* attribute), 651
`version` (*PsList* attribute), 612, 654, 745
`version` (*PsScan* attribute), 614, 748
`version` (*PsTree* attribute), 615, 656, 750
`version` (*RegExScanner* attribute), 185
`version` (*ScannerInterface* attribute), 163
`version` (*Sessions* attribute), 752
`version` (*Skeleton_Key_Check* attribute), 753
`version` (*Socket_filters* attribute), 657
`version` (*SockHandlers* attribute), 616
`version` (*Sockstat* attribute), 618
`version` (*SqliteCache* attribute), 89
`version` (*SSDT* attribute), 755
`version` (*Strings* attribute), 757
`version` (*SvcScan* attribute), 759
`version` (*SymlinkScan* attribute), 761
`version` (*ThrdScan* attribute), 763
`version` (*Timeliner* attribute), 787
`version` (*Timers* attribute), 659
`version` (*Trustedbsd* attribute), 660
`version` (*tty_check* attribute), 619
`version` (*UserAssist* attribute), 671
`version` (*VadInfo* attribute), 768
`version` (*VadWalk* attribute), 770
`version` (*VadYaraScan* attribute), 771
`version` (*VerInfo* attribute), 773
`version` (*Version1Format* attribute), 540
`version` (*Version2Format* attribute), 543
`version` (*Version3Format* attribute), 546
`version` (*Version4Format* attribute), 549
`version` (*Version5Format* attribute), 552
`version` (*Version6Format* attribute), 555
`version` (*Version7Format* attribute), 558
`version` (*Version8Format* attribute), 561
`version` (*VersionableInterface* attribute), 152
`version` (*VFSevents* attribute), 662
`version` (*VirtMap* attribute), 775
`version` (*VmaYaraScan* attribute), 621
`version` (*Volshell* attribute), 55, 58, 61, 64
`version` (*YaraScan* attribute), 789
`version` (*YaraScanner* attribute), 789
`Version1Format` (class in *volatility3.framework.symbols.intermed*), 537
`Version2Format` (class in *volatility3.framework.symbols.intermed*), 540
`Version3Format` (class in *volatility3.framework.symbols.intermed*), 543
`Version4Format` (class in *volatility3.framework.symbols.intermed*), 546
`Version5Format` (class in *volatility3.framework.symbols.intermed*), 549
`Version6Format` (class in *volatility3.framework.symbols.intermed*), 552
`Version7Format` (class in *volatility3.framework.symbols.intermed*), 555
`Version8Format` (class in *volatility3.framework.symbols.intermed*), 558
`VersionableInterface` (class in *volatility3.framework.interfaces.configuration*), 152
`VersionRequirement` (class in *volatility3.framework.configuration.requirements*), 118
`VFSevents` (class in *volatility3.plugins.mac.vfsevents*), 661
`vfsmount` (class in *volatility3.framework.symbols.linux.extensions*), 385
`vfsmount.VolTemplateProxy` (class in *volatility3.framework.symbols.linux.extensions*), 386
`VirtMap` (class in *volatility3.plugins.windows.virtmap*), 774
`virtual_process_from_physical()` (*PsScan* class method), 748
`virtual_to_physical_address()` (*LinuxIntelStacker* class method), 73
`virtual_to_physical_address()` (*MacIntelStacker* class method), 75
`visit()` (*TreeGrid* method), 175, 308
`visit_nodes()` (*RegistryHive* method), 241
`vm_area_struct` (class in *volatil-*

[ity3.framework.symbols.linux.extensions](#)), 389
[vm_area_struct.VolTemplateProxy](#) (class in [volatility3.framework.symbols.linux.extensions](#)), 389
[vm_map_entry](#) (class in [volatility3.framework.symbols.mac.extensions](#)), 431
[vm_map_entry.VolTemplateProxy](#) (class in [volatility3.framework.symbols.mac.extensions](#)), 431
[vm_map_object](#) (class in [volatility3.framework.symbols.mac.extensions](#)), 433
[vm_map_object.VolTemplateProxy](#) (class in [volatility3.framework.symbols.mac.extensions](#)), 433
[vma_dump\(\)](#) (Maps class method), 607, 648
[VmaYaraScan](#) (class in [volatility3.plugins.linux.vmayarascan](#)), 619
[VmwareFormatException](#), 248
[VmwareLayer](#) (class in [volatility3.framework.layers.vmware](#)), 248
[VmwareStacker](#) (class in [volatility3.framework.layers.vmware](#)), 251
[vnode](#) (class in [volatility3.framework.symbols.mac.extensions](#)), 435
[vnode.VolTemplateProxy](#) (class in [volatility3.framework.symbols.mac.extensions](#)), 435
[vnode_filters](#) (Kevents attribute), 636
[Void](#) (class in [volatility3.framework.objects](#)), 301
[Void.VolTemplateProxy](#) (class in [volatility3.framework.objects](#)), 301
[vol](#) (AggregateType property), 256
[vol](#) (Array property), 258
[vol](#) (BitField property), 261
[vol](#) (Boolean property), 264
[vol](#) (bpf_prog property), 333
[vol](#) (bt_sock property), 335
[vol](#) (Bytes property), 269
[vol](#) (Char property), 273
[vol](#) (ClassType property), 274
[vol](#) (CM_KEY_BODY property), 512
[vol](#) (CM_KEY_NODE property), 514
[vol](#) (CM_KEY_VALUE property), 516
[vol](#) (CMHIVE property), 510
[vol](#) (CONTROL_AREA property), 442
[vol](#) (cred property), 337
[vol](#) (dentry property), 339
[vol](#) (DEVICE_OBJECT property), 444
[vol](#) (DRIVER_OBJECT property), 446
[vol](#) (elf property), 399
[vol](#) (elf_linkmap property), 401
[vol](#) (elf_phdr property), 402
[vol](#) (elf_sym property), 404
[vol](#) (Enumeration property), 278
[vol](#) (EPROCESS property), 449
[vol](#) (ETHREAD property), 451
[vol](#) (EX_FAST_REF property), 453
[vol](#) (ExecutiveObject property), 499
[vol](#) (FILE_OBJECT property), 455
[vol](#) (fileglob property), 414
[vol](#) (files_struct property), 340
[vol](#) (Float property), 281
[vol](#) (fs_struct property), 342
[vol](#) (Function property), 282
[vol](#) (GenericIntelProcess property), 326
[vol](#) (hist_entry property), 397
[vol](#) (HMAP_ENTRY property), 518
[vol](#) (ifnet property), 416
[vol](#) (IMAGE_DOS_HEADER property), 495
[vol](#) (IMAGE_NT_HEADERS property), 497
[vol](#) (inet_sock property), 344
[vol](#) (inpcb property), 417
[vol](#) (Integer property), 286
[vol](#) (kauth_scope property), 419
[vol](#) (KDDEBUGGER_DATA64 property), 482
[vol](#) (kernel_cap_struct property), 347
[vol](#) (kernel_cap_t property), 350
[vol](#) (KMUTANT property), 457
[vol](#) (kobject property), 351
[vol](#) (KSYSTEM_TIME property), 459
[vol](#) (KTHREAD property), 461
[vol](#) (LIST_ENTRY property), 463
[vol](#) (list_head property), 353
[vol](#) (maple_tree property), 356
[vol](#) (MFTAttribute property), 489
[vol](#) (MFTEntry property), 490
[vol](#) (MFTFileName property), 492
[vol](#) (mm_struct property), 358
[vol](#) (MMVAD property), 465
[vol](#) (MMVAD_SHORT property), 468
[vol](#) (mnt_namespace property), 359
[vol](#) (module property), 362
[vol](#) (mount property), 366
[vol](#) (net property), 367
[vol](#) (netlink_sock property), 369
[vol](#) (OBJECT_HEADER property), 501
[vol](#) (OBJECT_SYMBOLIC_LINK property), 470
[vol](#) (ObjectInterface property), 168
[vol](#) (ObjectTemplate property), 304
[vol](#) (packet_sock property), 371
[vol](#) (PARTITION_ENTRY property), 485
[vol](#) (PARTITION_TABLE property), 487
[vol](#) (Pointer property), 289
[vol](#) (POOL_HEADER property), 503
[vol](#) (POOL_HEADER_VISTA property), 506
[vol](#) (POOL_TRACKER_BIG_PAGES property), 508
[vol](#) (PrimitiveObject property), 291

- `vol` (*proc property*), 421
- `vol` (*qstr property*), 373
- `vol` (*queue_entry property*), 423
- `vol` (*ReferenceTemplate property*), 305
- `vol` (*SERVICE_HEADER property*), 522
- `vol` (*SERVICE_RECORD property*), 524
- `vol` (*SHARED_CACHE_MAP property*), 472
- `vol` (*sock property*), 375
- `vol` (*sockaddr property*), 425
- `vol` (*sockaddr_dl property*), 427
- `vol` (*socket property*), 377, 429
- `vol` (*String property*), 297
- `vol` (*struct_file property*), 378
- `vol` (*StructType property*), 299
- `vol` (*SUMMARY_DUMP property*), 480
- `vol` (*super_block property*), 381
- `vol` (*SymbolSpace.UnresolvedTemplate property*), 322
- `vol` (*sysctl_oid property*), 431
- `vol` (*task_struct property*), 384
- `vol` (*Template property*), 169
- `vol` (*TOKEN property*), 474
- `vol` (*UNICODE_STRING property*), 476
- `vol` (*UnionType property*), 301
- `vol` (*unix_sock property*), 385
- `vol` (*VACB property*), 478
- `vol` (*vfsmount property*), 389
- `vol` (*vm_area_struct property*), 391
- `vol` (*vm_map_entry property*), 433
- `vol` (*vm_map_object property*), 435
- `vol` (*vnode property*), 437
- `vol` (*Void property*), 302
- `vol` (*vsock_sock property*), 393
- `vol` (*xdp_sock property*), 395
- `volatility3`
 - module, 47
- `volatility3.cli`
 - module, 48
- `volatility3.cli.text_filter`
 - module, 64
- `volatility3.cli.text_renderer`
 - module, 64
- `volatility3.cli.volargparse`
 - module, 68
- `volatility3.cli.volshell`
 - module, 49
- `volatility3.cli.volshell.generic`
 - module, 51
- `volatility3.cli.volshell.linux`
 - module, 55
- `volatility3.cli.volshell.mac`
 - module, 58
- `volatility3.cli.volshell.windows`
 - module, 61
- `volatility3.framework`
 - module, 69
- `volatility3.framework.automagic`
 - module, 70
- `volatility3.framework.automagic.construct_layers`
 - module, 71
- `volatility3.framework.automagic.linux`
 - module, 73
- `volatility3.framework.automagic.mac`
 - module, 75
- `volatility3.framework.automagic.module`
 - module, 78
- `volatility3.framework.automagic.pdbscan`
 - module, 79
- `volatility3.framework.automagic.stacker`
 - module, 83
- `volatility3.framework.automagic.symbol_cache`
 - module, 86
- `volatility3.framework.automagic.symbol_finder`
 - module, 91
- `volatility3.framework.automagic.windows`
 - module, 93
- `volatility3.framework.configuration`
 - module, 96
- `volatility3.framework.configuration.requirements`
 - module, 96
- `volatility3.framework.constants`
 - module, 120
- `volatility3.framework.constants.linux`
 - module, 124
- `volatility3.framework.constants.windows`
 - module, 127
- `volatility3.framework.contexts`
 - module, 127
- `volatility3.framework.exceptions`
 - module, 564
- `volatility3.framework.interfaces`
 - module, 139
- `volatility3.framework.interfaces.automagic`
 - module, 139
- `volatility3.framework.interfaces.configuration`
 - module, 141
- `volatility3.framework.interfaces.context`
 - module, 153
- `volatility3.framework.interfaces.layers`
 - module, 158
- `volatility3.framework.interfaces.objects`
 - module, 165
- `volatility3.framework.interfaces.plugins`
 - module, 169
- `volatility3.framework.interfaces.renderers`
 - module, 173
- `volatility3.framework.interfaces.symbols`
 - module, 176
- `volatility3.framework.layers`

- module, 185
- volatility3.framework.layers.avml
 - module, 186
- volatility3.framework.layers.cloudstorage
 - module, 189
- volatility3.framework.layers.codecs
 - module, 185
- volatility3.framework.layers.crash
 - module, 189
- volatility3.framework.layers.elf
 - module, 196
- volatility3.framework.layers.intel
 - module, 199
- volatility3.framework.layers.leechcore
 - module, 219
- volatility3.framework.layers.lime
 - module, 219
- volatility3.framework.layers.linear
 - module, 222
- volatility3.framework.layers.msf
 - module, 225
- volatility3.framework.layers.physical
 - module, 230
- volatility3.framework.layers.qemu
 - module, 235
- volatility3.framework.layers.registry
 - module, 238
- volatility3.framework.layers.resources
 - module, 242
- volatility3.framework.layers.scanners
 - module, 185
- volatility3.framework.layers.scanners.multiregex
 - module, 186
- volatility3.framework.layers.segmented
 - module, 244
- volatility3.framework.layers.vmware
 - module, 248
- volatility3.framework.layers.xen
 - module, 251
- volatility3.framework.objects
 - module, 254
- volatility3.framework.objects.templates
 - module, 303
- volatility3.framework.objects.utility
 - module, 305
- volatility3.framework.plugins
 - module, 306
- volatility3.framework.renderers
 - module, 306
- volatility3.framework.renderers.conversion
 - module, 309
- volatility3.framework.renderers.format_hints
 - module, 310
- volatility3.framework.symbols
 - module, 321
- volatility3.framework.symbols.generic
 - module, 324
- volatility3.framework.symbols.intermed
 - module, 531
- volatility3.framework.symbols.linux
 - module, 326
- volatility3.framework.symbols.linux.bash
 - module, 405
- volatility3.framework.symbols.linux.extensions
 - module, 331
- volatility3.framework.symbols.linux.extensions.bash
 - module, 395
- volatility3.framework.symbols.linux.extensions.elf
 - module, 397
- volatility3.framework.symbols.mac
 - module, 408
- volatility3.framework.symbols.mac.extensions
 - module, 412
- volatility3.framework.symbols.metadata
 - module, 561
- volatility3.framework.symbols.native
 - module, 562
- volatility3.framework.symbols.windows
 - module, 437
- volatility3.framework.symbols.windows.extensions
 - module, 440
- volatility3.framework.symbols.windows.extensions.crash
 - module, 478
- volatility3.framework.symbols.windows.extensions.kdbg
 - module, 480
- volatility3.framework.symbols.windows.extensions.mbr
 - module, 482
- volatility3.framework.symbols.windows.extensions.mft
 - module, 487
- volatility3.framework.symbols.windows.extensions.network
 - module, 493
- volatility3.framework.symbols.windows.extensions.pe
 - module, 493
- volatility3.framework.symbols.windows.extensions.pool
 - module, 497
- volatility3.framework.symbols.windows.extensions.registry
 - module, 508
- volatility3.framework.symbols.windows.extensions.services
 - module, 520
- volatility3.framework.symbols.windows.pdbconv
 - module, 525
- volatility3.framework.symbols.windows.pdbutil
 - module, 527
- volatility3.framework.symbols.windows.versions
 - module, 530
- volatility3.framework.symbols.wrappers
 - module, 564
- volatility3.plugins

- module, 567
- volatility3.plugins.banners
 - module, 775
- volatility3.plugins.configwriter
 - module, 777
- volatility3.plugins.frameworkinfo
 - module, 779
- volatility3.plugins.isfinfo
 - module, 780
- volatility3.plugins.layerwriter
 - module, 782
- volatility3.plugins.linux
 - module, 567
- volatility3.plugins.linux.bash
 - module, 567
- volatility3.plugins.linux.capabilities
 - module, 569
- volatility3.plugins.linux.check_afinfo
 - module, 572
- volatility3.plugins.linux.check_creds
 - module, 573
- volatility3.plugins.linux.check_idt
 - module, 575
- volatility3.plugins.linux.check_modules
 - module, 576
- volatility3.plugins.linux.check_syscall
 - module, 578
- volatility3.plugins.linux.elfs
 - module, 580
- volatility3.plugins.linux.envvars
 - module, 582
- volatility3.plugins.linux.iomem
 - module, 583
- volatility3.plugins.linux.keyboard_notifiers
 - module, 585
- volatility3.plugins.linux.kmsg
 - module, 587
- volatility3.plugins.linux.library_list
 - module, 596
- volatility3.plugins.linux.lsmod
 - module, 598
- volatility3.plugins.linux.lsof
 - module, 600
- volatility3.plugins.linux.malfind
 - module, 601
- volatility3.plugins.linux.mountinfo
 - module, 603
- volatility3.plugins.linux.proc
 - module, 606
- volatility3.plugins.linux.psaux
 - module, 608
- volatility3.plugins.linux.pslist
 - module, 609
- volatility3.plugins.linux.psscan
 - module, 612
- volatility3.plugins.linux.pstree
 - module, 614
- volatility3.plugins.linux.sockstat
 - module, 616
- volatility3.plugins.linux.tty_check
 - module, 618
- volatility3.plugins.linux.vmayarascan
 - module, 619
- volatility3.plugins.mac
 - module, 621
- volatility3.plugins.mac.bash
 - module, 621
- volatility3.plugins.mac.check_syscall
 - module, 623
- volatility3.plugins.mac.check_sysctl
 - module, 625
- volatility3.plugins.mac.check_trap_table
 - module, 626
- volatility3.plugins.mac.dmesg
 - module, 628
- volatility3.plugins.mac.ifconfig
 - module, 630
- volatility3.plugins.mac.kauth_listeners
 - module, 631
- volatility3.plugins.mac.kauth_scopes
 - module, 633
- volatility3.plugins.mac.kevents
 - module, 634
- volatility3.plugins.mac.list_files
 - module, 637
- volatility3.plugins.mac.lsmod
 - module, 638
- volatility3.plugins.mac.lsof
 - module, 640
- volatility3.plugins.mac.malfind
 - module, 642
- volatility3.plugins.mac.mount
 - module, 643
- volatility3.plugins.mac.netstat
 - module, 645
- volatility3.plugins.mac.proc_maps
 - module, 647
- volatility3.plugins.mac.psaux
 - module, 649
- volatility3.plugins.mac.pslist
 - module, 651
- volatility3.plugins.mac.pstree
 - module, 654
- volatility3.plugins.mac.socket_filters
 - module, 656
- volatility3.plugins.mac.timers
 - module, 657
- volatility3.plugins.mac.trustedbsd
 - module, 657

module, 659
volatility3.plugins.mac.vfsevents
module, 661
volatility3.plugins.timeliner
module, 784
volatility3.plugins.windows
module, 662
volatility3.plugins.windows.bigpools
module, 671
volatility3.plugins.windows.cachedump
module, 673
volatility3.plugins.windows.callbacks
module, 675
volatility3.plugins.windows.cmdline
module, 678
volatility3.plugins.windows.crashinfo
module, 680
volatility3.plugins.windows.devicetree
module, 681
volatility3.plugins.windows.dllexport
module, 683
volatility3.plugins.windows.driverirp
module, 685
volatility3.plugins.windows.drivermodule
module, 686
volatility3.plugins.windows.driverscan
module, 688
volatility3.plugins.windows.dumpfiles
module, 690
volatility3.plugins.windows.envvars
module, 692
volatility3.plugins.windows.filescan
module, 694
volatility3.plugins.windows.getservicesids
module, 696
volatility3.plugins.windows.getsids
module, 697
volatility3.plugins.windows.handles
module, 699
volatility3.plugins.windows.hashdump
module, 701
volatility3.plugins.windows.iat
module, 704
volatility3.plugins.windows.info
module, 706
volatility3.plugins.windows.joblinks
module, 708
volatility3.plugins.windows.lldrmodules
module, 710
volatility3.plugins.windows.lsadump
module, 711
volatility3.plugins.windows.malfind
module, 713
volatility3.plugins.windows.mbrscan
module, 715
volatility3.plugins.windows.memmap
module, 717
volatility3.plugins.windows.mftscan
module, 719
volatility3.plugins.windows.modscan
module, 722
volatility3.plugins.windows.modules
module, 724
volatility3.plugins.windows.mutantscan
module, 727
volatility3.plugins.windows.netscan
module, 729
volatility3.plugins.windows.netstat
module, 731
volatility3.plugins.windows.poolscanner
module, 736
volatility3.plugins.windows.privileges
module, 741
volatility3.plugins.windows.pslist
module, 743
volatility3.plugins.windows.psscan
module, 746
volatility3.plugins.windows.pstree
module, 749
volatility3.plugins.windows.registry
module, 663
volatility3.plugins.windows.registry.hivelist
module, 663
volatility3.plugins.windows.registry.hivescan
module, 665
volatility3.plugins.windows.registry.printkey
module, 667
volatility3.plugins.windows.registry.userassist
module, 669
volatility3.plugins.windows.sessions
module, 750
volatility3.plugins.windows.skeleton_key_check
module, 752
volatility3.plugins.windows.ssdt
module, 753
volatility3.plugins.windows.strings
module, 755
volatility3.plugins.windows.svcscan
module, 757
volatility3.plugins.windows.symblinkscan
module, 760
volatility3.plugins.windows.thrdscan
module, 762
volatility3.plugins.windows.truecrypt
module, 764
volatility3.plugins.windows.vadinfo
module, 766
volatility3.plugins.windows.vadwalk

- module, 768
- volatility3.plugins.windows.vadyscan
 - module, 770
- volatility3.plugins.windows.verinfo
 - module, 772
- volatility3.plugins.windows.virtmap
 - module, 774
- volatility3.plugins.yarascan
 - module, 787
- volatility3.schemas
 - module, 789
- volatility3.symbols
 - module, 790
- VolatilityException, 566
- VolatilityHandler (class in volatility3.framework.layers.resources), 243
- VolShell (class in volatility3.cli.volshell), 49
- Volshell (class in volatility3.cli.volshell.generic), 52
- Volshell (class in volatility3.cli.volshell.linux), 55
- Volshell (class in volatility3.cli.volshell.mac), 58
- Volshell (class in volatility3.cli.volshell.windows), 61
- vsock_sock (class in volatility3.framework.symbols.linux.extensions), 391
- vsock_sock.VolTemplateProxy (class in volatility3.framework.symbols.linux.extensions), 391

W

- walk_internal_list() (LinuxUtilities class method), 331
- walk_list() (queue_entry method), 423
- walk_list_head() (MacUtilities class method), 412
- walk_slist() (MacUtilities class method), 412
- walk_tailq() (MacUtilities class method), 412
- WarningFindSpec (class in volatility3), 47
- WindowsCrashDump32Layer (class in volatility3.framework.layers.crash), 189
- WindowsCrashDump64Layer (class in volatility3.framework.layers.crash), 192
- WindowsCrashDumpFormatException, 195
- WindowsCrashDumpStacker (class in volatility3.framework.layers.crash), 195
- WindowsIdentifier (class in volatility3.framework.automagic.symbol_cache), 91
- WindowsIntel (class in volatility3.framework.layers.intel), 207
- WindowsIntel32e (class in volatility3.framework.layers.intel), 210
- WindowsIntelPAE (class in volatility3.framework.layers.intel), 213
- WindowsIntelStacker (class in volatility3.framework.automagic.windows), 96
- WindowsKernelIntermedSymbols (class in volatility3.framework.symbols.windows), 437
- WindowsMetadata (class in volatility3.framework.symbols.metadata), 562
- WindowsMixin (class in volatility3.framework.layers.intel), 216
- WinSwapLayers (class in volatility3.framework.automagic.windows), 94
- wintime_to_datetime() (in module volatility3.framework.renderers.conversion), 310
- with_traceback() (ElfFormatException method), 199
- with_traceback() (InvalidAddressException method), 564
- with_traceback() (LayerException method), 564
- with_traceback() (LimeFormatException method), 219
- with_traceback() (MissingModuleException method), 565
- with_traceback() (OfflineException method), 565
- with_traceback() (PagedInvalidAddressException method), 565
- with_traceback() (PDBFormatException method), 225
- with_traceback() (PluginRequirementException method), 565
- with_traceback() (PluginVersionException method), 565
- with_traceback() (RegistryFormatException method), 238
- with_traceback() (RegistryInvalidIndex method), 242
- with_traceback() (SnappyException method), 189
- with_traceback() (SwappedInvalidAddressException method), 566
- with_traceback() (SymbolError method), 566
- with_traceback() (SymbolSpaceError method), 566
- with_traceback() (UnsatisfiedException method), 566
- with_traceback() (VmwareFormatException method), 248
- with_traceback() (VolatilityException method), 567
- with_traceback() (WindowsCrashDumpFormatException method), 195
- writable() (FileHandlerInterface method), 171
- writable() (NullFileHandler method), 52
- write() (AggregateType method), 256
- write() (Array method), 258
- write() (AVMLLayer method), 188
- write() (BitField method), 261
- write() (Boolean method), 264
- write() (bpf_prog method), 333
- write() (bt_sock method), 335
- write() (BufferDataLayer method), 232
- write() (Bytes method), 269
- write() (Char method), 273
- write() (ClassType method), 274

[write\(\) \(CM_KEY_BODY method\), 512](#)
[write\(\) \(CM_KEY_NODE method\), 514](#)
[write\(\) \(CM_KEY_VALUE method\), 516](#)
[write\(\) \(CMHIVE method\), 510](#)
[write\(\) \(CONTROL_AREA method\), 442](#)
[write\(\) \(cred method\), 337](#)
[write\(\) \(DataLayerInterface method\), 161](#)
[write\(\) \(dentry method\), 339](#)
[write\(\) \(DEVICE_OBJECT method\), 444](#)
[write\(\) \(DRIVER_OBJECT method\), 446](#)
[write\(\) \(elf method\), 399](#)
[write\(\) \(Elf64Layer method\), 198](#)
[write\(\) \(elf_linkmap method\), 401](#)
[write\(\) \(elf_phdr method\), 402](#)
[write\(\) \(elf_sym method\), 404](#)
[write\(\) \(Enumeration method\), 278](#)
[write\(\) \(EPROCESS method\), 449](#)
[write\(\) \(ETHREAD method\), 451](#)
[write\(\) \(EX_FAST_REF method\), 453](#)
[write\(\) \(ExecutiveObject method\), 499](#)
[write\(\) \(FILE_OBJECT method\), 455](#)
[write\(\) \(fileglob method\), 414](#)
[write\(\) \(FileHandlerInterface method\), 171](#)
[write\(\) \(FileLayer method\), 234](#)
[write\(\) \(files_struct method\), 341](#)
[write\(\) \(Float method\), 281](#)
[write\(\) \(fs_struct method\), 342](#)
[write\(\) \(Function method\), 282](#)
[write\(\) \(GenericIntelProcess method\), 326](#)
[write\(\) \(hist_entry method\), 397](#)
[write\(\) \(HMAP_ENTRY method\), 518](#)
[write\(\) \(ifnet method\), 416](#)
[write\(\) \(IMAGE_DOS_HEADER method\), 495](#)
[write\(\) \(IMAGE_NT_HEADERS method\), 497](#)
[write\(\) \(inet_sock method\), 344](#)
[write\(\) \(inpcb method\), 418](#)
[write\(\) \(Integer method\), 286](#)
[write\(\) \(Intel method\), 202](#)
[write\(\) \(Intel32e method\), 204](#)
[write\(\) \(IntelPAE method\), 207](#)
[write\(\) \(kauth_scope method\), 419](#)
[write\(\) \(KDDEBUGGER_DATA64 method\), 482](#)
[write\(\) \(kernel_cap_struct method\), 347](#)
[write\(\) \(kernel_cap_t method\), 350](#)
[write\(\) \(KMUTANT method\), 457](#)
[write\(\) \(kobject method\), 351](#)
[write\(\) \(KSYSTEM_TIME method\), 459](#)
[write\(\) \(KTHREAD method\), 461](#)
[write\(\) \(LayerContainer method\), 162](#)
[write\(\) \(LimeLayer method\), 221](#)
[write\(\) \(LinearlyMappedLayer method\), 224](#)
[write\(\) \(LIST_ENTRY method\), 463](#)
[write\(\) \(list_head method\), 354](#)
[write\(\) \(maple_tree method\), 356](#)
[write\(\) \(MFTAttribute method\), 489](#)
[write\(\) \(MFTEntry method\), 491](#)
[write\(\) \(MFTFileName method\), 492](#)
[write\(\) \(mm_struct method\), 358](#)
[write\(\) \(MMVAD method\), 465](#)
[write\(\) \(MMVAD_SHORT method\), 468](#)
[write\(\) \(mnt_namespace method\), 359](#)
[write\(\) \(module method\), 362](#)
[write\(\) \(mount method\), 366](#)
[write\(\) \(net method\), 367](#)
[write\(\) \(netlink_sock method\), 369](#)
[write\(\) \(NonLinearlySegmentedLayer method\), 246](#)
[write\(\) \(NullFileHandler method\), 52](#)
[write\(\) \(OBJECT_HEADER method\), 501](#)
[write\(\) \(OBJECT_SYMBOLIC_LINK method\), 470](#)
[write\(\) \(ObjectInterface method\), 168](#)
[write\(\) \(packet_sock method\), 371](#)
[write\(\) \(PARTITION_ENTRY method\), 485](#)
[write\(\) \(PARTITION_TABLE method\), 487](#)
[write\(\) \(PdbMSFStream method\), 227](#)
[write\(\) \(PdbMultiStreamFormat method\), 230](#)
[write\(\) \(Pointer method\), 289](#)
[write\(\) \(POOL_HEADER method\), 503](#)
[write\(\) \(POOL_HEADER_VISTA method\), 506](#)
[write\(\) \(POOL_TRACKER_BIG_PAGES method\), 508](#)
[write\(\) \(PrimitiveObject method\), 291](#)
[write\(\) \(proc method\), 421](#)
[write\(\) \(QemuSuspendLayer method\), 238](#)
[write\(\) \(qstr method\), 373](#)
[write\(\) \(queue_entry method\), 423](#)
[write\(\) \(RegistryHive method\), 241](#)
[write\(\) \(SegmentedLayer method\), 248](#)
[write\(\) \(SERVICE_HEADER method\), 522](#)
[write\(\) \(SERVICE_RECORD method\), 525](#)
[write\(\) \(SHARED_CACHE_MAP method\), 472](#)
[write\(\) \(sock method\), 375](#)
[write\(\) \(sockaddr method\), 425](#)
[write\(\) \(sockaddr_dl method\), 427](#)
[write\(\) \(socket method\), 377, 429](#)
[write\(\) \(String method\), 297](#)
[write\(\) \(struct_file method\), 379](#)
[write\(\) \(StructType method\), 299](#)
[write\(\) \(SUMMARY_DUMP method\), 480](#)
[write\(\) \(super_block method\), 381](#)
[write\(\) \(sysctl_oid method\), 431](#)
[write\(\) \(task_struct method\), 384](#)
[write\(\) \(TOKEN method\), 474](#)
[write\(\) \(TranslationLayerInterface method\), 165](#)
[write\(\) \(UNICODE_STRING method\), 476](#)
[write\(\) \(UnionType method\), 301](#)
[write\(\) \(unix_sock method\), 385](#)
[write\(\) \(VACB method\), 478](#)
[write\(\) \(vfsmount method\), 389](#)
[write\(\) \(vm_area_struct method\), 391](#)

`write()` (*vm_map_entry method*), 433
`write()` (*vm_map_object method*), 435
`write()` (*VmwareLayer method*), 251
`write()` (*vnnode method*), 437
`write()` (*Void method*), 302
`write()` (*vssock_sock method*), 393
`write()` (*WindowsCrashDump32Layer method*), 192
`write()` (*WindowsCrashDump64Layer method*), 195
`write()` (*WindowsIntel method*), 210
`write()` (*WindowsIntel32e method*), 213
`write()` (*WindowsIntelPAE method*), 216
`write()` (*WindowsMixin method*), 218
`write()` (*xdp_sock method*), 395
`write()` (*XenCoreDumpLayer method*), 253
`write_layer()` (*LayerWriter class method*), 783
`writelines()` (*FileHandlerInterface method*), 171
`writelines()` (*NullFileHandler method*), 52

X

`xdp_sock` (class in *volatility3.framework.symbols.linux.extensions*), 393
`xdp_sock.VolTemplateProxy` (class in *volatility3.framework.symbols.linux.extensions*), 393
`XenCoreDumpLayer` (class in *volatility3.framework.layers.xen*), 251
`XenCoreDumpStacker` (class in *volatility3.framework.layers.xen*), 253

Y

`YaraScan` (class in *volatility3.plugins.yarascan*), 787
`YaraScanner` (class in *volatility3.plugins.yarascan*), 789

Z

`zfill()` (*Bytes method*), 270
`zfill()` (*HexBytes method*), 317
`zfill()` (*MultiTypeData method*), 321
`zfill()` (*String method*), 297